UNIVERSITÀ DEGLI STUDI DI TRIESTE

Restoration and development of Arm's Java-based LEGv8 ISA simulator

Graduating student - Simone Deiana

Supervisor - Alberto Carini

Department of Engineering and Architecture

Trieste, 31 August 2024

Restoration and development of Arm's Java-based LEGv8 ISA simulator

Restoration and development of Arm's Java-based LEGv8 ISA simulator

Restoration and development of Arm's Java-based LEGv8 ISA simulator

WHAT IS LEGv8?

Restoration and development of Arm's Java-based LEGv8 ISA simulator

AN ISA FOR LEARNING COMPUTER ARCHITECTURES



From Computer Organization and Design ARM Edition: The Hardware Software Interface - Patterson, D.A. and Hennessy, J.L.

David A. Patterson

Peg Skorpinski, CC BY-SA 3.0 <https://creativecommons.org/licenses/by-sa/3.0>, via Wikimedia Commons



John L. Hennessy

Eric Chan, CC BY 2.0 <https://creativecommons.org/licenses/by/2.0>, via Wikimedia Commons

UNIVERSITÀ DEGLI STUDI DI TRIESTE

THE DESIGN PHILOSOPHY

- As simple as it can be…
- … but with a modern design
- Heavily inspired by ARMv8, almost a "subset"

THE MEMORY

- 64-bit addresses
- Harvard model



THE REGISTERS

- 32 64-bit "X" integer registers
- 32 64-bit "D" floating-point registers
- 32 32-bit "S" floating-point "registers"

THE INSTRUCTIONS

- 64-bit integer and IEEE-754 floating-point arithmetic
- Designed and optimized for pipelined execution

THE DATAPATH



From Computer Organization and Design ARM Edition: The Hardware Software Interface - Patterson, D.A. and Hennessy, J.L.

THE DATAPAH



INSTRUCTION MEMORY

From Computer Organization and Design ARM Edition: The Hardware Software Interface - Patterson, D.A. and Hennessy, J.L.

THE DATAPATH

REGISTERS AND CONTROL UNIT



From Computer Organization and Design ARM Edition: The Hardware Software Interface - Patterson, D.A. and Hennessy, J.L.

THE DATAPATH



From Computer Organization and Design ARM Edition: The Hardware Software Interface - Patterson, D.A. and Hennessy, J.L.

THE DATAPATH



From Computer Organization and Design ARM Edition: The Hardware Software Interface - Patterson, D.A. and Hennessy, J.L.

WHAT SIMULATOR, AND WHY?

Restoration and development of

Arm's Java-based LEGv8 ISA simulator

NO HARDWARE FOR LEGv8 => NEED A SIMULATOR

Michael H. („Laserlicht") / Wikimedia Commons

BUT WHICH ONE?



THE PROBLEM:

NO SOFTWARE CAN YET SIMULATE THE ENTIRE LEGv8 ISA!

THE SOLUTION:

- Write one from scratch

OR (BETTER)

- Improve one that already exists

THE GOOD NEWS

ARM HAS OFFICIALLY MADE A LEGv8 SIMULATOR

WHAT STANDS OUT:

- Written in Java (high level, extensible)
- Distributed as a web application
- Nice, functional UI
- Closely follows the textbook

STRUCTURE OF THE SIMULATOR



WHAT SIMULATOR, AND WHY?



UNIVERSITÀ DEGLI STUDI DI TRIESTE

THE BAD NEWS

IT'S INCOMPLETE AND BROKEN

FIXING AND RESTORING THE SIMULATOR

Restoration and development of Arm's Java-based LEGv8 ISA simulator

COMPARISONS DON'T WORK!

- No "if-else" conditionals
- No "switch-case" conditionals
- No "while" loops
- No "for" loops

THE COMPARISON BUG

```
1            ADDI      X0, XZR, #1
2            ADDI      X1, XZR, #2
3            CMP       X0, X1
4            B.LE      should_jump
5            ADD       X2, X0, X1
6  should_jump:        ADDI      X2, XZR, #16
7
```

X0 = 1, X1 = 2



PC	0x400008	Hex Dec	Z	0	N	0	C	0	V	0	
X0	0x1	Hex Dec	X16	0x0					Hex	Dec	
X1	0x2	Hex Dec	X17	0x0					Hex	Dec	
X2	0x0	Hex Dec	X18	0x0					Hex	Dec	

THE COMPARISON BUG

```
1           ADDI      X0, XZR, #1
2           ADDI      X1, XZR, #2
3           CMP       X0, X1
4           B.LE      should_jump
5           ADD       X2, X0, X1
6   should_jump:      ADDI      X2, XZR, #16
7
```

COMPARE X0 WITH X1



UNIVERSITÀ DEGLI STUDI DI TRIESTE

THE COMPARISON BUG

```
1           ADDI      X0, XZR, #1
2           ADDI      X1, XZR, #2
3           CMP       X0, X1
4           B.LE      should_jump
5           ADD       X2, X0, X1
6   should_jump:      ADDI      X2, XZR, #16
7
```

1 <= 2 ?

OF COURSE, LET'S JUMP!

PC	0x400010	Hex Dec	Z	0	N	1	C	0	V	1	
X0	0x1	Hex Dec	X16	0x0					Hex	Dec	
X1	0x2	Hex Dec	X17	0x0					Hex	Dec	
X2	0x0	Hex Dec	X18	0x0					Hex	Dec	

THE COMPARISON BUG

```
1           ADDI      X0, XZR, #1
2           ADDI      X1, XZR, #2
3           CMP       X0, X1
4           B.LE      should_jump
5           ADD       X2, X0, X1
6  should_jump:       ADDI      X2, XZR, #16
7
```

...OR NOT

PC	0x400014	Hex Dec	Z	0	N	1	C	0	V	1	
X0	0x1	Hex Dec	X16	0x0					Hex	Dec	
X1	0x2	Hex Dec	X17	0x0					Hex	Dec	
X2	0x3	Hex Dec	X18	0x0					Hex	Dec	

BRANCH AND LINKS DON'T WORK!

~~*void subroutine(arg1, ...)*~~

~~*float function(arg1, ...)*~~

CAN'T REUSE CODE

THE BRANCH AND LINK BUG

```
1           ADDI    X0, XZR, #1
2           BL      subroutine
3           B       exit
4
5   subroutine:
6           ADDI    X0, X0, #16
7           BR      LR
8   exit:
9
```

THE BRANCH AND LINK BUG

```
1           ADDI    X0, XZR, #1
2           BL      subroutine
3           B       exit
4
5   subroutine:
6           ADDI    X0, X0, #16
7           BR      LR
8   exit:
9
```

THE BRANCH AND LINK BUG

```
1           ADDI    X0, XZR, #1
2           BL      subroutine
3           B       exit
4
5   subroutine:
6           ADDI    X0, X0, #16
7           BR      LR
8   exit:
9
```

THE BRANCH AND LINK BUG

```
1           ADDI    X0, XZR, #1
2           BL      subroutine
3           B       exit
4
5   subroutine:
6           ADDI    X0, X0, #16
7           BR      LR
8   exit:
9
```

THE BRANCH AND LINK BUG

```
1           ADDI    X0, XZR, #1
2           BL      subroutine
3           B       exit
4
5   subroutine:
6           ADDI    X0, X0, #16
7           BR      LR
8   exit:
9
```

IT DOESN'T GO BACK!

ALL FIXED, BUT…

NOBODY KNOWS HOW IT WORKS!

THE PROJECT'S DEPENDENCIES



GWT

- Framework (formerly) from Google
- Generates web applications (client-server, client only) from Java
- Emulates Java's JVM with JavaScript

GWT

- Old, outdated, barely supported
- Convoluted custom build tools
- Limited emulation of JVM
- Basically needs Eclipse plug-in for real development

AceGWT

- Provides GWT bindings for the Ace editor
- Can be used like normal GWT component
- Also old, outdated, and unsupported

WORKING IT OUT:

- Need old version of Eclipse, and Eclipse GWT plug-in
- Reverse engineer the dependencies and where they are needed
- Configure the project to stop failing

FILLING THE GAPS

Restoration and development of Arm's Java-based LEGv8 ISA simulator

WHAT IS THE SIMULATOR MISSING?

- Incomplete integer arithmetic
- No visualization for the stack memory
- No IEEE-754 arithmetic and data instructions

THE MISSING INTEGER-BASED INSTRUCTIONS

- MUL – LOWER 64 BITS OF THE MULTIPLICATION
- SMULH – HIGHER 64 BITS OF THE SIGNED MULTIPLICATION
- UMULH – HIGHER 64 BITS OF THE UNSIGNED MULTIPLICATION
- SDIV – SIGNED DIVISION
- UDIV – UNSIGNED DIVISION
- LDA – LOAD ADDRESS OF A LABEL IN A REGISTER

Easy to implement in the existing codebase

but...

Java doesn't like big or unsigned numbers!

PROBLEM 1

- Java does not have primitive 128-bit integer types
- The BigInteger library exists
- GWT 2.7 doesn't emulate it (2.8 does)

PROBLEM 2

- Primitive integers are signed
- BigInteger also signed
- Bitmask converts 64-bit unsigned integers to 65-bit signed, perform signed operations, back to unsigned

STACK NOT VISUALIZED

- Important for testing and debugging complex programs (now we can write them)
- Useful to understand LEGv8 and stack management

TAKING SOME INSPIRATION



THE NEW STACK VIEW



ADDING FLOATING-POINT SUPPORT

- FADDS, FADDD – ADD TWO IEEE-754 VALUES
- FSUBS, FSUBD - SUBTRACT TWO IEEE-754 VALUES
- FMULS, FMULD - MULTPLY TWO IEEE-754 VALUES
- FDIVS, FDIVD – DIVIDE TWO IEEE-754 VALUES
- LDURS, LDURD – LOAD IEEE-754 VALUE FROM MEMORY
- STURS, STURD - STORE IEEE-754 VALUE TO MEMORY
- FCMPS, FCMPD – COMPARE TWO IEEE-754 VALUES

ARITHMETICAL INSTRUCTIONS



MEMORY ACCESS INSTRUCTIONS

- Simulator designed for integer use
- Memory uses integers to store bytes

IDEA: SEE INTEGERS LIKE RAW BITS

CONVERT FLOATS TO RAW BITS

CAN BE USED AS BINARY PROTOCOL

NO NEED TO CHANGE THE MEMORY!

COMPARISON INSTRUCTIONS

- LEGv8 does not specify flag-setting conditions for IEEE-754 comparisons

- Use ARMv8's ones:

IEEE-754 Relationship	ARM APSR Flags			
	N	Z	C	V
Equal	0	1	1	0
Less Than	1	0	0	0
Greater Than	0	0	1	0
Unordered *(At least one argument was NaN.)*	0	0	1	1

THE FINAL VIEW

```
1        MOVK    X0, #192
2        LSL     X0, X0, #8
3        MOVK    X0, #10
4        LSL     X0, X0, #16
5        SUBI    SP, SP, #16
6        STUR    X0, [SP, #0]
7        LDURS   S0, [SP, #0]
8
```

0x8000000000:	0x0	Hex	0x7fffffff80:	0x0	Hex		
0x7ffffffff8:	0x0	Hex	0x7fffffff78:	0x0	Hex		
0x7ffffffff0:	0xc00a0000	Hex	0x7fffffff70:	0x0	Hex		
0x7fffffffe8:	0x0	Hex	0x7fffffff68:	0x0	Hex		
0x7fffffffe0:	0x0	Hex	0x7fffffff60:	0x0	Hex		
0x7fffffffd8:	0x0	Hex	0x7fffffff58:	0x0	Hex		
0x7fffffffd0:	0x0	Hex	0x7fffffff50:	0x0	Hex		
0x7fffffffc8:	0x0	Hex	0x7fffffff48:	0x0	Hex		
0x7fffffffc0:	0x0	Hex	0x7fffffff40:	0x0	Hex		
0x7fffffffb8:	0x0	Hex	0x7fffffff38:	0x0	Hex		
0x7fffffffb0:	0x0	Hex	0x7fffffff30:	0x0	Hex		
0x7fffffffa8:	0x0	Hex	0x7fffffff28:	0x0	Hex		
0x7fffffffa0:	0x0	Hex	0x7fffffff20:	0x0	Hex		
0x7fffffff98:	0x0	Hex	0x7fffffff18:	0x0	Hex		
0x7fffffff90:	0x0	Hex	0x7fffffff10:	0x0	Hex		
0x7fffffff88:	0x0	Hex	0x7fffffff08:	0x0	Hex		

PC	0x40001c	Hex Dec	Z 0	N 0	C 0	V 0	D0	0xc00a0000	Hex Dec	D16	0x0	Hex Dec	S0	-2.15625	Hex Dec	S16	0x0	Hex Dec
X0	0xc00a0000	Hex Dec	X16	0x0	Hex Dec	D1	0x0	Hex Dec	D17	0x0	Hex Dec	S1	0x0	Hex Dec	S17	0x0	Hex Dec
X1	0x0	Hex Dec	X17	0x0	Hex Dec	D2	0x0	Hex Dec	D18	0x0	Hex Dec	S2	0x0	Hex Dec	S18	0x0	Hex Dec
X2	0x0	Hex Dec	X18	0x0	Hex Dec	D3	0x0	Hex Dec	D19	0x0	Hex Dec	S3	0x0	Hex Dec	S19	0x0	Hex Dec
X3	0x0	Hex Dec	X19	0x0	Hex Dec	D4	0x0	Hex Dec	D20	0x0	Hex Dec	S4	0x0	Hex Dec	S20	0x0	Hex Dec
X4	0x0	Hex Dec	X20	0x0	Hex Dec	D5	0x0	Hex Dec	D21	0x0	Hex Dec	S5	0x0	Hex Dec	S21	0x0	Hex Dec
X5	0x0	Hex Dec	X21	0x0	Hex Dec	D6	0x0	Hex Dec	D22	0x0	Hex Dec	S6	0x0	Hex Dec	S22	0x0	Hex Dec
X6	0x0	Hex Dec	X22	0x0	Hex Dec	D7	0x0	Hex Dec	D23	0x0	Hex Dec	S7	0x0	Hex Dec	S23	0x0	Hex Dec
X7	0x0	Hex Dec	X23	0x0	Hex Dec	D8	0x0	Hex Dec	D24	0x0	Hex Dec	S8	0x0	Hex Dec	S24	0x0	Hex Dec
X8	0x0	Hex Dec	X24	0x0	Hex Dec	D9	0x0	Hex Dec	D25	0x0	Hex Dec	S9	0x0	Hex Dec	S25	0x0	Hex Dec
X9	0x0	Hex Dec	X25	0x0	Hex Dec	D10	0x0	Hex Dec	D26	0x0	Hex Dec	S10	0x0	Hex Dec	S26	0x0	Hex Dec
X10	0x0	Hex Dec	X26	0x0	Hex Dec	D11	0x0	Hex Dec	D27	0x0	Hex Dec	S11	0x0	Hex Dec	S27	0x0	Hex Dec
X11	0x0	Hex Dec	X27	0x0	Hex Dec	D12	0x0	Hex Dec	D28	0x0	Hex Dec	S12	0x0	Hex Dec	S28	0x0	Hex Dec
X12	0x0	Hex Dec	SP	0x7fffffff0	Hex Dec	D13	0x0	Hex Dec	D29	0x0	Hex Dec	S13	0x0	Hex Dec	S29	0x0	Hex Dec
X13	0x0	Hex Dec	FP	0x0	Hex Dec	D14	0x0	Hex Dec	D30	0x0	Hex Dec	S14	0x0	Hex Dec	S30	0x0	Hex Dec
X14	0x0	Hex Dec	LR	0x0	Hex Dec	D15	0x0	Hex Dec	D31	0x0	Hex Dec	S15	0x0	Hex Dec	S31	0x0	Hex Dec
X15	0x0	Hex Dec	XZR	0x0	Hex Dec													

THE CHERRY ON TOP: MODERNIZING THE BUILD SYSTEM

INTEGRATING MAVEN

- Latest GWT and AceGWT support Maven
- Much easier to include if project also supports Maven

THE SWITCH

- Libraries are managed automatically
- Project not coupled to Eclipse, can use other IDEs or even terminal
- Can use Java 21, GWT 2.11
- More configurable and automatic builds

CONCLUSIONS

- Arm's LEGv8 simulator finally working
- Only one to implement every LEGv8 instruction
- Can now be developed with modern tools, set-up and build in seconds, much easier collaboration

THANK YOU FOR YOUR ATTENTION

THESIS AVAILABLE HERE

SIMULATOR AVAILABLE HERE