


# Data Science Practicum

**(Lecture 10, 20.11.)**

Denisa Šrámková




# Data Preparation



Exercise:

[https://github.com/simecek/dspracticum2023/blob/main/lesson10/ds\\_practicum\\_ex\\_ml\\_pipeline\\_final.ipynb](https://github.com/simecek/dspracticum2023/blob/main/lesson10/ds_practicum_ex_ml_pipeline_final.ipynb)

# Dataset



(0.01, 0.48, ... 1.0) → 😊 😞

<https://www.kaggle.com/competitions/titanic/data>

<https://www.kaggle.com/competitions/spaceship-titanic/data>

- **PassengerId** - A unique Id for each passenger. Each Id takes the form `gggg_pp` where `gggg` indicates a group the passenger is travelling with and `pp` is their number within the group. People in a group are often family members, but not always.
- **HomePlanet** - The planet the passenger departed from, typically their planet of permanent residence.
- **CryoSleep** - Indicates whether the passenger elected to be put into suspended animation for the duration of the voyage. Passengers in cryosleep are confined to their cabins.
- **Cabin** - The cabin number where the passenger is staying. Takes the form `deck/num/side`, where `side` can be either `P` for *Port* or `S` for *Starboard*.
- **Destination** - The planet the passenger will be debarking to.
- **Age** - The age of the passenger.
- **VIP** - Whether the passenger has paid for special VIP service during the voyage.
- **RoomService**, **FoodCourt**, **ShoppingMall**, **Spa**, **VRDeck** - Amount the passenger has billed at each of the *Spaceship Titanic's* many luxury amenities.
- **Name** - The first and last names of the passenger.
- **Transported** - Whether the passenger was transported to another dimension. This is the target, the column you are trying to predict.

## Data Dictionary

Variable	Definition	Key
survival	Survival	0 = No, 1 = Yes
pclass	Ticket class	1 = 1st, 2 = 2nd, 3 = 3rd
sex	Sex	
Age	Age in years	
sibsp	# of siblings / spouses aboard the Titanic	
parch	# of parents / children aboard the Titanic	
ticket	Ticket number	
fare	Passenger fare	
cabin	Cabin number	
embarke d	Port of Embarkation	C = Cherbourg, Q = Queenstown, S = Southampton

## Variable Notes

**pclass:** A proxy for socio-economic status (SES)

1st = Upper

2nd = Middle

3rd = Lower

**age:** Age is fractional if less than 1. If the age is estimated, is it in the form of `xx.5`

**sibsp:** The dataset defines family relations in this way...

Sibling = brother, sister, stepbrother, stepsister

Spouse = husband, wife (mistresses and fiancés were ignored)

**parch:** The dataset defines family relations in this way...





Parent = mother, father

Child = daughter, son, stepdaughter, stepson

Some children travelled only with a nanny, therefore `parch=0` for them.

# 0. Data exploration

- get to know your data
- make visualization to get more insights



# 1. Data cleaning

Handle:

- **missing** values
  - skip
  - eliminate row/ column,
  - interpolate
- **inconsistent** values (age in *Birth* column, value of String type in otherwise Int column, ...)
- **duplicate** values

## 2. Feature manipulation

- **encoding categorical features**
  - One-Hot encoding
  - Binning
- **scaling numerical features**
  - normalization
  - standardization


# 3. Dataset splitting

**Train:** used to build the model

**Validation:** to improve hyperparameters

**Test:** to test the hypothesis of the model (not used until the model is trained and its hyperparameters are decided)

## 4. Choosing the right solution + Training the model *(switch to exercise)*





# 5. Evaluation

## Classification metrics:

Sources: [22][23][24][25][26][27][28][29][30] view · talk · edit

		Predicted condition			
		Predicted Positive (PP)	Predicted Negative (PN)	Informedness, bookmaker informedness (BM) = TPR + TNR - 1	Prevalence threshold (PT) $= \frac{\sqrt{TPR \times FPR} - FPR}{TPR - FPR}$
Actual condition	Positive (P)	True positive (TP), hit	False negative (FN), type II error, miss, underestimation	True positive rate (TPR), recall, sensitivity (SEN), probability of detection, hit rate, $= \frac{TP}{P} = 1 - FNR$	False negative rate (FNR), miss rate $= \frac{FN}{P} = 1 - TPR$
	Negative (N)	False positive (FP), type I error, false alarm, overestimation	True negative (TN), correct rejection	False positive rate (FPR), probability of false alarm, fall-out $= \frac{FP}{N} = 1 - TNR$	True negative rate (TNR), specificity (SPC), selectivity $= \frac{TN}{N} = 1 - FPR$
	Prevalence $= \frac{P}{P + N}$	Positive predictive value (PPV), precision $= \frac{TP}{PP} = 1 - FDR$	False omission rate (FOR) $= \frac{FN}{PN} = 1 - NPV$	Positive likelihood ratio (LR+) $= \frac{TPR}{FPR}$	Negative likelihood ratio (LR-) $= \frac{FNR}{TNR}$
	Accuracy (ACC) $= \frac{TP + TN}{P + N}$	False discovery rate (FDR) $= \frac{FP}{PP} = 1 - PPV$	Negative predictive value (NPV) = $\frac{TN}{PN}$ $= 1 - FOR$	Markedness (MK), deltaP ( $\Delta p$ ) $= PPV + NPV - 1$	Diagnostic odds ratio (DOR) = $\frac{LR+}{LR-}$
	Balanced accuracy (BA) $= \frac{TPR + TNR}{2}$	F <sub>1</sub> score $= \frac{2PPV \times TPR}{PPV + TPR} = \frac{2TP}{2TP + FP + FN}$	Fowlkes–Mallows index (FM) $= \sqrt{PPV \times TPR}$	Matthews correlation coefficient (MCC) $= \sqrt{TPR \times TNR \times PPV \times NPV}$ $= -\sqrt{FNR \times FPR \times FOR \times FDR}$	Threat score (TS), critical success index (CSI), Jaccard index $= \frac{TP}{TP + FN + FP}$

# 5. Evaluation

## Classification metrics:

Sources: [22][23][24][25][26][27][28][29][30] view · talk · edit

		Predicted condition			
		Predicted Positive (PP)	Predicted Negative (PN)	Informedness, bookmaker informedness (BM) $= \text{TPR} + \text{TNR} - 1$	Prevalence threshold (PT) $= \frac{\sqrt{\text{TPR} \times \text{FPR}} - \text{FPR}}{\text{TPR} - \text{FPR}}$
Actual condition	Total population $= P + N$				
	Positive (P)	True positive (TP), hit	False negative (FN), type II error, miss, underestimation	True positive rate (TPR), recall, sensitivity (SEN), probability of detection, hit rate, power $= \frac{\text{TP}}{\text{P}} = 1 - \text{FNR}$	False negative rate (FNR), miss rate $= \frac{\text{FN}}{\text{P}} = 1 - \text{TPR}$
	Negative (N)	False positive (FP), type I error, false alarm, overestimation	True negative (TN), correct rejection	False positive rate (FPR), probability of false alarm, fall-out $= \frac{\text{FP}}{\text{N}} = 1 - \text{TNR}$	True negative rate (TNR), specificity (SPC), selectivity $= \frac{\text{TN}}{\text{N}} = 1 - \text{FPR}$
		Positive predictive value (PPV), precision $= \frac{\text{TP}}{\text{PP}} = 1 - \text{FDR}$	False omission rate (FOR) $= \frac{\text{FN}}{\text{PN}} = 1 - \text{NPV}$	Positive likelihood ratio (LR+) $= \frac{\text{TPR}}{\text{FPR}}$	Negative likelihood ratio (LR-) $= \frac{\text{FNR}}{\text{TNR}}$
		Prevalence $= \frac{\text{P}}{\text{P} + \text{N}}$	False discovery rate (FDR) $= \frac{\text{FP}}{\text{PP}} = 1 - \text{PPV}$	Negative predictive value (NPV) $= \frac{\text{TN}}{\text{PN}}$ $= 1 - \text{FOR}$	Markedness (MK), deltaP ( $\Delta p$ ) $= \text{PPV} + \text{NPV} - 1$
		Accuracy (ACC) $= \frac{\text{TP} + \text{TN}}{\text{P} + \text{N}}$			Diagnostic odds ratio (DOR) $= \frac{\text{LR}+}{\text{LR}-}$
		Balanced accuracy (BA) $= \frac{\text{TPR} + \text{TNR}}{2}$	F <sub>1</sub> score $= \frac{2\text{PPV} \times \text{TPR}}{\text{PPV} + \text{TPR}} = \frac{2\text{TP}}{2\text{TP} + \text{FP} + \text{FN}}$	Fowlkes–Mallows index (FM) $= \sqrt{\text{PPV} \times \text{TPR}}$	Matthews correlation coefficient (MCC) $= \sqrt{\text{TPR} \times \text{TNR} \times \text{PPV} \times \text{NPV}} - \sqrt{\text{FNR} \times \text{FPR} \times \text{FOR} \times \text{FDR}}$
					Threat score (TS), critical success index (CSI), Jaccard index $= \frac{\text{TP}}{\text{TP} + \text{FN} + \text{FP}}$

# 5. Evaluation

## Classification metrics:

Sources: [22][23][24][25][26][27][28][29][30] view · talk · edit

		Predicted condition		
		Predicted Positive (PP)	Predicted Negative (PN)	
Actual condition	Total population = P + N			Informedness, bookmaker informedness (BM) = TPR + TNR - 1
				Prevalence threshold (PT) $= \frac{\sqrt{TPR \times FPR} - FPR}{TPR - FPR}$
Positive (P)	True positive (TP), hit	False negative (FN), type II error, miss, underestimation	True positive rate (TPR), recall, sensitivity (SEN), probability of detection, hit rate, power $= \frac{TP}{P} = 1 - FNR$	False negative rate (FNR), miss rate $= \frac{FN}{P} = 1 - TPR$
Negative (N)	False positive (FP), type I error, false alarm, overestimation	True negative (TN), correct rejection	False positive rate (FPR), probability of false alarm, fall-out $= \frac{FP}{N} = 1 - TNR$	True negative rate (TNR), specificity (SPC), selectivity $= \frac{TN}{N} = 1 - FPR$
Prevalence $= \frac{P}{P + N}$	Positive predictive value (PPV), precision $= \frac{TP}{PP} = 1 - FDR$	False omission rate (FOR) $= \frac{FN}{PN} = 1 - NPV$	Positive likelihood ratio (LR+) $= \frac{TPR}{FPR}$	Negative likelihood ratio (LR-) $= \frac{FNR}{TNR}$
Accuracy (ACC) $= \frac{TP + TN}{P + N}$	False discovery rate (FDR) $= \frac{FP}{PP} = 1 - PPV$	Negative predictive value (NPV) = $\frac{TN}{PN}$ = 1 - FOR	Markedness (MK), deltaP ( $\Delta p$ ) = PPV + NPV - 1	Diagnostic odds ratio (DOR) = $\frac{LR+}{LR-}$
Balanced accuracy (BA) $= \frac{TPR + TNR}{2}$	F <sub>1</sub> score $= \frac{2PPV \times TPR}{PPV + TPR} = \frac{2TP}{2TP + FP + FN}$	Fowlkes–Mallows index (FM) $= \sqrt{PPV \times TPR}$	Matthews correlation coefficient (MCC) $= \sqrt{TPR \times TNR \times PPV \times NPV}$ $= -\sqrt{FNR \times FPR \times FOR \times FDR}$	Threat score (TS), critical success index (CSI), Jaccard index $= \frac{TP}{TP + FN + FP}$

# 5. Evaluation

## Classification metrics:

Sources: [22][23][24][25][26][27][28][29][30] view · talk · edit

		Predicted condition		
		Predicted Positive (PP)	Predicted Negative (PN)	
Actual condition	Total population = P + N			Informedness, bookmaker informedness (BM) = TPR + TNR - 1
				Prevalence threshold (PT) $= \frac{\sqrt{TPR \times FPR} - FPR}{TPR - FPR}$
Positive (P)	True positive (TP), hit	False negative (FN), type II error, miss, underestimation	True positive rate (TPR), recall, sensitivity (SEN), probability of detection, hit rate, power $= \frac{TP}{P} = 1 - FNR$	False negative rate (FNR), miss rate $= \frac{FN}{P} = 1 - TPR$
Negative (N)	False positive (FP), type I error, false alarm, overestimation	True negative (TN), correct rejection	False positive rate (FPR), probability of false alarm, fall-out $= \frac{FP}{N} = 1 - TNR$	True negative rate (TNR), specificity (SPC), selectivity $= \frac{TN}{N} = 1 - FPR$
Prevalence $= \frac{P}{P + N}$	Positive predictive value (PPV), precision $= \frac{TP}{PP} = 1 - FDR$	False omission rate (FOR) $= \frac{FN}{PN} = 1 - NPV$	Positive likelihood ratio (LR+) $= \frac{TPR}{FPR}$	Negative likelihood ratio (LR-) $= \frac{FNR}{TNR}$
Accuracy (ACC) $= \frac{TP + TN}{P + N}$	False discovery rate (FDR) $= \frac{FP}{PP} = 1 - PPV$	Negative predictive value (NPV) = $\frac{TN}{PN}$ = 1 - FOR	Markedness (MK), deltaP ( $\Delta p$ ) = PPV + NPV - 1	Diagnostic odds ratio (DOR) = $\frac{LR+}{LR-}$
Balanced accuracy (BA) $= \frac{TPR + TNR}{2}$	F <sub>1</sub> score $= \frac{2PPV \times TPR}{PPV + TPR} = \frac{2TP}{2TP + FP + FN}$	Fowlkes–Mallows index (FM) $= \sqrt{PPV \times TPR}$	Matthews correlation coefficient (MCC) $= \sqrt{TPR \times TNR \times PPV \times NPV}$ $= -\sqrt{FNR \times FPR \times FOR \times FDR}$	Threat score (TS), critical success index (CSI), Jaccard index $= \frac{TP}{TP + FN + FP}$



# 5. Evaluation


## Classification metrics:

Perceived vowel \ Vowel produced	i	e	a	o	u
i	15		1		
e	1		1		
a			79	5	
o			4	15	3
u				2	2

		Predicted condition		Sources: [22][23][24][25][26][27][28][29][30] view · talk · edit	
Total population = P + N		Predicted Positive (PP)	Predicted Negative (PN)	Informedness, bookmaker informedness (BM) = TPR + TNR − 1	Prevalence threshold (PT) $= \frac{\sqrt{\text{TPR} \times \text{FPR}} - \text{FPR}}{\text{TPR} - \text{FPR}}$
Actual condition	Positive (P)	True positive (TP), hit	False negative (FN), type II error, miss, underestimation	True positive rate (TPR), recall, sensitivity (SEN), probability of detection, hit rate, power $= \frac{\text{TP}}{\text{P}} = 1 - \text{FNR}$	False negative rate (FNR), miss rate $= \frac{\text{FN}}{\text{P}} = 1 - \text{TPR}$
	Negative (N)	False positive (FP), type I error, false alarm, overestimation	True negative (TN), correct rejection	False positive rate (FPR), probability of false alarm, fall-out $= \frac{\text{FP}}{\text{N}} = 1 - \text{TNR}$	True negative rate (TNR), specificity (SPC), selectivity $= \frac{\text{TN}}{\text{N}} = 1 - \text{FPR}$
Prevalence $= \frac{\text{P}}{\text{P} + \text{N}}$		Positive predictive value (PPV), precision $= \frac{\text{TP}}{\text{PP}} = 1 - \text{FDR}$	False omission rate (FOR) $= \frac{\text{FN}}{\text{PN}} = 1 - \text{NPV}$	Positive likelihood ratio (LR+) $= \frac{\text{TPR}}{\text{FPR}}$	Negative likelihood ratio (LR−) $= \frac{\text{FNR}}{\text{TNR}}$
Accuracy (ACC) $= \frac{\text{TP} + \text{TN}}{\text{P} + \text{N}}$		False discovery rate (FDR) $= \frac{\text{FP}}{\text{PP}} = 1 - \text{PPV}$	Negative predictive value (NPV) = $\frac{\text{TN}}{\text{PN}}$ $= 1 - \text{FOR}$	Markedness (MK), deltaP (Δp) $= \text{PPV} + \text{NPV} - 1$	Diagnostic odds ratio (DOR) = $\frac{\text{LR}^+}{\text{LR}^-}$
Balanced accuracy (BA) $= \frac{\text{TPR} + \text{TNR}}{2}$		F <sub>1</sub> score $= \frac{2\text{PPV} \times \text{TPR}}{\text{PPV} + \text{TPR}} = \frac{2\text{TP}}{2\text{TP} + \text{FP} + \text{FN}}$	Fowles–Mallows index (FM) $= \sqrt{\text{PPV} \times \text{TPR}}$	Matthews correlation coefficient (MCC) $= \sqrt{\text{TPR} \times \text{TNR} \times \text{PPV} \times \text{NPV}}$ $- \sqrt{\text{FNR} \times \text{FPR} \times \text{FOR} \times \text{FDR}}$	Threat score (TS), critical success index (CSI), Jaccard index $= \frac{\text{TP}}{\text{TP} + \text{FN} + \text{FP}}$

# 5. Evaluation

## Classification metrics:



<https://developers.google.com/machine-learning/crash-course/classification/roc-and-auc>

Sources: [22][23][24][25][26][27][28][29][30] view · talk · edit


		Predicted condition		
		Predicted Positive (PP)	Predicted Negative (PN)	
Actual condition	Total population = P + N			Informedness, bookmaker informedness (BM) = TPR + TNR - 1
				Prevalence threshold (PT) $= \frac{\sqrt{TPR \times FPR} - FPR}{TPR - FPR}$
Positive (P)	True positive (TP), hit	False negative (FN), type II error, miss, underestimation	True positive rate (TPR), recall, sensitivity (SEN), probability of detection, hit rate, power $= \frac{TP}{P} = 1 - FNR$	False negative rate (FNR), miss rate $= \frac{FN}{P} = 1 - TPR$
Negative (N)	False positive (FP), type I error, false alarm, overestimation	True negative (TN), correct rejection	False positive rate (FPR), probability of false alarm, fall-out $= \frac{FP}{N} = 1 - TNR$	True negative rate (TNR), specificity (SPC), selectivity $= \frac{TN}{N} = 1 - FPR$
	Prevalence $= \frac{P}{P + N}$	Positive predictive value (PPV), precision $= \frac{TP}{PP} = 1 - FDR$	False omission rate (FOR) $= \frac{FN}{PN} = 1 - NPV$	Positive likelihood ratio (LR+) $= \frac{TPR}{FPR}$
	Accuracy (ACC) $= \frac{TP + TN}{P + N}$	False discovery rate (FDR) $= \frac{FP}{PP} = 1 - PPV$	Negative predictive value (NPV) = $\frac{TN}{PN}$ $= 1 - FOR$	Negative likelihood ratio (LR-) $= \frac{FNR}{TNR}$
	Balanced accuracy (BA) $= \frac{TPR + TNR}{2}$	F <sub>1</sub> score $= \frac{2PPV \times TPR}{PPV + TPR} = \frac{2TP}{2TP + FP + FN}$	Fowlkes–Mallows index (FM) $= \sqrt{PPV \times TPR}$	Markedness (MK), deltaP (Δp) $= PPV + NPV - 1$
			Matthews correlation coefficient (MCC) $= \sqrt{TPR \times TNR \times PPV \times NPV}$ $= -\sqrt{FNR \times FPR \times FOR \times FDR}$	Diagnostic odds ratio (DOR) = $\frac{LR+}{LR-}$
				Threat score (TS), critical success index (CSI), Jaccard index $= \frac{TP}{TP + FN + FP}$

[https://en.wikipedia.org/wiki/Confusion\\_matrix](https://en.wikipedia.org/wiki/Confusion_matrix)

# 5. Evaluation

Classification metrics:

AUC





<https://developers.google.com/machine-learning/crash-course/classification/roc-and-auc>

Sources: [22][23][24][25][26][27][28][29][30] view · talk · edit

		Predicted condition		
		Predicted Positive (PP)	Predicted Negative (PN)	
Actual condition	Total population = P + N			Informedness, bookmaker informedness (BM) = TPR + TNR - 1
				Prevalence threshold (PT) $= \frac{\sqrt{TPR \times FPR} - FPR}{TPR - FPR}$
Positive (P)	True positive (TP), hit	False negative (FN), type II error, miss, underestimation	True positive rate (TPR), recall, sensitivity (SEN), probability of detection, hit rate, power $= \frac{TP}{P} = 1 - FNR$	False negative rate (FNR), miss rate $= \frac{FN}{P} = 1 - TPR$
Negative (N)	False positive (FP), type I error, false alarm, overestimation	True negative (TN), correct rejection	False positive rate (FPR), probability of false alarm, fall-out $= \frac{FP}{N} = 1 - TNR$	True negative rate (TNR), specificity (SPC), selectivity $= \frac{TN}{N} = 1 - FPR$
	Prevalence $= \frac{P}{P + N}$	Positive predictive value (PPV), precision $= \frac{TP}{PP} = 1 - FDR$	False omission rate (FOR) $= \frac{FN}{PN} = 1 - NPV$	Positive likelihood ratio (LR+) $= \frac{TPR}{FPR}$
	Accuracy (ACC) $= \frac{TP + TN}{P + N}$	False discovery rate (FDR) $= \frac{FP}{PP} = 1 - PPV$	Negative predictive value (NPV) = $\frac{TN}{PN}$ = 1 - FOR	Negative likelihood ratio (LR-) $= \frac{FNR}{TNR}$
	Balanced accuracy (BA) $= \frac{TPR + TNR}{2}$	F <sub>1</sub> score $= \frac{2PPV \times TPR}{PPV + TPR} = \frac{2TP}{2TP + FP + FN}$	Fowlkes–Mallows index (FM) $= \sqrt{PPV \times TPR}$	Markedness (MK), deltaP (Δp) = PPV + NPV - 1
			Matthews correlation coefficient (MCC) $= \sqrt{TPR \times TNR \times PPV \times NPV}$ $= -\sqrt{FNR \times FPR \times FOR \times FDR}$	Threat score (TS), critical success index (CSI), Jaccard index $= \frac{TP}{TP + FN + FP}$

[https://en.wikipedia.org/wiki/Confusion\\_matrix](https://en.wikipedia.org/wiki/Confusion_matrix)

## 6. Interpretability (optional)





# Homework

- 1) Finish the Exercise (reach at least 80% accuracy) and send the link to your solution on GitHub through <https://forms.gle/S4XVncJbSqwXtYJ36>