Cursor IDE: Qwen Model Configuration Guide

Complete Setup Instructions for DashScope Qwen Integration

Overview

This guide documents the complete process of configuring Cursor IDE to use the Qwen 3.7 Max model via Alibaba DashScope API. The configuration enables direct OpenAI-compatible requests to DashScope, bypassing Cursor default backend routing.

Prerequisites

Cursor IDE installed (tested with version 0.49+)

DashScope API key (Alibaba Cloud account)

Node.js (for database manipulation scripts)

Step 1: Obtain DashScope API Credentials

1. Log in to Alibaba Cloud Console
2. Navigate to DashScope service
3. Generate an API key (format: sk-ws-...)
4. Note your base URL:
https://ws-7mbeemz2jppnpp50.ap-southeast-1.maas.aliyuncs.com/compatible-mode/v1

Step 2: Configure Cursor Internal Database

Cursor stores configuration in a SQLite database at:
%APPDATA%\Cursor\User\globalStorage\state.vscdb

Use Node.js to directly modify the database entries. The key table is **ItemTable** and the main configuration key is:
src.vs.platform.reactivestorage.browser.reactiveStorageServiceImpl.persistentStorage

.applicationUser

```
const sqlite3 = require('C:/Users/naras/AppData/Local/Programs/cursor/\
resources/app/node_modules/@vscode/sqlite3'); const dbPath =
'C:/Users/naras/AppData/Roaming/Cursor/User/globalStorage/state.vscdb'; const db = new
sqlite3.Database(dbPath); const key =
'src.vs.platform.reactivestorage.browser.reactiveStorageServiceImpl\
.persistentStorage.applicationUser'; const apiKey = 'sk-ws-YOUR_API_KEY_HERE'; const
baseUrl = 'https://ws-7mbeemz2jppnpp50.ap-southeast-1.maas.aliyuncs.com\
/compatible-mode/v1'; const qwenModel = 'qwen3.7-max'; db.run('BEGIN TRANSACTION');
db.get('SELECT value FROM ItemTable WHERE key = ?', [key], (err, row) => { const data =
JSON.parse(row.value); data.openAIKey = apiKey; data.openAIBaseUrl = baseUrl; if
(!data.aiSettings) data.aiSettings = {}; if (!data.aiSettings.modelConfig)
data.aiSettings.modelConfig = {}; const modelEntry = { modelName: qwenModel, maxMode:
false, selectedModels: [{ modelId: qwenModel, parameters: [] }] }; // Apply to all
features ['cmd-k','composer','background-composer','composer-ensemble',
'plan-execution','spec','deep-search','quick-agent'].forEach(f => {
data.aiSettings.modelConfig[f] = {...modelEntry}; }); if
(!data.aiSettings.userAddedModels) data.aiSettings.userAddedModels = []; if
(!data.aiSettings.userAddedModels.includes(qwenModel))
data.aiSettings.userAddedModels.push(qwenModel); if
(!data.aiSettings.modelOverrideEnabled) data.aiSettings.modelOverrideEnabled = []; if
(!data.aiSettings.modelOverrideEnabled.includes(qwenModel))
data.aiSettings.modelOverrideEnabled.push(qwenModel); db.run('UPDATE ItemTable SET
value = ? WHERE key = ?', [JSON.stringify(data), key], function(err) { db.run('COMMIT');
db.run('PRAGMA wal_checkpoint(TRUNCATE)'); db.close(); }); });
```

Step 3: Set Environment Variables

Set the following system environment variables (User scope):

Variable	Value
CURSOR_LOCAL_AGENT_API_KEY	sk-ws-YOUR_API_KEY_HERE
CURSOR_LOCAL_AGENT_BASE_URL	https://ws-7mbeemz2jppnpp50.ap-southeast-1.maas.aliyuncs.com/compatible-mo
OPENAI_API_KEY	sk-ws-YOUR_API_KEY_HERE
OPENAI_BASE_URL	https://ws-7mbeemz2jppnpp50.ap-southeast-1.maas.aliyuncs.com/compatible-mo

Step 4: Enable Local Mode in Cursor

Cursor Agent mode routes through its backend by default. To use direct OpenAI-compatible requests, enable local mode by patching the JavaScript file:

```
# PowerShell script to patch Cursor = "C:\Users\\AppData\Local\Programs\cursor\resource
s\app\out\vs\workbench\workbench.glass.main.js" Copy-Item ".backup" -Force =
Get-Content -Raw = -replace 'localMode:!1', 'localMode:!0' Set-Content -Value
-NoNewline Write-Host "Patch applied: localMode enabled"
```

Important: This patch modifies Cursor internal code. Create a backup before applying. The patch may need to be reapplied after Cursor updates.

Step 5: Restart Cursor and Test

1. Completely close Cursor (kill all processes)
2. Restart Cursor to load new configuration
3. Open a chat window
4. Select qwen3.7-max from the model dropdown
5. Send a test message to verify the connection

Troubleshooting

Error: 'model is required'

The API key is not properly stored in applicationUserPersistentStorage. Re-run the database configuration script and ensure the transaction is committed.

Error: 'Unable to reach the model provider'

Cursor is still routing through its backend instead of using local mode. Verify:
- The JavaScript patch was applied successfully
- Environment variables CURSOR_LOCAL_AGENT_* are set
- Cursor was restarted after all changes

Model not appearing in dropdown

Check that qwen3.7-max is added to both userAddedModels and modelOverrideEnabled arrays in the database configuration.

Technical Details

Database Location: %APPDATA%\Cursor\User\globalStorage\state.vscdb
Key Storage: applicationUserPersistentStorage (JSON in ItemTable)
JavaScript File: workbench.glass.main.js in Cursor app/out/vs/workbench/
Local Mode Flag: Cv.localMode (build flag in JavaScript)
API Compatibility: OpenAI-compatible /v1 endpoint

Configuration Summary

Setting	Value
Model	qwen3.7-max
Provider	Alibaba DashScope
Base URL	ws-7mbeemz2jppnpp50.ap-southeast-1.maas.aliyuncs.com
API Type	OpenAI-compatible
Local Mode	Enabled (patched)

Document generated: June 20, 2026 | Cursor IDE + Qwen Model Configuration