

Product Name	Blender	Factory	MYLUX	Date	2026/5/14
P.O. No.	LS_H260311	Product Rating	220V, 60Hz 250W	Factory Model No.	Y-910
Customer Model No.	BL-C01FRD	Destination	Korea	Brand	HUROM
Order Qty	2200PCS	Standby Qty	0	INSP. QTY.	2200PCS
Sampling INSP. QTY.	125PCS	Serial No. : EF2605080001-EF2605082200			

INSPECTION STANDARD: Finished product inspection specification NO:QA-20-109-006 version: 01

IS02859 General Inspection, Level II, Normal, Single Sampling Plan

Acceptance Quality Level		Accept No.	Reject No.	Found No.	AQL JUDGEMENT		
CRITICAL:	0	0	0	0	ACCEPT		
MAJOR:	1.0	3	4	0			
MINOR:	2.5	7	8	6			
NO.	DESCRIPTION OF DEFECT				CR	MA	MI
1	Scratch mark on surface				0	0	3
2	Scratch mark on button				0	0	2
3	Dent mark on base				0	0	1
4							
5							
6							
7							
	Total :				0	0	6

Remark:

- 1、All the unacceptable products above, MYLUX will rework.
2、The defective photos are as shown below.

(1) Defect Photo

	
1. Scratch mark on surface - Minor	2. Scratch mark on surface - Minor
	
3. Scratch mark on surface - Minor	4. Scratch mark on button - Minor

			
5. Scratch mark on button - Minor		6. Dent mark on base - Minor	

(2) CRITICAL PARTS CHECK LIST

Object/ part NO.	Manufacturer	Type	Technical data	Certification	RESULT	PHOTO
Power cord	Toong Yean Plastic Ind. Co.,Ltd.	60227 IEC 52 (H03VVH2-F)	2x0.75mm ²	EN 50525-2	P	
Plug	Toong Yean Plastic Industrial Co.,Ltd.	TY-021	250V~, 2.5A	VDE 40002154	P	
Motor	Xiamen YOUo Intelligent Technology Co., Ltd	M5440CAV2224T 133	220-240V ~, 50- 60Hz, 250W	IEC/EN 60335- 1 IEC/EN 60335- 2-14	P	
Thermal protector	Zhangzhou Aupo Electronics Co., Ltd.	BF133	250V ~, 10A, 133°C	IEC 60691 EN 60691	P	
X-capacitor	KUNSHAN UTX VALUE ENTERPPISE CO., Ltd.	HQX X2	275/310V ~, 0.33uF, ,4 0/110/56/B	EC 60384-14 EN 60384-14	P	
Y-capacitor	Jyh Chung	JY	Y2, 300V~, 4700pF, 40/125/21	IEC 60384-14 EN 60384-14	P	
Micro switch	Guangdong Yushun Electric Appliance Ltd.	KW-5	250V~, 5A, 3E4, T125	IEC 61058-1 EN 61058-1	P	
Switch	zhejiang Jialong Electron Co.,Ltd.	KAN-9-GG-1	250V~, 10 (3) A, T85, 10E3	IEC 61058-1 EN 61058-1	P	

(3) Check the CDF record photos

Plug	Toong Yean Plastic Industrial Co.,Ltd.	TY-021	250 V~, 2.5 A	KC
Alt) Cord	Toong Yean Plastic Ind. Co., Ltd.	60227 IEC 52 (H03VVH2-F)	2 x 0.75 mm ²	KC
Motor	Xiamen YOUo Intelligent Technology Co., Ltd.	M5440CAV2224T13	220-240 V~, 50-60 Hz, 250 W	
Thermal protector (for Motor)	Zhangzhou Aupo Electronics Co., Ltd.	BF 133	250 V~, 10 A, 133 °C	KC
X-capacitor	KUNSHAN UTX VALUE ENTERPPISE CO., LTD.	HQX X2	275/310 V~, 0.33 μF, 40/110/56/B	KC
Micro switch	Guangdong Yushun Electric Appliance Ltd.	KW-5	250 V~, 5 A, 3E4, T125	KC
Switch	zhejiang Jialong Electron Co., Ltd.	KAN-9-GG-1	250 V~, 10(3) A, T85, 10E3	KC

Remark:

The "CRITICAL PARTS CHECK LIST" and "Check the CDF record photos "are based on the KC report (report No. HU071120-20012C)

(4) SERIAL NUMBER of INSPECTED UNITS

SERIAL NUMBER FORMAT AND RANGE:

The numbers below

2	Blending Water Test	PASS	PASS	PASS	PASS	PASS	PASS	PASS	PASS	Blank	Blank
3	Jar Leakage Test	PASS	PASS	PASS	PASS	PASS	PASS	PASS	PASS	Blank	Blank
Remark	The items (number1 to 3) are tested according to the S-2 standard,8 products are selected for testing, and the test results are as above.										
NO.	Test Item \Serial NO.	0447	1720	1317	0239	0664	1112	0673	1834	1550	1344
4	Hi-Pot Check (3000V/2s/5mA)	PASS	PASS	PASS	PASS	PASS	PASS	PASS	PASS	PASS	PASS
5	Leakege Current Test ($\leq 0.25\text{mA}$)	PASS	PASS	PASS	PASS	PASS	PASS	PASS	PASS	PASS	PASS
6	Cord Length ($85\pm 5\text{cm}$)	PASS	PASS	PASS	PASS	PASS	PASS	PASS	PASS	PASS	PASS
Remark	1、The above items (number4 to 6) are tested according to the G II standard, and the data is only part of the test results, because the space limit does not show all the results.										
NO.	Test Item \Serial NO.	0621					1758				
7	No-load Speed Test (16100-22100rpm)	17820rpm					18353rpm				
NO.	Test Item \Serial NO.	0124					0885				
8	Noise Test $\leq 95\text{dB}$	77.7dB					78.64dB				
NO.	Test Item \Serial NO.	0917					1564				
9	Jar Container Capacity $600\text{mL}\pm 30\text{mL}$	600.5mL					601.0mL				
	Jar Container Capacity $350\text{mL}\pm 17.5\text{mL}$	352.0mL					352.5mL				
Remark	The items (number7 to 9) are tested according to the Finished product inspection specification,2 products are selected for testing, and the test results are as above.										
NO.	Test Item \Serial NO.	1145		1878		1634		1259		0822	
10	Jar holder and the main body: Put the jar holder into main body, the screw force is 8-40kgf, and the loose force is 5-35kgf.	PASS		PASS		PASS		PASS		PASS	
	Operating Force Test Jar and Jar holder: Locking tightly force 30kgf.cm; Loose force $\leq 40\text{kgf.cm}$	PASS		PASS		PASS		PASS		PASS	
	Operating Force Test The micro switch starting force of the jar holder pressing into the main body is 0.5-8kgf	2.1kgf		2.3kgf		2.1kgf		2.0kgf		2.0kgf	



INSPECTION REPORT

REPORT NO. : LZX20260514-2

	Operating Force Test Lid and jar body: Locking tightly force is 30kgf.cm; Loose force ≤ 40kgf.cm	PASS	PASS	PASS	PASS	PASS
	Operating Force Test The open/close button force is 0.5kgf≤X≤ 4.1kgf	1.4kgf	1.6kgf	1.5kgf	1.6kgf	1.5kgf
Remark	The item (number10) is tested according to the Finished product inspection specification, 5 products are selected for testing, and the test results are as above.					
NO.	Test Item \Serial NO.	0824				
11	Power cord tension as per IEC60335-1 requirement ≥6kgf	PASS				
NO.	Test Item \Serial NO.	N/A	N/A	N/A	N/A	N/A
12	Upper cover size Factory drawing: 9.98±0.1mm	9.92	9.93	9.91	9.92	9.93
Remark	The items (number 12) are tested with the spare upper cover, because it can't be test unless destroy the cover. Factory's drawing still remain 9.98±0.1mm for production control.					

(6) INFORMATION CHECK LIST

NO.	Item	DETAILS/POSITION	Result
1	VOLTAGE SYSTEM	220V, 60Hz, 250W	P
2	BAR CODE	ON GIFT BOX 8809069580230	P
3	ACCESSORIES	User manual*1、Jar (350mL) *1、Jar (600mL) *1、Cup cap*2、 Blade base with blade*1	P
4	Printing	The PE bags and user manual printing match the reference drawings	P

(7) OTHER

Item	Inspection Standard	DETAILS	结果 Result
Drop Test	ISTA-1A	Carton Box GROSS WEIGHT: 6.99kg DROP TEST SEQUENCE: 760mm SAFETY : PASS FUNCTION : PASS APPEARANCE : PASS	P
Carton size	469×345×260mm	473×345×265mm	P
Gift Box Size	225×163×240mm	228×165×243mm	P
HOTOEM Information Technology Company Limited		Liang Zixuan	Li Yanlin
REPORTED BY		INSPECTOR' S SIGNATURE	FACTORY' S REPRESENTATIVE SIGNATURE