

Product Name	Blender	Factory	MYLUX	Date	2026/5/14
P.O. No.	LS_H260311	Product Rating	220-230V, 50-60Hz, 900W	Factory Model No.	Y-938
Customer Model No.	BL-D01FTG	Destination	Korea	Brand	HUROM
Order Qty	3300PCS	Standby Qty	0	INSP. QTY.	3300PCS
Sampling INSP. QTY.	200PCS	Serial No. : EF2605060001-EF2605063300			

INSPECTION STANDARD: Finished product inspection specification NO:QA-23-109-012 version: 02

ISO2859 General Inspection, Level II, Normal, Single Sampling Plan

Acceptance Quality Level		Accept No.	Reject No.	Found No.	AQL JUDGEMENT
CRITICAL:	0	0	0	0	ACCEPT
MAJOR:	1.0	5	6	0	
MINOR:	4.0	14	15	8	

NO.	DESCRIPTION OF DEFECT	CR	MA	MI
1	Flash on heat dissipation holes	0	0	2
2	Poor assembly on base	0	0	2
3	Scratch mark on base	0	0	4
4				
5				
6				
7				
Total :		0	0	8

Remark:

- 1、All the unacceptable products above, MYLUX will rework.
- 2、The defective photos are as shown below.

(1) Defect Photo

	
1. Flash on heat dissipation holes - minor	2. Flash on heat dissipation holes - minor

	
3. Poor assembly on base - minor	4. Poor assembly on base - minor
	
5. Scratch mark on base - minor	6. Scratch mark on base - minor
	
7. Scratch mark on base - minor	8. Scratch mark on base - minor

(2) CRITICAL PARTS CHECK LIST

Object/ part NO.	Manufacturer	Type	Technical data	Certification	RESULT	PHOTO
Supply cord	Toong Yean Plastic Ind. Co.,Ltd.	H03 VVH2-F (60227 IEC 52)	2x0.75mm ²	KC	P	
Plug	Toong Yean Plastic Industrial Co.,Ltd.	TY-019	AC250V, 16A	KC	P	
Motor	Xiamen YOUo Intelligent Technology Co., Ltd	M7643CAV2223P 160F	AC220-230V 50-60Hz 900W, Class F	/	P	
Motor protector	You Xian Lian Cheng Electron Co.Ltd.	17AM1 039A5+PTC	AC 250V, 160°C	IEC	P	

Micro switch	Guangdong Yushun Electric Appliance Ltd.	KW-5	250V~, 5A, 3E4, T125	IEC	P	
Switch	zhejiang Jialong Electron Co., Ltd.	KAN-9-GG-1	250V~, 10 (3) A, T85, 10E3	IEC	P	

(3) Check the CDF record photos


Power plug	Toong Yean Plastic Industrial Co., Ltd	TY-019	AC250 V, 16 A	KC
- (Alt.)	Toong Yean Plastic Ind. Co., Ltd.	H05 VVH2-F (60227 IEC 53)	2 x 0.75 mm ²	KC
Motor	Xiamen YOUo Intelligent Technology Co., Ltd	M7643CAV22 23P160F	AC220 - 230 V 50 - 60 Hz 900 W, Class F	Tested with appliance
- Motor protector	You Xian Lian Cheng Electron Co. Ltd.	17AM1 039A5+PTC	AC 250 V, 160 °C	IEC
- Y capacitor	Success Electronics Co Ltd	SF	Y2, 300 V ~, 4 700 pF, 40 / 125 / 56	IEC
- (Alt.)	Tenta Electric Industrial Co., Ltd.	MEX	0.33 μF, 275 VAC, X2, 40 / 100 / 21	IEC
Power switch	Zhejiang Jialong Electron Co., Ltd.	KAN-9-CC-1	250 VAC, 10(3) A, T85, 1E4, GWT 850	IEC
Micro-switch/interlock Switch	GUANGDONG YUSHUN ELECTRIC APPLIANCE LTD	KW-5	10.1A, 125 / 250 V ~, 3 E4, T125; 10(5) A, 125 / 250 V ~, 1E4, T125, GWT 850	IEC

Remark:

The "CRITICAL PARTS CHECK LIST" and "Check the CDF record photos "are based on the KC report (report No. HU071120-23014C)

(4) SERIAL NUMBER of INSPECTED UNITS

SERIAL NUMBER FORMAT AND RANGE:	The numbers below
---------------------------------	-------------------



(5) DATA TEST

NO.	Test Item \Serial NO.	0217	0094	2513	1204	2519	2608	1864	3269	Blank	Blank
1	Rated Power NO-load power (244-320W)	304	307	298	294	299	301	309	289	Blank	Blank
	500mL load rated water test load power (650-760W)	693	706	698	703	687	691	699	704	Blank	Blank
	700mL load rated water test load power (720-890W)	789	795	799	803	788	783	800	791	Blank	Blank
2	Blending Water Test (1min)	PASS	PASS	PASS	PASS	PASS	PASS	PASS	PASS	Blank	Blank
3	Jar Leakage Test (1Hour)	PASS	PASS	PASS	PASS	PASS	PASS	PASS	PASS	Blank	Blank
Remark	The items (number1 to 3) are tested according to the S-2 standard, 8 products are selected for testing, and the test results are as above.										
NO.	Test Item \Serial NO.	1656	0014	1795	0103	1955	1704	1498	2471	0443	2483
4	Electric Strength (1500V/3mA/2s)	PASS	PASS	PASS	PASS	PASS	PASS	PASS	PASS	PASS	PASS
5	Leakege Current Test ($\leq$ 0.25mA)	PASS	PASS	PASS	PASS	PASS	PASS	PASS	PASS	PASS	PASS
6	Cord Length (85 $\pm$ 5cm)	PASS	PASS	PASS	PASS	PASS	PASS	PASS	PASS	PASS	PASS
Remark	1、The above items (number4 to 6) are tested according to the G II standard, and the data is only part of the test results, because the space limit does not show all the results.										
NO.	Test Item \Serial NO.	1286					2624				
7	No-load Speed Test (18000-22000rpm)	19830rpm					19435rpm				
NO.	Test Item \Serial NO.	1283					1515				
8	Noise Test $\leq$ 90dB (1m, 700mL)	76.8dB					77.4dB				

NO.	Test Item \Serial NO.	0387			2667	
9	Jar Container Capacity 700mL±35mL	701.0mL			700.5mL	
	Jar Container Capacity 500mL±25mL	500.5mL			501.0mL	
Remark	The items （number7 to 9）are tested according to the Finished product inspection specification,2 products are selected for testing, and the test results are as above.					
NO.	Test Item \Serial NO.	2415	2817	2116	1979	0755
10	Press the button force: 0.7-2.3kgf	1.4	1.4	1.2	1.3	1.4
	Jar lid and filp lid: Locking force is 1.5- 3kgf.cm	2.2	2.0	2.1	2.0	1.9
	Jar lid and filp lid: Un-locking force is 0.3-2.2kgf.cm	1.6	1.4	1.4	1.5	1.4
	Jar base and main housing: Locking force is 23-37kgf.cm, and the un-locking force is 2.6-18kgf.cm	Pass	Pass	Pass	Pass	Pass
	Jar and jar base: Locking force is 25kgf.cm, and the un- locking force is 15- 30kgf.cm	Pass	Pass	Pass	Pass	Pass
Remark	The item （number10）is tested according to the Finished product inspection specification, 5 products are selected for testing, and the test results are as above.					
NO.	Test Item \Serial NO.	1677				
11	Power cord tension as per IEC60335-1 requirement ≥6kgf	Pass				

(6) INFORMATION CHECK LIST

NO.	Item	DETAILS/POSITION	Result
1	VOLTAGE SYSTEM	220-230V, 50-60Hz, 900W	P
2	BAR CODE	ON GIFT BOX 8809686402625	P
3	ACCESSORIES	User manual*1、Jar (500mL) *2、Jar (700mL) *1、Cup cap*2、Blade base with blade*1	P



INSPECTION REPORT

REPORT NO. : [LZX20260514-1](#)

4	Printing	The PE bags and user manual printing match the reference drawings		P
(7) OTHER				
Item	Inspection Standard	DETAILS		结果 Result
Drop Test	ISTA-1A	Carton Box GROSS WEIGHT: 6.92kg DROP TEST SEQUENCE: 760mm SAFETY : PASS FUNCTION : PASS APPEARANCE : PASS		P
Carton size	445×361×353mm	447×365×355mm		P
Gift Box Size	346×215×333mm	350×218×340mm		P
HOTOEM Information Technology Company Limited		Liang Zixuan	Li Yanlin	
REPORTED BY		INSPECTOR' S SIGNATURE	FACTORY' S REPRESENTATIVE SIGNATURE	