

INSPECTION AGREEMENT

SUPPLIER	HOTOEM
MODEL	BL-E01

APPROVAL SIGNATURE	
HOTOEM	 25.5.29
HUROM	

Revision No.	0
Revision Date	2025.05.28

◆ TABLE OF CONTENTS

Standard	INSPECTION AGREEMENT	Supplier	HOTOEM
		Model	BL-E01

No	SUBJECT
1	Revision History
2	Summary of Inspection Agreement
3	Standard of Inspection

● Revision history

Standard	INSPECTION AGREEMENT	Supplier	HOTOEM
		Model	BL-E01

Record

Rev. No	Rev. Date	PAGE	Description	Written by	Approval by
0	'25.05.28		- First written	HOTOEM	HUROM

◆ Summary of Inspection Agreement

Summary of Inspection Agreement	Supplier	HOTOEM
	Model	BL-E01

No	SUBJECT
1	Supplier(HOTOEM)는 생산하는 모든 제품에 대한 출하검사를 실시하는 것을 기본 원칙으로 한다. 출하검사는 생산된 품목에 대하여 1일 이내에 진행하며 출하검사 결과는 해당 LOT가 선적되기 이전 Buyer(HUROM)으로 전달한다.
2	Buyer(HUROM)은 본 제품에 대하여 입고되는 모든 제품에 대하여 별도의 입고검사를 진행하는 것을 기본 원칙으로 한다. 단 Buyer(HUROM)을 통하지 않고 해외로 바로 수출되는 제품에 대해서는 별도의 입고검사를 생략한다. 입고검사는 입고 후 7일 이내에 진행하며 부적합 사항이 발생 시 10일 이내에 결과를 통보하며 Supplier(HOTOEM)는 해당사항에 대하여 14일 이내에 대책을 회신한다.
3	▶ 출하검사(HOTOEM) 판정기준 - 출하검사 기준서에 의거하여 진행 - 외관검사 기준은 별도 기준서(Apperance limit standard) 참조 ▶ 입고검사(HUROM) 판정기준 - 성능/안전 : AQL S1 Level (Critical=0, Major=2.5, Minor=4.0) - 외관/사양 : AQL S3 Level (Critical=0, Major=2.5, Minor=6.5)
4	Supplier(HOTOEM)는 제품에 대한 신뢰성을 보증하기 위하여 신뢰성 시험을 하기와 같이 실시한다. - 안전관련 : 1회/년 , 내구성관련 : 2회/년 - 환경(ROHS)관련 : 1회/년 상기 주기로 시험을 실시하며 결과를 Buyer(HUROM)로 전달한다.

◆ Summary of Inspection Agreement

Summary of Inspection Agreement	Supplier	HOTOEM
	Model	BL-E01

No	SUBJECT
1	The Supplier (HOTOEM) is responsible for the outgoing inspection of all products in produced. The outgoing inspection shall be conducted within 1 day for the all products in produced and outgoing inspection results are forward to Buyer(HUROM) before shipped.
2	The basic principle of Buyer (HUROM) conducts an additional incoming inspection for all products received for this product. However, The incoming inspection will be omitted for some products which products directly to export overseas markets without Buyer (HUROM). The incoming inspection shall be conducted within 7days after received products and if any nonconformities occur, the results shall be notified within 10 days. The Supplier (HOTOEM) will respond to the action within 14 days.
3	► The outgoing inspection criteria - It will be proceed according to the QC standard file. - Standard of apperance will be according to the appendix file ► The incoming inspection(HUROM) criteria - Performance/Safety : AQL S1 Level (Critical=0, Major=2.5, Minor=4.0) - Appearance/specification : AQL S3 Level (Critical=0,Major=2.5,Minor=6.5)
4	To ensure reliability of the product, the Supplier (HOTOEM) shall conduct a reliability test as follows. - Regarding the Safety : once/year, Regarding the Durability : twice/year - Regarding the Environment(ROHS) : once/year The reliability tests are conducted at the cycles mentioned above and the results are forward to the buyer (HUROM)..

一、Description 说明

1. Applicable customer : General 适用客户: 通用

客户若有特殊品质要求的项目, 结合相关客户的《客户品质要求》检验; 相关安全要求结合 IEC60335-1 标准制定的,若其中有部分内容与上述文件产生冲突者,则采用较为严格的要求。

If the customer has items with special quality requirements, the inspection shall be carried out in combination with the "Customer Quality Requirements" of the relevant customer. The relevant safety requirements are formulated in accordance with the IEC60335-1 standard. If any part of them conflicts with the above-mentioned documents, the stricter requirements shall be adopted.

고객이 특수 품질 기준 요구 있는 프로젝트에 대해서 고객의 <품질기준요구>에 따라 검사한다. 유관 안전 기준은 IEC60335-1 과 결합하여 제정하고, 그중에 부분 내용과 상기 말한 문서와 충돌한 경우 더 엄격한 것을 기준으로 한다.

2. 适用机种 model: Y-928 table blender、研磨杯 grinder jar: 300mL、个人杯 tumbler jar: 600mL、绞肉杯 chopper jar: 450mL; 果汁杯 blending jar: 1500mL
电气规格 electric Spec.: 220V-240V 50-60Hz 1000W



注.: (以上图片仅供参考, ,具体详见 ID Spec) Note: (The above pictures are for reference only. For details, please refer to ID Spec.)

3、检查类型: 适用成品抽样检查。

Inspection type: Applicable to finished product sampling inspection.

검사 유형: 완제품 샘플링 검사

4、权责部门: 由品技部派检验员实施抽样检查。

The responsible department: The Quality and Technology Department will dispatch inspectors to conduct sampling inspections.

담당 부서: 품질 기술 검사원이 샘플링 검사 실시한다

5、抽样方案: 依 ISO 2859 (即 GB2828) 正常检查一次抽样检查方案 II 级水平。

Sampling plan: In accordance with ISO 2859 (i.e. GB2828), conduct a normal inspection at the level of Grade II of the sampling inspection plan.

샘플링 기준: ISO 2859(즉,GB2828)에 의하여 정상검사 1Ⅱ 회 샘플링 검사 Ⅱ로 한다

核准:

审核:

制定:罗文 2025-5-9

不良区分及 AQL 水平: 根据不良对产品质量及安全的影响程度, 分为:

A 致命不良 CR=0

指对人体生命及财产会造成危险或威胁, 会被客户当场退回的不良。

Defect classification and AQL level: According to the degree of impact of defects on product quality and safety, it is divided into:

A CR=0

It refers to something that poses a danger or threat to human life and property and will be returned on the spot by the customer.

인체 생명 혹은 재산에 일으키는 위험 및 위협, 고객이 당장 반품한 불량

B 严重不良 MA=1.0

任何客户(消费者)皆不愿购买之不良与正常适用时的不良或外观严重不良, 且须更换零件者。

B MA=1.0

Any defective product that no customer (consumer) wishes to purchase, is in poor condition during normal use, or has a seriously poor appearance and requires replacement of parts.

고객이 구매를 싫어하는 불량 및 정상 사용시의 불량 및 외관 심한 불량, 그리고 부품 교체

필요할 것

C 轻微不良 MI=4.0

对较挑剔的消费者不愿购买之不良或勿须其他特殊工具即可修正之不良。(如螺丝松动或外表污渍等)

C MI=4.0

Defects that are reluctant to be purchased by more discerning consumers or can be corrected without the need for other special tools. (Such as loose screws or surface stains, etc.)

까다로운 소비자가 구매를 싫어한 불량 혹은 기타 특수 도구로 수정 가능한 불량 (볼트

풀림 및 외관 오염등)

6、未标明抽样水平的测试项目依 I 级水平, 首件必须做全项目检查。

For test items without indicated sampling levels, at the level of Grade I, the first item must undergo a full inspection.

샘플링 기준을 표기하지 않은 프로젝트는 I 급으로 하고, 초도샘플은 전체 항목 검사 필수

二、drop test 落地实验

1、每制令之首次提交批, 在抽样的样品中任取一台彩盒包装之成品, 依客户要求标准进行落地, (若没有客户要求, 则按《国际安全运输协会包装运输标准》进行落地), 并记录测试方法和结果。

For the first batch of each order submitted, any one finished product in color box packaging is selected from the sampled samples and landed in accordance with the customer's required standards (if there is no customer's requirement, it shall be landed in accordance with the "International Association for Safe Transport Packaging and Transport Standards"), and the test methods and results shall be recorded.

매 제조 명령의 초도 제출 로트, 샘플링된 샘플중에 임의의 1 대를 포장박스 상태로 고객의

기준으로 낙하시험 진행하고(고객이 요구 없을 경우 <국제 안전 운송 협의 포장 운송

核准:

审核:

制定:罗文 2025-5-9

기준>으로 낙하 진행한다.) 시험 방법 및 결과 기록

2、Following the lata standard for packaging and transportation requirement 《国际安全运输协会包装运输标准》：单体 92CM，整箱根据相应的重量对应的高度在 30mm 的硬木板按一角三棱六面进行。

단품: 92 츠, 포장된 중량에 따라 높이가 30mm 인 나무판에 1 각 3 능 6 면으로 진행

A: 重量 Weight : 0.453—9.5kg, 高度 Height: 76.2cm

B: 重量 Weight: 9.51—18.56kg, 高度 Height: 61cm

C: 重量 Weight: 18.57—27.63kg, 高度 Height: 46cm

D: 重量 Weight: 27.64—45.3kg, 高度 Height: 31cm

3、结果 Result: A、The function should be normal and no abnormal noise; Appearance parts should be no damage or serious deformation etc.

使用功能应正常且无异音；外观部件应无破损或严重变形、凹陷等不良；

B、B、If the product has cracked, the IEC test finger cannot touch the charged body when tested.

有破裂的地方用 IEC 测试指测试不能触及到带电体；

C、Need to pass the pressure test: 1500V/5mA*2S(Test the motor shaft, main housing and button switch location)

要能通过耐压测试：1500V/5mA*2S（测试马达轴，产品外壳及按钮开关位置）。

三、Test items 成品果汁机检验项目：

包括成品果汁机电气性能检验、功能测试、电源线及插头检查、结构检查、外观检查、印刷包装检验。

This includes electrical performance inspection, functional testing, power cord and plug inspection, structural inspection, appearance inspection, and printing and packaging inspection of the finished juice machine.

전기 성능검사, 기능시험, 전원코드 및 플러그 검사, 구조검사, 외관 검사, 인쇄포장 검사 포함한다.

核准：

审核：

制定:罗文 2025-5-9

1. 成品电气性能检验项目 Finished product electrical performance inspection items _ 전기 성능 검사 항목 :

1.1 耐压测试 Hi-pot test 내전압

1.2 泄漏电流测试 Leakage current test 누설전류

1.3 功率测试 power test 출력시험

1. 成品功能测试项目（产品若有以下功能时）

Finished product function test items (when the product has the following functions)_ 기능 검사 항목:

2.1 打水测试 Blending water test 물 교반

2.2 检漏测试 Jar leakage test 누수시험

2.3 转速测试 RPM test RPM 시험

2.4 噪音测试 Noise test 소음시험

2.5 杯体容量检查 Jar Container Capacity 용기용량

2.6 整机各部件配合力度检查 Operating force test 제품 각 부품 매칭 힘 검사

2. 成品电源线及插头检查项目 _전원코드 및 플러그:

3.1 电源线的规格型号及材质 Check the power cord model and material 전원코드 사양 규격 및 재질

4. 结构检查 structural inspection _구조검사

5. 成品外观检查项目 Finished product appearance inspection items _제품 외관검사

6. 印刷及包装检查项目 Printing and packing check items_인쇄 및 포장:

6.1 外箱 master carton 외상자

6.2 彩盒 gift box 포장박스

6.3 说明书/保修卡/贴纸 Instruction manual/Warranty card/sticker 사용설명서,보증카드,스티커

6.4 内衬 Lining 이너

6.5 PE 袋 PE bag PE 비닐

6.6 内有异物检查 Check if there is a foreign body 내부 이물질

核准:

审核:

制定:罗文 2025-5-9

序号 N o.	检验项目 Test item	技术要求 Technical requirements	检验方法 Inspection method	抽样方案 Sampling plan	判定标准 criterion
1.1	electric strength 电气强度	Electric Strength test: 1500V/5mA*2Sec, non-breakdown and flickering during tested the motor shaft, main housing and button switch location. 耐压测试：1500V/5mA*2Sec 测试马达轴位置，产品外壳及按钮开关位置不可击穿、闪烁。 내전압: 1500V/5mA*2Sec 로 모터 축, 제품 외피, 버튼 스위치를 시험한다. 터짐 및 깜빡이 없을 것	withstand voltage tester 耐压仪 내접안기	II级	CR
1.2	Leakage current test 泄漏电流测试 누설 전류	Test at 1.06 times the rated voltage, the leakage current within 5 seconds is $\leq 0.25\text{mA}$. (Note: Leakage testing is required for both ON and OFF states). 以 1.06 倍额定电压测试,5 秒内泄漏电流 $\leq 0.25\text{mA}$.(注：ON 和 OFF 状态均需测试泄漏). 1.06 배 정격전압으로 5 초이내의 누설 전류가 $\leq 0.25\text{mA}$ (PS: ON & OFF 상태 모두 누설 측정)	Leakage current meter 泄漏电流仪 누설 전류계	No-load condition is level I, and Load condition is level S-2	CR
1.3	power test 功率测试 기능 시험	Define the standard based on 230V power. 1. 1500ML blending jar no-load power (with clutch) : Setting 1 power: 280-342W; Setting 2 power: 408-525W; Setting P power: 408-525W; 2. Chopper jar power(with S blade): Setting 1 power: 240-420W; Setting 2 power: 345-610W; Setting P 330-635W; 3. Blending water power((1500ML rated capacity water) : 772-944W; 以 230V/50HZ 额定电压测试 1. 空载功率(带离合器)：一档功率：280-342W；二档功率：408-525W； P 档功率：：408-525W； 2. 绞肉杯功率(带 S 刀)：一档功率：240-420W；二档功率：345-610W； P 档功率：330-635W； 整机打水功率（1500ML 额定容量水）：772-944W； 2、超出规定范围 $\leq 10\text{W}$ 규정 범위 $\leq 10\text{W}$ 를 초과함 3、Exceed the prescribed limits $10\text{W} < X \leq 20\text{W}$ 超出规定范围 $10\text{W} < X \leq 20\text{W}$ 규정 범위 $10\text{W} < X \leq 20\text{W}$ 를 초과함	Power instrument 功率仪 目视 visual	空载按 I 级 负载按 S-2	MI MA

核准: 审核: 制定:罗文 2025-5-9

成品检验规范

NO:QA-25-109- 版本号: 01

2.1	Blending water test 打水 测试 물고 반 시험	Put on the rated voltage of the product, screw the jar with the rated capacity of water into the main machine, and test it in high speed for 1 minute. No leakage is allowed at the jar holder and no overflow is allowed between the jar holder and the blade holder for a short time(Only for 1500ML blending jar). 将产品接通额定电压, 将装好额定容量水的杯子旋入主机, 以高速档测试 1 分钟,杯座处不可有漏水现象及打水片刻杯座与刀座之间不可溢水(只适用于 1500ML 果汁杯)。	manual operation 手动 수동	S-2	MA
2.2	Jar leakage test 检漏 测试 누수 시험	1. Put the tumbler/chopper jar/blending jar into the rated capacity of room temperature water, 2. Use 30Kgf.c m² torque to screw the measured jar lid or jar holder into the tumbler, and put it upside down for 1H without leakage. 3. Use 30Kgf.c m² torque to screw the measured jar lid or jar holder into the chopper jar/ blending jar, and put it upside down for 1H without leakage. 1.将个人杯/绞肉杯/果汁杯装入额定容量常温的水, 2. 个人杯用 30Kgf. c m ² 的扭力将被测杯盖或底座旋入杯内, 倒置静放 1H 不能出现漏水。 3. 绞肉杯/果汁杯用 30Kgf. c m ² 的扭力将被测底座旋入杯内, 倒置静放 1H 不能出现漏水。	Torsiomet er, Fixture, Stop Watch 扭力计 夹具 秒表 토크계 지그 타이머		MA
2.3	RPM test 转速 测试	Test after the main machine runs 30S(test the clutch): For 230V/50Hz, the no-load speed on setting P is 23600±10%RPM. 以 230V/50Hz 主机运行 30S 后测试: (测试离合器) 最大档空载转速为: 23600±10%rpm;	频闪仪 变频电 源 strobo scope 변압기	2PCS 每 栈板 팔렛 별 2pcs	MA
2.4	Nois e test 噪音 测试 소음 시험	Measured the distance in any direction from the product is 1m, and the noise is ≤ 90dB under the 1500ml water load. 距离产品 1m 处任何方向测量, 杯子装 1500mL 的水测试, 打水的噪音应≤90dB。 제품 1m 인 거리에서 임의의 방향으로 시험한다. 용기에 1500ml 인 물을 넣고 작동 소음이 ≤90dB 이어야 한다.	噪音仪 noise- monito ring equip ment 소음계		MA

核准:

审核:

制定:罗文 2025-5-9

2.5	Jar	Tumbler capacity: 600±30mL(With a capacity tolerance of ± 5%) 1500ML blending jar capacity: 1500±75mL(With a capacity tolerance of ± 5%) 将空杯子称好重量后电子秤归零,往杯内加水至指定的杯体标示容量,最后称出所得的重量，个人杯：600mL±5%、果汁杯 1500mL±5%。	电子称	MA
	Container		水	
	Capacity		electronic scale,	
	杯体		water	
	容量		전자저울	
	检查		물	
	용기			
	용량			


2.6	Operating force test 整机各部件配合力度检查 부품매칭 힘	1. 旋钮开关：1 档力值范围 0.2-1.7kgf. cm 2 档力值范围 0.2-2.0kgf. cm; P 档力值范围 0.3-2.5kgf. cm; Knob: Setting 1 force: 0.2-1.7kgf.cm; Setting 2 force:0.2-2.0kgf.cm Setting P force:0.3-2.5kgf.cm. 2. 果汁杯组与主机组：扣进力力值 16-40kgf. cm; 松退力力值 9-30kgf. cm; Blending jar assembly and main base: Locking force is 16-40kgf.cm and un-locking force is 9-30kgf.cm. 3. 果汁杯与杯座组：旋紧力力值30kgf. cm ； (杯座的三角形与容器的锁扣标识最左边对齐的力值) 松退力力值 18.5-30kgf. cm; Blending jar and jar base: Locking force is 30kgf. cm (The triangle of the jar base and the lock of the container Mark aligned on the far left). And un-locking force is 18.5-30kgf. cm. 4. 果汁杯与果汁杯盖组：打开力值 1.3-4kgf. cm; 闭合力值 0.8-4kgf. cm. Blending jar and jar lid: Open force is 1.3-4kgf.cm, and close force is 0.8-4kgf.cm. 5. 小盖与果汁杯盖组：扣进力力值 1.5-17.5kgf. cm; 松退力力值 2.5-17.5kgf. cm; Blending jar lid and cap: Locking force is 1.5-17.5kgf.cm and un-locking force is 2.5-17.5kgf.cm.	扭力计 torsiometer	夹具 Fixture	实际操作 actual operation	first article inspection 首件检查 초품검사	MA
-----	---	---	--------------------	---------------	--------------------------	--	----

	6. 研磨杯与杯座组：扣进力力值 30kgf. cm；(杯座的三角形与容器的锁扣标识最左边对齐的力值) 松退力力值 12. 5-31. 5kgf. cm; Grinder and grinder base: Locking force is 30kgf. cm (The triangle of the jar base and the lock of the container Mark aligned on the far left).and un-locking force is 12. 5-31. 5kgf. cm. 7. 研磨杯组与主机组：扣进力力值 8. 5-35kgf. cm; 松退力力值 6. 5-30kgf. cm; Grinder assembly and main base: Locking force is 8. 5-35kgf. cm and un-locking force is 6. 5-30kgf. cm. 8. 绞肉杯与绞肉杯座组（如果力值出现偏差允许多次测量进行判定）。：扣进力力值 ≤ 30kgf. cm; 松退力力值 15-35kgf. cm; Chopper and chopper base(If there is a deviation in the force value, multiple measurements are allowed for determination): Locking force is ≤ 30kgf. cm and un-locking force is 15-35kgf. cm. 9. 绞肉杯组与主机组：扣进力力值 14-38kgf. cm; 松退力力值 7-30kgf. cm; Chopper assembly and main base: Locking force is 14-38kgf. cm and un-locking force is 7-30kgf. cm. 10. 个人杯盖组与个人杯：扣进力力值 30kgf. cm; 松退力力值 20. 5-36kgf. cm; Tumbler lid and jar: Locking force is 30kgf. cm and un-locking force is 20. 5-36kgf. cm. 11. 个人杯盖与个人翻盖：扣进力力值 2-10kgf. cm; 松退力力值 1. 5-10kgf. cm; Tumbler lid and cap: Open force is 2-10kgf. cm and close force is 1. 5-10kgf. cm.			
--	---	--	--	--

3.1	Check the power cord 电源线检查 전원코드 검사	A、电源线材质、耐温、截面积（$S= \pi r^2n$，n=线芯数）、规格符合要求（首件检查） Material, temperature resistance, cross-sectional area ($S=\pi R^2 n$, n= number of cores) and specifications of power cord all meet the requirements (first item inspection). 전원코드 재질 내고온, 절단면적 ($S= \pi r^2n$, n=선심수량)、규격은 준에 부합한다. (초도샘플 검사) B、插头不可有毛边或成型不良；电源线外露均需：85±5cm, H03VVH2-F 线，插头为两圆插.黑色电源线 The plug must not have burrs or poor shaping. The exposed length of power cord should all be 85±5cm, H03VVH2-F wire, and the plug should be two round plug. Black power cord. 플러그에 burr 혹은 성형불량이 없어야 하고, 전원코드 노출길이 : 85±5cm, H03VVH2-F 선, 플러그는 원형(2 개) C、电源线外露长度符合客户要求,不符（少 5CM 以上）。 The exposed length of the power cord meets the customer's requirements, if not (More than 5CM). 전원코드 노출길이 고객 기준에 부합한다. 부합하지 않을 것(5cm 이상 적을 시)	目测 卷尺 Visual ; flexible rule	II级	MA
		D、电源线外露长度符合客户要求,不符（少 5CM 以内）。 The exposed length of the power cord meets the customer's requirements, if not (Less than 5CM). 전원코드 노출길이 고객 기준에 부합한다. 부합하지 않을 것(5cm 이내 적을 시) E、电源线不允许异色，脏污，印刷不良，插头压伤。 The power cord must not be of different colors, dirty, poorly printed or have the plug crushed. 전원코드에 이색, 오염, 인쇄불량, 플러그 손상이 없을 것			MI

4.1	The whole Machine fit inspection 整机配合检查 제품 조립 검사	1. Check the cooperation between the jar holder and the main machine: after the jar holder and the jar body are put into the main machine, they should be able to press down the micro switch and fall into the upper body. They cannot be put out of place.(MA) 2. The micro switch could not reset or jam, it is MA issue. 3. The motor axis and the main body hole shall ensure their concentricity, and the concentricity fixture shall be able to pass through smoothly. Otherwise, MA shall be determined. 4. When the blade holder is matched with the jar, rotate the upper clutch 360°, and it is CR defect that the blade touches the jar wall. 1. 杯座与主机配合检查：杯座与杯体放入主机后要能将微动开关压下并落到上本体内，不可放不到位。 2. 微动开关不回弹或卡涩。 3. 马达轴心与本体孔应保证其同心度,同心度治具应能顺利穿过。 4. 刀座与杯子配合后，旋转上离合器 360° ,刀片碰到杯壁为 CR 缺陷。	手动 目测 Manual visual 수동 육안	S-2	MA
		5. Check the jar lid and jar, after assembly, it should be smooth and assembly in place. 杯盖与杯子配合检查：杯子与杯盖及杯座装配，应能顺畅并可旋到位。	手动 manual 수동		MA

4.2	Screw torque test 螺丝扭力测试 볼트 토크	1. All parts of the lock screw specification/material to meet the technical requirements. 2. All parts of the screw can not be locked out of place/loose/lock hole, rust, etc. 3. The torque between the blade assembly and the upper clutch should be $\geq 3\text{kgf.cm}$. 4. The torque force of the locking metal screw shall be no less than 5kgf . 5. The torque force of locking non-metallic screws shall be no less than 3kgf. 6. If the torque is insufficient, the twisting Angle should be above 180 degrees. 1. 各部位锁附螺丝规格/材质符合技术要求。 각 부위 나사 체결 규격/재질은 기술 기준에 부합한다 2. 各部位螺丝不可锁不到位/配合松动/锁穿孔，螺丝生锈等。 각 부위 나사 제대로 조립 안됨/풀림/체결 과잉/발청 등이 없어야 한다 3. 刀片组与上离合器的扭力应$\geq 3\text{kgf.cm}$。 칼날모듈과폴리(상)의 토크는 $\geq 3\text{kgf.cm}$이어야 한다 4. 锁金属螺丝扭力需不小于 5kgf 测试，不可滑牙，螺丝断。 금속 나사 토크는 5kgf 이상으로 시험하고 체결 불량 및 나사 끊어짐이 없어야 한다 5. 锁非金属螺丝扭力需不小于 3kgf 测试，不可滑牙，螺丝断。 비금속 나사 토크는 3kgf 이상으로 시험하고 체결 불량 및 나사 끊어짐이 없어야 한다 6. 若扭力不足，扭动角度在 180 度以上。 토크 힘 부족하면 회전 각도는 180 도이상 이어야 한다.	目视 扭力计 手动 Visual ; torsion meter ; manual 육안수 동검사 토크계 수동	首 件 检 查	MA
		7. If the torque is insufficient for fixing the motor assembly. 若固定马达组的螺丝扭力不足。 모터모듈의 나사 토크 부족 시			MI

4.3	internal connection 内部连接 内部连接 内部连接	1. A.Motor specification is M7643CA2224P160F AC220-240V/50-60HZ/1000W Y-928; 马达的规格为：M7643CA2224P160F AC220-240V/50-60HZ/1000W Y-928 B、保护装置及其固定在定子漆包线的方式：带温控器（PTC160℃双保护）装置，铁扎带固定紧贴在定子漆包线表面。 The protective device and its fixation method on the stator enameled wire: equipped with a temperature controller (PTC160℃ dual protection) device, and the iron cable tie is tightly fixed on the surface of the stator enameled wire. 보호장치와 정자코일에 고정 방식: 온도제어장치 있음(PTC160℃ 2중보호), 타이로 고정하여 정자코일 표면에 밀착하게 고정 C、PTC 的扎线带;扎带绑紧与线圈之间不能有明显的间隙； 及保险碳刷左右两边必须要有凸点，防止碳刷寿命结束后弹簧和线芯被转子卷入。 PTC should use cable ties. The cable ties should be tightly bound and there should be no obvious gap between them and the coils. The left and right sides of the safety carbon brush must have protrusions to prevent the spring and wire core from being drawn in by the rotor after the carbon brush's service life ends. PTC 의 타이 : 타이와 코일 사이에 명확한 틈새가 없어야 하고, 또한 안전 브러쉬 좌우 양측에 도출한 점이 있어야 하며, 브러쉬 수명이 끝난 후에 스프링과 심선이 회전자로 회전되지 않길 방지한다. 碳刷与整流子接触，OK  碳刷装反，变成弹簧与整流子接触，NG  D、马达碳刷不可装反，如右图所示： The carbon brushes of the motor must not be installed in reverse, as shown in the right picture： 모터브러쉬 반대로 조립되지 않아야 한다. 우측 그림과 같이 1. 微动开关的规格为：KW-5 10.1A 125/250VAC /10(5)A 125/250VAC；焊锡无虚焊、锡珠、锡渣等不良。 The specification of the microswitch is: KW-5 10.1A 125/250VAC /10(5)A 125/250VAC; There are no defects such as false soldering, solder beads or solder slag in the solder. 마이크로스위치 규격：KW-5 10.1A 125/250VAC /10(5)A 125/250VAC 납땜에 제대로 용접되지 않음/용접 구슬/찌꺼기 등 불량이 없을 것 2. 旋钮开关：型号 RS1 3A 6A 125/250VAC T125 Knob: model is RS1 3A 6A 125/250VAC T125 3. PCB：Y-921-EMC	目测 Visual	耐压机 Hi-pot tester 내전압기	拉力计 tension meter 인장력계	目视 visual	首件检查 first article inspection MA

成品检验规范

NO:QA-25-109- 版本号: 01

		4. 马达连接导线规格为: 20AWG, 线材为 1015#, 火线为红色, 零线为蓝色。 The specification of the motor connection wire is: 20AWG, the wire material is 1015#, the live wire is red, and the neutral wire is blue. 모터 도선 규격:20AWG, 재질:1015#, 빨간색 L 선, 파산색 N 선 5. 配线不可破皮:线皮破, 未见线芯, 施加 1500V/3mA /2S 高压测试,有耐压不良。 The insulation of the wiring must not be broken: The insulation of the wire is broken, the core of the wire is not visible, and a high-voltage test of 1500V/3mA /2S is applied, indicating poor voltage resistance. 배선 피복에 파손이 없어야 한다: 피복이 파손되고 선심이 보이지 않으면, 1500V/3mA /2S 로 고압시험 하고, 불량 발생할 것			CR
		6. 导线与开关焊接拉力要>1.5kgf/ 3 秒。 The welding tensile force of the wire and the switch should be greater than 1.5kgf per 3 seconds. 도선과 스위치 용접 인장력 >1.5kgf/ 3 초이어야 한다 7. 所有线芯与开关焊锡的部分都要钩焊。 All the parts where the wire cores are soldered to the switch must be hook-soldered. 모든 선심과 스위치 납땜 부분이 모두 후크웰딩되어야 한다.			MA
		8. 电源线拉力依 IEC60335-1 中要求: 或参照文件编号 “QA-10-011-024 第 2 版”, 当 产品重量≤1kg 时, 用 3kgf 的力, 当产品重量>1 且≤4kg 时, 用 6kgf 的力以最不力的方向拉 25 次,每次持续 1 秒,线芯与绝缘层位移不可超过 2mm。 The tensile strength of the power cord is in accordance with the requirements of IEC60335-1: Or refer to the document number “QA-10-011-024 2nd Edition”. When the product weight is ≤1kg, apply a force of 3kgf. When the product weight is > 1 but ≤4kg, apply a force of 6kgf and pull 25 times in the weakest direction, each time for 1 second. The displacement between the wire core and the insulation layer should not exceed 2mm. 전원코드 인장력은 IEC60335-1 에 따르다. 혹은 문서 “QA-10-011-024 제 2 버전” 을 참조한다. 제품 중량이 ≤1kg 시, 3kgf 의 힘을 사용, 제품 중량이 >1 또한 ≤4kg 시 6kgf 의 힘으로 가장 불리한 방향으로 25 번을 당기고 매번 1 초동안 유지 한다. 선심과 절연층의 위치 이동은 2mm 를 초과하지 않아야 한다	吊磅 Crane Scale 크레이 저울		CR
4.4	safe distance 安全距离 안전거리	According to the TUV safety regulations, the distance between live parts and between live parts and non-live parts must be should be >3mm. 以 TUV 安规要求: 带电体与带电体间,带电体与非电体间距离须>3mm。 TUV 기준: 통전부와 통전부 사이, 통전부와 비통전부 사이의 거리 >3mm	手指测 试仪 Finger tester 핑거시 험기		CR

核准:

审核:

制定:罗文 2025-5-9

NO:QA-25-109- 版本号: 01

1. 擦拭检查 Wipe inspection: 1) 成品表面不可有脏污，灰尘，异物。整体外观相同色件颜色无明显色差\变形\毛边,无明显划痕\碰伤\汽泡\污渍等。 The surface of the finished product must not have dirt, dust or foreign objects. The overall appearance of the same-color parts shows no obvious color difference, deformation, burrs, obvious scratches, dents, bubbles, stains, etc. 제품 표면에 오염/먼지/이물질이 없어야 한다. 전체 외관 같은 색상 부품들이 뚜렷한 색차/변형/burr/스크래치/찍힘/기포/오염등이 없을 것 2) 商标印刷:标识字体居中,线条粗细一致,字迹清晰,无漏字\色差（参考 ID SPEC） Brand logo printing: The font of the logo is centered, the line thickness is consistent, the handwriting is clear, and there are no missing characters or color differences (refer to ID SPEC) 상표 인쇄: 표시 문자 중간으로 하고, 굵기 일치하고, 글자 뚜렷하고, 글자 누락 및 색상 차이 없을 것 (ID Spec 참조)	
3) 底盖模印商标、客户型号、电气规格、安规认证标志、产地、警告语等符合相关要求。（此项判 CR） The bottom cover is imprinted with trademarks, customer models, electrical specifications, safety certification marks, place of origin, warning statements, etc. in compliance with relevant requirements. (This item is judged as CR) 밑판에 상표/ 고객모델/전기가양/안전인증표시/원산지/경고문구 등이 유관 준에 부합한다.	

目視
visual
육안

MI

第 15 页 共 22 页

	4) 商标印刷附着力在首件检查时随机测试 1 台应能通过以下两种方式测试: The adhesion of trademark printing should be randomly tested on one unit during the first piece inspection. It should be able to be tested through the following two methods: 상표 인쇄 부착력은 초도 샘플 검사 시 1 대를 시험해서 아래 2 가지 방식인 시험을 통과할 수 있다. A、810 胶带测试: 将胶带紧贴附于印刷表面,以 45 左右角度迅速将胶带拉起,连续测试三次,每次必须保证用新胶带。测试后不能完全断线或脱落。 810 Tape test: Attach the tape tightly to the printed surface, quickly pull it up at an Angle of about 45 degrees, and test it three times in a row. Each time, make sure to use a new tape. The test should not be completely disconnected or detached. 810 테이프 시험: 테이프를 인쇄표면에 밀착하게 붙이고 45 도 각으로 테이프를 신속히 당긴다. 3 번 연속하고, 매번 테이프 교체한다. 시험한 후 떨어지지 않아야 한다. B、75%酒精测试: 以蘸 75%酒精的软布条轻轻(约 1.5kg 的力)擦拭来回 15 次,测试后不能出现完全断线或脱落现象。 75% alcohol test: Gently wipe back and forth 15 times with a soft cloth dipped in 75% alcohol (with a force of about 1.5kg). After the test, there should be no complete thread breakage or detachment. 75% 알코올: 75% 알코올을 묻힌 면포 (약 1.5kg 의 힘)으로 왕복 15 번을 닦는다. 시험한 후 떨어지지 않아야 한다.	810 胶 带 810 tape 810 테 이프 75% 酒 精 75% alcohol 75%알 코올 手动 manual 수동	2PCS 每 栈板 팔렛 당 2pcs	MA
--	--	---	--	-----------

	1. Appearance and clearance coordination inspection: 1) part color should be correct (refer to ID Spec). 2) no color difference is allowed in the coordination of parts; No hair or other dirt is allowed inside the jar. No cracks, breakage or burrs are allowed on the outside. 3) the gap between the bottom base and the lower body is less than 0.5mm; Bottom base thimble and drain must not have rough edges. 4) The gap between jar lid and flip lid should be ≤1.0mm. 5) Defective labels and other inappropriate labels shall not be attached to finished products (CR) 6) the clutch shall be rotated in place and shall not fall off. The flatness shall be tested and the screw teeth of the thread shall not be deviated. 7) the size of the inner hole of the blade holder should be standard, the blade should not rust or deform, and the jar holder should be rotated 360° after matching with the jar body.The blade shall not touch the jar wall. 8) the operation of the micro switch should be smooth and not jam. 9) the whole machine shall be tested on the workbench, and no traces shall be found on the foot pad. 10) The flip lid can stay and remain in any position when opened. 11) Possible damage Poor Burr (CR)/crack, broken(MA) Scratches, poor coating (MI) 4.外观及间隙配合检查 외관 및 틈새 검사: 1) 部品颜色要正确（参考 ID Spec）。 부품 색상이 정확해야 한다. (ID Spec 참조) 2) 部品配合不可有色差; 杯体内不可出现头发或其他脏物,外表不可有裂纹、破损、毛边。 부품 매칭에 색상차이 없어야 하고, 용기내에 머리카락 혹은 기타 오염물이 없어야 하고, 외관에 균열/파손/burr 가 없을 것 3) 底座与下大身配合间隙或断差≤0.5mm；底座顶针和排水口不可有毛边。 밀판과 하부 본체 조립 GAP 혹은 단차≤0.5mm, 밀판 핀과 배수구에 burr 가 없을 것 4) 杯盖与翻盖扣合间隙应≤1.0mm。 용기뚜껑 + 마개 틈새 ≤1.0mm 이어야 한다 5) 成品上不可贴有不良标签和其它不适宜的标签（判 CR） 제품에 불량 스티커 혹은 기타 비적합 스티커 없을 것 (CR 판정) 6) 离合器需旋到位且不可脱落,必须测试平整度不可歪斜，其螺纹的螺牙方向不可错。 폴리가 제대로 회전해야하고 풀리지 않아야 한다. 평정도 시험하고 비틀어지지 않아야하고, 나사탭 방향이 정확해야 한다. 7) 刀座内孔的尺寸要标准，刀片不可生锈、变形，与杯体配合后旋转杯座 360° 刀片不可碰到杯壁。 칼날베이스 내부구멍 치수 표준해야한다. 칼날에 발청/변형이 없어야 하고, 용기와 조립한후 360 도로 회전 시 칼날이 용기벽과 접촉 없을 것 . 8) 微动开关操作须顺畅,不可卡涩。 마이크로스위치 조작이 원활하고 걸리지 않을 것 9) 整机在工作台上测试,脚垫在工作台上磨擦不可有痕迹。 제품은 작업대에 시험시, 발판이 작업대에 마모되어 흔적이 남지 않을 것 10) 翻盖打开时可停留并保持在任何位置。 뚜껑을 열시에 멈출 수 있고 임의의 위치로 유지 가능 11) 有可能受伤害 Burr 不良（CR） / 裂痕，破损 不良(MA)刮痕，涂层不良 (MI) 상해 입힐수 있는 burr (CR)/파열 파손(MA)/스크래치 도장불량(MI)	目测 visual 육안 塞规 plug gauge 틈새계 이지 手动 manual 수동	II 级	MI MA
--	---	---	---------------------	----------------------

		12)Check that the body of the jar can not be dirty, and the lid should be firmly matched. 检查杯体内不能有的脏污，与杯盖配合要牢固。 용기내에 오염이 없어야 하고, 뚜껑과이 조립이 견고해야 한다.			MA
5.2	Check if there is a foreign body 内有异物检查	Pick up the product and shake it a few times: There is a metal foreign body. 拿起产品摇晃几下_제품을 흔들렀을 때: 有金属异物。금속 이물질 있는 것	目测 visual 육안	II级	CR
	내부 이물질	There are non-metallic foreign bodies. 有非金属异物。 비금속 이물질 있는 것			MA
5.3	Stability test 稳定性测试	Flatness check: put the product on a plane for stability test. Flatness (represented by d) of the machine shall be 0.5~1.0mm. 整机平坦度检查:将产品放在一个平面上进行稳定性测试，整机平坦度(以 d 表示)需 0.5~1.0mm 范围内 제품 안정성시험: 제품을 평평한 대면에 올려서 안정성 시험한다. 제품의 평탄도(d로 표현)는 0.5~1.0mm 범위에 있어야 한다.	平面玻璃 plain glass		MI
	안정성시험	若 if d>1.0mm	평면 유리 틈새게이지		MA

6.1	Master carton 外箱 원상자	The master carton printing should be same as the artwrok, and the appearance should be good. 1、外箱之尺寸体积符合印刷内容技术要求。（首检时必须检查） The size and volume of the master box comply with the technical requirements of the printed content. It must be inspected during the first inspection. 외상자 치수 용적은 인쇄 내용 요구에 부합(초도검사시 필수 검사) 2、外箱须装订良好，不可印刷不良、脏污、缺材、破损、潮湿、变形。 The master box must be well bound and must not have poor printing, be dirty, lack materials, be damaged, be damp or deformed. 외상자 잘 고정되어야 하고, 인쇄불량/오염/재로부족/파손/습기/변형 등이 없을 것 3、外箱之编号、盖章、贴纸（如条码、警告标志）须符合技术要求。 The C/T No., stamp and stickers (such as barcode, warning signs) of the master box must comply with the technical requirements. 외상자 번호/도장/스티커(코드, 경고문구)가 기준에 부합한다 4、外箱编号要求连续性，不可重复、遗漏，严格依客户要求或资料要求。 The C/T No on the master box must be continuous, without repetition or omission, and strictly in accordance with the customer's requirements or the data requirements. 외상자 번호가 연속성이 있어야 하고, 중복/누락이 없어야 하고, 고객 기준 혹은 자료요구에 따름 5、外箱要按要求使用胶带封粘，装入成品后须放平整，封贴平整，不可翘边，少粘胶。 The master box should be sealed and adhered with tape as required. After loading the finished products, they must be placed flat, sealed and pasted evenly, without lifting the edges and with minimal adhesive. 외상자에 요구에 따라 테이핑하고, 제품을 포장한 후 평평하고 완전하다. 스티커도 평평하고 완전하고, 들뜸이나 접착제 부족 없을 것 6、产品装入合箱后，间隙<3mm。 After the product is packed into the master box, and closed, the gap is less than 3mm. 제품 넣고 박스 조립한 후 틈새 < 3mm	目测 visual 육안	II 级	MI
-----	----------------------------	--	--------------------	---------	----

		7、外箱耐折度符合要求(上摇盖先向内折 90° ,再向外折 180° ,经开合 180° 往复 5 次, 纸箱面纸不可裂缝, 里纸板裂缝≤7mm。) (首件检查) The folding endurance of the master box meets the requirements (first fold the upper flap inward by 90°, then outward by 180°, and repeat the opening and closing of 180° five times. The surface paper of the carton must not crack, and the crack of the inner cardboard should be ≤7mm.) (First inspection) 외상자 내접이성이 기준에 부합한다(위 커버 먼저 안으로 90 도를 접고, 밖으로 180 도를 접는다.개폐 180 도를 5 번을 반복하여, 박스 표면 종이 파열이 없어야 하고, 안면 종이 파열이 ≤7mm)(초도샘플 검사) 8、不干胶字体资料正确, 字体印刷清晰, 色泽一致, 不许有印刷不良等现象。 The label font should be correct, the font printing should be clear, the color consistent, and there should be no poor printing or other such phenomena. 스티커 글씨체 자료 정확하고, 글자 인쇄 뚜렷하고 빛깔이 일치한다. 인쇄 불량 등 현상이 없을 것	手动 目测 Manual Visual 수동 육안		MA
6.2	Color box 彩盒 컬러 박스	The material, color, printing content should be same as the artwork. The barcode level shoule be above B. 1、彩盒之材质、颜色、印刷内容、印刷位置、客户商标、型号、电脑条码、产地、各认证标志、环保标志须符合要求。 The material, color, printed content, printing position, customer trademark, model, computer barcode, place of origin, various certification marks and environmental protection marks of the color box must meet the requirements. 컬러박스 재질/색상/인쇄내용/인쇄위치/고객상표/모델/바코드/원산지/각인증표시/환경보호표시 등 기준에 부합한다. 2、彩盒须粘牢, 不可脱胶, 条形码扫描等级需达到 B 级以上。 The color box must be firmly adhered without delamination, and the barcode scanning grade should reach B or above. 컬러박스 견고하고 풀리지 않아야 한다. 바코드 식별 등급이 B 급이상 3、彩盒耐折度、油墨附着力符合技术要求。(首件检查) The folding endurance of the color box and the adhesion of the ink meet the technical requirements. (First inspection) 컬러박스 내접이성,잉크 부착력 등이 기준에 부합한다(초도샘플 검사)	目测 visual 육안 扫描仪 scanner 스캐너 卷尺 flexible rule 줄자		MA

NO:QA-25-109- 版本号: 01

核准: 审核: 制定: 罗文 2025-5-9

		3. 保护膜垫付位置，垫付方向光滑面朝向成品表面。 The position where the protective film is placed, with the smooth side facing the surface of the finished product. 보호막 위치, 매끄러운 면이 제품 표면으로 향한다.			
6.6	Check if there is a foreign body 内有 异物 检查 내부 이물질 검사	1. Check the quantity of the complete machine in the MS is consistent with the actual situation. 2. The materials contained in each color box are consistent with the materials required in the BOM table. 3.Disgusting objects appear in color box or blister box (such as worms, rags, etc.) It is CR issue. 1、检查箱内整机数量与实际相符。 박스 내 제품 수량과 실제 일치 2、每个彩盒内所含物料于 BOM 表里所要求的物料一致，有漏装物料或错装物料现象。 각 포장박스에 포함된 부품이 BOM 표에 요구한 부품과 일치한다. 누락 및 착오 현상 있을 것 3、彩盒或吸塑盒里面出现恶心的物品（如虫子，抹布等）判 CR 포장박스 및 플라스틱 박스에 혐오감 일으키는 물질(벌레, 걸레등)CR			