




POLITECNICO
MILANO 1863

SCUOLA DI INGEGNERIA INDUSTRIALE
E DELL'INFORMAZIONE



PSI

Multi-Criteria Decision Analysis for the Evaluation of Nuclear Reactor Designs

TESI DI LAUREA MAGISTRALE IN
NUCLEAR ENGINEERING - INGEGNERIA NUCLEARE

Author: **Simone Pagliuca**

Student ID: 247812

Advisor: Prof. Stefano Lorenzi

Co-advisors: Prof. Russell McKenna, Dr. Peter Burgherr, Dr. River Huang

Academic Year: 2024-25

Abstract

Here goes the Abstract in English of your thesis followed by a list of keywords. The Abstract is a concise summary of the content of the thesis (single page of text) and a guide to the most important contributions included in your thesis. The Abstract is the very last thing you write. It should be a self-contained text and should be clear to someone who hasn't (yet) read the whole manuscript. The Abstract should contain the answers to the main scientific questions that have been addressed in your thesis. It needs to summarize the adopted motivations and the adopted methodological approach as well as the findings of your work and their relevance and impact. The Abstract is the part appearing in the record of your thesis inside POLITesi, the Digital Archive of PhD and Master Theses (Laurea Magistrale) of Politecnico di Milano. The Abstract will be followed by a list of four to six keywords. Keywords are a tool to help indexers and search engines to find relevant documents. To be relevant and effective, keywords must be chosen carefully. They should represent the content of your work and be specific to your field or sub-field. Keywords may be a single word or two to four words.

Keywords: here, the keywords, of your thesis

Abstract in lingua italiana

Qui va l'Abstract in lingua italiana della tesi seguito dalla lista di parole chiave.

Parole chiave: qui, vanno, le parole chiave, della tesi

Contents

Abstract	i
Abstract in lingua italiana	iii
Contents	v
Introduction	1
1 Literature Review and Objectives	5
1.1 Literature Review	5
1.2 Applying MAVT to choose a Reactor	6
2 Preparation	9
2.1 Criteria for Reactor Selection in Comparative Analysis	9
2.2 Country Selection for Comparative Analysis	13
2.3 Attribute Definition	13
2.3.1 Technical parameters	13
2.3.2 MOX Fuel Compatibility	14
2.3.3 Technological Readiness	15
2.3.4 Safety	15
2.3.5 Capital Costs	15
2.3.6 Commissioning Time	16
2.3.7 Operational Costs	17
2.3.8 Potential Impact on the energy market	17
2.3.9 Potential Impact on greenhouse gas emissions	18
2.3.10 Waste	18
2.3.11 Size - Nominal output power	18
2.3.12 Load Following Capabilities	18
3 Analysis	21

4 Results	23
Bibliography	25
A Appendix A	37
B Appendix B	39
List of Figures	41
List of Tables	43
List of Symbols	45
Acknowledgements	47

Introduction

A brief History of Nuclear Power

Origins

The 1930s and 1940s witnessed rapid advancement in nuclear science. In 1932 James Chadwick discovered the neutron [15] and a year later Leo Szilard hypothesized fission chain reactions. In 1938, Otto Hahn and Fritz Strassmann produced barium by bombarding uranium with neutrons, demonstrating nuclear fission [37]. These breakthroughs culminated in Enrico Fermi's team achieving the first controlled nuclear chain reaction in the Chicago Pile-1 in 1942.

Initial advancements were speeded up by World War II through the Manhattan Project and led to the atomic bombings of Hiroshima (6 August 1945) and Nagasaki (9 August 1945) but the recognition of the peaceful potential of nuclear technology led to the famous speech "Atoms for Peace" by USA President Eisenhower in 1953 to the United Nations [19] which established the foundation for international nuclear cooperation. The International Atomic Energy Agency (IAEA) and the European Atomic Energy Community (EURATOM) were established 4 years after, in 1957, and were tasked with promoting peaceful nuclear applications while serving as independent authorities for safety regulation and non-proliferation oversight.

In the 1950s numerous reactor designs were born driven by both, civilian and military necessities. The Experimental Breeder Reactor I (EBR-I) in Idaho (USA) first produced electricity in 1951 (powering four light bulbs), followed by the Obninsk Nuclear Power Plant (USSR) in 1954, which became the first to feed approximately 5 MWe into a local power grid. The world's first commercial-scale nuclear power station, Calder Hall-1 (UK), began operation in 1956, connected to the national grid with a capacity of 50 MWe. The United States pioneered the light water reactor development (LWR), originally developed in the military for naval propulsion, launching the USS Nautilus in 1954. The first civilian application of the LWR technology in the USA was the Shippingport Atomic Power Station, which started operation in 1957 with a capacity of 60 MWe [43].

To guarantee their independence, each country developed their own nuclear reactor, which resulted in technological diversification. The United Kingdom developed gas-cooled Magnox reactors, optimized for both electricity and plutonium production, while the Soviet Union initiated development of the graphite-moderated, water-cooled RBMK design. Canada's nuclear program focused on pressurized heavy water reactor (PHWR) technology, culminating in the 1962 Rolphoton demonstration reactor and the first commercial CANDU reactor at Douglas Point in 1968 [43]. Regarding LWRs, the USA developed the BWR (Boiling Water Reactor) and adapted their naval reactors to create commercial PWRs (Pressurized Water Reactor), at the same time the USSR developed their own version of the same technology, the VVER ("Water-Water Energetic Reactor"), with some design differences that still persist to this day.

Between the 60s and 70s a numerous countries commissioned their first nuclear reactors: Belgium (1962), Italy (1963), Japan (1963), Sweden (1964), Switzerland (1969), Slovakia (1972), Argentina (1974), Bulgaria (1974) and Armenia (1976) [43]. Following the 1973 oil crisis, the deployment of nuclear power plants was accelerated in some countries as an energy security strategy. Most notably France implemented the Messmer Plan, named after the Prime Minister at the time, to greatly expand the nuclear plant fleet [30].

Two setbacks: 1986 and 2011

Nuclear expansion continued through the 1980s until 1986. As news from the Chernobyl disaster came to western countries, fear of the potential risks of nuclear power intensified. The public opposition grew significantly so that, even if safety and regulatory updates were implemented, several countries decided to slow down, reduce or halt altogether their nuclear programs, such was the case of Italy after the results of the 1987 referendum, which resulted in the complete phase-out of nuclear power [54, 43].

By the 1990s, multiple western countries had suspended nuclear deployment entirely, including Germany and Switzerland. France, previously the most active builder, connected 10 reactors between 1990-1999, while the United States and United Kingdom only deployed 4 and 1 reactors respectively during the same period. Italy completed its nuclear phase-out by 1990 with the permanent shutdown of all operating reactors. Following the post-Soviet economic transition, Russia resumed its nuclear program and has since continued expansion of its reactor fleet [43].

In the early 2000s a nuclear renaissance, driven by concerns over climate change, energy security, and rising fossil fuel prices, lead to the design of Generation III+ reactors, such as the European Pressurized Reactor (EPR) or the US AP-1000. However after the 2011

Fukushima Daiichi accident Western nations experienced a significant setback: Germany accelerated its nuclear phase-out policy, while Italy reaffirmed its anti-nuclear position through a popular referendum [53]. In the following years projects faced substantial delays, cost overruns, and public opposition, with France's Flamanville-3 EPR serving as a particularly illustrative case: experiencing budget increases to more than four times original estimates and construction timelines tripled from initial projections [58].

Contrastingly, Eastern nations pursued an opposite trajectory. China, having initiated its nuclear program in the 1990s with Qinshan-1 (connected in 1991), has since maintained aggressive expansion. Over the past three decades, China has brought 56 additional reactors online and currently has 29 under construction, positioning itself to surpass both France and the United States in total reactor capacity within the coming decade [43].

Recent years

The current political scenario

In 2020, the COVID-19 pandemic exposed vulnerabilities in global economic systems and Russia's invasion of Ukraine in 2022 further revealed Europe's energy dependencies [11, 84, 10]. At the same time, decarbonization goals to combat climate change have prompted Western nations to reconsider nuclear energy as a valid power source able to provide low-carbon, reliable power while enhancing energy independence and system resilience [23].

This strategic reassessment of nuclear is evident in recent policy initiatives. The European Union's classification of nuclear power as a sustainable investment under its taxonomy for climate mitigation [24], alongside programs like the U.S. Department of Energy's Advanced Reactor Demonstration Program [90], are a clear indicator of the renewed interest in nuclear technologies.

This historical overview demonstrates that the initial decision to adopt nuclear power is a strategic and political choice, deeply influenced by historical context. However, the subsequent selection of a specific reactor design involves complex trade-offs across technical, economic, regulatory, social, environmental, and geopolitical aspects. Moreover the choice is inevitably tied to specific national energy requirements.

The state of Nuclear Designs in 2025

As mentioned before, several technologies have been developed throughout the years, with some being split between opposing political sides, most notably the western implemen-

tation of the PWR technology and its soviet counterpart, the VVER, which is nowadays the most common reactor type by far, counting 306 out of the total 416 reactors worldwide. Followed by heavy water reactors (46) and BWRs (43). The current generation is usually referred to as Generation III+ reactors, variations of previous iterations from the 90s (Gen III) updated to the latest safety standards. Generation IV reactors are mostly under development or at demonstration phases and employ innovative means of cooling, like molten salts or molten metals. Small Modular Reactors (SMRs) on the other hand represent a different approach to the building strategy of the power plant itself. Since the beginning, the nuclear industry has exploited economies of scale by building larger and larger reactors. Unfortunately in the last years, nuclear commissioning has reached the status of "Mega Projects". These term is used to refer to very large projects where economies of scale tend to fail due to the complexity of the task at hand, resulting in massive delays and cost overruns [28, 12]. To counter this phenomena the industry is trying to develop SMRs: smaller, standardized reactors that can be built mostly off site to take advantage of economies of multiples. Some SMR designs are based on novelty generation IV technologies while others take advantage of well known water-based designs.

Challenges and solutions of our days

The present landscape presents policymakers with significant decision-making challenges. Renewed interest in nuclear power, geopolitical uncertainties and technological innovations, complicates the selection of an optimal reactor design. While nuclear commitments involve decade-long development timelines, 60-year operational lifespans, and substantial financial investments, modern energy policies must also consider evaluation of electricity demand, public dynamics, and supply chain vulnerabilities.

To address this complex decision-making environment, analytical frameworks have been developed, notably Multi-Criteria Decision Analysis (MCDA) which provides systematic support for evaluating alternatives when multiple, conflicting, criteria must be considered.

1 | Literature Review and Objectives

1.1. Literature Review

A review of relevant literature reveals numerous applications of MCDA methods across diverse fields. Focusing specifically on studies combining MCDA with nuclear power decision-making, several distinct approaches emerge:

Site selection studies represent the most common application, typically employing GIS-based software to evaluate potential locations for new nuclear installations within limited geographical regions. These analyses frequently incorporate quantitative non-technical factors such as population proximity [17] [8]. Abdullah et al. (2025) extend this approach by including social dimensions like public acceptance and tourism impacts, which present challenges for quantification [1]. Notably, Devanand et al. (2019) develop an algebraic optimization model to identify optimal SMR locations in Singapore, though like most site-focused studies, they favor a design without systematic comparison [18].

A second category compares different nuclear technologies. Kiser and Otero (2023) evaluates PWRs, SMRs, and Molten Salt Reactors [46], while Locatelli and Mancini (2011) compares large and small reactor designs [49]. Birikorang's study stands out for its regional focus on South Africa and comparison of three specific reactor models (NuScale SMR, EM2-HTGR, FTR-MSR), though its technological comparisons mix designs at different maturity levels [9]. Notably, all three studies utilize the Analytic Hierarchy Process (AHP) or its Fuzzy variant. The last one (Birikorang) draws on the IAEA's INPRO methodology for advanced nuclear technology comparison [41].

Broader energy comparison studies by Hernández-Torres (2025), Pasaoglu (2018), and Atilgan (2016) evaluate multiple generation options (typically eight alternatives) employing AHP-TOPSIS, AHP, and MAVT methodologies respectively. These studies use generic, averaged parameters for each technology class [38, 72, 5]. In contrast, Castellazo (2014) adopts a more precise approach using Multi-Attribute Value Theory (MAVT)

to compare thirteen energy technologies, employing specific reference plants (e.g. EPR reactor for nuclear power) rather than generalized technology averages [80].

Three studies show particular relevance to the current research. Zolkaffly et al. (2014) evaluates nuclear plant models in Malaysia but suffers from outdated data and neglects non-technical aspects [100]. Topaloğlu (2025) applies the Analytic Network Process (ANP) to compare reactor types (PWR, BWR, PHWR) and locations, though social considerations remain limited to site-specific factors [88]. Goushis (2025) employs TOPSIS to assess SMR deployment in the EU for coal replacement, but focuses on a single reactor model rather than comparative technology evaluation [35].

The literature review reveals three gaps in nuclear energy decision-making research. First, most studies focus solely on site selection rather than comparing different nuclear technologies. Second, comparisons between nuclear designs lack consideration of a specific decision-making context. Third, studies that do consider specific decision-making context, examine various energy generation options as broad technology categories (e.g., nuclear, solar, wind) rather than conducting detailed analyses of specific reactor models or power plant designs.

This study addresses these research gaps by applying Multi-Criteria Decision Analysis (MCDA), specifically employing Multi-Attribute Value Theory (MAVT), to compare reactor designs. The analysis explicitly incorporates country-specific conditions and examines their influence on the ranking of different nuclear installations.

1.2. Applying MAVT to choose a Reactor

Multi Attribute Value Theory (MAVT), first presented by Keeney in 1996 [45], is a ranking method that computes a score for each alternative based on a set of criteria. To each criteria correspond and indicator that is translated into a value by means of value functions. Values can then be aggregated following a hierarchical structure and applying weights to signify relative importance of a given criteria.

Value Functions are the characteristic feature of this method that allow to, first of all, reduce any metric, based on qualitative or quantitative data, to a scalar comparable with other different metrics. And second, it allows to convey the more implicit information that a metric might carry. For example to evaluate a job offer, an obvious metric is its salary, in monetary terms. The perceived value, that is how the personal judgment of the salary, will never simply scale linearly with the amount of money received, anything below a certain threshold dictated by monthly costs (e.g. rent, food, transportation etc) will

have a significantly lower value than any offer above it. At the same time a hundred euro difference between two low salary offers might be considered much more significant than the same difference between two high offers.

The Aggregation process can be approached in different ways... here i can explain the aggregation, i do not explain the non linear aggregation methods if we are not going to use (i will just acknowledge their existence)

–OLD have been clarified in the previous paragraph, the way that these are determined varies based on the study choices. A possible way could be based on survey results, where questions are posed to the general public, this usually involve a way of direct elicitation, that is asking directly to rank criteria or express judgment on each of them. These methods works with the general public given their simplicity and intuitivity but is not well considered by experts, quoting Morton and Fasolo (2009) "People's ability to understand and respond to direct importance questions baffles us. Both of us regard such questions as meaningless and refuse to answer them. It could be that our intuitions have been destroyed by our atypically extensive exposure to DA." [55]. As suggested by Reichert et al. (2015), technical matters should be addressed with expert elicitation while the higher level objectives, that should reflect "major societal trade-offs" can be weighted based on population or stakeholder opinions [74]. As noted by Marttunen et al. (2016) [51], direct elicitation is also more prone to biases such as the equalising bias which is the tendency of distributing weights evenly across a set of options, leading to less discriminating results. On the other hand more sophisticated elicitation methods, such as swing elicitation are less intuitive and can be misunderstood where proposed to the general public as happened in the elicitation by Aubert et al. 2020 [6], which results were used in the study by Haag et al. 2022 [36]. In their case they tried swing elicitation to the general public and approximately 73% of the respondents did not correctly understand the elicitation method. This study do not uses surveys or stakeholder elicitation but relies on expert judgment, for that reason swing elicitation is deemed appropriate. Swing elicitation [34] is a non direct method to determine weights by asking to evaluate the relative importance of swings, between the worst and best case scenario of two criteria. For example, "On a scale from 1 to 10, how much more important is increasing your salary from 1200 (minimum wage) to 1800 (highest on the market) compared to increasing your annual paid leave from 4 weeks (minimum by law) to 10 (maximum on the market) ?".

Elicitation of weights in Multi-Criteria Decision Analysis (MCDA) varies according to methodological choices. While survey-based approaches using direct elicitation methods (e.g., ranking criteria or expressing judgments) offer simplicity and intuitiveness for general public participation, they face significant criticism from experts. Morton and Fasolo (2009) [55] highlight fundamental concerns: "People's ability to understand and respond to direct importance questions baffles us. Both of us regard such questions as meaningless and refuse to answer them. It could be that our intuitions have been destroyed by our atypically extensive exposure to DA."

Reichert et al. (2015) [74] recommend a differentiated approach: technical criteria should be weighted through expert elicitation, while higher-level objectives reflecting major societal trade-offs may incorporate population or stakeholder opinions. This distinction is particularly important given the biases associated with direct elicitation methods. Marttunen et al. (2016) [51] note the prevalence of equalizing bias, where respondents tend to distribute weights evenly across options, reducing result discrimination. Conversely, more sophisticated methods like swing elicitation, while less prone to such biases, present challenges for public comprehension. Aubert et al. (2020) [6] demonstrated this limitation when approximately 73% of general public respondents failed to correctly understand the swing elicitation method in their study (later utilized by Haag et al., 2022 [36]).

Given these considerations and the technical nature of this analysis, this study employs expert judgment through swing elicitation [34]. This indirect weighting method evaluates the relative importance of improvements between worst- and best-case scenarios for different criteria. For example: "On a scale from 1 to 10, how much more important is increasing your salary from €1,200 (minimum wage) to €1,800 (market maximum) compared to increasing annual paid leave from 4 weeks (legal minimum) to 10 weeks (market maximum)?"

Review signposts as I write... This study will consider real world data, literature estimates, industry claims and expert judgment to define indicators, their value functions and weights. It evaluates six nuclear power plant designs to rank their suitability in four different European national contexts. In the first section the selection process of reactors to be evaluated is presented, followed by the choice of four countries. In the second section the definition of indicators, value functions and weights is discussed. The third section is dedicated to the final discussion

2 | Preparation

2.1. Criteria for Reactor Selection in Comparative Analysis

This study focuses on a curated set of reactor designs at an advanced stage of development. The selection process begins with the the IAEA "Nuclear Reactors in the World" [63], which catalogs operational, under-construction, and decommissioned reactors globally.

The initial selection process applied two primary exclusion criteria. First, designs were eliminated based on supplier origin, removing all reactors associated with countries unlikely to engage in nuclear technology transfer with Europe under the current geopolitical climate. This filter specifically excluded reactors developed in or supplied by Russia, China, and other nations maintaining restricted technology-sharing agreements with Western markets.

Second, reactors commissioned before 2000 were excluded from consideration, as their designs represent outdated technological standards. The complete filtering methodology is documented in the accompanying analysis notebook (PRIS Data Analysis.ipynb), which details how the initial dataset was reduced to nine distinct reactor models.

From this pre-selected group, three designs - the EPR-1750, APR-1400, and AP-1000 - were prioritized for comprehensive analysis. It should be noted that while the EPR (1650 MWe) and EPR-1750 share significant design similarities, they are treated as separate models in this study. Additionally, the Advanced Boiling Water Reactor (ABWR), though listed as operational in the IAEA ARIS database, was excluded following verification through the PRIS database, which indicates all ABWR units have suspended operation since 2011 [43]. The selection process and its outcomes are summarized in Table 2.1.

Subsequently, the IAEA Advanced Reactors Information System (ARIS) database [2], was consulted to identify advanced reactor models classified as under design, under regulatory

review, under construction, or operational. Demonstrations units and prototypes were excluded from this set, yielding 10 candidate designs. To avoid redundancy, models already included in the prior selection (e.g., Generation III+ designs captured in both datasets) were removed. Each remaining design was then assessed for development status, technological readiness, and applicability to European energy systems as summarized in Table 2.2.

The overall selection produced a set of six reactors, three Generation III+ and three SMRs. Their main characteristics are summarized in Table 2.3. The most notable differences are the integrated designs of the BWRX-300 and Nuscale SMR which eliminate the external primary loop in favour of steam generator inside the reactor pressure vessel. This allows for compact construction and allows to exploit natural circulation for cooling. Then the Nuscale SMR is the only model designed to be deployed in a multi unit configuration, with up to 12 modules in the same containment building. **Maybe here add a paragraph for each design to explain their main features.**

Reactor Name	Country	Technology-sharing	Commercial Operation	Up Date	to Decision
APR1400	S.Korea	✓	✓	✓	Selected
CAREM Prototyp	Argentina	✓	✗	✓	Rejected
PRE KONVOI	Germany	✓	✓	✗	Rejected
EPR 1750	France	✓	✓	✓	Selected
AP1000	USA	✓	✓	✓	Selected
ABWR	Japan	✓	✗	✓	Rejected
APWR	Japan	✓	✗	✓	Rejected
EPR	France	✓	✓	✗	Rejected
OPR-1000	S.Korea	✓	✓	✗	Rejected

Table 2.1: Selection of reactor models for analysis

Reactor Name	Country	Used	Reasoning
APR+	S.Korea	✗	As reported in the manufacturer website [22] this design is mean to be an "indigenous reactor cleared of obstacles to export"
ATMEA	Japan, France	✗	Joint venture was abandoned in 2019 [7]
BWRX300	USA, Canada	✓	Design from GE-Hitachi, a lot of support from US and Canada as well as interes in the EU [60] [61].
i-SMR	S.Korea	✗	Never expressed interest in development outside south Asia and the middle east, no updates since early 2024.
iMSR400	US	✗	No interest overseas, project seems to be at an early stage of development.
Natrium	US	✗	Demo plant [87].
Nuward	France	✗	After the change in direction of 2024 the project has been set back [7].
Nuscale	US	✓	Even if there was some financial controversy in 2024 [7]. the project seems to be still moving forward in terms of goverment founding [7] and regulatory review [7].
PRISM	US	✗	GE-Hitachi considers it a "concept ... currently being put into practice in two reactors: Natrium and ARC-100" [7].
Rolls Royce SMR	UK	✓	It's moving forward and from the technological point of view this is the simples as it it litteraly a scaled down PWR[7].
SMART	S.Korea, Saudi Arabia	✗	Plan to export only to south-east asia and middle east [62].

Table 2.2: Selection of advanced reactor models for analysis

Reactor Name	Type	Construction	P_e (MWe)	Supplier
APR1400	PWR	1 Unit	1340	KEPCO (S.Korea)
EPR 1750	PWR	1 Unit	1630	Framatome (France)
AP1000	PWR	1 Unit	1120	Westinghouse (USA)
BWRX300	i-BWR	1 Unit	300	GE-Hitachi (USA-Canada)
Rolls Royce SMR	PWR	4 to 12 Units	470	Rolls Royce (UK)
Nuscale	i-PWR	1 Unit	77	Nuscale Power (USA)

Table 2.3: Final selection of reactor models for analysis

2.2. Country Selection for Comparative Analysis

This study evaluates four European countries: France, Italy, Poland and Switzerland, to assess how national energy contexts influence the ranking of nuclear reactor designs.

In Italy, the energy market is divided into different zones, each with its own demand patterns. For this analysis, Northern Italy serves as the focal region being the country's most industrialized and energy-intensive area[7]. It is characterized by exceptionally high electricity demand, a strong reliance on imports, and above-average greenhouse gas emission intensity, making it a critical bottleneck in Italy's decarbonization efforts. Additionally, the country's historical political volatility introduces uncertainty into long-term energy planning.

France, with $\sim 70\%$ of its electricity generated by nuclear power[7], represents a mature nuclear market. Here, the marginal gains from additional reactors are likely minimal, offering insight into how reactor rankings shift in a saturated nuclear energy landscape.

Poland, heavily dependent on coal and among Europe's highest GHG emitters [7], presents an opposite case. As the country seeks to modernize its grid and reduce emissions through nuclear energy [7], it provides an opportunity to assess which reactor designs could best support its transition while meeting growing energy demand.

Finally, Switzerland provides a unique case due to its low electricity demand, hydropower-dominated grid, and prudent nuclear policy. Its constrained grid capacity and emphasis on energy independence make it ideal for assessing small modular reactors (SMRs) and their role in complementing renewables.

2.3. Attribute Definition

Throughout this section we will define the indicators.

2.3.1. Technical parameters

...

2.3.2. MOX Fuel Compatibility

Mixed Oxide (MOX) fuel is produced through spent nuclear fuel reprocessing and offers a solution for partially closing the nuclear fuel cycle in thermal reactors. While this process generates some secondary waste, it provides several strategic advantages: reducing final nuclear waste volumes, minimizing mining waste, and decreasing dependence on uranium imports. The latter is particularly relevant for Europe, which lacks significant domestic uranium deposits. However, reprocessing also presents proliferation risks since the extracted plutonium could potentially be diverted for weapons production. Due to these competing factors, nuclear fuel reprocessing is a fundamental strategic decision; the United States has foregone this practice, while France and UK have implemented the process in their nuclear programs [16].

Given the European context of this study, MOX compatibility is considered a relevant reactor attribute. The evaluation methodology assigned each reactor design an initial score (0-10) based on its maximum MOX core fraction capability, followed by qualitative adjustments reflecting design-specific features. The complete scoring process and results are detailed in Table 2.4.

Reactor Model	MOX[%]	Considerations	Score	Sources
APR1400	33	-	3/10	[2]
EPR 1750	100	50% without modifications, to reach 100% "design adaptations which are not significantly costly" are required.	9/10	[2, 4]
AP1000	50	50% without modification, to reach 100% major modifications are required	6/10	[2, 27]
BWRX-300	0	GNF-2 Not manufactured with MOX	0/10	[13]
Rolls Royce SMR	0	Rolls Royce states that they are not planning to use MOX	0/10	[76]
NuScale	0	Not licensing for MOX but a study reveals support is possible without design modifications	1/10	[95, 66]

Table 2.4: MOX fuel compatibility scores and maximum MOX fraction

2.3.3. Technological Readiness

Expert consultation

2.3.4. Safety

To be discussed

2.3.5. Capital Costs

DRAFT

Option	PROs	CONs
Use NOAK estimates	Use of estimates in all cases, comparable values	It's not realistic and not fair towards more mature designs
Use FOAK estimates/data	Better data for three large reactors	We are mixing up real data and estimates
Use NOAK and apply FOAK-to-NOAK conversion	Comparable values, with awareness of current know-how	rely on a model
Present NOAK and FOAK to experts along with technological readiness overview and let them evaluate	As before	rely on expert judgment

Table 2.5: Options overview

The same applies to commissioning time.

It is important to note that these costs refer to an Nth of a kind installation and will not be representative of the FOAK costs. Moreover as detailed by Rothwell 2022 [79] the costs of recent nuclear installations in Europe and the US have been significantly higher than those announced at the start of the project. For this reason we will apply a FOAK-to-NOAK factor to better represent the real costs. For example the EPR-1600 announced costs for Flamanville-3 was $1886 \text{ USD}_{2020}/kW_e$ but have risen to $8600 \text{ USD}_{2020}/kW_e$ [59]. All Values are summarized in Table 2.6.

For reference, the capital costs of the same plants as the previous section have been

reported by the US Energy Information Administration [91].

We want to clarify that the data has all been converted to 2020 USD since the main source of data [83] and [59] reports all costs in this currency and year.

Reactor Model	Capital Cost of NOAK [\$/kWe]	Capital Cost of FOAK [\$/kWe]	Data Source
APR-1400	1828	2410	[83, 59]
EPR-1750	2150	8600	[83, 59]
AP-1000	2000	8600	[83, 59]
BWRX-300	2318	3467	[75]
Rolls Royce SMR	6050	7408	[73]
NuScale	2850	3600	[67]
Other Power Plants			
Onshore Wind	-	1265	[91]
Solar PV + Battery	-	2175	[91]
Hydroelectric	-	6007	[91]

Table 2.6: Capital costs for selected reactor models

2.3.6. Commissioning Time

DRAFT

See observations in the previous section

I would apply a +0.5 years to planned commissioning time on the APR and AP based on the planned commissioning time of the EPR that differs by 0.5 between UK and Chinese plannings.

Reactor Model	Planned Commissioning Time	Commis- sioning Time	Last unit commissioning Time	Commis- sioning Time	Data Source
APR1400	5.0 in Korea		10 and 8 in Korea		[58]
EPR 1750	5.0 in Europe, 4.5 in China		9 in Taishan, 17 in Flamanville and Olkiluoto		[58]
AP1000	5.0 in USA		9 in Sanmen, 10 and 11 at Vogtle		[58]
BWRX-300	2 ~ 3		NA		[32]
Rolls Royce SMR	4.0		NA		[77]
NuScale	3.0		NA		[68]

Table 2.7: Technological readiness and planned commissioning time

2.3.7. Operational Costs

Lascks presentation of the attribute

Steigerwald et al. (2023) [83] provides comprehensive cost analyses for future nuclear installations, including capital and operational expenditures for both SMRs and large reactors. The study reports operational costs in USD_{2020}/MWh_e for EPR and APR1400 designs, as well as a "Long-Term US" category which this analysis uses as AP1000 costs. For SMRs, operational costs were originally presented in power-based units (USD_{2020}/MW_e), requiring conversion to energy-based measurements (USD_{2020}/MWh_e) using a Gaussian distribution of capacity factors ($\mu = 90\%$, $\sigma = 5\%$) according to:

$$\frac{USD_{2020}}{MWh_e} = \frac{USD_{2020}}{MW_e} \cdot \frac{1}{CF \cdot 8760 \frac{h}{year}}$$

The same study reports fuel costs of $6.23USD_{2020}/MWh_e$ for PWR-based technologies with the exceptions of NuScale at $7.15USD_{2020}/MWh_e$ and the only BWR reactor at $29.55USD_{2020}/MWh_e$. For comparative context, operational cost estimates for utility-scale onshore wind, hydroelectric, and solar PV (with single axis tracking and DC battery storage) were obtained from the U.S. Energy Information Administration [91]. All cost data have been standardized to 2020 USD to maintain consistency with the primary data sources [83, 59], values are presented in Table 2.8.

Reactor Model	Operative Cost [\$/MWh]	Data Source
APR-1400	18.44	[83]
EPR-1750	14.26	[83]
AP-1000	18.69	[83]
BWRX-300	18.30 ± 0.82	[83]
Rolls Royce SMR	65.68 ± 2.94	[83]
NuScale	22.76 ± 1.02	[83]
Other Power Plants		
Onshore Wind	28.08	[91]
Solar PV + Battery	33.33	[91]
Hydroelectric	28.49	[91]

Table 2.8: Economic costs for selected reactor models

2.3.8. Potential Impact on the energy market

To write

2.3.9. Potential Impact on greenhouse gas emissions

To write

2.3.10. Waste

To write

2.3.11. Size - Nominal output power

To write

2.3.12. Load Following Capabilities

Load-following capability can be quantitatively assessed using characteristic curves that represent ramp-up and ramp-down rates as a function of load (expressed as percentage of nominal power $\%P_{nom}$), as illustrated in Figure 2.1. To facilitate comparative analysis, these performance curves are reduced to scalar values through integration of the area under said curve.

For benchmarking purposes, load-following capabilities were calculated for two modern gas turbine configurations: A heavy-duty combined cycle plant featuring two GE Vernova 9HA.02 gas turbines (2015 data) [33] and an equivalent plant configuration utilizing aeroderivative GE LM2500XPRESS+G5 DLE UPT gas turbines (2025 data) [31]. Hydroelectric plants are also included as a reference for the highest flexibility, a 1989 publication by the US Office of Technology Assessment [89] reports that the response rate of large ($>60\text{MW}$) hydroelectric plants ranges from 4 to 6 $\%P_{nom}/\text{s}$, which translates to 240 to 360 $\%P_{nom}/\text{min}$. A graph from a 1994 conference reported in a technical analysis from 2009 shows that some hydro plant can achieve 0 to 100% in much less than a minute and from black startup to full power in around 5 minutes For the comparison we indicate greater than 100%. [81, 56]

To establish an upper benchmark hydroelectric plants were included in the comparative analysis. A 1989 U.S. Office of Technology Assessment report [89] documents that large ($>60\text{ MW}$) hydroelectric facilities demonstrate remarkable load-following capabilities, with response rates ranging from 4 to 6 $\%P_{nom}/\text{s}$ (equivalent to 240-360 $\%P_{nom}/\text{min}$). Additional performance data from a 1994 conference presentation, cited in a 2009 technical analysis [81, 56], indicates that certain hydroelectric installations can achieve 0-100% load changes in under one minute and black start to full power operation in approximately five

minutes. For the purposes of this comparison, hydroelectric flexibility is conservatively represented as $>100\%P_{nom}/\text{min}$.

The results of these analyses are presented in Table 2.9.




Figure 2.1: Example load following capability curve for EPR-1750

Reactor Model	Load Following Capability $\left[\frac{\%P_{nom}^2}{min} \right]$	Data Source
APR1400	0.21	[2]
EPR 1750	2.88	[69]
AP1000	4.25	[2]
BWRX-300	0.25	[2]
Rolls Royce SMR	2.00	[2]
NuScale	2.00	[21]
GE 9HA.02 2xCC	7.02	[33]
GE LM2500XPRESS+G5 2xCC	40.54	[31]
Hydroelectric	>100	[89, 81, 56]

Table 2.9: Load following capabilities and power output

3 | Analysis

4 | Results

Bibliography

- [1] Ade Gafar Abdullah et al. “The social factors considered in site selection for nuclear power plants: A case study of Borneo Island, Indonesia”. In: *Progress in Nuclear Energy* 180 (2025), p. 105626. ISSN: 0149-1970. DOI: <https://doi.org/10.1016/j.pnucene.2025.105626>. URL: <https://www.sciencedirect.com/science/article/pii/S0149197025000241>.
- [2] International Atomic Energy Agency. *Advanced Reactors Information System (ARIS)*. Accessed: 2025-06-10. 2025. URL: <https://aris.iaea.org/>.
- [3] AREVA NP, EDF Energy. *Sub-Chapter 15.1: Level 1 Probabilistic Safety Assessment*. Technical Report. Accessed: 2025-09-30. EDF Energy, Nov. 2012. URL: https://www.edfenergy.com/sites/default/files/sub-chapter_15.1_-_level_1_psa.pdf.
- [4] M. Arslan et al. “MOX recycling in GEN 3 + EPR Reactor homogeneous and stable full MOX core”. In: American Nuclear Society, 555 North Kensington Avenue, La Grange Park, IL 60526 (United States). American Nuclear Society - ANS; La Grange Park (United States), July 2013. URL: <https://www.osti.gov/biblio/22257897>.
- [5] Burcin Atilgan and Adisa Azapagic. “An integrated life cycle sustainability assessment of electricity generation in Turkey”. In: *Energy Policy* 93 (2016), pp. 168–186. ISSN: 0301-4215. DOI: <https://doi.org/10.1016/j.enpol.2016.02.055>. URL: <https://www.sciencedirect.com/science/article/pii/S030142151630091X>.
- [6] Alice H. Aubert, Fabien Esculier, and Judit Lienert. “Recommendations for online elicitation of swing weights from citizens in environmental decision-making”. In: *Operations Research Perspectives* 7 (2020), p. 100156. ISSN: 2214-7160. DOI: <https://doi.org/10.1016/j.orp.2020.100156>. URL: <https://www.sciencedirect.com/science/article/pii/S2214716020300464>.
- [7] A. N. Author. *Example Reference Title*. Accessed: 2025-09-10. City, 2025. URL: <https://www.example.com>.
- [8] Murat Başeğmez. “Strategic multi-criteria framework for nuclear plant siting: Integrating AHP, EWM, and Game Theory with GIS”. In: *Progress in Nuclear Energy*

- 188 (2025), p. 105897. ISSN: 0149-1970. DOI: <https://doi.org/10.1016/j.pnucene.2025.105897>. URL: <https://www.sciencedirect.com/science/article/pii/S0149197025002951>.
- [9] S.A. Birikorang et al. “Choosing the right reactor technology: A key step to strengthen nuclear security in West Africa’s nuclear energy plans”. In: *Annals of Nuclear Energy* 226 (2026), p. 111837. ISSN: 0306-4549. DOI: <https://doi.org/10.1016/j.anucene.2025.111837>. URL: <https://www.sciencedirect.com/science/article/pii/S0306454925006541>.
- [10] Lasse Boehm and Alex Wilson. *EU energy security and the war in Ukraine: From sprint to marathon*. Briefing. Accessed: 2025-10-15. Feb. 2023. URL: [https://www.europarl.europa.eu/RegData/etudes/BRIE/2023/739362/EPRS_BRI\(2023\)739362_EN.pdf](https://www.europarl.europa.eu/RegData/etudes/BRIE/2023/739362/EPRS_BRI(2023)739362_EN.pdf).
- [11] Jarosław Brodny and Magdalena Tutak. “Assessing the energy security of European Union countries from two perspectives – A new integrated approach based on MCDM methods”. In: *Applied Energy* 347 (2023), p. 121443. ISSN: 0306-2619. DOI: <https://doi.org/10.1016/j.apenergy.2023.121443>. URL: <https://www.sciencedirect.com/science/article/pii/S0306261923008073>.
- [12] Naomi J. Brookes and Giorgio Locatelli. “Power plants as megaprojects: Using empirics to shape policy, planning, and construction management”. In: *Utilities Policy* 36 (2015), pp. 57–66. ISSN: 0957-1787. DOI: <https://doi.org/10.1016/j.jup.2015.09.005>. URL: <https://www.sciencedirect.com/science/article/pii/S0957178715300217>.
- [13] Canadian Nuclear Safety Commission. *BWRX-300 Design: Non-Proprietary Information on Fuel Design Qualification and BWR Fuel Licensing*. Technical Report. Accessed: 2025-09-30. Canadian Nuclear Safety Commission, 2024. URL: <https://api.cnsccsn.gc.ca/dms/digital-medias/CMD24-H3-Ref-BWRX-300-DNNP-GNF2-Fuel-Design-Qualification-and-BWR-Fuel-Licensing-Non-Proprietary-Information.PDF>.
- [14] Travis S. Carless, W. Michael Griffin, and Paul S. Fischbeck. “The environmental competitiveness of small modular reactors: A life cycle study”. In: *Energy* 114 (2016), pp. 84–99. ISSN: 0360-5442. DOI: <https://doi.org/10.1016/j.energy.2016.07.111>. URL: <https://www.sciencedirect.com/science/article/pii/S0360544216310350>.
- [15] James Chadwick. “The Existence of a Neutron”. In: *Proceedings of the Royal Society of London Series A* 136 (1932), pp. 692–708. DOI: 10.1098/rspa.1932.0112. URL: <https://doi.org/10.1098/rspa.1932.0112>.

- [16] Congressional Research Service (CRS). *Considerations for Reprocessing of Spent Nuclear Fuel*. Report R48364. Accessed: 2025-10-16. Congressional Research Service, 2025. URL: <https://www.congress.gov/crs-product/R48364>.
- [17] Mohammed M. Damoom et al. “Potential areas for nuclear power plants siting in Saudi Arabia: GIS-based multi-criteria decision making analysis”. In: *Progress in Nuclear Energy* 110 (2019), pp. 110–120. ISSN: 0149-1970. DOI: <https://doi.org/10.1016/j.pnucene.2018.09.018>. URL: <https://www.sciencedirect.com/science/article/pii/S0149197018302464>.
- [18] Aravind Devanand, Markus Kraft, and Iftekhar A Karimi. “Optimal site selection for modular nuclear power plants”. In: *Computers and Chemical Engineering* 125 (2019), pp. 339–350. ISSN: 0098-1354. DOI: <https://doi.org/10.1016/j.compchemeng.2019.03.024>. URL: <https://www.sciencedirect.com/science/article/pii/S0098135419300997>.
- [19] Dwight D. Eisenhower. *Atoms for Peace: Address to the General Assembly of the United Nations*. Speech. Accessed: 2025-09-30. New York, NY, Dec. 1953. URL: <https://www.eisenhowerlibrary.gov/research/online-documents/atoms-peace>.
- [20] Electricity Maps. *2024 Carbon Intensity Data for Poland, Switzerland, France, and Northern Italy*. Accessed: 2025-09-30; Data version: January 27, 2025. Electricity Maps, Jan. 2025. URL: <https://www.electricitymaps.com>.
- [21] ENCO. *Analysis of Small Modular Reactor (SMR) Concepts*. Technical Report. Accessed: 2025-09-30. Federal Ministry of Labour and Economy (BMLUK), Austria, 2022. URL: https://www.bmluk.gv.at/dam/jcr:26805e08-47f2-402e-8121-921e1f121144/Analysis_of_SMR_Concepts.pdf.
- [22] KEPCO Engineering and Inc. Construction Company. *Reactor Descriptions*. Accessed: 2025-06-10. 2025. URL: <https://www.kepco-enc.com/menu.es?mid=a20202030100>.
- [23] European Commission. *2050 long-term strategy*. https://climate.ec.europa.eu/eu-action/climate-strategies-targets/2050-long-term-strategy_en. Accessed: 2025-10-01. 2024. URL: https://climate.ec.europa.eu/eu-action/climate-strategies-targets/2050-long-term-strategy_en.
- [24] European Commission. *Commission Delegated Regulation (EU) 2021/2139 of 4 June 2021 supplementing Regulation (EU) 2020/852 of the European Parliament and of the Council by establishing the technical screening criteria for determining the conditions under which an economic activity qualifies as contributing substantially to climate change mitigation or climate change adaptation and for determining whether that economic activity causes no significant harm to any of*

- the other environmental objectives*. Accessed: 2025-10-01. European Union, 2025. URL: <https://eur-lex.europa.eu/legal-content/EN/TXT/?uri=CELEX:02021R2139-20250108>.
- [25] European Network of Transmission System Operators for Electricity (ENTSO-E). *Transparency Platform*. Accessed: 2025-09-30. ENTSO-E, 2025. URL: <https://transparency.entsoe.eu/>.
- [26] European Nuclear Society (Euronuclear). *Opinion Poll: The Majority of the Swiss Support Nuclear Energy*. Accessed: 2025-09-30. European Nuclear Society, 2023. URL: <https://www.euronuclear.org/news/opinion-poll-the-majority-of-the-swiss-support-nuclear-energy/>.
- [27] Robert J. Fetterman. “AP1000 core design with MOX loading”. In: *Annals of Nuclear Energy* 36.3 (2009). PHYSOR 2008, pp. 324–330. ISSN: 0306-4549. DOI: <https://doi.org/10.1016/j.anucene.2008.11.022>. URL: <https://www.sciencedirect.com/science/article/pii/S0306454908002983>.
- [28] Bent Flyvbjerg. “What you Should Know about Megaprojects and Why: An Overview”. In: *Project Management Journal* 45.2 (2014), pp. 6–19. DOI: 10.1002/pmj.21409. URL: <https://doi.org/10.1002/pmj.21409>.
- [29] Framatome. *GNF2 Fuel Assembly: Product Sheet*. Accessed: 2025-09-30. Framatome, May 2018. URL: https://www.framatome.com/solutions-portfolio/docs/default-source/default-document-library/product-sheets/a0529-p-us-g-en-328-05-18-ftp.pdf?Status=Master&sfvrsn=60b7ce1d_2.
- [30] FundingUniverse. *Électricité de France History*. Accessed: 2025-09-30. FundingUniverse, 2025. URL: <https://www.fundinguniverse.com/company-histories/electricit%C3%A9-de-france-history/>.
- [31] GE Vernova. *LM2500XPRESS Gas Turbine: Product Factsheet*. Product Factsheet. Accessed: 2025-10-16. 2025. URL: https://www.gevernova.com/content/dam/gepower-new/global/en_US/downloads/gas-new-site/products/gas-turbines/gev-aero-fact-sheets/GEA35746-GEV-LM2500XPRESS-Product-Factsheet.pdf.
- [32] GE Vernova. *Nuclear Energy Solutions*. Accessed: 2025-09-30. GE Vernova, 2025. URL: <https://www.gevernova.com/nuclear>.
- [33] General Electric (GE). *GE 9HA Gas Turbine: Technical Overview and Performance Specifications*. Technical Brochure. Accessed: 2025-10-16. 2015. URL: <https://f.machineryhost.com/1c549272d486597e78d102330c36981e/USPE%20GE%209HA%20Gas%20Turbine.pdf>.

- [34] Paul Goodwin and George Wright. *Decision Analysis for Management Judgment*. Wiley, 2004. ISBN: 978-0-470-86108-0. URL: <https://books.google.ch/books?id=yxPgmAEACAAJ>.
- [35] Rahul Goushis. “Evaluating the feasibility of modular nuclear reactors in the European Union: A GIS-based multicriteria decision analysis approach to meet Paris Agreement”. In: *Applied Energy* 400 (2025), p. 126565. ISSN: 0306-2619. DOI: <https://doi.org/10.1016/j.apenergy.2025.126565>. URL: <https://www.sciencedirect.com/science/article/pii/S0306261925012954>.
- [36] Fridolin Haag, Alice H. Aubert, and Judit Lienert. “ValueDecisions, a web app to support decisions with conflicting objectives, multiple stakeholders, and uncertainty”. In: *Environmental Modelling & Software* 150 (2022), p. 105361. ISSN: 1364-8152. DOI: <https://doi.org/10.1016/j.envsoft.2022.105361>. URL: <https://www.sciencedirect.com/science/article/pii/S1364815222000676>.
- [37] Otto Hahn and Fritz Strassmann. “Nachweis der Entstehung aktiver Bariumisotope aus Uran und Thorium durch Neutronenbestrahlung; Nachweis weiterer aktiver Bruchstücke bei der Uranspaltung”. In: *Naturwissenschaften* 27.6 (Feb. 1939), pp. 89–95. ISSN: 1432-1904. DOI: [10.1007/BF01488988](https://doi.org/10.1007/BF01488988). URL: <https://doi.org/10.1007/BF01488988>.
- [38] José Antonio Hernández-Torres et al. “Integrated multi-criteria decision-making approach for power generation technology selection in sustainable energy systems”. In: *Renewable Energy* 243 (2025), p. 122481. ISSN: 0960-1481. DOI: <https://doi.org/10.1016/j.renene.2025.122481>. URL: <https://www.sciencedirect.com/science/article/pii/S0960148125001430>.
- [39] IFOP. *Les Français et le nucléaire : adhésion et traits d’image*. Accessed: 2025-09-30. IFOP, Sept. 2022. URL: <https://www.ifop.com/article/les-francais-et-le-nucleaire-adhesion-et-traits-dimage/>.
- [40] Il Sole 24 Ore. “Sustainable Nuclear Comes into Law: Here Is the Government Strategy in Ten Questions and Answers”. In: (2024). Accessed: 2025-09-30. URL: <https://en.ilsole24ore.com/art/sustainable-nuclear-comes-law-here-is-government-strategy-ten-questions-and-answers-AGvZZsDD>.
- [41] International Atomic Energy Agency (IAEA). *Application of Multi-criteria Decision Analysis Methods to Comparative Evaluation of Nuclear Energy System Options: Final Report of the INPRO Collaborative Project KIND*. Technical Report. Accessed: 2025-09-30. International Atomic Energy Agency, 2019. URL: https://www-pub.iaea.org/MTCD/Publications/PDF/P1853_web.pdf.
- [42] International Atomic Energy Agency (IAEA). *Climate Change and Nuclear Power 2022*. Report. Accessed: 2025-09-30. International Atomic Energy Agency, 2022.

- URL: <https://www.iaea.org/topics/nuclear-power-and-climate-change/climate-change-and-nuclear-power-2022>.
- [43] International Atomic Energy Agency (IAEA). *Power Reactor Information System (PRIS) Database*. Accessed: 2025-09-30. International Atomic Energy Agency, 2025. URL: <https://pris.iaea.org/PRIS/home.aspx>.
 - [44] IPSOS. *Gli italiani e l'energia: Forum QualEnergia 2024*. Survey Report. Accessed: 2025-09-30. Legambiente, 2024. URL: <https://www.legambiente.it/wp-content/uploads/2024/11/Forum-QualEnergia-sondaggio-ipsos-2024.pdf>.
 - [45] Ralph L. Keeney. "Value-focused thinking: Identifying decision opportunities and creating alternatives". In: *European Journal of Operational Research* 92.3 (1996), pp. 537–549. ISSN: 0377-2217. DOI: [https://doi.org/10.1016/0377-2217\(96\)00004-5](https://doi.org/10.1016/0377-2217(96)00004-5). URL: <https://www.sciencedirect.com/science/article/pii/S0377221796000045>.
 - [46] Lauren Kiser and Luis Daniel Otero. "Multi-criteria decision model for selection of nuclear power plant type". In: *Progress in Nuclear Energy* 159 (2023), p. 104647. ISSN: 0149-1970. DOI: <https://doi.org/10.1016/j.pnucene.2023.104647>. URL: <https://www.sciencedirect.com/science/article/pii/S0149197023000823>.
 - [47] Korea Hydro and Nuclear Power Co., Ltd. (KHNP). *Major Characteristics of the EU-APR Reactor*. Presentation. Accessed: 2025-09-30. Apr. 2018. URL: <https://sep.com.pl/photo/files/07b%20-%20KHNP%20-%20Major%20Characteristics%20of%20EU-APR%20Reactor.pdf>.
 - [48] Bojie Liu et al. "Critical review of nuclear power plant carbon emissions". In: *Frontiers in Energy Research* Volume 11 - 2023 (2023). ISSN: 2296-598X. DOI: 10.3389/fenrg.2023.1147016. URL: <https://www.frontiersin.org/journals/energy-research/articles/10.3389/fenrg.2023.1147016>.
 - [49] Giorgio Locatelli and Mauro Mancini. "A framework for the selection of the right nuclear power plant". In: *International Journal of Production Research* 50.17 (2012), pp. 4753–4766. DOI: 10.1080/00207543.2012.657965. URL: <https://international.anl.gov/training/materials/BL/Literature/Giorgio%20Locatelli%20Papers/A%20framework%20for%20the%20selection%20of%20the%20right%20nuclear%20power%20plant.pdf>.
 - [50] Anil Markandya and Paul Wilkinson. "Electricity Generation and Health". In: *The Lancet* 370.9591 (Sept. 2007), pp. 979–990. ISSN: 0140-6736. DOI: 10.1016/S0140-6736(07)61253-7. URL: [https://doi.org/10.1016/S0140-6736\(07\)61253-7](https://doi.org/10.1016/S0140-6736(07)61253-7).
 - [51] Mika Marttunen, Valerie Belton, and Judit Lienert. "Are objectives hierarchy related biases observed in practice? A meta-analysis of environmental and energy applications of Multi-Criteria Decision Analysis". In: *European Journal of Opera-*

- tional Research* 265.1 (2018), pp. 178–194. ISSN: 0377-2217. DOI: <https://doi.org/10.1016/j.ejor.2017.02.038>. URL: <https://www.sciencedirect.com/science/article/pii/S0377221717301777>.
- [52] J. P. McBride et al. “Radiological Impact of Airborne Effluents of Coal and Nuclear Plants”. In: *Science* 202.4372 (Dec. 1978), pp. 1045–1050. ISSN: 0036-8075. DOI: 10.1126/science.202.4372.1045. URL: <https://doi.org/10.1126/science.202.4372.1045>.
- [53] Ministero dell’Interno (Italy). *Risultati del Referendum - 12 Giugno 2011*. Election Data. Accessed: 2025-09-30. Ministero dell’Interno, 2011. URL: <https://elezionistorico.interno.gov.it/index.php?tpel=F&dtel=12/06/2011&es0=S&tpa=Y&lev0=0&levsut0=0&ms=S&tpe=A>.
- [54] Ministero dell’Interno (Italy). *Risultati del Referendum - 8 Novembre 1987*. Election Data. Accessed: 2025-09-30. Ministero dell’Interno, 1987. URL: <https://elezionistorico.interno.gov.it/index.php?tpel=F&dtel=08/11/1987&tpa=I&tpe=A&lev0=0&levsut0=0&es0=S&ms=S>.
- [55] A Morton and B Fasolo. “Behavioural decision theory for multi-criteria decision analysis: a guided tour”. In: *Journal of the Operational Research Society* 60.2 (2009), pp. 268–275. DOI: 10.1057/palgrave.jors.2602550. URL: <https://doi.org/10.1057/palgrave.jors.2602550>.
- [56] MWH. *Technical Analysis of Pumped Storage and Integration with Wind Power in the Pacific Northwest*. Technical Report. Accessed: 2025-10-16. U.S. Army Corps of Engineers Northwest Division Hydroelectric Design Center, Aug. 2009. URL: <https://www.hydro.org/wp-content/uploads/2017/08/PS-Wind-Integration-Final-Report-without-Exhibits-MWH-3.pdf>.
- [57] National Council on Radiation Protection and Measurements (NCRP). *Ionizing Radiation Exposure of the Population of the United States*. Report 160. Paywalled; Data accessed via U.S. EPA summary. National Council on Radiation Protection and Measurements, 2009. URL: <https://ncrponline.org/publications/reports/ncrp-report-160-2/>.
- [58] NEA. *Unlocking Reductions in the Construction Costs of Nuclear*. Accessed: 2025-09-10. Paris, 2020. URL: https://www.oecd-nea.org/jcms/pl_30653/unlocking-reductions-in-the-construction-costs-of-nuclear.
- [59] NEA. *Unlocking Reductions in the Construction Costs of Nuclear*. Paris: OECD Publishing, 2020.
- [60] World Nuclear News. *Early works agreement for BWRX-300 SMRs in Finland and Sweden*. Accessed: 2025-06-10. 2025. URL: <https://www.world-nuclear->

- news.org/articles/early-works-agreement-for-bwr-300-smrs-in-finland-and-sweden.
- [61] World Nuclear News. *Hungary looking at deployment of US small modular reactors*. Accessed: 2025-06-10. 2025. URL: <https://www.world-nuclear-news.org/articles/hungary-looking-at-deployment-of-us-small-modular-reactors>.
 - [62] World Nuclear News. *South Korean SMR design approved by regulator*. Accessed: 2025-06-10. Sept. 26, 2024. URL: <https://www.world-nuclear-news.org/articles/south-korean-smr-design-approved-by-regulator>.
 - [63] *Nuclear Power Reactors in the World*. entity 2. Vienna: INTERNATIONAL ATOMIC ENERGY AGENCY, 2024. ISBN: 978-92-0-122224-4. URL: </publications/15748/nuclear-power-reactors-in-the-world>.
 - [64] NucNet. “Majority Continues to Support Nuclear Energy, Says Survey”. In: (Mar. 2023). Accessed: 2025-09-30. URL: <https://www.nucnet.org/news/majority-continues-to-support-nuclear-energy-says-survey-3-1-2023>.
 - [65] NucNet. “Poland Survey”. In: (Dec. 2024). Accessed: 2025-09-30. URL: <https://www.nucnet.org/news/more-than-92-support-plans-for-first-nuclear-power-plant-12-5-2024>.
 - [66] NuScale Power. *NuScale Announces MOX Capability*. Accessed: 2025-09-30. NuScale Power, Jan. 2016. URL: <https://www.nuscalepower.com/press-releases/2016/nuscale-announces-mox-capability>.
 - [67] NuScale Power. *NuScale Power Announces an Additional 25 Percent Increase in NuScale Power Module Output*. Accessed: 2025-10-01. Nov. 2020. URL: <https://www.nuscalepower.com/press-releases/2020/nuscale-power-announces-an-additional-25-percent-in-nuscale-power-module-output>.
 - [68] NuScale Power. *NuScale Power Module: Product Overview*. Accessed: 2025-09-30. NuScale Power, 2025. URL: <https://www.nuscalepower.com/products/nuscale-power-module>.
 - [69] OECD Nuclear Energy Agency (NEA). *Technical and Economic Aspects of Load Following with Nuclear Power Plants*. Technical Report. Accessed: 2025-09-30. OECD Nuclear Energy Agency, June 2011. URL: https://www.oecd-neo.org/upload/docs/application/pdf/2021-12/technical_and_economic_aspects_of_load_following_with_nuclear_power_plants.pdf.
 - [70] Our World in Data. *Death Rates from Energy Production per TWh*. Accessed: 2025-09-30; Data sources: Markandya & Wilkinson (2007); Sovacool et al. (2016); UNSCEAR (2008 & 2018). Our World in Data, 2025. URL: <https://ourworldindata.org/grapher/death-rates-from-energy-production-per-twh>.

- [71] H. Paillere. “Nuclear energy for a net zero world”. In: (2021), [12 p.]
- [72] Guzay Pasaoglu, Nicolas Pardo Garcia, and Ghassan Zubi. “A multi-criteria and multi-expert decision aid approach to evaluate the future Turkish power plant portfolio”. In: *Energy Policy* 119 (2018), pp. 654–665. ISSN: 0301-4215. DOI: <https://doi.org/10.1016/j.enpol.2018.04.044>. URL: <https://www.sciencedirect.com/science/article/pii/S030142151830260X>.
- [73] Power Technology. “Rolls Royce plans first UK modular nuclear reactor for 2029”. In: *Power Technology* (Apr. 2022). Accessed: 2025-10-01. URL: <https://www.power-technology.com/news/uk-first-smr-rolls-royce/>.
- [74] Peter Reichert et al. “The conceptual foundation of environmental decision support”. In: *Journal of Environmental Management* 154 (2015), pp. 316–332. ISSN: 0301-4797. DOI: <https://doi.org/10.1016/j.jenvman.2015.01.053>. URL: <https://www.sciencedirect.com/science/article/pii/S0301479715001140>.
- [75] Reuters Events. “GE Hitachi chases gas plant displacement with new 300 MW reactor”. In: *Reuters Events | Nuclear* (Apr. 2018). Accessed: 2025-10-01. URL: <https://www.reutersevents.com/nuclear/ge-hitachi-chases-gas-plant-displacement-new-300-mw-reactor>.
- [76] Rolls-Royce SMR. *Generic Design Assessment (GDA) Public Consultation: Have Your Say*. Accessed: 2025-09-30. Rolls-Royce SMR, 2025. URL: <https://gda.rolls-royce-smr.com/have-your-say>.
- [77] Rolls-Royce SMR. *Our Approach to Small Modular Reactors*. Accessed: 2025-09-30. Rolls-Royce SMR, 2025. URL: <https://www.rolls-royce-smr.com/our-approach>.
- [78] Rolls-Royce SMR. *Rolls-Royce SMR Select UK-Based Fuel Solution*. Accessed: 2025-09-30. Rolls-Royce SMR, Oct. 2023. URL: <https://www.rolls-royce-smr.com/press/rolls-royce-smr-select-uk-based-fuel-solution>.
- [79] Geoffrey Rothwell. “Projected electricity costs in international nuclear power markets”. In: *Energy Policy* 164 (2022), p. 112905. ISSN: 0301-4215. DOI: <https://doi.org/10.1016/j.enpol.2022.112905>. URL: <https://www.sciencedirect.com/science/article/pii/S0301421522001306>.
- [80] Edgar Santoyo-Castelazo and Adisa Azapagic. “Sustainability assessment of energy systems: integrating environmental, economic and social aspects”. In: *Journal of Cleaner Production* 80 (2014), pp. 119–138. ISSN: 0959-6526. DOI: <https://doi.org/10.1016/j.jclepro.2014.05.061>. URL: <https://www.sciencedirect.com/science/article/pii/S0959652614005381>.
- [81] P F Shiers, F S Fisher, and J A Kosberg. “The Mt. Hope Waterpower Project: A pumped storage facility that enhances the environment while supplying on-demand

- electrical needs”. In: American Society of Civil Engineers, New York, NY (United States), Dec. 1995. URL: <https://www.osti.gov/biblio/219975>.
- [82] Benjamin K. Sovacool et al. “Balancing safety with sustainability: assessing the risk of accidents for modern low-carbon energy systems”. In: *Journal of Cleaner Production* 112 (2016), pp. 3952–3965. ISSN: 0959-6526. DOI: <https://doi.org/10.1016/j.jclepro.2015.07.059>. URL: <https://www.sciencedirect.com/science/article/pii/S0959652615009877>.
- [83] Björn Steigerwald et al. “Uncertainties in estimating production costs of future nuclear technologies: A model-based analysis of small modular reactors”. In: *Energy* 281 (2023), p. 128204. ISSN: 0360-5442. DOI: <https://doi.org/10.1016/j.energy.2023.128204>. URL: <https://www.sciencedirect.com/science/article/pii/S0360544223015980>.
- [84] Julianna Sterling, Missaka Warusawitharana, and Xiangyu Zhang. “European Energy Import Dependency”. In: *FEDS Notes* (Apr. 2025). DOI: 10.17016/2380-7172.3768. URL: <https://doi.org/10.17016/2380-7172.3768>.
- [85] SWG S.p.A. *Nucleare italiano per i cittadini, le imprese e il territorio*. Survey Report. Accessed: 2025-09-30. iWeek, 2024. URL: <https://primapavia.it/media/2024/04/Nucleare-italiano-per-i-cittadini-le-imprese-e-il-territorio-2024-04-15.pdf>.
- [86] SWI swissinfo.ch. “Risks Remain as Switzerland Weighs a Return to Nuclear Power”. In: (2025). Accessed: 2025-09-30. URL: <https://www.swissinfo.ch/eng/emissions-reduction/risks-remain-as-swiss-weigh-a-return-to-nuclear-power/89549444>.
- [87] TerraPower. *Sodium Reactor Technology*. Accessed: 2025-06-10. 2025. URL: <https://www.terrapower.com/sodium/>.
- [88] Fatih Topaloglu. “Analytic network process (ANP) based decision support tool for nuclear power plant location and reactor type selection”. In: *Nuclear Engineering and Technology* 57.3 (2025), p. 103228. ISSN: 1738-5733. DOI: <https://doi.org/10.1016/j.net.2024.09.031>. URL: <https://www.sciencedirect.com/science/article/pii/S1738573324004777>.
- [89] U.S. Congress, Office of Technology Assessment. *Electric Power Wheeling and Dealing: Technological Considerations for Increasing Competition*. Report OTA-E-409. Washington, DC: U.S. Government Printing Office, May 1989. URL: <https://ota.fas.org/reports/8913.pdf>.
- [90] U.S. Department of Energy (DOE). *Advanced Reactor Demonstration Program*. Accessed: 2025-10-15. U.S. Department of Energy, Office of Nuclear Energy, 2020.

- URL: <https://www.energy.gov/ne/advanced-reactor-demonstration-program>.
- [91] U.S. Energy Information Administration (EIA). *Capital Cost and Performance Characteristics for Utility Scale Power Generating Technologies*. Technical Report. Accessed: 2025-10-16. U.S. Energy Information Administration, Jan. 2024. URL: https://www.eia.gov/analysis/studies/powerplants/capitalcost/pdf/capital_cost_AE02025.pdf.
 - [92] U.S. Environmental Protection Agency (EPA). *Radiation Sources and Doses*. Accessed: 2025-10-15; Data sourced from NCRP Report No. 160 (2009). U.S. Environmental Protection Agency, 2025. URL: <https://www.epa.gov/radiation/radiation-sources-and-doses>.
 - [93] U.S. Nuclear Regulatory Commission. *Design Description*. Technical Report. Accessed: 2025-09-30. U.S. Nuclear Regulatory Commission, 2005. URL: <https://www.nrc.gov/docs/ML0522/ML052280170.pdf>.
 - [94] U.S. Nuclear Regulatory Commission. *Safety Evaluation by the Office of Nuclear Reactor Regulation: NuScale Power Module*. ML23161A411. Accessed: 2025-09-30. U.S. Nuclear Regulatory Commission, June 2011. URL: <https://www.nrc.gov/docs/ML1117/ML11171A411.pdf>.
 - [95] U.S. Nuclear Regulatory Commission. *Standard Review Plan for Environmental Reviews for Nuclear Power Plants*. Technical Report. Accessed: 2025-09-30. U.S. Nuclear Regulatory Commission, 2017. URL: <https://www.nrc.gov/docs/ML1700/ML17007A001.pdf>.
 - [96] Westinghouse Electric Company. “Poland’s First Nuclear Plant Moves Forward with Westinghouse-Bechtel-PEJ Agreement”. In: (2025). Accessed: 2025-09-30. URL: <https://info.westinghousenuclear.com/news/polands-first-nuclear-plant-moves-forward-with-westinghouse-bechtel-pej-agreement>.
 - [97] World Nuclear Association. *Switzerland’s Nuclear Industry Profile*. Accessed: 2025-09-30. World Nuclear Association, 2025. URL: <https://world-nuclear.org/information-library/country-profiles/countries-o-s/switzerland>.
 - [98] World Nuclear News. “Go-Ahead for Preliminary Works at Polish Plant Site”. In: (Sept. 2025). Accessed: 2025-09-30. URL: <https://www.world-nuclear-news.org/articles/go-ahead-for-preliminary-works-at-polish-plant-site>.
 - [99] World Nuclear News. “Poll Finds Majority of Swiss Support Nuclear New Build”. In: (2023). Accessed: 2025-09-30. URL: <https://www.world-nuclear-news.org/articles/poll-finds-majority-of-swiss-support-nuclear-new-build>.

- [100] Muhammed Zulfakar Zolkaffly and Ki-In Han. “Reactor technology assessment and selection utilizing systems engineering approach”. In: *AIP Conference Proceedings* 1584.1 (Feb. 2014), pp. 22–31. ISSN: 0094-243X. DOI: 10.1063/1.4866099. eprint: https://pubs.aip.org/aip/acp/article-pdf/1584/1/22/11739325/22_1_online.pdf. URL: <https://doi.org/10.1063/1.4866099>.

A | Appendix A

If you need to include an appendix to support the research in your thesis, you can place it at the end of the manuscript. An appendix contains supplementary material (figures, tables, data, codes, mathematical proofs, surveys, . . .) which supplement the main results contained in the previous chapters.

B | Appendix B

It may be necessary to include another appendix to better organize the presentation of supplementary material.

List of Figures

2.1	Example load following capability curve for EPR-1750	19
-----	--	----

List of Tables

2.1	Selection of reactor models for analysis	10
2.2	Selection of advanced reactor models for analysis	11
2.3	Final selection of reactor models for analysis	12
2.4	MOX fuel compatibility scores and maximum MOX fraction	14
2.5	Options overview	15
2.6	Capital costs for selected reactor models	16
2.7	Technological readiness and planned commissioning time	16
2.8	Economic costs for selected reactor models	17
2.9	Load following capabilities and power output	19

List of Symbols

Variable	Description	SI unit
$\boldsymbol{u}$	solid displacement	m
$\boldsymbol{u}_f$	fluid displacement	m

Acknowledgements

Here you might want to acknowledge someone.

This work was supported by the ENEN2plus mobility grant.



**Co-funded by
the European Union**

