



# Mobile Programming Laboratory

ANDROID  
Preferences



# Teachers

Ing. Tarquini Francesco, Ph.D

Ph.D in Computer Science Engineering

[francesco.tarquini@univaq.it](mailto:francesco.tarquini@univaq.it)

Ing. D'Errico Leonardo

Ph.D Student in Computer Science Engineering

[leonardo.derrico@graduate.univaq.it](mailto:leonardo.derrico@graduate.univaq.it)



# Teaching Materials

Available on MOODLE platform

<http://www.didattica.univaq.it>

Google Drive Repository

<https://drive.google.com/drive/folders/1ISqZfn0i9Ub3eWNXbvW00rd0hD9ya8OL?usp=sharing>



# Topics

- Settings
- SharedPreferences




# Settings

Apps often include settings that allow users to modify app features and behaviors.

For example, some apps allow users to specify whether notifications are enabled or specify how often the app syncs data with the cloud.

If you want to provide settings for your app, you should use Android's **Preference** APIs to build an interface that's consistent with the user experience in other Android apps (including the system settings).





# Settings

A Preference object is the building block for a single setting.

Each Preference appears as an item in a list and provides the appropriate UI for users to modify the setting.

A few of the most common preferences are:

`CheckBoxPreference`: Shows a checkbox for a setting that is either enabled or disabled

`ListPreference`: Opens a dialog with a list of radio buttons

`EditTextPreference`: Opens a dialog with an `EditText`

`SwitchPreference`: Shows a switch for a setting that is either enabled or disabled



# Settings

The developer has to create a XML file in res/xml/ folder.

```
<?xml version="1.0" encoding="utf-8"?>
<PreferenceScreen xmlns:android="http://schemas.android.com/apk/res/android">

    <PreferenceCategory android:title="Category name">


        <EditTextPreference
            android:key="option key 1"
            android:summary="Description of the preference"
            android:title="Title" />

        <CheckBoxPreference
            android:defaultValue="true"
            android:key="option key 2"
            android:summary="Description of the preference"
            android:title="Title" />
    </PreferenceCategory>

    <PreferenceCategory android:title="Category name">
        <SwitchPreference
            android:defaultValue="true"
            android:key="option key 1"
            android:summary="Description of the preference"
            android:title="Title" />

        <EditTextPreference
            android:key="option key 1"
            android:summary="Description of the preference"
            android:title="Title" />
    </PreferenceCategory>

</PreferenceScreen>
```





# Settings

The second step is to create a Java class to handle the layout.

This class is a Screen, thus an Activity (deprecated)

```
public class Settings extends PreferenceActivity {  
  
    @Override  
    public void onCreate(Bundle savedInstanceState) {  
        super.onCreate(savedInstanceState);  
        addPreferencesFromResource(R.xml.settings);  
    }  
}
```





# Settings

or a Fragment.

```
public class Settings extends AppCompatActivity {

    @Override
    public void onCreate(Bundle savedInstanceState) {
        super.onCreate(savedInstanceState);

        // Display the fragment as the main content.
        getFragmentManager().beginTransaction()
            .replace(android.R.id.content, new SettingsFragment())
            .commit();
    }

    public static class SettingsFragment extends PreferenceFragment {
        @Override
        public void onCreate(Bundle savedInstanceState) {
            super.onCreate(savedInstanceState);

            // Load the preferences from an XML resource
            addPreferencesFromResource(R.xml.settings);
        }
    }
}
```



# Settings

**Each Preference** the developer adds has a corresponding **key-value pair** that the system uses to save the setting in a default **SharedPreferences** file for his app's settings.

When the user changes a setting, the system updates the corresponding value in the SharedPreferences file for you.



# SharedPreferences

The SharedPreferences is an interface for accessing and modifying preference data returned.

For any particular set of preferences, there is a single instance of this class that all clients share.

Modifications to the preferences must go through an SharedPreferences.Editor object to ensure the preference values remain in a consistent state and control when they are committed to storage.

Objects that are returned from the various get methods must be treated as immutable by the application

The SharedPreferences stores the data in an XML file inside the private data of the application and every data are stored using a key-value pair



# SharedPreferences

To write a data using Shared Preferences the developer must use its Editor.

```
SharedPreferences preferences = PreferenceManager.getDefaultSharedPreferences(getApplicationContext());  
SharedPreferences.Editor editor = preferences.edit();  
editor.putString("key", "value");  
editor.apply();
```

To read a data:

```
SharedPreferences preferences = PreferenceManager.getDefaultSharedPreferences(getApplicationContext());  
String value = preferences.getString("key", "fallbackValue");
```