


Frequent (Sub)Graph Patterns

- Given a labeled graph dataset D = $\{G_1, G_2, ..., G_n\}$, the supporting graph set of a subgraph g is $D_g = \{G_i \mid g \subseteq G_i, G_i \in D\}$
 - \square support(g) = $|D_g|/|D|$
- □ A (sub)graph g is **frequent** if $support(g) \ge min_sup$
- Ex.: Chemical structures
- Alternative:
 - Mining frequent subgraph patterns from a single large graph or network

 $min_sup = 2$

Frequent Graph Patterns



Applications of Graph Pattern Mining

- Bioinformatics
 - Gene networks, protein interactions, metabolic pathways
- Chem-informatics: Mining chemical compound structures
- Social networks, web communities, tweets, ...
- Cell phone networks, computer networks, ...
- Web graphs, XML structures, Semantic Web, information networks
- Software engineering: Program execution flow analysis
- Building blocks for graph classification, clustering, compression, comparison, and correlation analysis
- Graph indexing and graph similarity search

Graph Pattern Mining Algorithms: Different Methodologies

- Generation of candidate subgraphs
 - Apriori vs. pattern growth (e.g., FSG vs. gSpan)
- Search order
 - Breadth vs. depth
- Elimination of duplicate subgraphs
 - Passive vs. active (e.g., gSpan [Yan & Han, 2002])
- Support calculation
 - Store embeddings (e.g., GASTON [Nijssen & Kok, 2004], FFSM [Huan, Wang, & Prins, 2003], MoFa [Borgelt & Berthold, ICDM'02])
- Order of pattern discovery
 - □ Path → tree → graph (e.g., GASTON [Nijssen & Kok, 2004])