Algorithm 1 Meta-evolution

Inputs: baseline; G generations; O offspring per generation; P population size; tasks T; N_{init} initial seeds; B reevaluation seeds per generation; N_{val} validation seeds.

`population` $\leftarrow$ [`baseline`]
`archive` $\leftarrow$ {}
for $g = 1, \ldots, G$ **do**
  for $o = 1, \ldots, O$ **do** ▷ *Sample offspring*
    `parents` $\leftarrow$ SAMPLEPARENTS(`population`)
    $x_o \leftarrow$ LLM(`parents`)
    EVALUATE(x_o, T, N_{init})
    `archive` $\leftarrow$ `archive` $\cup \{x_o\}$
  end for
  $\hat{\mu}_x, n_x \leftarrow$ mean score, seed count of $x \in$ `archive` ▷ *Reevaluate with TTTS*
  $\psi_x \leftarrow$ top-two Thompson probability of x under $\mathcal{N}(\hat{\mu}_x, \hat{\sigma}^2/n_x)$
  Draw B members from `archive` with probability $\propto \psi_x$
  Evaluate each drawn member on new seeds and update $\hat{\mu}_x, n_x$
  `population` $\leftarrow \{\arg\max_{x \in \texttt{archive}} \hat{\mu}_x(t) \mid t \in T\}$ ▷ *MAP-Elites, one niche per task*
  Fill remaining slots (up to P) by highest overall $\hat{\mu}_x$
end for
for $x \in$ `population` **do** ▷ *Final validation reevaluation*
  `val`$[x] \leftarrow$ EVALUATE($x, T_{\text{val}}, N_{\text{val}}$)
end for
return $\arg\max_{x \in \texttt{population}}$ `val`$[x]$