
Computer Vision & Food Recognition

Simon Bedford
September, 2016

Food is an increasingly important content category



50m visitors in Dec 2015

30,000 professional recipes
150,00 user-submitted recipes

epicurious

Cooking website:
7-8M monthly visitors




168M+ posts #food
76M+ posts #foodporn




Food-related videos viewed
23bn times in 2015




Opportunities for Machine-learning + food images



Machine
Learning
Algorithm



Classified
Food item(s)




Find relevant
recipes

Estimate calorie
count


Identify ingredients

Example use case



Problem and approach

The aim is to create a food classification algorithm that can take images of prepared food dishes as input and output a single prediction for the type of dish




The dataset

- ❖ Food-101 Data Set from the ETH Zurich Computer Vision Laboratory
- ❖ 101 Categories
- ❖ 1,000 images per category
- ❖ 6GB in total

Focus on 12 categories

- | | | |
|------------------|--------------|----------------|
| ❖ Pork Chop | ❖ Lasagne | ❖ French Toast |
| ❖ Guacamole | ❖ Apple Pie | ❖ Cheesecake |
| ❖ Hamburger | ❖ Fried Rice | ❖ Carrot Cake |
| ❖ Chocolate Cake | ❖ Steak | ❖ Pizza |



Mixed data quality


Pizza



Hamburger




Steak



Approach 1: Machine-learning models + features

Best F1 Score:
0.33



- Classifier not good enough
- Move on to Deep Learning

Models:

- ❖ k-Nearest Neighbours
- ❖ Support Vector Machines
- ❖ Decision Trees
- ❖ Random Forests
- ❖ ADA Boost Classifier
- ❖ Naive Bayes Classifiers
- ❖ Linear & Quadratic Discriminant Analysis




Features:

- ❖ RGB Histograms
- ❖ Individual Pixel Values
- ❖ Number of Edges
- ❖ Number of Corners
- ❖ Unsupervised methods (e.g, Principal Component Analysis, k-Means Clustering)


“Supervised” learning algorithms

Manually chosen features


Approach 2: Feature extraction from Convolutional Neural Network (VGG Net)




Approach 3: Fine Tuning AlexNet (CNN)



Fine Tuning Procedure



F1-scores



Future Work for Optimisation

- ❖ Fine-tuning hyper-parameters e.g., dropout rate
- ❖ Increase training batch size (currently 150)
- ❖ More data augmentation
- ❖ Fine tune more recent models e.g., VGGNet, GoogleNet
- ❖ Ensemble of fine-tuned models

Recommendations


1. Expand the model to include all 101 food categories from the existing dataset.
2. Seek to increase the number of images by looking for other sources of data.
3. Invest more time in optimising the model
4. Consider a pilot based on using a smaller set of 10-15 consolidated food categories
5. Use more sophisticated techniques such as object detection & semantic segmentation for identifying multiple food-types in single image

APPENDIX

Differences in RGB histograms between image categories




Comparison of Machine Learning classifiers




Best machine learning procedure

Overall F1
score 0.33




- Classifier not good enough
- Move on to Deep Learning

Image divided into 32 x 32
grid (256 cells in total)




For each cell
calculate:

- Average red pixel value
- Average green pixel value
- Average blue pixel value
- Number of edges
- Number of corners




Chain all
features
together into
one vector
(..1,280
features..)




Random Forest
+
Grid Search for
Hyperparameter
Optimization


Machine Learning: F1 Scores




Machine Learning: Confusion Matrix




Feature Extraction: F1 Scores




Fine Tuning: Training Curve




Per-class results: Comparison of methods



Fine Tuning: Precision-Recall



Fine Tuning: Confusion Matrix



Fail Cases Examples




















Steak Predicted as Pork Chop



Pork Chop Predicted as Steak



Machine Learning vs CNNs for Image Classification

	Machine learning	CNNs
Classification Accuracy		
Training Speed		
Testing Speed		
Ease of getting started		
Resources required		
Feature Selection		
Overall	 	    

- Able to test 40+ models quite quickly
- Makes you think more about underlying images & their content
- Ultimately, not accurate enough

- Harder to get going and needed to use external computing resources
- Once started, training models easier than expected
- Increase in accuracy makes up for everything else

Note: Personal opinions based upon experience with this project