

Performance Modeling of Computer Systems and Networks

Prof. Vittoria de Nitto Personè

Feedback 2: Esercizi di esame

Università degli studi di Roma Tor Vergata
Department of Civil Engineering and Computer Science Engineering

Copyright © Vittoria de Nitto Personè, 2021
<https://creativecommons.org/licenses/by-nc-nd/4.0/>



1

Consider a web server with the following system characteristics:

- Single processor with capacity 10^5 op./sec
- Exponential mean service demand 4×10^4 op./job
- System utilization 60%.

By knowing the job size, the service provider adopts a simple Size Based - priority scheduling without preemption: jobs with size less (or equal) than the average will have the highest priority (class 1); jobs with size greater than the average have the lowest priority (class 2). Determine:


- a. the mean response time for both classes and the global mean response time.

The service provider wants to investigate if a dual core server would improve the service performance.

- b. Conjecture the behaviour of the performance measures for both classes, by writing the mean waiting and response time definition for the dual core case.

2

ex9size-basedPrior2021.pdf

Analytical models
size-based priority

Low load medium load high load

$\rho =$	0.4	0.6	0.8
$\lambda =$	1	1.5	2 job/s
$\lambda_1 =$	0.63212	0.94818	1.26424 job/s
$\lambda_2 =$	0.36788	0.55182	0.73576 job/s

consistency check:

$$\lambda = \sum_{i=1}^r \lambda_i$$


V. de Nitto Personè

3

3

Lezione 29 aprile 2021

Multiserver with priority classes



$$E(T_Q) = p_1 \frac{P_Q E(S)}{(1-\rho_1)} + p_2 \frac{P_Q E(S)}{(1-\rho)(1-\rho_1)}$$

4

Conjecture: multiserver with priority classes SB

$$E(T_Q) = p_1 \frac{P_Q E(S)}{(1-\rho_1)} + p_2 \frac{P_Q E(S)}{(1-\rho)(1-\rho_1)}$$

$$\rho_k = \lambda \int_{x_{k-1}}^{x_k} t f(t) dt$$

5

1. Il responsabile di uno sportello comunale per il rilascio di certificati anagrafici vuole investigare le prestazioni del servizio. Analizzando lo storico dell'attività, si desume che una distribuzione uniforme $Uniform(2, 15)$ ¹ può ben caratterizzare il tempo di servizio (espresso in min). Gli utenti, identificati con la propria richiesta, arrivano in modo random con frequenza 0.112 req/min. Si assuma che sia possibile conoscere il tempo di servizio della pratica all'istante di arrivo. Si calcolino i seguenti indici:

- 1.a. tempi di attesa e risposta per una pratica qualsiasi;
- 1.b. i tempi di attesa e risposta per classi e globali assumendo di usare un meccanismo prioritario opportunamente scelto (senza prelazione);
- 1.c. lo *slowdown* condizionato, per richieste di 5 min e di 10 min, nel caso 1.a;
- 1.d. lo *slowdown* condizionato, per richieste di 5 min e di 10 min, nel caso 1.b;

Si commenti al riguardo del vantaggio della soluzione al punto 1.b. Indicare le assunzioni utilizzate per la soluzione.

6

Si ricorda che per una distribuzione uniforme $Uniform(a, b)$, la densità è $f(x)=1/(b-a)$, la cumulativa è $F(x)=(x-a)/(b-a)$, la media è pari a $(a+b)/2$ e la varianza $(b-a)^2/12$.

$$\begin{aligned} E(s) &= (2+15)/2 = 8.5 \text{ min} \\ \sigma^2(s) &= (15-2)^2/12 = 14.083333 \\ E(s^2) &= \sigma^2(s) + E(s)^2 \\ E(s^2) &= 14.083333 + 72.25 = 86.333333 \\ \lambda &= 0.112 \\ \rho &= 0.112 \times 8.5 = 0.952 \end{aligned}$$

M/U/1 → KP

$$\begin{aligned} E(T_Q) &= (\lambda/2 E(s^2)/(1-\rho)) = (0.056 \times 86.333333)/0.048 = 100.72222 \text{ min oltre 1 ora e mezzo!} \\ E(T_S) &= E(T_Q) + E(s) = 109.22222 \end{aligned}$$

7

2 classi SB, no preemptive

classe 1 [2, 8.5], classe 2 (8.5, 15)

$$\begin{aligned} p_1 &= F(8.5) - F(2) = (8.5-2)/(15-2) = 0.5 \\ p_2 &= F(15) - F(8.5) = 1 - 0.5 = 0.5 \end{aligned}$$

$$f(t) = 1/13$$

$$\begin{aligned} E(s_1) &= \int_2^{8.5} t f(t) dt = \frac{1}{13} \int_2^{8.5} t dt = \frac{1}{13} \left[\frac{t^2}{2} \right]_2^{8.5} = \frac{1}{13} \left(\frac{72.25 - 4}{2} \right) = \frac{68.25}{13} = 5.25 \\ E(s_2) &= \int_{8.5}^{15} t f(t) dt = \frac{1}{13} \int_{8.5}^{15} t dt = \frac{1}{13} \left[\frac{t^2}{2} \right]_{8.5}^{15} = \frac{1}{13} \left(\frac{225 - 72.25}{2} \right) = \frac{152.75}{13} = 11.75 \end{aligned}$$

$$\lambda_1 = 0.112/2 = 0.056, \lambda_2 = 0.112/2 = 0.056$$

$$\rho_1 = \lambda_1 E(s_1) = 0.056 \times 5.25 = 0.294, \quad \rho_2 = \lambda_2 E(s_2) = 0.056 \times 11.75 = 0.658$$

8

$$E(T_{Q1}) = (\lambda / 2 E(s^2)) / (1 - \rho_1) = (0.05686.333333) / 0.706 =$$

= 6.84797 questa l'attesa per la pratica di 5 min!!!

$$E(T_{Q2}) = (\lambda / 2 E(s^2)) / ((1 - \rho) (1 - \rho_1)) = (0.05686.333333) / (0.0480.706) =$$

= 142.66604 questa l'attesa per la pratica di 10 min!!!

$$E(T_Q) = p_1 E(T_{Q1}) + p_2 E(T_{Q2}) = 74.757005 \text{ attesa globale ridotta!!!}$$

$$E(T_{S1}) = E(T_{Q1}) + E(s_1) = 12.09797, \quad E(T_{S2}) = E(T_{Q2}) + E(s_2) = 154.41604$$

$$E(T_S) = p_1 E(T_{S1}) + p_2 E(T_{S2}) = 83.257005 \text{ risposta globale ridotta!!!}$$

9

Slowdown

$$sd(x=5) = 1 + 100.72222/5 = 21.144444 \text{ senza priorità}$$

$$sd_1(x=5) = 1 + 6.84797/5 = 2.369594$$

$$sd(x=10) = 1 + 100.72222/10 = 10.072222 \text{ senza priorità}$$

$$sd_2(x=10) = 1 + 142.66604/10 = 15.2666$$

10

Consider a web server with processing capacity $C = 10^5$ op/sec. The server receives requests with a mean rate 2 req/sec. The requests have different demand Z . Consider the following intervals:

- ❖ $Z < 20.000$ op
- ❖ $20.000 \text{ op} \leq Z < 40.000 \text{ op}$
- ❖ $Z \geq 40.000 \text{ op}$

By assuming that:

- i. the mean size is 40.000 op, characterized by an exponential distribution;
- j. the arrival rate is characterized by a Poisson process;

Define a management mechanism of the server to satisfy the following QoS requirements:

1. Mean response time ≤ 1.5 s for all requests
2. Mean waiting time ≤ 0.5 s, for $Z < 40.000 \text{ op}$.

Evaluate

- a. The mean *throughput* for the server with the chosen management mechanism;
- b. The mean *conditional slowdown* for jobs with size $x=0.1$ s, 0.3 s
- c. Compare the mean slowdown obtained in b. with the corresponding mean slowdown for FIFO and PS scheduling.

Please comment all the obtained results.


11

classi SB, no preemptive

$$E(s) = Z/C = 0.4 \text{ s}$$

12

ex9size-basedPrior2021.pdf

Analytical models
size-based priority

Low load medium load high load

$\rho =$	0.4	0.6	0.8
$\lambda =$	1	1.5	2 job/s
$\lambda_1 =$	0.63212	0.94818	1.26424 job/s
$\lambda_2 =$	0.36788	0.55182	0.73576 job/s

consistency check:

$$\lambda = \sum_{i=1}^r \lambda_i$$

V. de Nitto Personè

13

13

3 classi SB, no preemptive

classe 1 (0, 0.2], classe 2 (0.2, 0.4), classe 3 (0.4, ∞)

 $E(s_1)=0.091701183$ s, $E(s_2)=0.291698$ s, $E(s_3)=0.8$ s $p_1=0.393469$, $p_2=0.238652$, $p_3=0.367879$ $\rho_1=0.072164$, $\rho_2=0.139229$, $\rho_3=0.588606$

- The mean *throughput* : il sistema è stabile ($\rho=0.8$) $\rightarrow 0.2$ j/s
- The mean *conditional slowdown* for jobs with size $x=0.1$ s, 0.3 s:

$$Sd(0.1) = 4.44888, Sd(0.3) = 2.457793$$

- Compare the mean slowdown with the corresponding for FIFO and PS scheduling:

$$Sd_{FIFO}(0.1) = 17, Sd_{FIFO}(0.3) = 6.333333$$

$$Sd_{PS} = 5$$

14


- 1.2. Consider a single-core server hosting a web service. Requests arrive to the server according to a Poisson, with an average inter-arrival time of 200 ms.
1. a. Knowing that the maximum buffer size is $N = 4$ (including the jobs in service) and that each request requires on average 200 ms of processing time, compute the throughput of the system.
 2. b. Consider a CPU upgrade to a faster single-core processor which can process a request in 150 ms. Compute the throughput of the upgraded system.
 3. c. Consider a CPU upgrade to a slower quad-core processor, which can process a request in 300 ms using one of its processor cores. Compute the throughput of the upgraded system.

15

Analytical models
basic laws


lect9Markov2021

Single server center with finite buffer



$X(t) \equiv n^\circ$ di job nel centro

$$E = \{0, 1, 2, \dots, C\}$$



Prof. Vittoria de Nitto Personè

16

16

a. Knowing that the maximum buffer size is $N = 4$ (including the jobs in service) and that each request requires on average 200 ms of processing time, compute the throughput of the system.

$$X=4 \text{ j/s}$$


b. Consider a CPU upgrade to a faster single-core processor which can process a request in 150 ms. Compute the throughput of the upgraded system.

$$X=4.4814 \text{ j/s}$$


17

c. Consider a CPU upgrade to a slower quad-core processor, which can process a request in 300 ms using one of its processor cores. Compute the throughput of the upgraded system.

18



$$\lambda = 5 \text{ j/s}, \quad \mu = 1/300 \text{ j/ms} = 3.33333 \text{ j/s}$$



$$p_{\text{loss}} = \pi_4 = 0.048 \quad \lambda' = \lambda (1 - p_{\text{loss}}) = 4.76 \text{ j/s}$$

$$\rho = \lambda' / m\mu = 4.76 / 13.333333 = 0.357$$

Prof. Vittoria de Nitto Personè

19