

Performance Modeling of Computer Systems and Networks

Prof. Vittoria de Nitto Personè

Analytical models
(single resource)

Università degli studi di Roma Tor Vergata
Department of Civil Engineering and Computer Science Engineering


Copyright © Vittoria de Nitto Personè, 2021
<https://creativecommons.org/licenses/by-nc-nd/4.0/>



1

Analytical models
conceptual model

Single server center



Terminology


service time S	$S = 1/\mu$
time in the queue T_Q	waiting time
time in the system T_S	residence/response time
number in the system N_S	
number in the queue N_Q	
number in the service U, ρ	

Prof. Vittoria de Nitto Personè

2

2

Single server center



$E(T_Q), E(T_S), E(N_S), E(N_Q), \text{Prob}\{T_S > t\}, E(n)_t$


1. As λ , the mean arrival rate, increases, all the performance metrics mentioned above increase.
2. As μ , the mean service rate, increases, all the performance metrics mentioned above decrease.

Prof. Vittoria de Nitto Personè

3

3

Single server center



$E(T_Q), E(T_S), E(N_S), E(N_Q), \text{Prob}\{T_S > t\}, E(n)_t$

Def. throughput


$t=1, E(n)_1$ n° of completions (departures) in the time unit

Prof. Vittoria de Nitto Personè

4

4

Single server center



Def. utilization

How can we “mathematically” define the utilization?


$$\rho = \lambda / \mu$$

Prof. Vittoria de Nitto Personè

5

5

Single server center



$E(T_Q), E(T_S), E(N_S), E(N_Q), \text{Prob}\{T_S > t\}, E(n)_t$


$$E(T_S) = E(T_Q) + E(S)$$

Prof. Vittoria de Nitto Personè

6

6


Single server center



$$E(T_Q), E(T_S), E(N_S), E(N_Q), \text{Prob}\{T_S > t\}, E(n)_t$$

$$E(N_S) = E(N_Q) + E(\text{number in service})$$


Single server center



$$E(T_Q), E(T_S), E(N_S), E(N_Q), \text{Prob}\{T_S > t\}, E(n)_t$$

$$E(N_S) = E(N_Q) + \rho$$

Single server center




Which system has greater throughput?

Prof. Vittoria de Nitto Personè

9

9

Single server center



By assuming *job flow balance*, the throughput is the same !!

For both systems $X = \lambda = 1/6 \text{ j/s}$

BUT the faster server shows the shorter queue and so shorter mean response time

In other words, improving the mean response time does not necessarily improve the throughput

Prof. Vittoria de Nitto Personè

10

10

Single server center

If the center is in stochastic equilibrium (stationary condition),

$$\lambda < \mu, \quad \rho = \lambda / \mu < 1$$

$$E(n)_1 = X = \lambda$$

Throughput is independent of the service rate μ

If the center is NOT in stochastic equilibrium,

$$\lambda > \mu,$$


$$E(n)_1 = X = \mu$$

the center cannot work off the arrival rate, the queue grows unlimited

11

Single server center

What's up if $\lambda > \mu$?




the center cannot work off the arrival rate, the queue grows unlimited

$$E(N_Q \text{ in } T) \geq \lambda T - \mu T = T(\lambda - \mu) \rightarrow \infty \text{ as } T \rightarrow \infty$$

12

Single server center with finite buffer




Each arrival when the queue is *full* will be lost
Which is the throughput?

Prof. Vittoria de Nitto Personè

13

13

Single server center with finite buffer



Each arrival when the queue is *full* will be lost
Which is the throughput?

$$X \neq \lambda$$

No!
On the contrary

$$X < \lambda$$


~~$$\rho = \lambda / \mu$$~~

Prof. Vittoria de Nitto Personè

14

14

Single server center with finite buffer



Each arrival when the queue is *full* will be lost
Which is the throughput?


~~$X \neq \lambda$~~
 ~~$\rho = \lambda / \mu$~~
No!
On the contrary
 $X < \lambda$

Prof. Vittoria de Nitto Personè

15

15

Multi Server Queue




Prof. Vittoria de Nitto Personè

16

16


Multi Server Queue



$$E(S_i) = 1 / \mu \quad E(S) = 1 / m\mu = E(S_i) / m$$

17

Multi Server Queue




$$E(N_s) = \begin{cases} E(N_q) + \rho & \text{if } m=1 \\ E(N_q) + m\rho & \text{if } m>1 \end{cases}$$

But how is the utilization defined for the multiserver case?

18

Multi Server Queue




$$\rho_i = \frac{\lambda_i}{\mu} = \frac{\lambda}{m\mu} \quad \rho_{glob} = \frac{\lambda}{\mu_{glob}} = \frac{\lambda}{m\mu}$$

Prof. Vittoria de Nitto Personè

19

19

Multi Server Queue




$$\rho = \begin{cases} \frac{\lambda}{\mu} = \lambda E(S_i) & \text{if } m = 1 \\ \frac{\lambda}{m\mu} = \frac{\lambda E(S_i)}{m} & \text{if } m > 1 \end{cases}$$

Prof. Vittoria de Nitto Personè

20

20

Multi Server Queue




$$\rho_i = \rho_{glob} = \frac{\lambda}{m\mu}$$

Prof. Vittoria de Nitto Personè

21

21

Multi Server Queue




$$E(T_s) = E(T_q) + E(S_i)$$

Prof. Vittoria de Nitto Personè

22

22

Multi Server Queue



$$E(T_s) = E(T_q) + E(S_i)$$


$$E(T_Q) = f(\lambda, m, E(S_i))$$

Prof. Vittoria de Nitto Personè

23

23

Little's law is very important for its broad applicability.
In general, we can see Little's law as applied at a black box:
it states relations between mean values




Little's Law (1961)

- (a) queue discipline is FIFO,
- (b) service node capacity is infinite,
- (c) flow balance

$$N = \lambda T$$


If λ is the mean arrival rate, T is the mean residence time in the black box, N is the mean population in the black box, the theorem asserts that, if the system is "stable", the mean population is given by the "mean arrival flow" multiplied the mean time the jobs spend in the black box

24




If the black box is the whole center, the theorem is applied to the center mean population:

$$E(N_S) = \lambda E(T_S)$$



If the black box is just the queue, the theorem is applied to the queue mean population:

$$E(N_Q) = \lambda E(T_Q)$$




If the black box is just the server, the theorem is applied to the server "mean population", in other words to the utilization:

$$\rho = \lambda E(S)$$

Prof. Vittoria de Nitto Personè

25

But if the black box is a network of centers, anyway interconnected,




$$N = \lambda T$$

The theorem is applied to the entire network!!

26

Single server center




$$\begin{aligned}
 E(T_s) &= E(T_q) + E(S) & \text{Little's law} & & E(N_s) &= \lambda E(T_s) \\
 E(N_s) &= E(N_q) + \rho & & & E(N_q) &= \lambda E(T_q)
 \end{aligned}
 \quad \Rightarrow \quad
 \begin{aligned}
 E(T_s) &= \frac{E(N_s)}{\lambda} \\
 E(T_q) &= \frac{E(N_q)}{\lambda}
 \end{aligned}$$

Prof. Vittoria de Nitto Personè

27

27

Multi Server Queue



$$\begin{aligned}
 E(T_s) &= E(T_q) + E(S_i) \\
 \text{Little's law} & & E(N_s) &= \lambda E(T_s) \\
 E(N_q) &= \lambda E(T_q)
 \end{aligned}
 \quad \Rightarrow \quad
 \begin{aligned}
 E(T_s) &= \frac{E(N_s)}{\lambda} \\
 E(T_q) &= \frac{E(N_q)}{\lambda}
 \end{aligned}$$

Prof. Vittoria de Nitto Personè

28

28

Consider a web server with a mean processing rate of 1.2 job/s.
If the server receives requests with a rate of 0.45 job/s and it has 0.225
enqueued jobs on average, determine:

- a) the average utilization
- b) the average response time.

During rush hours the arrival rate grows of 20% and the average number of
enqueued jobs becomes 0.3681818.

Determine:

- c) the performance metrics a) and b)
- d) which further increasing in arrival rate makes the server collapsing
- e) the performance metrics a) and b) for the limiting case d).

Let us consider a server that processes jobs with rate 0.8 jobs/s.
By assuming that the server receives jobs with a rate depending on the time slot as
follows:

- 8.00 a.m. – 12.00 a.m. average arrival rate 1.5 jobs/s
- 12.00 a.m. – 2.00 p.m. average arrival rate 0.5 jobs/s
- 2.00 p.m. – 7.00 p.m. average arrival rate 1.5 jobs/s
- 7.00 p.m. – 9.00 p.m. average arrival rate 0.5 jobs/s
- 9.00 p.m. – 8.00 a.m. average arrival rate 0.05 jobs/s

Determine:

- a) average arrival rate per day (24 hours)
- b) average utilization per day
- c) average throughput per day
- d) average throughput for each time slot

Please, justify and comment the results by indicating the used laws.