



ICT Training Center

Il tuo partner per la Formazione e la Trasformazione digitale della tua azienda



Note



SPRING AI

GENERATIVE ARTIFICIAL INTELLIGENCE CON JAVA

Simone Scannapieco

Corso avanzato per Venis S.p.A, Venezia, Italia

Novembre 2025

Note



SETUP PROGETTO SPRING AI

MULTI-CONFIGURAZIONE

Note

- ➔ Selezione modello LLM in base alla task
 - ➔ Ragionamento complesso richiede modelli più potenti
 - ➔ Richieste semplici affidate a modelli più contenuti
 - ➔ Creazione *pipeline* con LLM specializzati in sotto-task
 - ➔ Strategia di *fallback*
 - ➔ Molteplici configurazioni permettono *switch* automatici a modelli secondari se il primario non risponde
 - ➔ Test comparativi
 - ➔ In base ad accuratezza, latenza, costi, ...
 - ➔ Preferenze utente
 - ➔ Approccio *user-centric* all'interazione con i modelli

Note

- ➔ Inizializzare un progetto Spring con le seguenti caratteristiche:
 - ➔ Maven come *build tool*
 - ➔ Spring Boot alla versione più recente **non SNAPSHOT**
 - ➔ Linguaggio **Java 21**
 - ➔ Group **it.venis.ai.spring**
 - ➔ Artifact **demo**
 - ➔ **jar packaging**
 - ➔ **Spring Web, OpenAI o Ollama** come dipendenze
 - ⚠️ Riportare variabili di ambiente `env` in `launch.json` e `settings.json`

Note

- Stub di progetto Spring AI multi-configurazione (Gemini + Ollama)

 - 1 Creazione `application.yml` per applicativo multi LLM
 - 2 Creazione `docker-compose.yml` per servizio Docker Ollama
 - 3 Creazione file variabili di ambiente per servizio Ollama
 - 4 Creazione script per `start`, `stop` ed eliminazione servizi Docker
 - 5 Creazione configurazione multi-LLM
 - 6 Creazione modelli per domanda e risposta
 - 7 Creazione interfaccia ed implementazione del servizio di richiesta
 - 8 Creazione del controllore MVC
 - 9 Test delle funzionalità con Postman/Insomnia

Note

File application.yml

File docker-compose.yml

```
services:
  spring-ai-llm-gpu:
    image: ollama/ollama:${OLLAMA_VERSION:-latest}
    hostname: spring-ai-llm
    container_name: spring_ai_llm
    environment:
      OLLAMA_DEBUG: ${OLLAMA_DEBUG:-false}
      OLLAMA_FLASH_ATTENTION: ${OLLAMA_FLASH_ATTENTION:-false}
      OLLAMA_KEEP_ALIVE: ${OLLAMA_KEEP_ALIVE:-"5m"}
      OLLAMA_MAX_LOADED_MODELS: ${OLLAMA_MAX_LOADED_MODELS:-1}
      OLLAMA_NUM_PARALLEL: ${OLLAMA_NUM_PARALLEL:-1}
    ports:
      - ${OLLAMA_PORT:-11434}:11434
  deploy:
    resources:
      reservations:
        devices:
          - driver: nvidia
            count: all
            capabilities: [gpu]
  volumes:
    - spring_ai_llm:/root/.ollama
  restart: unless-stopped
  profiles: [llm-gpu]
...
...
```

Note

File docker-compose.yml

```
...  
  
spring-ai-llm-cpu:  
  image: ollama/ollama:${OLLAMA_VERSION:-latest}  
  hostname: spring-ai-llm  
  container_name: spring_ai_llm  
  environment:  
    OLLAMA_DEBUG: ${OLLAMA_DEBUG:-false}  
    OLLAMA_FLASH_ATTENTION: ${OLLAMA_FLASH_ATTENTION:-false}  
    OLLAMA_KEEP_ALIVE: ${OLLAMA_KEEP_ALIVE:-"5m"}  
    OLLAMA_MAX_LOADED_MODELS: ${OLLAMA_MAX_LOADED_MODELS:-1}  
    OLLAMA_NUM_PARALLEL: ${OLLAMA_NUM_PARALLEL:-1}  
  ports:  
    - ${OLLAMA_PORT:-11434}:11434  
  volumes:  
    - spring_ai_llm:/root/.ollama  
  restart: unless-stopped  
  profiles: [llm-cpu]  
  
volumes:  
  spring_ai_llm:  
    name: spring_ai_llm
```

Note

File spring-ai.env

```
# MODE:  
# "llm-cpu" --> Large Language Model in cpu mode  
# "llm-gpu" --> Large Language Model in gpu mode  
MODE=llm-cpu  
COMPOSE_PROFILES=${MODE}  
LOG_LEVEL=WARNING  
  
# Ollama configuration  
#OLLAMA_VERSION=0.1.39  
OLLAMA_PORT=11434  
OLLAMA_DEBUG=false  
OLLAMA_FLASH_ATTENTION=false  
OLLAMA_KEEP_ALIVE="5m"  
OLLAMA_MAX_LOADED_MODELS=2  
OLLAMA_NUM_PARALLEL=1  
  
# default: latest  
# default: 11434  
# default: false  
# default: false  
# default: "5m"  
# default: 1  
# default: 1
```

Note

File start_spring_ai_services.sh

```
#!/bin/bash

stack=spring-ai-demo-services
rmi=local
file=docker-compose.yml
envfile=spring-ai.env

if [ -z ${1+x} ];
then rmi=local;
else rmi=$1;
fi

## --rmi flag must be one of: all, local
docker compose -f $file -p $stack --env-file $envfile up --build --remove-orphans --force-recreate --detach
```

Note

File stop_spring_ai_services.sh

```
#!/bin/bash

stack=spring-ai-demo-services
rmi=local
file=docker-compose.yml
envfile=spring-ai.env

if [ -z ${1+x} ];
then rmi=local;
else rmi=$1;
fi

## --rmi flag must be one of: all, local
docker compose -f $file -p $stack --env-file $envfile down --rmi $rmi
```

Note

File erase_spring_ai_services.sh

```
#!/bin/bash

stack=spring-ai-demo
rmi=local
file=docker-compose.yml
envfile=spring-ai.env

if [ -z ${1+x} ];
then rmi=local;
else rmi=$1;
fi

## --rmi flag must be one of: all, local
docker compose -f $file -p $stack --env-file $envfile down --rmi $rmi --volumes
```

Note

Configurazione Gemini + Ollama

```
package it.venis.ai.spring.demo.config;

import org.springframework.ai.chat.client.ChatClient;
import org.springframework.ai.ollama.OllamaChatModel;
import org.springframework.ai.openai.OpenAiChatModel;
import org.springframework.context.annotation.Bean;
import org.springframework.context.annotation.Configuration;

@Configuration
public class ChatClientConfig {

    @Bean
    public ChatClient geminiChatClient(OpenAiChatModel geminiChatClient) {
        return ChatClient.create(geminiChatClient);
        /*
         * or:
         * ChatClient.Builder chatClientBuilder = ChatClient.builder(geminiChatClient);
         * return chatClientBuilder.build();
         */
    }

    @Bean
    public ChatClient ollamaChatClient(OllamaChatModel ollamaChatModel) {
        ChatClient.Builder chatClientBuilder = ChatClient.builder(ollamaChatModel);
        return chatClientBuilder.build();
        /*
         * or:
         * return ChatClient.create(ollamaChatModel);
         */
    }
}
```

Note

Modello per domanda

```
package it.venis.ai.spring.demo.model;

import java.util.UUID;

public record Question(UUID id, String question) {

    public Question(String question) {
        this(UUID.randomUUID(), question);
    }
}
```

Modello per risposta

```
package it.venis.ai.spring.demo.model;  
  
public record Answer(String answer) {  
}
```

Note

Interfaccia servizio

```
package it.venis.ai.spring.demo.services;

import it.venis.ai.spring.demo.model.Answer;
import it.venis.ai.spring.demo.model.Question;

public interface QuestionService {

    Answer getGeminiAnswer(Question question);

    Answer getOllamaAnswer(Question question);

}
```

Note

Implementazione servizio

```
package it.venis.ai.spring.demo.services;

...
@Service
@Configuration
public class QuestionServiceImpl implements QuestionService {

    private final ChatClient geminiChatClient;
    private final ChatClient ollamaChatClient;

    public QuestionServiceImpl(@Qualifier("geminiChatClient") ChatClient geminiChatClient,
                               @Qualifier("ollamaChatClient") ChatClient ollamaChatClient) {
        this.geminiChatClient = geminiChatClient;
        this.ollamaChatClient = ollamaChatClient;
    }

    @Override
    public Answer getGeminiAnswer(Question question) {
        return new Answer(this.geminiChatClient.prompt()
            .user(question.question())
            .call()
            .content());
    }

    @Override
    public Answer getOllamaAnswer(Question question) {
        return new Answer(this.ollamaChatClient.prompt()
            .user(question.question())
            .call()
            .content());
    }
}
```

Note

Implementazione controllore REST

```
package it.venis.ai.spring.demo.controllers;

import org.springframework.web.bind.annotation.PostMapping;
import org.springframework.web.bind.annotation.RequestBody;
import org.springframework.web.bind.annotation.RestController;

import it.venis.ai.spring.demo.model.Answer;
import it.venis.ai.spring.demo.model.Question;
import it.venis.ai.spring.demo.services.QuestionService;

@RestController
public class QuestionController {

    private final QuestionService service;

    public QuestionController(QuestionService service) {
        this.service = service;
    }

    @PostMapping("/gemini/ask")
    public Answer geminiAskQuestion(@RequestBody Question question) {
        return this.service.getGeminiAnswer(question);
    }

    @PostMapping("/ollama/ask")
    public Answer ollamaAskQuestion(@RequestBody Question question) {
        return this.service.getOllamaAnswer(question);
    }
}
```

Note

<https://github.com/simonescannapieco/spring-ai-advanced-dgroove-venis-code.git>

Branch: 1-spring-ai-gemini-ollama-configuration

Note