



This image shows a single sheet of white paper with horizontal ruling lines. The lines are evenly spaced and run across the width of the page. There are no margins, text, or other markings on the paper.

SPRING AI

GENERATIVE ARTIFICIAL INTELLIGENCE CON JAVA

Simone Scannapieco

Corso base per Venis S.p.A, Venezia, Italia

Settembre 2025

Note

[illegible]



AUTOMATIC PROMPTING

Note

This image shows a single sheet of white paper with horizontal blue or grey ruling lines. The lines are evenly spaced and run across the width of the page, providing a template for handwriting practice or general writing. There are no margins, text, or other markings on the paper.

- ➡ Tecnica per sfruttare il codice genetico del LLM
- ➡ Strategia: scrivere *prompt* che generano *prompt* più allineati con il modo di ragionare del LLM
 - ➡ Si chiede al LLM di generare varianti semantiche del *prompt* utente
 - ➡ Il LLM analizza tali varianti in base a delle **metriche di valutazione** del risultato
 - ➡ BLEU (BiLingual Evaluation Understudy)
 - ➡ ROUGE (Recall-Oriented Understudy for Gisting Evaluation)
 - ➡ L'utente ottiene delle varianti semantiche da poter ulteriormente raffinare
- ⚠ Sgrava l'utente da parte della responsabilità nella scrittura di un buon *prompt*
- ➡ Vantaggi
 - ➡ Approccio semi-automatizzato per la creazione di *dataset* mirati
- ➡ Svantaggi
 - ➡ Richiede un approccio iterativo per determinare le migliori formulazioni
 - ➡ Metriche classiche sono ottimi indicatori ma non specializzate per la *task*

[illegible]

- Simone Scannapieco

[illegible]

Sei un generatore automatico di prompt.
Lo `''user''` deve addestrare un chatbot e ha bisogno di diverse varianti semantiche della `''richiesta''` da usare come dati di addestramento.
Genera una lista puntata di {numero} varianti della richiesta dello `''user''`.

```
'''Richiesta''': {prompt}
```

This image shows a blank sheet of white paper with horizontal ruling lines. The lines are evenly spaced and run across the width of the page. There are no margins, text, or other markings on the paper.

Applica la metrica di valutazione {metrica} alle seguenti varianti: {lista}.
Ordina e restituisci ciascuna variante e relativo punteggio in ordine decrescente
di punteggio di valutazione.
{formato}

[illegible]

```
package it.unisai.spring.demo.data;

public enum EvaluationMetric {

    BLEU("BLEU (Bilingual Evaluation Understudy)"),
    ROUGE_1("ROUGE-1 (Recall-Oriented Understudy for Gisting Evaluation con sovrapposizione di unigrammi)"),
    ROUGE_2("ROUGE-2 (Recall-Oriented Understudy for Gisting Evaluation con sovrapposizione di bigrammi)"),
    ROUGE_L("ROUGE-L (Recall-Oriented Understudy for Gisting Evaluation basato su Least Common Subsumer)"),
    ROUGE_W("ROUGE-W (Recall-Oriented Understudy for Gisting Evaluation basato su Least Common Subsumer pesato)"),
    ROUGE_S("ROUGE-S (Recall-Oriented Understudy for Gisting Evaluation basato su co-occorrenza di skip-bigrammi)"),
    ROUGE_SU("ROUGE-SU (Recall-Oriented Understudy for Gisting Evaluation basato co-occorrenza di skip-bigrammi e unigrammi)");

    private String metric;

    EvaluationMetric(String metric) {

        this.metric = metric;

    }

    public String getMetric() {

        return metric;

    }

}
```

[illegible]


```
package it.venis.ai.spring.demo.model;

import com.fasterxml.jackson.annotation.JsonPropertyDescription;

public record Prompt(
    @JsonPropertyDescription("Il contenuto del prompt") String prompt,
    @JsonPropertyDescription("Il punteggio del prompt secondo la metrica") Double evaluation_score) {
}
```

Note

This image shows a single sheet of white paper with horizontal blue or grey ruling lines. The lines are evenly spaced and run across the width of the page, providing a template for handwriting practice. There are no margins, text, or other markings on the paper.

```
package it.venis.ai.spring.demo.model;

import java.util.Objects;
import java.util.UUID;

import it.venis.ai.spring.demo.data.EvaluationMetric;

public record PromptEvaluationRequest(UUID id, String prompt, EvaluationMetric metric) {

    public PromptEvaluationRequest(String prompt, EvaluationMetric metric) {
        this(UUID.randomUUID(), prompt, metric);
    }

    @Override
    public EvaluationMetric metric() {
        return Objects.requireNonNullElse(this.metric, EvaluationMetric.BLEU);
    }
}
```

This image shows a blank sheet of white paper with horizontal ruling lines. The lines are evenly spaced and run across the width of the page. There are no margins, text, or other markings on the paper.

```
package it.venis.ai.spring.demo.model;

import java.util.List;

public record PromptEvaluationResponse(List<Prompt> evaluated_prompts) {
}
```

[illegible]

```
package it.venis.ai.spring.demo.services;

import it.venis.ai.spring.demo.model.Answer;
import it.venis.ai.spring.demo.model.ArtifactRequest;
import it.venis.ai.spring.demo.model.DefinitionRequest;
import it.venis.ai.spring.demo.model.DefinitionResponse;
import it.venis.ai.spring.demo.model.Question;

public interface GeminiFromClientService {

    String getAnswerFromClient(String question);

    Answer getAnswerFromClient(Question question);

    Answer getDefinitionFromClient(DefinitionRequest definitionRequest);

    Answer getCustomFormatDefinitionFromClient(DefinitionRequest definitionRequest);

    Answer getJSONUserFormatDefinitionFromClient(DefinitionRequest definitionRequest);

    DefinitionResponse getJSONOutputConverterFormatDefinitionFromClient(DefinitionRequest definitionRequest);

    Answer getSentimentForArtifact(ArtifactRequest artifactRequest);

    Answer getNERinYAMLForArtifact(ArtifactRequest artifactRequest);

    Answer getSuggestionForArtifact(ArtifactRequest artifactRequest);

    Artifact getGeneratedArtifact(ArtifactRequest artifactRequest, Integer numChoices, Integer numParagraphs);

    Answer getGenreForArtifact(ArtifactRequest artifactRequest);

    PromptEvaluationResponse getEvaluatedPrompts(PromptEvaluationRequest promptEvaluationRequest);
}
```

Note

This image shows a blank sheet of white paper with horizontal ruling lines. The lines are evenly spaced and run across the width of the page. There are no margins, text, or other markings on the paper.

```
package it.venis.ai.spring.demo.services;

import java.util.Map;
import org.springframework.ai.chat.client.ChatClient;
import org.springframework.ai.template.st.StTemplateRenderer;
import org.springframework.beans.factory.annotation.Value;
import org.springframework.core.io.Resource;
import org.springframework.stereotype.Service;
import it.venis.ai.spring.demo.model.Answer;
import it.venis.ai.spring.demo.model.DefinitionRequest;
import it.venis.ai.spring.demo.model.Question;

@Service
public class GeminiFromClientServiceImpl implements GeminiFromClientService {

    private final ChatClient chatClient;

    public GeminiFromClientServiceImpl(ChatClient.Builder chatClientBuilder) {
        this.chatClient = chatClientBuilder.build();
    }

    @Override
    public String getAnswerFromClient(String question) {
        return this.chatClient.prompt()
            .user(question)
            .call()
            .content();
    }
}
```

Note

[illegible]

```

...
@Value("classpath:templates/set-prompt-alternatives-system-prompt.st")
private Resource promptAlternativesSystemPrompt;

@Value("classpath:templates/get-prompt-alternatives-user-prompt.st")
private Resource promptAlternativesUserPrompt;

@Value("classpath:templates/get-ordered-prompt-alternatives-prompt.st")
private Resource orderedPromptAlternativesPrompt;

@Override
public PromptEvaluationResponse getEvaluatedPrompts(PromptEvaluationRequest promptEvaluationRequest) {
    BeanOutputConverter<PromptEvaluationResponse> converter =
        new BeanOutputConverter<>(PromptEvaluationResponse.class);

    String listResponse = this.chatClient.prompt()
        .options(ChatOptions.builder()
            .model("gemini-2.0-flash")
            .temperature(2.0)
            // .topP(1.0)
            // .topK(30)
            .maxTokens(2000)
            // .frequencyPenalty(0.1)
            // .presencePenalty(0.1)
            .build())
        .system(s -> s.text(this.promptAlternativesSystemPrompt)
            .params(Map.of("numero", 10)))
        .user(u -> u.text(this.promptAlternativesUserPrompt)
            .params(Map.of("prompt", promptEvaluationRequest.prompt())))
        .templateRenderer(StTemplateRenderer.builder().startDelimiterToken('{')
            .endDelimiterToken('}')
            .build())
        .call()
        .content();
}
...

```

This image shows a blank sheet of white paper with horizontal ruling lines. The lines are evenly spaced and run across the width of the page. There are no margins, text, or other markings on the paper.

```

    String orderedListResponse = this.chatClient.prompt()
        .options(ChatOptions.builder()
            .model("gemini-2.0-flash")
            .temperature(0.0)
            //.topP(1.0)
            //.topK(30)
            .maxTokens(2000)
            //.frequencyPenalty(0.1)
            //.presencePenalty(0.1)
            .build())
        .user(u -> u.text(this.orderedPromptAlternativesPrompt)
            .params(Map.of("metrica", promptEvaluationRequest.metric().getMetric(),
                "lista", listResponse,
                "formato", converter.getFormat()))))
        .templateRenderer(StTemplateRenderer.builder().startDelimiterToken('{')
            .endDelimiterToken('}')
            .build())
        .call()
        .content();

    return converter.convert(orderedListResponse);
}
}

```

Note

[illegible]

```
package it.venis.ai.spring.demo.controllers;

import org.springframework.web.bind.annotation.RestController;
...
import it.venis.ai.spring.demo.services.GeminiFromClientService;
import org.springframework.web.bind.annotation.PostMapping;
import org.springframework.web.bind.annotation.RequestBody;

@RestController
public class QuestionFromClientController {

    private final GeminiFromClientService geminiService;

    ...

    @PostMapping("/client/genre")
    public Answer getGeneratedArtifact(@RequestBody ArtifactRequest artifactRequest) {

        return this.geminiService.getGenreForArtifact(artifactRequest);

    }

    @PostMapping("/client/evaluate")
    public PromptEvaluationResponse getEvaluatedPrompts(@RequestBody PromptEvaluationRequest promptEvaluationRequest) {

        return this.geminiService.getEvaluatedPrompts(promptEvaluationRequest);

    }

}
```

[illegible]

16 / 16

This image shows a blank sheet of white paper with horizontal ruling lines. The lines are evenly spaced and run across the width of the page. There are no margins, text, or other markings on the paper.