25Way Din

Yellow / Blue		1	S172 Beam Current
Orange / Green		2	T171 Control Current
Yellow / Red		3	U170 Implant
Black		4	208 / 209 Ov
Blue / Black	- Constitution of the Cons	5	136 Shutter Open lamp
Yellow / Green		6	F192 Beam current lamp
Red / Blue		7	G189 Control Current lamp
Green / Red		8	J186 Implant lamp
Orange / Blue		9	194 Alarm Mute lamp
		10	
		11	
		12	
		13	
Red	- CONTRACTOR	14	200 24v
Red / Black		15	F191 Beam Current Ready lamp
Red / Brown		16	H188 Control Current Ready lamp
White / Green		17	Alarm mute switch common to relay coil
White / Red		18	Alarm mute switch N/O to Proc panel mute swith N/O
White / Blue		19	Alarm mute switch N/C to proc panel mute switch N/C
White	Lateral	20	Alarm Sounder +ve
Blue	- Constitution of the Cons	21	Alarm sounder -ve
Bido		22	
		23	
Δ			Ream Current mater va accounts
Aqua		24	Beam Current meter -ve see note
Yellow	-	25	Beam Current meter +ve see note

		CLIC Pro	CLiC Processor Remote Control Panel	itrol Panel	
EBB B S	Ö	onnection to I	Connection to Processor via 25 way DIN connector	y DIN connect	JC
	SIZE	FSCM NO	DWG NO	Ş	REV
28 October 2003	SCALE	1:1	SHEET	T 1 of 3	