

Other Retrieval Methods

Simon Pfreundschuh

December 18, 2017

Overview

1. Background
2. Markov Chain Monte Carlo
3. Bayesian Monte Carlo Integration
4. Machine Learning

Background

- ▶ We still want to solve the retrieval problem:

$$p(\mathbf{x}|\mathbf{y}) \propto p(\mathbf{y}|\mathbf{x})p(\mathbf{x}) \quad (1)$$

- ▶ Rodgers tells use how to do that if
 - ▶ $p(\mathbf{x})$ is Gaussian.
 - ▶ We have a(n at most *moderately non-linear*) forward model F
- ▶ But practically F should also
 - ▶ provide Jacobians,
 - ▶ not be too computationally complex.

Background

The Solutions

- ▶ Markov Chain Monte Carlo:
 - ▶ If you have a forward model and need the *full posterior distribution*.
- ▶ Database Retrievals:
 - ▶ (Bayesian) Monte Carlo Integration (BMCI)
 - ▶ Machine Learning
 - ▶ If performance is critical or if you don't have a forward model.

Markov Chain Monte Carlo

Advantages

- ▶ Direct sampling of the a posteriori distribution $p(\mathbf{x}|\mathbf{y})$
- ▶ No Jacobians required
- ▶ Not based on any assumptions

Disadvantages

- ▶ Very Slow

Markov Chain Monte Carlo

- ▶ General method to sample from arbitrary distributions
- ▶ Sequential sampling: Next sample depends only on current state
 - ▶ *Markov chain property*
- ▶ Sample converge to target distribution

Basic Idea

- ▶ Sample *proposal state* from a proposal distribution (often a random walk).
- ▶ Accept or discard proposal depending on change in likelihood
- ▶ Repeat until convergence

Markov Chain Monte Carlo

Let $p(\mathbf{x}|\mathbf{y})$ be the posterior we want to sample from and $J(\mathbf{x}|\mathbf{x}_i)$ a *symmetric proposal distribution*, i.e. satisfying $J(\mathbf{x}_i|\mathbf{x}_j) = J(\mathbf{x}_j|\mathbf{x}_i)$.

Metropolis Algorithm

1. Draw a starting point \mathbf{x}_0 with $p(\mathbf{x}_0|\mathbf{y}) > 0$
2. Iterate for $i = 1, \dots, n$:
 - 2.1 Sample a proposal \mathbf{x}^* from the proposal distribution $J(\mathbf{x}|\mathbf{x}_{i-1})$.
 - 2.2 Calculate

$$r = \frac{p(\mathbf{x}^*|\mathbf{y})}{p(\mathbf{x}_{i-1}|\mathbf{y})} \quad (2)$$

2.3 Set

$$\mathbf{x}_i = \begin{cases} \mathbf{x}^* & \text{with probability } \min(r, 1) \\ \mathbf{x}_{i-1} & \text{otherwise.} \end{cases} \quad (3)$$

Markov Chain Monte Carlo

Why does it work?

A Markov chain is guaranteed to have a *unique stationary distribution* if

- ▶ it is *aperiodic*,
- ▶ not *transient*,
 - ▶ i.e. there is no state that is not recurrent,
- ▶ *irreducible*,
 - ▶ i.e. there is no state for which there is a non-reachable state.

Thus only need to show that the stationary distribution is the posterior $p(\mathbf{x}|\mathbf{y})$.

Markov Chain Monte Carlo

Why does it work?

- ▶ Assume $p(\mathbf{x}_i|\mathbf{y}) = p(\mathbf{x}|\mathbf{y})$, i.e. the true posterior
- ▶ Then:

$$p(\mathbf{x}_i, \mathbf{x}_{i+1}|\mathbf{y}) = p(\mathbf{x}_i|\mathbf{y})J(\mathbf{x}_{i+1}, \mathbf{x}_i)\min\left(\frac{p(\mathbf{x}_{i+1}|\mathbf{y})}{p(\mathbf{x}_i|\mathbf{y})}, 1\right) \quad (4)$$

$$= \operatorname{argmax}_{\mathbf{x}_i, \mathbf{x}_{i+1}} \{p(\mathbf{x}|\mathbf{y})\} J(\mathbf{x}_{i+1}, \mathbf{x}_i) \quad (5)$$

- ▶ This is symmetric as well: $p(\mathbf{a}, \mathbf{b}) = p(\mathbf{b}, \mathbf{a})$
- ▶ Symmetry of the joint distribution implies equality of the marginal distributions:

$$p(\mathbf{x}_{i+1}|\mathbf{y}) = p(\mathbf{x}_i|\mathbf{y}) = p(\mathbf{x}|\mathbf{y}) \quad (6)$$

Markov Chain Monte Carlo

Things to Consider

- ▶ If the posterior probability of a proposed state is higher than that of the current state, the proposal is always accepted.
 - ▶ The state will move towards high posterior densities.
- ▶ Algorithm needs time to reach stationary distribution:
warm-up phase
- ▶ Consecutive samples are not independent.

Bayesian Monte Carlo Integration (BMCI)

- ▶ MCMC is (conceptually) nice, but also inherently slow.
- ▶ BMCI uses a database of *precomputed simulations* or *observations*.

General Idea

- ▶ Use a database of pairs (\mathbf{y}, \mathbf{x}) of observations and known \mathbf{x}
- ▶ Use importance sampling to transform samples in database to samples of the posterior

Bayesian Monte Carlo Integration (BMCI)

Consider the expected value $\mathcal{E}_{\mathbf{x}|\mathbf{y}}\{f(\mathbf{x})\}$ of a function f computed with respect to the a posteriori distribution $p(\mathbf{x}|\mathbf{y})$:

$$\int f(\mathbf{x}')p(\mathbf{x}'|\mathbf{y}) d\mathbf{x}' \quad (7)$$

Using Bayes theorem, the integral can be computed as

$$\int f(\mathbf{x}')p(\mathbf{x}'|\mathbf{y}) d\mathbf{x}' = \int f(\mathbf{x}') \frac{p(\mathbf{y}|\mathbf{x}')p(\mathbf{x}')}{\int p(\mathbf{y}|\mathbf{x}'') d\mathbf{x}''} d\mathbf{x}' \quad (8)$$

$$= \int f(\mathbf{x}')w(\mathbf{y}, \mathbf{x}')p(\mathbf{x}') d\mathbf{x}' \quad (9)$$

$$= \mathcal{E}_{\mathbf{x}}\{f(\mathbf{x})w(\mathbf{y}, \mathbf{x})\} \quad (10)$$

Bayesian Monte Carlo Integration (BMCI)

If the database is distributed according to our a priori assumptions, we can thus approximate any integral over the posterior distribution by:

$$\int f(\mathbf{x}') p(\mathbf{x}'|\mathbf{y}) d\mathbf{x}' \approx \sum_{i=1}^n f(\mathbf{x}_i) w(\mathbf{y}, \mathbf{x}_i) \quad (11)$$

Bayesian Monte Carlo Integration (BMCI)

The Weighting Function

- Assuming the database is exact up to a zero-mean, Gaussian error with covariance matrix \mathbf{S}_e the weighting function $w(\mathbf{y}, \mathbf{x})$ is given by:

$$w(\mathbf{y}, \mathbf{x}_i) = \frac{1}{C} \cdot \exp \left\{ -\frac{(\mathbf{y} - \mathbf{y}_i)^T \mathbf{S}_e^{-1} (\mathbf{y} - \mathbf{y}_i)}{2} \right\} \quad (12)$$

with normalization factor C

$$C = \int w(\mathbf{y}, \mathbf{x}) d\mathbf{x} \approx \sum_{i=1}^n w(\mathbf{y}, \mathbf{x}_i) \quad (13)$$

Bayesian Monte Carlo Integration (BMCI)

The Retrieval

- This can be used to retrieve the mean and variance of the posterior distribution:

$$\bar{x} = \mathcal{E}_{x|y}\{x\} \approx \sum_{i=1}^n w(\mathbf{y}, x_i) x_i \quad (14)$$

$$\text{var}(x) = \mathcal{E}_{x|y}\{(x - \bar{x})^2\} \approx \sum_{i=1}^n w(\mathbf{y}, x_i) (x_i - \mathcal{E}_{x|y}\{x\})^2 \quad (15)$$

- Or even the CDF of the posterior:

$$F_{x|y}(x) = \int_{-\infty}^x p(x') dx' \quad (16)$$

$$\approx \sum_{\mathbf{x}_i < \mathbf{x}} w(\mathbf{y}, x_i) \quad (17)$$

Bayesian Monte Carlo Integration (BMCI)

Things to Consider

- ▶ A very large database may be required to truthfully represent the a priori and provide sufficient a posteriori statistics.
 - ▶ Solution: Weighting/clustering of database samples
- ▶ Traversing the database can take quite some time.
 - ▶ Solution: Sorting the database in a smart way

Bayesian Monte Carlo Integration (BMCI)

Example: Global Precipitation Measurement (GMP) Retrieval

International satellite mission to provide next-generation observations of rain and snow worldwide every three hours.




Figure: GPROF 2010 Retrieval Algorithm Flow (**gprof**).

Bayesian Monte Carlo Integration (BMCI)

Example: Global Precipitation Measurement (GMP) Retrieval

- ▶ Over Ocean:
 - ▶ Uses simulated database generated from profiles observed by the TRMM precipitation radar
 - ▶ Input: TBs, total precipitable water (TPR) from OEM, sea surface temperature (SST) from NWP
 - ▶ database with 65×10^6 entries stratified into SST/TPR bins of width 1 K / 1 mm.
 - ▶ Clustering algorithm used on bins to improve retrieval speed

Bayesian Monte Carlo Integration (BMCI)

Example: Global Precipitation Measurement (GMP) Retrieval




Figure: Trends in oceanic precipitation (**gprof**).

Bayesian Monte Carlo Integration (BMCI)

Example: Global Precipitation Measurement (GMP) Retrieval




FIG. 10. April–June 2014 average mean surface precipitation of the GPM constellation conical sensors.

Figure: Precip from GPROF (**gprof**).

Machine Learning

Idea

- ▶ Try to learn the inverse method $\mathbf{x} = R(\mathbf{y})$ directly from the data.
- ▶ Regression is an old problem: Plenty of methods to choose from
 - ▶ Traditional regression analysis
 - ▶ Machine Learning

Machine Learning

Neural Networks

- Universal estimators that compute a vector of output activations $\mathbf{y} = f_{NN}(\mathbf{x})$ from a vector of input activations \mathbf{x} :

$$\mathbf{x}_0 = \mathbf{x} \tag{18}$$


$$\mathbf{x}_i = f_i(\mathbf{W}_i \mathbf{x}_{i-1} + \theta_i) \tag{19}$$

$$\mathbf{y} = \mathbf{x}_n \tag{20}$$

- Weight matrices \mathbf{W}_i and bias vectors θ_i are *learnable parameters* of the network.


Machine Learning

Neural Networks




Machine Learning

Neural Networks




Machine Learning

Neural Networks




Machine Learning

Neural Networks




Machine Learning

Neural Networks




Machine Learning

Neural Networks



Machine Learning

Neural Networks



Machine Learning

Neural Networks

(Not so) Recent Trends

- ▶ Deep networks
- ▶ End-to-end learning
- ▶ Very hot topic currently

Deep Learning

- ▶ Complex models, large amounts of data
- ▶ Enabled through batch learning (independence of dataset size) and fast (parallel) CPUs (GPUs)

Machine Learning

Neural Networks

Training

- Supervised learning: Minimize mean of loss function $\mathcal{L}(\hat{\mathbf{y}}, \mathbf{y})$ over training set $\{\mathbf{x}_i, \mathbf{y}_i\}_{i=1}^n$.


$$\underset{\mathbf{W}_i, \theta_i}{\text{minimize}} \frac{1}{n} \sum_{i=1}^N \mathcal{L}(f_{NN}(\mathbf{x}_i, \mathbf{W}_i, \theta_i), \mathbf{y}_i) \quad (21)$$

- Use gradient information for efficient training
- Perform training on randomized minibatches (subsets of the training set)

Machine Learning


Neural Networks

$$\begin{bmatrix} x_{0,0} & \dots & x_{0,m} \\ x_{1,0} & \dots & x_{1,m} \\ \vdots & & \vdots \\ x_{n,0} & \dots & x_{n,m} \end{bmatrix}$$



Machine Learning

Neural Networks




Machine Learning

Neural Networks

$$\mathbf{U}_1 = f_1(\mathbf{X}\mathbf{W}_1^T + \theta_1) \quad \mathbf{U}_2 = f_2(\mathbf{U}_1\mathbf{W}_2^T + \theta_2)$$

$$\begin{bmatrix} x_{0,0} & \dots & x_{0,m} \\ x_{1,0} & \dots & x_{1,m} \\ \vdots & & \vdots \\ x_{n,0} & \dots & x_{n,m} \end{bmatrix}$$




Machine Learning

Neural Networks

$$\begin{bmatrix} x_{0,0} & \dots & x_{0,m} \\ x_{1,0} & \dots & x_{1,m} \\ \vdots & & \vdots \\ x_{n,0} & \dots & x_{n,m} \end{bmatrix}$$

$$\mathbf{U}_1 = f_1(\mathbf{X}\mathbf{W}_1^T + \boldsymbol{\theta}_1) \quad \mathbf{U}_2 = f_2(\mathbf{U}_1\mathbf{W}_2^T + \boldsymbol{\theta}_2)$$




Machine Learning

Neural Networks

$$\mathbf{U}_1 = f_1(\mathbf{X}\mathbf{W}_1^T + \boldsymbol{\theta}_1) \quad \mathbf{U}_2 = f_2(\mathbf{U}_1\mathbf{W}_2^T + \boldsymbol{\theta}_2)$$

$$\begin{bmatrix} x_{0,0} & \dots & x_{0,m} \\ x_{1,0} & \dots & x_{1,m} \\ \vdots & & \vdots \\ x_{n,0} & \dots & x_{n,m} \end{bmatrix}$$




$J_X(\mathbf{y}, \hat{\mathbf{y}})$

Machine Learning

Neural Networks

$$\mathbf{U}_1 = f_1(\mathbf{X}\mathbf{W}_1^T + \boldsymbol{\theta}_1) \quad \mathbf{U}_2 = f_2(\mathbf{U}_1\mathbf{W}_2^T + \boldsymbol{\theta}_2)$$

$$\begin{bmatrix} x_{0,0} & \dots & x_{0,m} \\ x_{1,0} & \dots & x_{1,m} \\ \vdots & & \vdots \\ x_{n,0} & \dots & x_{n,m} \end{bmatrix}$$




$J_X(\mathbf{y}, \hat{\mathbf{y}})$

Machine Learning

Neural Networks

$$\begin{bmatrix} x_{0,0} & \dots & x_{0,m} \\ x_{1,0} & \dots & x_{1,m} \\ \vdots & & \vdots \\ x_{n,0} & \dots & x_{n,m} \end{bmatrix}$$

$$\mathbf{U}_1 = f_1(\mathbf{X}\mathbf{W}_1^T + \boldsymbol{\theta}_1) \quad \mathbf{U}_2 = f_2(\mathbf{U}_1\mathbf{W}_2^T + \boldsymbol{\theta}_2)$$



$$\frac{dJ_{\mathcal{X}}}{d\mathbf{W}_2} = \left(\mathbf{f}'_2 \odot \frac{dJ_{\mathcal{X}}}{d\mathbf{U}_2} \right)^T \mathbf{U}_1$$

Machine Learning

Neural Networks

$$\begin{bmatrix} x_{0,0} & \dots & x_{0,m} \\ x_{1,0} & \dots & x_{1,m} \\ \vdots & & \vdots \\ x_{n,0} & \dots & x_{n,m} \end{bmatrix}$$

$$\mathbf{U}_1 = f_1(\mathbf{X}\mathbf{W}_1^T + \boldsymbol{\theta}_1) \quad \mathbf{U}_2 = f_2(\mathbf{U}_1\mathbf{W}_2^T + \boldsymbol{\theta}_2)$$



$J_{\mathcal{X}}(\mathbf{y}, \hat{\mathbf{y}})$


$$\frac{dJ_{\mathcal{X}}}{d\boldsymbol{\theta}_2} = \left(\mathbf{f}'_2 \odot \frac{dJ_{\mathcal{X}}}{d\mathbf{U}_2} \right)^T \mathbf{1}$$

Machine Learning

Neural Networks

$$\mathbf{U}_1 = f_1(\mathbf{X}\mathbf{W}_1^T + \theta_1) \quad \mathbf{U}_2 = f_2(\mathbf{U}_1\mathbf{W}_2^T + \theta_2)$$

$$\begin{bmatrix} x_{0,0} & \dots & x_{0,m} \\ x_{1,0} & \dots & x_{1,m} \\ \vdots & & \vdots \\ x_{n,0} & \dots & x_{n,m} \end{bmatrix}$$




$$J_{\mathcal{X}}(\mathbf{y}, \hat{\mathbf{y}})$$

$$\frac{dJ_{\mathcal{X}}}{d\mathbf{U}_1} = \left(\mathbf{f}'_2 \odot \frac{dJ_{\mathcal{X}}}{d\mathbf{U}_2} \right) \mathbf{W}_2$$


Machine Learning

Neural Networks



Machine Learning

Neural Networks





Machine Learning

Neural Networks

$$\mathbf{U}_1 = f_1(\mathbf{X}\mathbf{W}_1^T + \boldsymbol{\theta}_1) \quad \mathbf{U}_2 = f_2(\mathbf{U}_1\mathbf{W}_2^T + \boldsymbol{\theta}_2)$$

$$\begin{bmatrix} x_{0,0} & \dots & x_{0,m} \\ x_{1,0} & \dots & x_{1,m} \\ \vdots & & \vdots \\ x_{n,0} & \dots & x_{n,m} \end{bmatrix}$$



$$J_{\mathcal{X}}(\mathbf{y}, \hat{\mathbf{y}})$$

$$\frac{dJ_{\mathcal{X}}}{d\boldsymbol{\theta}_1} = \left(\mathbf{f}'_1 \odot \frac{dJ_{\mathcal{X}}}{d\mathbf{U}_1} \right)^T \mathbf{1}$$

Machine Learning

Neural Networks

Advantages

- ▶ Computational performance
 - ▶ Optimized CPU/GPU codes readily available
- ▶ Flexibility

Disadvantages


- ▶ Need hyperparameter tuning for optimal performance
- ▶ More-or-less black box models

Machine Learning

Neural Networks

NN Performance on Intel Xeon Processor E5-1680 v4

Example




Machine Learning

Neural Networks

Example


NN Performance on NVIDIA Tesla K20



Machine Learning

Neural Networks

Example



References