

TEKSCAN COMPUTER REQUIREMENTS

For your Tekscan system to function properly, your computer must meet or exceed the following requirements:

Suggested Minimum Computer Requirements (desktop or laptop) for all Tekscan Systems

- Intel Pentium 600 MHz or higher processor¹ with 128 MB RAM (512 MB RAM recommended)
- 1 GB hard drive and 1 CD ROM drive
- Windows 2000 (SP4), XP (SP2), Vista or 7 operating system (32-bit versions only)²

Computer Interface Requirements

System	Tekscan Platform (Computer Interface)				
	ELF (one USB/handle)	Evolution (one USB/handle)	Mobile (one USB)	PCI ^{3, 4} (one PCI slot/card)	VersaTek (one USB 2.0)
BPMS		✓			
CONFORMat		✓			✓
FlexiForce ELF	✓				
F-Scan			✓		✓
Grip			✓		✓
Hoof			✓		
HR Mat					✓
I-Scan		✓		✓	✓
K-Scan		✓			
MatScan		✓			✓
PrestoScan		✓			
Saddle			✓		
TireScan				✓	✓
T-Scan		✓			
Walkway		✓			✓
Wiper		✓			

Requirements for Optional Video Synch Features (in addition to the above requirements)

- Additional 20 GB Hard drive space (ATA-33, 7200 RPM speed) on the main computer
- Firewire (iLink or IEEE1394) or USB port on the main computer
- Digital Video camcorder with Firewire (iLink or IEEE1394) or USB connection⁵, or webcam⁶ with USB connection

¹ Walkway systems using the 7101 sensor that require scan rates higher than 60 Hz. require a computer with a 2 GHz or higher dual core processor.

² Evolution I-Scan, CONFORMat, BPMS, and T-Scan III systems are compatible with both 32- and 64-bit operating systems. ELF software is not yet supported with the Windows 7 operating system.

³ Using a PCI-based system with a laptop will require a PCMCIA Cardbus to PCI expansion box. One such box is the CB1F made by www.magma.com. Ensure your laptop is compatible with the MAGMA system.

⁴ PCI-based systems have a known issue when run on PCs or laptops where Hyperthreading is enabled. For more information, see our knowledge base article: [Periodic saturated \(red\) frames during recordings with Tekscan PCI electronics and computers with Hyperthreading enabled.](#)

⁵ Camcorders connected via USB cannot record simultaneously with Tekscan movie (*.fsx) files. You can, however, import these videos separately into the Tekscan software and synchronize them after they are imported.

⁶ Webcam support is available only for CONFORMat and BPMS systems. Webcams connected via USB 1.0 may suffer from dropped frames. A USB 2.0 connection between the Computer and camera is recommended.