


Conditionals and Loops

Ruilizhen HU

122090168@link.cuhk.edu.cn

Overview

- Conditionals
 - The **if** statement
- Loops
 - The **while** statement
 - The **for** loop
 - The **do while** statement
- Nesting
- Debugging



The if statement

Execute certain statements depending on the values of certain variables

- Evaluate a boolean expression
- If **true**, execute a statement
- The else option: If **false**, execute a different statement

Condition is true

```
int number = 10;

if (number > 0) {
    // code
}

// code after if
```

Condition is false

```
int number = 10;

if (number < 0) {
    // code
}

// code after if
```

```
public class Flip
{
    public static void main(String[] args)
    {
        if (Math.random() < 0.5)
            System.out.println("Heads");
        else
            System.out.println("Tails");
    }
}
```

The `if` statement

Example of `if` statement use: error checks

```
public class IntOps
{
    public static void main(String[] args)
    {
        int a = Integer.parseInt(args[0]);
        int b = Integer.parseInt(args[1]);
        int sum = a + b;
        int prod = a * b;
        System.out.println(a + " + " + b + " = " + sum);
        System.out.println(a + " * " + b + " = " + prod);
        if (b == 0) System.out.println("Division by zero");
        else System.out.println(a + " / " + b + " = " + a / b);
        if (b == 0) System.out.println("Division by zero");
        else System.out.println(a + " % " + b + " = " + a % b);
    }
}
```

% java IntOps 5 2

5 + 2 = 7

5 * 2 = 10

5 / 2 = 2

5 % 2 = 1

% java IntOps 5 0

5 + 0 = 5

5 * 0 = 0

Division by zero

Division by zero

Good programming practice. Use conditionals to check for *and avoid* runtime errors.

The if statement - Extension

else if

1st Condition is true

```
int number = 2;  
if (number > 0) {  
    // code  
}  
else if (number == 0){  
    // code  
}  
else {  
    //code  
}  
//code after if
```


2nd Condition is true

```
int number = 0;  
if (number > 0) {  
    // code  
}  
else if (number == 0){  
    // code  
}  
else {  
    //code  
}  
//code after if
```

All Conditions are false

```
int number = -2;  
if (number > 0) {  
    // code  
}  
else if (number == 0){  
    // code  
}  
else {  
    //code  
}  
//code after if
```

Fig: else-if ladder



The `if` statement - Extension

```
class Test{  
    public static void main(String[] args){  
        int rating = 8;  
  
        if(rating < 5) {  
            System.out.println("Bad rating");  
        }  
  
        else {  
            if(rating < 8) {  
                System.out.println("Average rating");  
            }  
            else {  
                System.out.println("Good rating");  
            }  
        }  
    }  
}
```

→ If rating is less than 5

→ If rating is not less than 5

Rating is not less than 5
+
Rating is less than 8


Rating is not less than 5
+
Rating is not less than 8

The **while** statement

Execute certain statements repeatedly until certain conditions are met

- Evaluate a boolean expression
- If **true**, execute a sequence of statements
- **Repeat**

While Loop



The **while** statement - Cautions

- Add braces
- Do not add the semicolon after the “while”

Pop quiz on while loops

Q. Anythina wrona with the followinga code?

```
public class PQwhile
{
    public static void main(String[] args)
    {
        int n = Integer.parseInt(args[0]);
        int i = 0;
        int v = 1;
        while (i <= n)
        { System.out.println(v);
          i = i + 1;
          v = 2 * v; }
    }
}
```

A. Yes! Needs braces.

```
public class Sqrt
{
    public static void main(String[] args)
    {
        double EPS = 1E-15; ← error tolerance (15 places)
        double c = Double.parseDouble(args[0]);
        double t = c;
        while (Math.abs(t - c/t) > t*EPS)
            t = (c/t + t) / 2.0;
        System.out.println(t);
    }
}
```

```
int i = 0;
while ( i < 999);
{
    System.out.println("hello");
    i = i + 1;
}
```


The **for** loop

An alternative repetition structure

- Evaluate an initialization statement
- Evaluate a boolean expression
- If true, execute a sequence of statements, then execute an increment statement
- **Repeat**

Example:

```
int v = 1;
for (int i = 0; i <= n; i++)
{
    System.out.println( i + " " + v );
    v = 2*v;
}
```

initialization statement

boolean expression

increment statement

Prints the powers of two from 2^0 to 2^n

Every for loop has an equivalent while loop:

```
int v = 1;
while (i <= n)
{
    System.out.println( i + " " + v );
    v = 2*v;
    i++;
}
```

$i++;$ \rightarrow $i=i+1;$

The **for** loop

Q. What does the following program print?

```
public class PQfor
{
    public static void main(String[] args)
    {
        int f = 0, g = 1;
        for (int i = 0; i <= 10; i++)
        {
            System.out.println(f);
            f = f + g;
            g = f - g;
        }
    }
}
```

A.

Beginning-of-loop trace

i	f	g
0	0	1
1	1	0
2	1	1
3	2	1
4	3	2
5	5	3
6	8	5
7	13	8
8	21	13
9	34	21
10	55	34

↑
values printed


Fibonacci Sequence

The **do while** statement

The do/while loop is a variant of the while loop

- Execute the code block once before checking if the condition is true
- Evaluate a boolean expression
- If **true**, execute the code block again
- **Repeat**

Do - While Loop



The `do while` statement

Example

```
int i = 0;
do {
    System.out.println(i);
    i++;
}
while (i < 5);
```

```
int counter = 0;
do {
    System.out.println("Will I print?");
} while (counter > 0);
```

Note: The `do while` statements can always be rewritten as the `while` statement

Nesting

- Any “statement” within a conditional or loop may itself be a conditional or a loop statement
- Enables complex control flows
- Adds to challenge of debugging

income	rate
0 - \$47,450	22%
\$47,450 - \$114,649	25%
\$114,650 - \$174,699	28%
\$174,700 - \$311,949	33%
\$311,950 +	35%

```
if (income < 47450) rate = 0.22;
else
{
    if (income < 114650) rate = 0.25;
    else
    {
        if (income < 174700) rate = 0.28;
        else
        {
            if (income < 311950) rate = 0.33;
            else
            {
                rate = 0.35;
            }
        }
    }
}
```


if statement
within an if statement

if statement
within an if statement
within an if statement

if statement
within an if statement
within an if statement
within an if statement



Debugging

Programmers. Everyday.



Debugging

- Bug: A mistake in a program
- Debugging: The process of eliminating bugs



Debugging

[Debugging the Eclipse IDE for Java Developers](#)

[Tutorial: Debug your first Java application](#)

Problem 1

Polynomial Derivative

Write a program Pderivative that takes an polynomial and find its n-th order derivative. Input n in the first line and then input the polynomial in the second line. Assume that the last integer in the second line is not 0.

Input:

3

1 5 9 0 8 6 2

which means to calculate the 3rd order derivative of the polynomial

$$1 + 5 \times x + 9 \times x^2 + 0 \times x^3 + 8 \times x^4 + 6 \times x^5 + 2 \times x^6$$

OJ link: http://10.26.200.14/d/csc2003_2024_Spring/p/P10006

Problem 1

1. How do you differentiate it once
2. How do you apply the method multiple times

Problem 1

1. How do you differentiate it once
for loop here
2. How do you apply the method
multiple times
while loop here

```
for (int i = 0; i < num.length - cnt; i++)  
    num[i] = num[i + 1] * (i + 1);
```

```
int cnt = 0;  
while (cnt < n) {  
    cnt++;  
    for (int i = 0; i < num.length - cnt; i++)  
        num[i] = num[i + 1] * (i + 1);  
}
```

Problem 2

Add By Digit

We define the new operation Add By Digit (ABD) as: treat each digit of a positive decimal number as a single digit and add them together. For example:

$$ABD(15698) = 1 + 5 + 6 + 9 + 8 = 29$$

Write a Java program that takes an integer n and do ABD operation to n until it becomes a single digit. For example, if we input 692341, do ABD and get 25; then we do ABD to 25 and get 7. Since 7 is a single digit, we output 7.

Input:

692341

Output:

7

OJ link: http://10.26.200.14/d/csc2003_2024_Spring/p/P10007

Problem 2

1. How to get a single digit from the given integer
2. How to apply the method multiple times

Problem 2

1. How to get a single digit from the given integer
2. How to apply the method multiple times

```
n % 10;
```

```
int sum = 0;

while (n > 0) {
    sum += n % 10;
    n /= 10;
}
```

Problem 3

Integer Log

Write a static method `intLog()` that takes an `int` argument `n` and returns the largest integer not larger than the base-2 logarithm of `n`.

Input:

6

Output:

2

Problem 3

Enumerate one by one:

```
int ans = 0, product = 1;
while (product <= n) {
    ans++;
    product *= 2;
}
ans--;
```


Problem 3

Method of bisection:

```
int L = 0, R = 30;
while (L + 1 < R) {
    int MID = (L + R) / 2;
    if (Math.pow(a:2, MID) > n)
        R = MID;
    else
        L = MID;
}
```

Q&A