

Annotated
Version

Machine Learning Course - CS-433

Text Representation Learning

Dec 10, 2020


changes by Martin Jaggi 2020, 2019, 2018, 2017, ©Martin Jaggi 2016

Last updated on: December 9, 2020

EPFL

Motivation

Finding numerical representations for words is fundamental for all machine learning methods dealing with text data.




Goal: For each word, find mapping (embedding)

word \rightarrow feature vector

$$w_i \mapsto \mathbf{w}_i \in \mathbb{R}^K \leftarrow \dim = \text{vocabulary size}$$

discrete \rightarrow continuous representation

Representation should capture semantics of the word.




Constructing good feature representations (= representation learning) benefits all ML applications.

The Co-Occurrence Matrix

A big corpus of un-labeled text can be represented as the co-occurrence counts

$n_{ij} := \# \text{contexts where word } w_i \text{ occurs together with word } w_j$



Needs definition of \times

- **Context** e.g. document, paragraph, sentence, window = "5 words apart"

- **Vocabulary**

$$\mathcal{V} := \{w_1, \dots, w_D\}$$

For words $w_d = 1, 2, \dots, D$ and context words $w_n = 1, 2, \dots, N$, the co-occurrence counts n_{ij} form a very sparse $D \times N$ matrix.

in practice
 $D = N$

Learning Word-Representations (Using Matrix Factorization)

Find a factorization of the co-occurrence matrix!

Typically uses log of the actual counts, i.e. $x_{dn} := \log(n_{dn})$.

• word 2 vec

• GloVe

We will aim to find \mathbf{W}, \mathbf{Z} s.t.

$$\mathbf{X} \approx \mathbf{W}\mathbf{Z}^\top.$$

So for each pair of words (w_d, w_n) , we try to 'explain' their co-occurrence count by a numerical representation of the two words

- in fact by the inner product of the two feature vectors $\mathbf{W}_{d:}, \mathbf{Z}_{n:}$.

$\log(\# \text{co-occurrence}(w_d, w_n))$

$$\min_{\mathbf{W}, \mathbf{Z}} \mathcal{L}(\mathbf{W}, \mathbf{Z}) := \frac{1}{2} \sum_{(d,n) \in \Omega} f_{dn} [x_{dn} - (\mathbf{W}\mathbf{Z}^\top)_{dn}]^2$$

weighting

same as netflix

where $\mathbf{W} \in \mathbb{R}^{D \times K}$ and $\mathbf{Z} \in \mathbb{R}^{N \times K}$ are tall matrices, having only $K \ll D, N$ columns.

The set $\Omega \subseteq [D] \times [N]$ collects the indices of non-zeros of the count matrix \mathbf{X} .

Each row of those matrices forms a representation of a word (\mathbf{W}) or a context word (\mathbf{Z}) respectively.

2014

GloVe

This model is called GloVe, and is a variant of word2vec.


Weights f_{dn} : Give “importance” of each entry. Choosing $f_{dn} := 1$ is ok.

GloVe weight function:

$$f_{dn} := \min \{1, (n_{dn}/n_{\max})^\alpha\}, \quad \alpha \in [0; 1] \quad \text{e.g. } \alpha = \frac{3}{4}$$

observed count

cut-off




Choosing K

K e.g. 50, 100, 500

how many features?

Word Analogies



Newspapers			
New York	New York Times	Baltimore	Baltimore Sun
San Jose	San Jose Mercury News	Cincinnati	Cincinnati Enquirer
NHL Teams			
Boston	Boston Bruins	Montreal	Montreal Canadiens
Phoenix	Phoenix Coyotes	Nashville	Nashville Predators
NBA Teams			
Detroit	Detroit Pistons	Toronto	Toronto Raptors
Oakland	Golden State Warriors	Memphis	Memphis Grizzlies
Airlines			
Austria	Austrian Airlines	Spain	Spainair
Belgium	Brussels Airlines	Greece	Aegean Airlines
Company executives			
Steve Ballmer	Microsoft	Larry Page	Google
Samuel J. Palmisano	IBM	Werner Vogels	Amazon

Training

- Stochastic Gradient Descent (SGD)
- Alternating Least-Squares (ALS)

← lab
efficiency per step
 $O(k)$
independent of N, D

Open questions:

- Parallel and distributed training
- Does regularization help?

down-side
of GloVe:
precomputing X


Alternative: Skip-Gram Model

(Original word2vec) 2013

Uses binary classification (logistic regression objective), to separate real word pairs (w_d, w_n) from fake word pairs. Same inner product score = matrix factorization.

Given w_d , a context word w_n is

- real = appearing together in a context window of size 5
- fake = any word $w_{n'}$ sampled randomly: Negative sampling (also: Noise Contrastive Estimation)



Contrastive
learning

Language Models

Self-

Unsupervised training:

$w_1 w_2 w_3 \dots w_n$?
next word

Can a model generate text? - train classifier to predict the continuation (next word) of given text

- Multi-class:

Use soft-max loss function with a large number of classes

D = vocabulary size

- Binary classification:

Predict if next word is real or fake (i.e. a negative sample, as above)

Impressive recent progress using large models, such as transformers

(e.g. GPT-2, GPT-3) ← 11B parameters

<https://transformer.huggingface.co/doc/gpt2-large>

purpose




get features (Rep. L.)



generate text

Learning Representations of Sentences & Documents

Supervised: For a supervised task (e.g. predicting the emotion of a tweet), we can use matrix-factorization (below) or convolutional neural networks (see next weeks).



Unsupervised:

- Adding or averaging (fixed, given) word vectors
- Training word vectors such that adding/averaging works well
- sent 2 vec
- Direct unsupervised training for sentences (appearing together with context sentences) instead of words

e.g. for supervised
sentence classification

FastText



Matrix factorization to learn document/sentence representations (supervised).

Given a sentence $s_n = (w_1, w_2, \dots, w_m)$, let $\mathbf{x}_n \in \mathbb{R}^{|\mathcal{V}|}$ be the bag-of-words representation of the sentence.

$$\min_{\mathbf{W}, \mathbf{Z}} \mathcal{L}(\mathbf{W}, \mathbf{Z}) := \sum_{s_n \text{ a sentence}} f(y_n \underbrace{\mathbf{W} \mathbf{Z}^T}_{\text{sentence representation}} \mathbf{x}_n)$$

where $\mathbf{W} \in \mathbb{R}^{1 \times K}$, $\mathbf{Z} \in \mathbb{R}^{|\mathcal{V}| \times K}$ are the variables, and the vector $\mathbf{x}_n \in \mathbb{R}^{|\mathcal{V}|}$ represents our n -th training sentence.

Here f is a linear classifier loss function, and $y_n \in \{\pm 1\}$ is the classification label for sentence \mathbf{x}_n .



like logistic regression

SGD
efficiency

Further Pointers

1. word2vec:

code: code.google.com/p/word2vec/

paper:

“Distributed representations of words and phrases and their compositionality” - T Mikolov, I Sutskever, K Chen, GS Corrado, J Dean. NIPS 2013

2. GloVe:

code and vectors: nlp.stanford.edu/projects/glove/

paper:

“GloVe: Global Vectors for Word Representation” - Pennington, J., Socher, R., Manning, C. D.. EMNLP 2014

3. Write with transformers:

code and demo: transformer.huggingface.co/doc/gpt2-large

4. FastText & sent2vec

code: github.com/facebookresearch/fastText

papers:

“Bag of Tricks for Efficient Text Classification” - Joulin, A., Grave, E., Bojanowski, P., Mikolov, T. - **EC-ACL**, 2017.

“Enriching Word Vectors with Subword Information” - Bojanowski, P., Grave, E., Joulin, A., Mikolov, T. - **TACL**, 2017.

“Unsupervised Learning of Sentence Embeddings using Compositional n-Gram Features” - Pagliardini, M., Gupta, P., Jaggi, M. **NAACL** 2018.