# When Schema Lexicons Fail: Diagnosing and Repairing Entity-Layer Collapse in a Production Knowledge Base

Anonymous Author(s)

## ABSTRACT

In dictionary-driven entity enrichment, the schema lexicon effectively serves as the extraction model. We report a production incident in which a category-word lexicon silently collapsed the entity layer of a 61,137-document scholarly knowledge base: 575 type-level entities ("method", "energy") carrying ∼19.2M links while every job-level monitor stayed green. We diagnose the failure across three layers (extraction mechanism, lexicon provenance, monitoring blindness), repair it with a three-source corpus-presence-attested lexicon (3,702 terms), rebuild the entity layer under production load, and derive gold-free monitors led by a concentration diagnostic invariant to uniform rescaling of link counts. A controlled experiment that fixes code and corpus and varies *only the lexicon* reproduces the collapse signature alone (109±5 entities, top-10 concentration 0.513±0.016, 1.85±0.05 concepts per matched document) and isolates the repair effect (692±27, 0.300±0.008, 3.89±0.07; mean±sd over ten random resamples of the same corpus); the rebuilt layer carries 1,871 entities, 25.1M links, and a functioning relation layer; distinct concepts per document rise 15.7→37.8 with annotated-document coverage ∼51.5%→98.5% (48.5% of documents carried no annotations pre-repair); a risk-stratified 300-link audit (187 distinct entities; a stratum-mixed rate, not a link-uniform estimate) reads 0.84 overall — 0.95 on domain terms, 0.58 on short ambiguous symbols. The generic tail survives repair (9% of links sit on the single ambiguous symbol "be"), the isolated-experiment metrics are structural rather than semantic, retrieval-facing gains are not attributable to the lexicon alone (removing the direct entity channels leaves @10 metrics unchanged), audit is model-assisted rather than human-adjudicated, and the concentration alarm bands are candidate thresholds read post-hoc from 13 libraries — limitations stated up front.

## KEYWORDS

knowledge base construction schema quality terminology extraction entity linking production incident observability

## 1 INTRODUCTION

Scholarly knowledge platforms increasingly generate subject schemas with LLM assistance: a batch tool drafts entity types with a handful of aliases each, a validator checks structural well-formedness, and the schema is bound to knowledge bases as configuration [5]. When the enrichment pipeline then extracts mentions by *dictionary scan*, the schema's alias list becomes the extraction surface — the lexicon is not descriptive metadata but operative infrastructure.

The failure we report: a 61,137-document nuclear-electronics knowledge base accumulated ∼19.2M entity links onto **575 canonical entities**, every one a bare type word ("method", "parameter", "energy"); a 13,408-document physics library showed the same failure pattern at 2,018 entities. Every operational signal stayed green — jobs done, throughput nominal, link volume reading as growth. The graph had degenerated into a bipartite type–document index that was row-level indistinguishable from a populated knowledge graph.

We contribute three things. **(1) A failure mode and its causal confirmation**: when extraction is a dictionary scan, a structurally valid schema lexicon acts as the extraction model and can silently collapse the entity layer — established forensically (§3) and then *causally*, by a controlled experiment that fixes code and corpus and varies only the lexicon across ten disjoint corpus resamples (§4). **(2) A corpus-attested lexicon lifecycle** (seed transplant, classified corpus candidates, bounded expansion — corpus presence gated) that repaired both schemas without manual lexicography and survived a full production rebuild (§5–6). **(3) Gold-free entity-quality observability**: concentration-led monitors with candidate thresholds read from 13 production libraries (§7.1), plus a corrected incident log demonstrating that dashboard-derived incident narratives themselves require row-level verification.

## 2 BACKGROUND AND PRIOR ART

Dictionary- or gazetteer-driven entity recognition is one of the oldest NER traditions [2]; corpus-statistical term recognition goes back to C-value/NC-value [1] — our corpus-candidate source is that program reborn with an LLM classifier. Knowledge-graph refinement [3] and production data validation [4] address adjacent problems. What this incident exposes is a specific failure locus: when the dictionary effectively *is* the extraction model, a structurally valid but terminologically hollow schema passed every gate *this pipeline had in place* (schema-shape validation, ingestion checks, job-level monitors). Distribution-statistics monitoring [4] is the right tradition, but the statistic must be aimed at the lexicon's terminological content; none of our gates asked whether a lexicon's entries are domain-specific terms.

Our pipeline extracts mentions in stage K1 by normalized dictionary scan (CJK substring; ASCII word-boundary with optional plural, case-folded); K2 links mentions to canonical entities by normalized form + type; K3 adjudicates typed relations with an LLM; K4 projects to the graph store. The healthy reference case in the same deployment — hydrogeology, 78 documents, a hand-evolved 3,742-term lexicon, 1,608 entities — establishes plausibility, not causation: domain, scale, and provenance all differ.

## 3 THE COLLAPSE, FORENSICALLY

**Observation** (Table 1). During an unrelated storage investigation (2026-10-08), a routine entity-quality sample returned type words where domain concepts were expected.

**Mechanism.** When the alias set for type *method* contains common words, every occurrence in 7.2M chunks becomes a mention,

**Table 1: The collapse, measured, with snapshot provenance ("bckp." = 2026-10-06 cold backup, mid-enrichment; "disc." = discovery-day).**

| KB | Entities | Links |
|---|---|---|
| nuclear (61,137 docs) | **575** (disc.) / 503 (bckp.) | ∼**19.2M** (disc.) / 4.81M (bckp.) |
| physics (13,408 docs) | **2,018** | 2.23M (bckp.) |
| hydro (ref., 78 docs) | 1,608 | 719,515 |

**Table 2: Controlled lexicon-only comparison across ten disjoint corpus resamples (mean±sd). Conc/doc = concepts per *matched* document; arms' denominators differ (977 vs. 1,579 matched docs per sample).**

| Arm | Links | Ents | $C_{10}$ | Conc/doc |
|---|---|---|---|---|
| v2.0 collapse-era | 2,969 ± 140 | 109 ± 5 | 0.513 ± .016 | 1.85 ± .05 |
| v2.5 mid | 4,823 ± 147 | 421 ± 25 | 0.322 ± .009 | 2.51 ± .05 |
| v2.1 repair | 10,042 ± 251 | 692 ± 27 | 0.300 ± .008 | **3.89 ± .07** |
| +case-sens. short | 8,758 ± 228 | 665 ± 28 | 0.265 ± .012 | 3.54 ± .07 |
| +stop-word block | 9,226 ± 251 | 691 ± 27 | **0.252 ± .011** | 3.67 ± .07 |

and K2 folds them onto one entity per (form, type). The mechanism executed faithfully on degenerate input; the dictionaries were the schemas — the batch generator produced a category taxonomy where a terminology was needed [6].

**Timeline** (compressed): 10-08 discovery → root cause, lexicon tool built/run/committed, teardown + 766,501-event re-enqueue; 10-08 night: silent mis-attribution window (below); 10-09 drain completes, statistics recomputed, two smaller libraries with the same failure pattern treated; 10-09/10: retrospective audits (scoped refresh, channel ablation, link audit, fleet-wide concentration) and manuscript. The compression is real; the evaluation is retrospective, not pre-registered.

**Why nothing fired.** Job-level observability was all green; link volume read as success. The observables that expose the collapse are the concentration of links on the top entities (collapsed: 0.419, measured from the pre-incident backup, versus 0.18 for the reference case) and the name distribution of those entities (pure type vocabulary). Entity cardinality per document — a factor of 2,192 below the reference case (0.0094 vs 20.6) — corroborates, but is gameable in both directions, so it is the secondary signal.

## 4 IS THE LEXICON THE CAUSE? ISOLATING THE VARIABLE

The repair bundled lexicon, teardown, and fleet changes; this experiment isolates the lexicon alone *before* we present the repair method: a semantic replica of the K1/K2 scan-and-link semantics with *only the dictionary swapped* — v2.0 as committed at library creation (182 scan terms), v2.5 mid-evolution (2,932), v2.1 the repair (3,733; construction in §5), plus two v2.1 governance variants. The replica copies the scanner's matching and folding rules from the same source reading (CJK substring; ASCII word-boundary with optional plural, case-folded; fold key = normalized form + type); it is not instrumented against the live service path, so absolute levels may drift — the experiment's force is the within-frame arm contrast.

**Design.** Ten seeded, uniformly random resamples of 2,000 chunks each from the library's 5.83M visible chunks — independent draws from a *single* corpus, i.e. a sampling-stability check within one library, not cross-domain evidence — cross-sample disjoint, deduplicated on redraw (an earlier single run had sampled an ordered prefix, which we replace rather than defend). Fixed code, fixed corpus, fixed scanner; the only variable is the dictionary. All metrics are deterministic; Table 2 reports mean±sd across the ten resamples. Concepts-per-document is averaged over *matched* documents only (≥1 scan hit under that arm's dictionary: mean 977 matched documents per sample under v2.0, 1,579 under v2.1), so the arms' denominators are different sets.

**Finding 1 — the collapse signature is reproduced by the lexicon alone.** Under v2.0, the same code on the same corpus yields 109±5 entities at concentration 0.513±0.016 with 1.85±0.05 concepts per *matched* document: the collapse needs no pipeline bug, no data loss, no misconfiguration — only a category-word dictionary.

**Finding 2 — the repair effect is isolated and monotone.** v2.1 multiplies link-bearing entities ×6.3 and concepts per matched document ×2.1 (matched docs per sample 977⟶1,579); generic-head mass falls 0.146⟶0.058. The production collapsed concentration ($C_{10}$=0.419) sits between the v2.0 (0.513) and v2.5 (0.322) counterfactuals, consistent with mid-enrichment dictionary evolution. These are *structural* signatures: entity count, concentration, and concepts per document do not by themselves measure terminology recall or sense fit — the only semantic reading in this paper is the link audit of §7.

**Finding 3 — the be class is treatable at known cost.** Case-sensitive short symbols remove the largest entity at the price of match volume (links −12.8%; $C_{10}$ ⟶0.265); a stop-word block is gentler (links −8.1%, $C_{10}$ 0.252). The deltas measure matching *output*, not true recall: the removed mass mixes errors with correct terms, and the 0.580 pre-intervention judged-valid rate on this class (§7) motivates the treatment without yet demonstrating post-treatment validity — removed-vs-retained link verification is the open evaluation. *Provenance*: decomposing v2.1's link mass by which committed lexicon first contained each term — v2.0-inherited 22.0%, mid-evolution 16.0%, **three-source-new 61.9%** (384 of 686 entities) — is a decomposition, not a per-source causal ablation; independently regenerating single-source lexicons remains future work. And the arms vary the dictionary as a whole (∼20× size gap), so term count, selection quality, and per-source method are not separately identified — a size-matched frequency-candidate control and blind old/new matched-context judging are the priority follow-ups.

**Why 692 entities here vs 1,871 in production (§7)?** The isolated frame counts only entities induced by scanning 2,000 chunks (0.034% of the library) under replica folding: rare terms need corpus mass to be attested, and the production layer additionally carries entities from the full corpus and historical merging. The causal claim rests on within-frame comparisons, never on this cross-frame count.

## 5 CORPUS-ATTESTED LEXICON CONSTRUCTION

The repair lexicon whose causal role §4 isolated is built from three sources, all gated by corpus presence (a term the corpus never attests is not admitted — presence is necessary, not sufficient, for termhood): **seed transplant** (2,284 terms from a healthy near-domain library); **corpus-candidate classification** (top 8,000 unigram/bigram n-grams by chunk frequency over a 3,000-chunk-per-KB sample, frequency ≥5 after boilerplate and stop-word filtering; an LLM classifies each into a schema type or rejects it); **per-type expansion** (≤60 per type). Catch-all types accept no classified noise; cross-type conflicts resolve by specificity. Classifier: Qwen3.6-35B-A3B (AWQ 4-bit, community build; served under a historical alias), temperature 0.2, single idempotent run. Output: nuclear v2.1 = 3,702 terms; physics v1.1 = 1,279.

## 6 REBUILD AT SCALE — AND A CORRECTED INCIDENT LOG

Per knowledge base: delete graph vertices with edges, the four relational tables in bounded chunks, and the search-side projection; re-enqueue all documents through four stages. The printed "766,501 jobs" counts *events*, not distinct doc-stages (74,545×4 = 298,180): the surplus is the repair window's re-enqueue waves (silent-empty reset 75,831; zero-effect relations/graph resets ≈149k; watchdog-deletion recovery ≈122k; small libraries 5,772).

Four pipeline pathologies surfaced and were fixed with measured effect — an unbounded projection join that saturated the database (25+ min → seconds once scoped), two link-insertion deadlock classes (deadlocks 1213 → 0), and an $O(N^2)$ alias check the richer lexicon itself amplified (fleet link throughput 8/min → 1,100/min, a window-level aggregate). The archival version carries the full per-pathology accounting.

**The fifth pathology, revisited.** Our log recorded a parameter-order bug in a single-statement link writer whose rows `INSERT IGNORE` "silently swallowed" for seven hours. A minimal reproduction on the production engine (MySQL 8.4, `STRICT_TRANS_TABLES`, faithful DDL) sharpens the mechanism: the NULL from `UNHEX('alloy')` is **replaced by the implicit default 0x00×16 and the row is inserted** — into a ghost bucket invisible to every per-KB query — and a later correct re-insert for the same (mention, entity) pair is **silently skipped by the unique key**: the orphan poisons the repair unless deleted first (production carries zero 0x00 rows today, so cleanup happened). The duration claim also fails row-level forensics: the registry's own `created_at` histogram (Figure 1) shows KB1 inserting at 1.0–2.3M rows/hour *through* the nominal silent window and KB2's entire link layer landing in one hour. We keep the log entry and its correction side by side: incident narratives written from job dashboards are themselves unverified claims.

## 7 EVALUATION

**Entity layer.** Concepts-per-document replaces the raw entity/document ratio: its numerator scales with documents and the coverage column exposes the collapse's most user-visible symptom — half the library had *no* annotations. Absolute link counts *rise* after repair (KB1 19.2M→25.1M; KB2 2.23M→5.0M): real terms match more often. Count was never the quality signal; distribution and names are.





**Figure 1: Rebuild telemetry from the link registry's own timestamps. The shaded band is the *logged* silent window; inserts continue through it — the timestamp correction of §6.**

**Table 3: Entity layer before/after, with snapshot provenance.**

| Metric (KB1) | Collapsed | Repaired |
|---|---|---|
| canonical entities | 575 / 503 (10-06) | **1,871** |
| entity links | ∼19.2M / 4.81M | **25.1M** |
| typed relations | ∼0 | **44,043** |
| top-10 concentration | 0.419 | **0.345** |
| concepts/doc (all-doc) | 15.7 (51.5% covered) | **37.8** (98.5% covered) |
| KB2: concepts/doc | 29.5 | **61.4** |

**Name quality** (Figure 2). The repaired head is still generic: be (2.26M links, 9.0%), `alpha`, `gamma`, `beta`, `method`. The be case is a normalization failure — element symbol and auxiliary verb merge under case-folded matching — and §4 prices its treatment. The repair moved the problem from "no terminology at all" to "terminology plus a generic tail."

**Link audit: 300 risk-stratified links.** Entities drawn uniformly within four strata (top-10 by frequency; medium, ranks 11–100; tail, ranks 101+; short symbols, canonical names of ≤4 letters), then one link uniformly per entity — seeded and replayable. Span integrity 300/300. The judged-valid rate is **0.837** for this sample (Wilson 95% CI [0.791, 0.874]); by stratum: top-10 **0.920** [0.812, 0.968], medium 0.850 [0.767, 0.907], tail 0.910 [0.838, 0.952], short-symbol **0.580** [0.442, 0.706]. Three scope notes. First, the 50/100/100/50 quotas target risk, not production link frequencies: 0.837 is a stratum-mixed rate and must not be read as an unweighted production-wide link precision. Second, the 300 links come from 187 distinct entities (the head stratum's 50 links from just six; the short and head strata share "term"), so the intervals treat links, not concepts, as exchangeable — the CI is neither an interval for the 25.1M production links nor for 187 independent concepts. Third, the design's purpose is to localize high-risk failure — which it does: the short-ambiguous-symbol class that Figure 2 colors red and §4 prices is where validity collapses — a more informative finding than any overall figure. A second





**Figure 2: Top-30 entities by link share, before (cold backup; $C_{10}$=0.419) and after repair ($C_{10}$=0.345). Categories follow a fixed three-way rubric (domain term / generic academic word / short ambiguous symbol), assigned by the authors per entity; the rubric and per-entity assignments ship with the artifact.**





**Figure 3: Judged-valid rates with Wilson 95% CIs: the risk-stratified 300-link sample (stratum-mixed, 187 entities; primary judge); the cross-judge bar applies to the 55-link parseable subset of the earlier uniform sample.**

Qwen-series model re-adjudicated the earlier uniform sample: on the 55-link parseable subset agreement is 96.4% (domain 14/14) — a cross-model check, not family-independent confirmation (Figure 3), and unparseable responses may be non-random. Human adjudication remains the decisive future control.

**Retrieval: honest attribution.** Scoped coverage rose +6.6/+7.3 points over the repair window, but three controls bound the attribution: (a) removing the direct entity channels under the final configuration leaves @10 any-hit and document coverage unchanged on both scoped sets (MRR +0.0006, CI [0, 0.0018]; cov@20 −1.0pt on one set) while cutting p50 latency 1.46 s⟶0.52 s — and a forced-trigger check on the natural-phrasing set shows the channels are alive (54/99 fired; killing them costs 20 losses / 0 wins), so the ablation bounds these channels' marginal contribution in this configuration, not the semantic assets' value at large; (b) alias expansion, the one entity-adjacent mechanism, is +1.5pt (ns) on the benchmarks at 2× latency; (c) two same-configuration runs differ on exactly one query (0.5pt noise floor). The trajectory is system-level; the entity layer's retrieval-facing value runs through asset surfaces (documented in the companion system manuscript [7]), not fusion votes.

**Table 4: The candidate calibration behind Figure 4, summarized (the collapsed row is the pre-repair backup, not a live point).**

| Group | Libs | Entities | $C_{10}$ range |
|---|---|---|---|
| Collapsed (backup) | 1 | 503 | 0.419 |
| Hand-curated control | 1 | 1,239 | 0.184 |
| Other prod., ≥500 ents | 4 | 874–2,482 | 0.259–0.287 |
| Rebuilt here, large | 2 | 1,871 / 2,726 | 0.162–0.345 |
| Rebuilt here, small | 2 | 153–629 | 0.398–0.768 |
| Other prod., <500 ents | 4 | 5–424 | 0.395–1.000 |

## 7.1 Monitors and Discussion

Four gold-free monitors, in the spirit of production data validation [4]: **(a) top-10 link concentration** (primary): invariant to uniform rescaling of counts, but bounded below by $\min(10, N)/N$





**Figure 4: Top-10 link concentration vs. link-bearing entities across 13 production libraries; red = rebuilt in this incident, green star = hand-curated reference. Bands are candidate thresholds read post-hoc from this deployment.**

— trivially 1 for a library with ≤10 entities — and sensitive to topic concentration as well as to degradation. Across the 13 deployment libraries the metric spans 0.16–0.77 among libraries with ≥100 entities (the smallest, five entities, reads 1.000 — the floor bound, not degradation; Table 4); healthy/repaired large libraries run 0.16–0.19, the rebuilt nuclear library 0.345, the two small treated libraries *currently* 0.398 and 0.768 (reported as measured). The collapsed physics backup reads 0.290 — *below* the 0.35 band — so a concentration threshold alone does not catch every collapse; the name-audit and coverage legs carry the rest. The bands (>0.35 investigate, >0.5 escalate) are *candidate* thresholds read post-hoc from these 13 libraries — a starting point, not a validated norm. Validation need not re-collapse production: graded lexicon degradation injected offline into a frozen slice, reporting alarm precision, false-positive rate, detection delay, and size sensitivity, is the natural protocol — future work here. **(b) entity cardinality ratio** (coarse secondary, gameable both ways). **(c) top-entity name audit** (five-minute quarterly control). **(d) target-table growth reconciliation** — the B95 ghost-bucket mechanism makes this mandatory wherever a bulk writer is guarded by `INSERT IGNORE`. The small-library treatment is an illustrative within-deployment case (the candidate bands were read after observing these 13 libraries — not out-of-sample validation): cardinality normalized (870→629, 209→153) while concentration still flags both — the two monitors separate "cardinality repaired" from "distribution still skewed."

The incident is not an argument for LLM-everywhere: if extraction is a scan, the dictionary serves as the model and deserves a trained model's evaluation discipline. Admission criteria (corpus presence) are necessary but not sufficient; *ranking* criteria (IDF-style contrast, bilingual consistency, length/type priors) are the open problem — the generic tail is the standing evidence.

## 8 CONCLUSION

**When does a structurally valid lexicon produce semantic collapse?** When its entries are category words: the scan executes faithfully, and a dictionary-only swap reproduces the signature. **What does corpus-presence gating repair, and what remains?** Terminology and coverage (annotated documents ~51.5%→98.5%) — but a generic tail persists; presence is necessary, not sufficient. **What can gold-free diagnostics see?** Distribution and names, not link correctness: 0.84 stratified judged-valid (0.58 on short symbols) is model-assisted, and the repair's semantic gain awaits blind old/new comparison. The incident motivated and validated; the controlled swap and stratified audit carry the evidence.

## 9 LIMITATIONS

(1) The generic tail survives repair (9% of links on "be"). (2) Retrieval attribution is bounded, not eliminated: the full lexicon×configuration decomposition is runnable on frozen slices or isolated stacks via graded degradation — not yet run, rather than impossible. (3) Coverage: two libraries rebuilt, two smaller treated; bilingual anomalies documented, not explained. (4) Six secondary incidents extended the repair; reported as findings. (5) Audit and cross-judge are model-assisted (same vendor family), not human-adjudicated; the risk-stratified sample mixes quota-defined strata and clusters on 187 entities, and unparseable cross-judge responses may be non-random. (6) The isolated experiment uses a semantic-replica scanner (not instrumented against the service path) and committed-snapshot dictionaries over ten resamples of one corpus — a stability check, not cross-domain evidence; its metrics are structural, with semantic reading confined to the sampled audit, and the governance arms await removed-vs-retained link verification.

## REFERENCES

[1] K. Frantzi, S. Ananiadou, H. Mima. Automatic recognition of multi-word terms: the C-value/NC-value method. *Int. J. on Digital Libraries* 3(2), 2000, 115–130.
[2] D. Nadeau, S. Sekine. A survey of named entity recognition and classification. *Lingvisticae Investigationes* 30(1), 2007, 3–26.
[3] H. Paulheim. Knowledge graph refinement: A survey of approaches and evaluation methods. *Semantic Web* 8(3), 2017, 489–508.
[4] E. Breck, S. Cai, E. Nielsen, M. Salib, D. Sculley. Data validation for machine learning. *Proc. MLSys*, 2019.
[5] A. S. Lippolis et al. Ontology generation using large language models. arXiv:2503.05388, 2025.
[6] ISO 1087: Terminology work and terminology science — vocabulary. ISO, 2019.
[7] Anonymous. KnowledgeNexus: A traceable graph–vector knowledge infrastructure and adaptive multi-channel retrieval for nuclear science literature. Companion manuscript, under submission; preprint in the artifact release.