

# *FAQ - new svn repository and project*

## **List of Frequently Asked Questions**

Where do I find a quickstart guide for svn? . . . . .	2
How do I set up a new svn repository? . . . . .	2
How do I start a new svn project? . . . . .	2
How do I import my new project into the repository? . . . . .	2
How do I list the content of my repository? . . . . .	3
How do I create a tagged version? . . . . .	3
How do I initialize a new user branch? . . . . .	3
How do I check out a working copy? . . . . .	3
How do I check out a working copy of a specific revision No.? . . . .	3
How do I change a given log message of my repository? . . . . .	4
How do I show the version number of my svn installation? . . . . .	4
How do I show the version number of a given svn repository? . . . . .	4
How do I archive my repository? . . . . .	4
How do I set up my repository from archive? . . . . .	5

### Where do I find a quickstart guide for svn?

For quickstart of svn you may refer to:

```
http://svnbook.red-bean.com/  
nightly/de/svn-book.html\#svn.intro.quickstart
```

### How do I set up a new svn repository?

You may log on as root and choose an appropriate location for you repository:

```
su  
mkdir /var/svn
```

If you assign the sticky-bit (t), files can only be deleted by the owner:

```
chmod +t /var/svn
```

Log off as root:

```
exit
```

To setup the new repository use the `svnadmin` command:

```
svnadmin create /var/svn/repos ; ls /var/svn/repos
```

### How do I start a new svn project?

Start with a new folder and generate the basic directory structure of your svn project:

```
mkdir ~/work  
mkdir ~/work/myproject  
mkdir ~/work/myproject/trunk  
mkdir ~/work/myproject/tags  
mkdir ~/work/myproject/branches
```

Place all files you want to assign to the new project into `trunk`.

### How do I import my new project into the repository?

Use `svn import` and assign a brief description (type in one line):

```
svn import ~/work/myproject file:///var/svn/repos/myproject  
-m "initial import myproject"
```

### How do I list the content of my repository?

Use `svn list` to browse your repository, e.g.:

```
svn list file:///var/svn/repos
svn list file:///var/svn/repos/myproject
svn list file:///var/svn/repos/myproject/trunk
```

### How do I create a tagged version?

You create a tagged version from trunk, e.g.:

```
svn copy file:///var/svn/repos/myproject/trunk
         file:///var/svn/repos/myproject/tags/Version-1.00
         -m "tagged version 1.0"
```

### How do I initialize a new user branch?

You can initialize a new user branch directly from trunk or from a tagged version, e.g.:

```
svn copy file:///var/svn/repos/myproject/trunk
         file:///var/svn/repos/myproject/branches/anyuser
         -m "first user branch"

svn copy file:///var/svn/repos/myproject/tags/Version-1.00
         file:///var/svn/repos/myproject/branches/anyuser
         -m "first user branch"
```

### How do I check out a working copy?

You can check out a working copy from trunk, a user's branch or a tagged version, e.g.

```
svn checkout file:///var/svn/repos/myproject/trunk myproject
svn co file:///var/svn/repos/myproject/branch/anyuser myproject
svn co file:///var/svn/repos/myproject/tags/Version-1.00 myproj_v1.0
```

### How do I check out a working copy of a specific revision No.?

A working copy of a specific revision number is checked out as follows (e.g. from trunk):

```
svn checkout -r 6 file:///var/svn/repos/myproject/trunk myproject
```

### How do I change a given log message of my repository?

Use `svnadmin setlog` with `--bypass-hooks`, e.g. for log message of revision No. 6:

```
echo "new log message" > newlogmessage
```

```
svnadmin setlog /var/svn/repos -r 6 newlogmessage --bypass-hooks
```

Please notice: the `--bypass-hooks` should be used very carefully.

Alternatively a hook called `pre-revprop-change` must be created by your administrator. In this case you can use the same command without the `--bypass-hooks`:

```
svnadmin setlog /var/svn/repos -r 6 newlogmessage
```

### How do I show the version number of my svn installation?

You can show the version number of your svn program as follows:

```
svn --version --quiet
```

### How do I show the version number of a given svn repository?

The version number of a given repository (i.e. svn version used to generate the repository) is contained in the `./db/format` file:

```
more /var/svn/repos/db/format
```

The number listed on the first line indicates the version number as follows:

1 => 1.1+ ; 2 => 1.4+ ; 3 => 1.5+ ; 4 => 1.6+ ; 5 => 1.7-dev ; 6 => 1.8 ; 7 => 1.9

The `+` symbol indicates upward-compatibility, e.g. 1.4+ says it was generated by svn version 1.4 and is readable by higher versions.

### How do I archive my repository?

Use `svnadmin dump` to export the content of your repository to a portable file:

```
svnadmin dump /var/svn/repos > svn_repos.dump
```

You may also want to create a log file of your repository:

```
svn log file:///var/svn/repos > svn_repos.log
```

### How do I set up my repository from archive?

Use `svnadmin load` to import the content of your archive file to your repository:

```
svnadmin create /var/svn/repos_new
```

```
svnadmin load /var/svn/repos_new < svn_repos.dump
```