synthetic variance application d03-omitted

[section A]
FIELD | owner_name | Owner | Avery Synthetic
FIELD | representative | Owner Rep | Riley Synthetic
FIELD | mailing_address | Mailing Address | 100 Example Avenue, Edmonton, Alberta
FIELD | application_date | Date of Reqeuest | 2026-10-20
FIELD | signature | | signed
FIELD | owner_rep_signature_date | Date2 | 2026-10-20

[section B]
FIELD | legal_description | | Lot 4 Block 8 Plan 1234567
FIELD | lot | Lot | 4
FIELD | block | Block | 8
FIELD | plan | Plan | 1234567
FIELD | alternative_description | | The proposed soffit stays vented aluminum where the north exposing wall h
limiting distance: 1.2 m
storeys: 2
sprinklered: no
product thickness: 10 mm

[section C]
FIELD | code_or_standard | Code or Standard | National Building Code - 2023 Alberta Edition (2nd printing), Di
FIELD | section_c.article | Article(s) | 9.10.15.5.(8)
FIELD | objective | Objective | OP3.1
FIELD | function | Function | F03
FIELD | section_c.intent | Intent statement | NBC 2020 Intent Statements, explanatory only. National explanato
FIELD | heading | | spatial separation soffit overhang

[section process]
FIELD | risk_assessment | | If the soffit remains vented over the north wall at the stated 1.2 m limiting dis
FIELD | mitigating_measures | | Non-vented soffit material and protection on the north overhang address the l
FIELD | assumptions_and_limits | | Assumes the north wall limiting distance stays 1.2 m, the house remains a

[section D]
FIELD | supporting_doc | Supporting Doc | Synthetic product sheet for the soffit assembly
FIELD | responsible_party | Name Responsible | Casey Synthetic, product specialist
FIELD | document_date | | 2026-10-01
FIELD | engineering_required | | no
FIELD | professional_name | |
FIELD | professional_qualifications | |

[section B]
FIELD | division_c_2_3_1 | | The Division C Section 2.3.1 documentation for this alternative solution is incl

[attachment drawings]
limiting distance: 1.2 m
storeys: 2
sprinklered: no
product thickness: 10 mm