Date _____

Q4:

```
function getValidDays( ) returns integer
  day : integer, day ← 0
  while d<=0 OR d>7
  Output "days: "
  Input days

return days

function CalculateDailySales (daynum : int) returns real
  orders : integer , orders ← 0
  Output "orders: "
  Input orders
  sale[orders] : array of Real
  total, amount, max, avg : real ← 0
    for i <= 1 to orders
      amount = 0.0
      while (amount <= 0.0)
        Output "amount: "
        Input amount
      sales[i] = amount

    max = sales[0]
    for j = 1 to orders
      total += sale[i]
      if (sale[i] > max)
        max = sale[i]
    avg = total / orders
```

Unics Products make you Unique!!!

Date

Output total, avg, max
return total

function findHighestSalesDay (dailysales[]: array of real,
numdays : integer) returns integer
highest_sales = integer ← 0
max = ~~float~~ integer ← dailysales[0]
for i = 1 to numdays
if dailySales[i] > max
max = dailysales[i]
highest_sale = i

return highest_sale

Procedure displayBarchart (dailysales[]: array of real,
numdays : integer)
asterisk: integer ← 0
for i = 1 to numdays
asterisk = dailysales[i]/100
Output i
~~Out~~
for j = 1 to asterisks
Output *

main →

totaldays : index : integer ← 0
~~dailysales[1~~ totaldays = getValiddays ( )
dailysales [totaldays] : array of Real
total : real ← 0.0

Unics Products make you Unique!!!

Date

```
for i = 1 to total_days
    Output "Day", i
    daily_sales[i] = calculateDailySales[i]
    total += daily_sales[i]
integer
index = findHighestSalesDay(daily_sales, total_days)
Output total, index, daily_sale[index - 1]

displayBarChart(daily_sales, total_days)
```

→ Inputs:
1. festival days
2. Order cant
3. amount for each order

→ Outputs:
for each day:
1. total sales
2. avg sale ~~per day~~
3. Highest order amount

→ Summary:
1. totals sales on all days
2. Day with the highest sale, and amount on that day.

→ Bar chart summary

Unics PRODUCTS Unics Products make you Unique!!!

CamScanner