

# Security in Computing

Fifth Edition



Charles P. Pfleeger  
Shari Lawrence Pfleeger  
Jonathan Margulies

FREE SAMPLE CHAPTER

SHARE WITH OTHERS



# Security in Computing

---

FIFTH EDITION

*This page intentionally left blank*

# Security in Computing

---

**FIFTH EDITION**

**Charles P. Pfleeger  
Shari Lawrence Pfleeger  
Jonathan Margulies**



**PRENTICE  
HALL**

Upper Saddle River, NJ • Boston • Indianapolis • San Francisco  
New York • Toronto • Montreal • London • Munich • Paris • Madrid  
Capetown • Sydney • Tokyo • Singapore • Mexico City

Many of the designations used by manufacturers and sellers to distinguish their products are claimed as trademarks. Where those designations appear in this book, and the publisher was aware of a trademark claim, the designations have been printed with initial capital letters or in all capitals.

The authors and publisher have taken care in the preparation of this book, but make no expressed or implied warranty of any kind and assume no responsibility for errors or omissions. No liability is assumed for incidental or consequential damages in connection with or arising out of the use of the information or programs contained herein.

For information about buying this title in bulk quantities, or for special sales opportunities (which may include electronic versions; custom cover designs; and content particular to your business, training goals, marketing focus, or branding interests), please contact our corporate sales department at [corpsales@pearsoned.com](mailto:corpsales@pearsoned.com) or (800) 382-3419.

For government sales inquiries, please contact [governmentsales@pearsoned.com](mailto:governmentsales@pearsoned.com).

For questions about sales outside the U.S., please contact [international@pearsoned.com](mailto:international@pearsoned.com).

Visit us on the Web: [informit.com/ph](http://informit.com/ph)

*Library of Congress Cataloging-in-Publication Data*

Pfleeger, Charles P., 1948–

Security in computing / Charles P. Pfleeger, Shari Lawrence Pfleeger, Jonathan Margulies.—Fifth edition.

pages cm

Includes bibliographical references and index.

ISBN 978-0-13-408504-3 (hardcover : alk. paper)—ISBN 0-13-408504-3 (hardcover : alk. paper)

1. Computer security. 2. Data protection. 3. Privacy, Right of. I. Pfleeger, Shari Lawrence. II. Margulies, Jonathan. III. Title.

QA76.9.A25P45 2015

005.8—dc23

2014038579

Copyright © 2015 Pearson Education, Inc.

All rights reserved. Printed in the United States of America. This publication is protected by copyright, and permission must be obtained from the publisher prior to any prohibited reproduction, storage in a retrieval system, or transmission in any form or by any means, electronic, mechanical, photocopying, recording, or likewise. To obtain permission to use material from this work, please submit a written request to Pearson Education, Inc., Permissions Department, One Lake Street, Upper Saddle River, New Jersey 07458, or you may fax your request to (201) 236-3290.

ISBN-13: 978-0-13-408504-3

ISBN-10: 0-13-408504-3

Text printed in the United States on recycled paper at Courier in Westford, Massachusetts.

First printing, January 2015

**Executive Editor**  
Bernard Goodwin

**Editorial Assistant**  
Michelle Housley

**Managing Editor**  
John Fuller

**Project Editor**  
Elizabeth Ryan

**Copy Editor**  
Mary Lou Nohr

**Proofreader**  
Linda Begley

**Cover Designer**  
Alan Clements

**Compositor**  
Shepherd, Inc.

*To Willis Ware, a hero of  
computer security and privacy.*

*This page intentionally left blank*

# Contents

	<b>Foreword</b>	<b>xix</b>
	<b>Preface</b>	<b>xxv</b>
	<b>Acknowledgments</b>	<b>xxxi</b>
	<b>About the Authors</b>	<b>xxxiii</b>
<b>Chapter 1</b>	<b>Introduction</b>	<b>1</b>
1.1	What Is Computer Security?	2
	<i>Values of Assets</i>	4
	<i>The Vulnerability–Threat–Control Paradigm</i>	5
1.2	Threats	6
	<i>Confidentiality</i>	8
	<i>Integrity</i>	10
	<i>Availability</i>	11
	<i>Types of Threats</i>	13
	<i>Types of Attackers</i>	16
1.3	Harm	21
	<i>Risk and Common Sense</i>	22
	<i>Method–Opportunity–Motive</i>	26
1.4	Vulnerabilities	28
1.5	Controls	28
1.6	Conclusion	31
1.7	What’s Next?	32
1.8	Exercises	34



<b>Chapter 2</b>	<b>Toolbox: Authentication, Access Control, and Cryptography</b>	<b>36</b>
2.1	Authentication	38
	<i>Identification Versus Authentication</i>	38
	<i>Authentication Based on Phrases and Facts: Something You Know</i>	40
	<i>Authentication Based on Biometrics: Something You Are</i>	53
	<i>Authentication Based on Tokens: Something You Have</i>	65
	<i>Federated Identity Management</i>	68
	<i>Multifactor Authentication</i>	70
	<i>Secure Authentication</i>	70
2.2	Access Control	72
	<i>Access Policies</i>	72
	<i>Implementing Access Control</i>	75
	<i>Procedure-Oriented Access Control</i>	85
	<i>Role-Based Access Control</i>	85
2.3	Cryptography	86
	<i>Problems Addressed by Encryption</i>	87
	<i>Terminology</i>	87
	<i>DES: The Data Encryption Standard</i>	95
	<i>AES: Advanced Encryption System</i>	98
	<i>Public Key Cryptography</i>	100
	<i>Public Key Cryptography to Exchange Secret Keys</i>	103
	<i>Error Detecting Codes</i>	109
	<i>Trust</i>	117
	<i>Certificates: Trustable Identities and Public Keys</i>	121
	<i>Digital Signatures—All the Pieces</i>	124
2.4	Exercises	127
<b>Chapter 3</b>	<b>Programs and Programming</b>	<b>131</b>
3.1	Unintentional (Nonmalicious) Programming Oversights	133
	<i>Buffer Overflow</i>	134
	<i>Incomplete Mediation</i>	152
	<i>Time-of-Check to Time-of-Use</i>	155
	<i>Undocumented Access Point</i>	157
	<i>Off-by-One Error</i>	159
	<i>Integer Overflow</i>	160

	<i>Unterminated Null-Terminated String</i>	161
	<i>Parameter Length, Type, and Number</i>	162
	<i>Unsafe Utility Program</i>	162
	<i>Race Condition</i>	163
3.2	Malicious Code—Malware	166
	<i>Malware—Viruses, Trojan Horses, and Worms</i>	167
	<i>Technical Details: Malicious Code</i>	176
3.3	Countermeasures	196
	<i>Countermeasures for Users</i>	197
	<i>Countermeasures for Developers</i>	203
	<i>Countermeasure Specifically for Security</i>	216
	<i>Countermeasures that Don't Work</i>	224
	Conclusion	229
	Exercises	229
<b>Chapter 4</b>	<b>The Web—User Side</b>	<b>232</b>
4.1	Browser Attacks	234
	<i>Browser Attack Types</i>	234
	<i>How Browser Attacks Succeed: Failed Identification and Authentication</i>	240
4.2	Web Attacks Targeting Users	245
	<i>False or Misleading Content</i>	246
	<i>Malicious Web Content</i>	253
	<i>Protecting Against Malicious Web Pages</i>	259
4.3	Obtaining User or Website Data	260
	<i>Code Within Data</i>	261
	<i>Website Data: A User's Problem, Too</i>	265
	<i>Foiling Data Attacks</i>	266
4.4	Email Attacks	267
	<i>Fake Email</i>	267
	<i>Fake Email Messages as Spam</i>	267
	<i>Fake (Inaccurate) Email Header Data</i>	273
	<i>Phishing</i>	274
	<i>Protecting Against Email Attacks</i>	275
4.5	Conclusion	277
4.6	Exercises	278

<b>Chapter 5</b>	<b>Operating Systems</b>	<b>280</b>
5.1	Security in Operating Systems	280
	<i>Background: Operating System Structure</i>	281
	<i>Security Features of Ordinary Operating Systems</i>	282
	<i>A Bit of History</i>	284
	<i>Protected Objects</i>	286
	<i>Operating System Tools to Implement Security Functions</i>	292
5.2	Security in the Design of Operating Systems	308
	<i>Simplicity of Design</i>	309
	<i>Layered Design</i>	309
	<i>Kernelized Design</i>	312
	<i>Reference Monitor</i>	313
	<i>Correctness and Completeness</i>	314
	<i>Secure Design Principles</i>	315
	<i>Trusted Systems</i>	316
	<i>Trusted System Functions</i>	319
	<i>The Results of Trusted Systems Research</i>	325
5.3	Rootkit	329
	<i>Phone Rootkit</i>	329
	<i>Rootkit Evades Detection</i>	330
	<i>Rootkit Operates Unchecked</i>	334
	<i>Sony XCP Rootkit</i>	335
	<i>TDSS Rootkits</i>	336
	<i>Other Rootkits</i>	338
5.4	Conclusion	338
5.5	Exercises	339
<b>Chapter 6</b>	<b>Networks</b>	<b>341</b>
6.1	Network Concepts	342
	<i>Background: Network Transmission Media</i>	343
	<i>Background: Protocol Layers</i>	349
	<i>Background: Addressing and Routing</i>	350
	<b>Part I—War on Networks: Network Security Attacks</b>	<b>353</b>
6.2	Threats to Network Communications	354
	<i>Interception: Eavesdropping and Wiretapping</i>	354
	<i>Modification, Fabrication: Data Corruption</i>	361
	<i>Interruption: Loss of Service</i>	366
	<i>Port Scanning</i>	369
	<i>Vulnerability Summary</i>	374

6.3	Wireless Network Security	374
	<i>WiFi Background</i>	374
	<i>Vulnerabilities in Wireless Networks</i>	381
	<i>Failed Countermeasure: WEP (Wired Equivalent Privacy)</i>	388
	<i>Stronger Protocol Suite: WPA (WiFi Protected Access)</i>	390
6.4	Denial of Service	396
	<i>Example: Massive Estonian Web Failure</i>	396
	<i>How Service Is Denied</i>	398
	<i>Flooding Attacks in Detail</i>	402
	<i>Network Flooding Caused by Malicious Code</i>	403
	<i>Network Flooding by Resource Exhaustion</i>	407
	<i>Denial of Service by Addressing Failures</i>	408
	<i>Traffic Redirection</i>	413
	<i>DNS Attacks</i>	414
	<i>Exploiting Known Vulnerabilities</i>	419
	<i>Physical Disconnection</i>	420
6.5	Distributed Denial-of-Service	421
	<i>Scripted Denial-of-Service Attacks</i>	423
	<i>Bots</i>	426
	<i>Botnets</i>	426
	<i>Malicious Autonomous Mobile Agents</i>	430
	<i>Autonomous Mobile Protective Agents</i>	430
	<b>Part II—Strategic Defenses: Security Countermeasures</b>	<b>432</b>
6.6	Cryptography in Network Security	432
	<i>Network Encryption</i>	433
	<i>Browser Encryption</i>	437
	<i>Onion Routing</i>	443
	<i>IP Security Protocol Suite (IPsec)</i>	444
	<i>Virtual Private Networks</i>	447
	<i>System Architecture</i>	450
6.7	Firewalls	451
	<i>What Is a Firewall?</i>	452
	<i>Design of Firewalls</i>	453
	<i>Types of Firewalls</i>	454
	<i>Personal Firewalls</i>	465
	<i>Comparison of Firewall Types</i>	467
	<i>Example Firewall Configurations</i>	467
	<i>Network Address Translation (NAT)</i>	472
	<i>Data Loss Prevention</i>	473

6.8	Intrusion Detection and Prevention Systems	474
	<i>Types of IDSs</i>	476
	<i>Other Intrusion Detection Technology</i>	481
	<i>Intrusion Prevention Systems</i>	482
	<i>Intrusion Response</i>	483
	<i>Goals for Intrusion Detection Systems</i>	486
	<i>IDS Strengths and Limitations</i>	488
6.9	Network Management	489
	<i>Management to Ensure Service</i>	489
	<i>Security Information and Event Management (SIEM)</i>	492
6.10	Conclusion	496
6.11	Exercises	496

## **Chapter 7      Databases      501**

7.1	Introduction to Databases	502
	<i>Concept of a Database</i>	502
	<i>Components of Databases</i>	502
	<i>Advantages of Using Databases</i>	506
7.2	Security Requirements of Databases	507
	<i>Integrity of the Database</i>	507
	<i>Element Integrity</i>	508
	<i>Auditability</i>	510
	<i>Access Control</i>	511
	<i>User Authentication</i>	512
	<i>Availability</i>	512
	<i>Integrity/Confidentiality/Availability</i>	512
7.3	Reliability and Integrity	513
	<i>Protection Features from the Operating System</i>	513
	<i>Two-Phase Update</i>	514
	<i>Redundancy/Internal Consistency</i>	516
	<i>Recovery</i>	516
	<i>Concurrency/Consistency</i>	517
7.4	Database Disclosure	518
	<i>Sensitive Data</i>	518
	<i>Types of Disclosures</i>	519
	<i>Preventing Disclosure: Data Suppression and Modification</i>	529
	<i>Security Versus Precision</i>	530

7.5	Data Mining and Big Data	535
	<i>Data Mining</i>	536
	<i>Big Data</i>	540
7.6	Conclusion	549
	Exercises	549

## Chapter 8 Cloud Computing 551

8.1	Cloud Computing Concepts	551
	<i>Service Models</i>	552
	<i>Deployment Models</i>	552
8.2	Moving to the Cloud	553
	<i>Risk Analysis</i>	553
	<i>Cloud Provider Assessment</i>	554
	<i>Switching Cloud Providers</i>	556
	<i>Cloud as a Security Control</i>	557
8.3	Cloud Security Tools and Techniques	560
	<i>Data Protection in the Cloud</i>	561
	<i>Cloud Application Security</i>	566
	<i>Logging and Incident Response</i>	567
8.4	Cloud Identity Management	568
	<i>Security Assertion Markup Language</i>	570
	<i>OAuth</i>	573
	<i>OAuth for Authentication</i>	577
8.5	Securing IaaS	579
	<i>Public IaaS Versus Private Network Security</i>	580
8.6	Conclusion	583
	<i>Where the Field Is Headed</i>	584
	<i>To Learn More</i>	584
8.7	Exercises	584

## Chapter 9 Privacy 586

9.1	Privacy Concepts	587
	<i>Aspects of Information Privacy</i>	587
	<i>Computer-Related Privacy Problems</i>	590
9.2	Privacy Principles and Policies	596
	<i>Fair Information Practices</i>	596
	<i>U.S. Privacy Laws</i>	597

	<i>Controls on U.S. Government Websites</i>	599
	<i>Controls on Commercial Websites</i>	600
	<i>Non-U.S. Privacy Principles</i>	603
	<i>Individual Actions to Protect Privacy</i>	605
	<i>Governments and Privacy</i>	607
	<i>Identity Theft</i>	609
9.3	<b>Authentication and Privacy</b>	610
	<i>What Authentication Means</i>	611
	<i>Conclusions</i>	615
9.4	<b>Data Mining</b>	616
	<i>Government Data Mining</i>	617
	<i>Privacy-Preserving Data Mining</i>	617
9.5	<b>Privacy on the Web</b>	619
	<i>Understanding the Online Environment</i>	620
	<i>Payments on the Web</i>	621
	<i>Site and Portal Registrations</i>	622
	<i>Whose Page Is This?</i>	622
	<i>Precautions for Web Surfing</i>	624
	<i>Spyware</i>	628
	<i>Shopping on the Internet</i>	630
9.6	<b>Email Security</b>	632
	<i>Where Does Email Go, and Who Can Access It?</i>	632
	<i>Interception of Email</i>	633
	<i>Monitoring Email</i>	633
	<i>Anonymous, Pseudonymous, and Disappearing Email</i>	634
	<i>Spoofing and Spamming</i>	635
	<i>Summary</i>	636
9.7	<b>Privacy Impacts of Emerging Technologies</b>	636
	<i>Radio Frequency Identification</i>	636
	<i>Electronic Voting</i>	640
	<i>VoIP and Skype</i>	642
	<i>Privacy in the Cloud</i>	642
	<i>Conclusions on Emerging Technologies</i>	643
9.8	<b>Where the Field Is Headed</b>	644
9.9	<b>Conclusion</b>	645
9.10	<b>Exercises</b>	645

<b>Chapter 10</b>	<b>Management and Incidents</b>	<b>647</b>
10.1	Security Planning	647
	<i>Organizations and Security Plans</i>	648
	<i>Contents of a Security Plan</i>	649
	<i>Security Planning Team Members</i>	656
	<i>Assuring Commitment to a Security Plan</i>	656
10.2	Business Continuity Planning	658
	<i>Assess Business Impact</i>	660
	<i>Develop Strategy</i>	660
	<i>Develop the Plan</i>	661
10.3	Handling Incidents	662
	<i>Incident Response Plans</i>	662
	<i>Incident Response Teams</i>	665
10.4	Risk Analysis	668
	<i>The Nature of Risk</i>	669
	<i>Steps of a Risk Analysis</i>	670
	<i>Arguments For and Against Risk Analysis</i>	684
10.5	Dealing with Disaster	686
	<i>Natural Disasters</i>	686
	<i>Power Loss</i>	688
	<i>Human Vandals</i>	689
	<i>Interception of Sensitive Information</i>	692
	<i>Contingency Planning</i>	694
	<i>Physical Security Recap</i>	698
10.6	Conclusion	699
10.7	Exercises	700
<b>Chapter 11</b>	<b>Legal Issues and Ethics</b>	<b>702</b>
11.1	Protecting Programs and Data	704
	<i>Copyrights</i>	704
	<i>Patents</i>	711
	<i>Trade Secrets</i>	714
	<i>Special Cases</i>	716
11.2	Information and the Law	717
	<i>Information as an Object</i>	717
	<i>Legal Issues Relating to Information</i>	720



	<i>The Legal System</i>	721
	<i>Summary of Protection for Computer Artifacts</i>	724
11.3	Rights of Employees and Employers	725
	<i>Ownership of Products</i>	725
	<i>Employment Contracts</i>	727
11.4	Redress for Software Failures	728
	<i>Selling Correct Software</i>	729
	<i>Reporting Software Flaws</i>	731
11.5	Computer Crime	733
	<i>Why a Separate Category for Computer Crime Is Needed</i>	734
	<i>Why Computer Crime Is Hard to Define</i>	736
	<i>Why Computer Crime Is Hard to Prosecute</i>	736
	<i>Examples of Statutes</i>	737
	<i>International Dimensions</i>	741
	<i>Why Computer Criminals Are Hard to Catch</i>	742
	<i>What Computer Crime Does Not Address</i>	743
	<i>Summary of Legal Issues in Computer Security</i>	743
11.6	Ethical Issues in Computer Security	744
	<i>Differences Between the Law and Ethics</i>	744
	<i>Studying Ethics</i>	746
	<i>Ethical Reasoning</i>	747
11.7	Incident Analysis with Ethics	750
	<i>Situation I: Use of Computer Services</i>	750
	<i>Situation II: Privacy Rights</i>	752
	<i>Situation III: Denial of Service</i>	753
	<i>Situation IV: Ownership of Programs</i>	754
	<i>Situation V: Proprietary Resources</i>	756
	<i>Situation VI: Fraud</i>	757
	<i>Situation VII: Accuracy of Information</i>	758
	<i>Situation VIII: Ethics of Hacking or Cracking</i>	759
	<i>Situation IX: True Representation</i>	762
	<i>Conclusion of Computer Ethics</i>	764
	Conclusion	765
	Exercises	765
<b>Chapter 12</b>	<b>Details of Cryptography</b>	<b>768</b>
12.1	Cryptology	769
	<i>Cryptanalysis</i>	769
	<i>Cryptographic Primitives</i>	773

	<i>One-Time Pads</i>	775
	<i>Statistical Analysis</i>	776
	<i>What Makes a “Secure” Encryption Algorithm?</i>	777
12.2	Symmetric Encryption Algorithms	779
	<i>DES</i>	779
	<i>AES</i>	789
	<i>RC2, RC4, RC5, and RC6</i>	792
12.3	Asymmetric Encryption with RSA	795
	<i>The RSA Algorithm</i>	795
	<i>Strength of the RSA Algorithm</i>	797
12.4	Message Digests	799
	<i>Hash Functions</i>	799
	<i>One-Way Hash Functions</i>	799
	<i>Message Digests</i>	800
12.5	Digital Signatures	802
	<i>Elliptic Curve Cryptosystems</i>	802
	<i>El Gamal and Digital Signature Algorithms</i>	803
	<i>The NSA–Cryptography Controversy of 2012</i>	804
12.6	Quantum Cryptography	807
	<i>Quantum Physics</i>	807
	<i>Photon Reception</i>	808
	<i>Cryptography with Photons</i>	808
	<i>Implementation</i>	811
12.7	Conclusion	811

## Chapter 13 Emerging Topics 813

13.1	The Internet of Things	814
	<i>Medical Devices</i>	815
	<i>Mobile Phones</i>	818
	<i>Security in the Internet of Things</i>	820
13.2	Economics	821
	<i>Making a Business Case</i>	821
	<i>Quantifying Security</i>	825
	<i>Current Research and Future Directions</i>	832
13.3	Electronic Voting	834
	<i>What Is Electronic Voting?</i>	835
	<i>What Is a Fair Election?</i>	836
	<i>What Are the Critical Issues?</i>	837

13.4	Cyber Warfare	841
	<i>What Is Cyber Warfare?</i>	842
	<i>Possible Examples of Cyber Warfare</i>	843
	<i>Critical Issues</i>	846
13.5	Conclusion	850
	<b>Bibliography</b>	<b>851</b>
	<b>Index</b>	<b>877</b>

# Foreword

*From the authors:* Willis Ware kindly wrote the foreword that we published in both the third and fourth editions of *Security in Computing*. In his foreword he covers some of the early days of computer security, describing concerns that are as valid today as they were in those earlier days.

Willis chose to sublimate his name and efforts to the greater good of the projects he worked on. In fact, his thoughtful analysis and persuasive leadership contributed much to the final outcome of these activities. Few people recognize Willis's name today; more people are familiar with the European Union Data Protection Directive that is a direct descendant of the report [WAR73a] from his committee for the U.S. Department of Human Services. Willis would have wanted it that way: the emphasis on the ideas and not on his name.

Unfortunately, Willis died in November 2013 at age 93. We think the lessons he wrote about in his Foreword are still important to our readers. Thus, with both respect and gratitude, we republish his words here.

In the 1950s and 1960s, the prominent conference gathering places for practitioners and users of computer technology were the twice yearly Joint Computer Conferences (JCCs)—initially called the Eastern and Western JCCs, but later renamed the Spring and Fall JCCs and even later, the annual National (AFIPS) Computer Conference. From this milieu, the topic of computer security—later to be called information system security and currently also referred to as “protection of the national information infrastructure”—moved from the world of classified defense interests into public view.

A few people—Robert L. Patrick, John P. Haverty, and myself among others—all then at The RAND Corporation (as its name was then known) had been talking about the growing dependence of the country and its institutions on computer technology. It concerned us that the installed systems might not be able to protect themselves and their data against intrusive and destructive attacks. We decided that it was time to bring the security aspect of computer systems to the attention of the technology and user communities.

The enabling event was the development within the National Security Agency (NSA) of a remote-access time-sharing system with a full set of security access controls, running on a Univac 494 machine, and serving terminals and users not only within the headquarters building at Fort George G. Meade, Maryland, but also worldwide. Fortunately, I knew details of the system.

Persuading two others from RAND to help—Dr. Harold Peterson and Dr. Rein Turn—plus Bernard Peters of NSA, I organized a group of papers and presented it to the SJCC conference management as a ready-made additional paper session to be chaired by me. [1] The conference accepted the offer, and the session was presented at the Atlantic City (NJ) Convention Hall in 1967.

Soon thereafter and driven by a request from a defense contractor to include both defense classified and business applications concurrently in a single mainframe machine functioning in a remote-access mode, the Department of Defense, acting through the Advanced Research Projects Agency (ARPA) and later the Defense Science Board (DSB), organized a committee, which I chaired, to study the issue of security controls for computer systems. The intent was to produce a document that could be the basis for formulating a DoD policy position on the matter.

The report of the committee was initially published as a classified document and was formally presented to the sponsor (the DSB) in January 1970. It was later declassified and republished (by The RAND Corporation) in October 1979. [2] It was widely circulated and became nicknamed “the Ware report.” The report and a historical introduction are available on the RAND website. [3]

Subsequently, the United States Air Force (USAF) sponsored another committee chaired by James P. Anderson. [4] Its report, published in 1972, recommended a 6-year R&D security program totaling some \$8M. [5] The USAF responded and funded several projects, three of which were to design and implement an operating system with security controls for a specific computer.

Eventually these activities led to the “Criteria and Evaluation” program sponsored by the NSA. It culminated in the “Orange Book” [6] in 1983 and subsequently its supporting array of documents, which were nicknamed “the rainbow series.” [7] Later, in the 1980s and on into the 1990s, the subject became an international one leading to the ISO standard known as the “Common Criteria.” [8]

It is important to understand the context in which system security was studied in the early decades. The defense establishment had a long history of protecting classified information in document form. It had evolved a very elaborate scheme for compartmenting material into groups, sub-groups and super-groups, each requiring a specific personnel clearance and need-to-know as the basis for access. [9] It also had a centuries-long legacy of encryption technology and experience for protecting classified information in transit. Finally, it understood the personnel problem and the need to establish the trustworthiness of its people. And it certainly understood the physical security matter.

Thus, *the* computer security issue, as it was understood in the 1960s and even later, was how to create in a computer system a group of access controls that would implement or emulate the processes of the prior paper world, plus the associated issues of protecting such software against unauthorized change, subversion and illicit use, and of embedding the entire system in a secure physical environment with appropriate

management oversights and operational doctrine and procedures. The poorly understood aspect of security was primarily the software issue with, however, a collateral hardware aspect; namely, the risk that it might malfunction—or be penetrated—and subvert the proper behavior of software. For the related aspects of communications, personnel, and physical security, there was a plethora of rules, regulations, doctrine and experience to cover them. It was largely a matter of merging all of it with the hardware/software aspects to yield an overall secure system and operating environment.

However, the world has now changed and in essential ways. The desk-top computer and workstation have appeared and proliferated widely. The Internet is flourishing and the reality of a World Wide Web is in place. Networking has exploded and communication among computer systems is the rule, not the exception. Many commercial transactions are now web-based; many commercial communities—the financial one in particular—have moved into a web posture. The “user” of any computer system can literally be anyone in the world. Networking among computer systems is ubiquitous; information-system outreach is the goal.

The net effect of all of this has been to expose the computer-based information system—its hardware, its software, its software processes, its databases, its communications—to an environment over which no one—not end-user, not network administrator or system owner, not even government—has control. What must be done is to provide appropriate technical, procedural, operational and environmental safeguards against threats as they might appear or be imagined, embedded in a societally acceptable legal framework.

And appear threats did—from individuals and organizations, national and international. The motivations to penetrate systems for evil purpose or to create malicious software—generally with an offensive or damaging consequence—vary from personal intellectual satisfaction to espionage, to financial reward, to revenge, to civil disobedience, and to other reasons. Information-system security has moved from a largely self-contained bounded environment interacting with a generally known and disciplined user community to one of worldwide scope with a body of users that may not be known and are not necessarily trusted. Importantly, security controls now must deal with circumstances over which there is largely no control or expectation of avoiding their impact. Computer security, as it has evolved, shares a similarity with liability insurance; they each face a threat environment that is known in a very general way and can generate attacks over a broad spectrum of possibilities; but the exact details or even time or certainty of an attack is unknown until an event has occurred.

On the other hand, the modern world thrives on information and its flows; the contemporary world, society and institutions cannot function without their computer-communication-based information systems. Hence, these systems must be protected in all dimensions—technical, procedural, operational, environmental. The system owner and its staff have become responsible for protecting the organization’s information assets.

Progress has been slow, in large part because the threat has not been perceived as real or as damaging enough; but also in part because the perceived cost of comprehensive information system security is seen as too high compared to the risks—especially the financial consequences—of not doing it. Managements, whose support with appropriate funding is essential, have been slow to be convinced.

This book addresses the broad sweep of issues above: the nature of the threat and system vulnerabilities (Chapter 1); cryptography (Chapters 2 and 12); software vulnerabilities (Chapter 3); the Common Criteria (Chapter 5); the World Wide Web and Internet (Chapters 4 and 6); managing risk (Chapter 10); and legal, ethical and privacy issues (Chapter 11). The book also describes security controls that are currently available such as encryption protocols, software development practices, firewalls, and intrusion-detection systems. Overall, this book provides a broad and sound foundation for the information-system specialist who is charged with planning and/or organizing and/or managing and/or implementing a comprehensive information-system security program.

Yet to be solved are many technical aspects of information security—R&D for hardware, software, systems, and architecture; and the corresponding products. Notwithstanding, technology per se is not the long pole in the tent of progress. Organizational and management motivation and commitment to get the security job done is. Today, the collective information infrastructure of the country and of the world is slowly moving up the learning curve; every mischievous or malicious event helps to push it along. The terrorism-based events of recent times are helping to drive it. Is it far enough up the curve to have reached an appropriate balance between system safety and threat? Almost certainly, the answer is “no, not yet; there is a long way to go.” [10]

—Willis H. Ware  
RAND  
Santa Monica, California

## Citations

1. “Security and Privacy in Computer Systems,” Willis H. Ware; RAND, Santa Monica, CA; P-3544, April 1967. Also published in Proceedings of the 1967 Spring Joint Computer Conference (later renamed to AFIPS Conference Proceedings), pp 279 seq, Vol. 30, 1967.  
 “Security Considerations in a Multi-Programmed Computer System,” Bernard Peters; Proceedings of the 1967 Spring Joint Computer Conference (later renamed to AFIPS Conference Proceedings), pp 283 seq, vol 30, 1967.  
 “Practical Solutions to the Privacy Problem,” Willis H. Ware; RAND, Santa Monica, CA; P-3544, April 1967. Also published in Proceedings of the 1967 Spring Joint Computer Conference (later renamed to AFIPS Conference Proceedings), pp 301 seq, Vol. 30, 1967.  
 “System Implications of Information Privacy,” Harold E. Peterson and Rein Turn; RAND, Santa Monica, CA; P-3504, April 1967. Also published in Proceedings of the 1967 Spring Joint Computer Conference (later renamed to AFIPS Conference Proceedings), pp 305 seq, vol. 30, 1967.
2. “Security Controls for Computer Systems,” (Report of the Defense Science Board Task Force on Computer Security), RAND, R-609-1-PR. Initially published in January 1970 as a classified document. Subsequently, declassified and republished October 1979.
3. <http://rand.org/publications/R/R609.1/R609.1.html>, “Security Controls for Computer Systems”; R-609.1, RAND, 1979 <http://rand.org/publications/R/R609.1/intro.html>, Historical setting for R-609.1
4. “Computer Security Technology Planning Study,” James P. Anderson; ESD-TR-73-51, ESD/AFSC, Hanscom AFB, Bedford, MA; October 1972.
5. All of these documents are cited in the bibliography of this book. For images of these historical papers on a CDROM, see the “History of Computer Security Project, Early Papers Part 1,” Professor Matt Bishop; Department of Computer Science, University of California at Davis. <http://seclab.cs.ucdavis.edu/projects/history>
6. “DoD Trusted Computer System Evaluation Criteria,” DoD Computer Security Center, National Security Agency, Ft George G. Meade, Maryland; CSC-STD-001-83; Aug 15, 1983.
7. So named because the cover of each document in the series had a unique and distinctively colored cover page. For example, the “Red Book” is “Trusted Network Interpretation,” National Computer Security Center, National Security Agency, Ft. George G. Meade, Maryland; NCSC-TG-005, July 31, 1987. USGPO Stock number 008-000-00486-2.
8. “A Retrospective on the Criteria Movement,” Willis H. Ware; RAND, Santa Monica, CA; P-7949, 1995. <http://rand.org/pubs/papers/P7949/>
9. This scheme is nowhere, to my knowledge, documented explicitly. However, its complexity can be inferred by a study of Appendices A and B of R-609.1 (item [2] above).
10. “The Cyberposture of the National Information Infrastructure,” Willis H. Ware; RAND, Santa Monica, CA; MR-976-OSTP, 1998. Available online at: <http://www.rand.org/publications/MR/MR976/mr976.html>.



*This page intentionally left blank*

# Preface

Tablets, smartphones, TV set-top boxes, GPS navigation devices, exercise monitors, home security stations, even washers and dryers come with Internet connections by which data from and about you go to places over which you have little visibility or control. At the same time, the list of retailers suffering massive losses of customer data continues to grow: Home Depot, Target, T.J. Maxx, P.F. Chang's, Sally Beauty. On the one hand people want the convenience and benefits that added connectivity brings, while on the other hand, people are worried, and some are seriously harmed by the impact of such incidents. Computer security brings these two threads together as technology races forward with smart products whose designers omit the basic controls that can prevent or limit catastrophes.

To some extent, people sigh and expect security failures in basic products and complex systems. But these failures do not have to be. Every computer professional can learn how such problems occur and how to counter them. Computer security has been around as a field since the 1960s, and it has developed excellent research, leading to a good understanding of the threat and how to manage it.

One factor that turns off many people is the language: Complicated terms such as polymorphic virus, advanced persistent threat, distributed denial-of-service attack, inference and aggregation, multifactor authentication, key exchange protocol, and intrusion detection system do not exactly roll off the tongue. Other terms sound intriguing but opaque, such as worm, botnet, rootkit, man in the browser, honeynet, sandbox, and script kiddie. The language of advanced mathematics or microbiology is no less confounding, and the Latin terminology of medicine and law separates those who know it from those who do not. But the terms and concepts of computer security really have straightforward, easy-to-learn meaning and uses.

The premise of computer security is quite simple: Vulnerabilities are weaknesses in products, systems, protocols, algorithms, programs, interfaces, and designs. A threat is

---

**Vulnerability: weakness**

**Threat: condition that exercises vulnerability**

**Incident: vulnerability + threat**

**Control: reduction of threat or vulnerability**

---

a condition that could exercise a vulnerability. An incident occurs when a threat does exploit a vulnerability, causing harm. Finally, people add controls or countermeasures to prevent, deflect, diminish, detect, diagnose, and respond to threats. All of computer security is built from that simple framework. This book is about bad things that can happen with computers and ways to protect our computing.

## WHY READ THIS BOOK?

Admit it. You know computing entails serious risks to the privacy of your personal data, the integrity of your data, or the operation of your computer. Risk is a fact of life: Crossing the street is risky, perhaps more so in some places than others, but you still cross the street. As a child you learned to stop and look both ways before crossing. As you became older you learned to gauge the speed of oncoming traffic and determine whether you had the time to cross. At some point you developed a sense of whether an oncoming car would slow down or yield. We hope you never had to practice this, but sometimes you have to decide whether darting into the street without looking is the best means of escaping danger. The point is all these matters depend on knowledge and experience. We want to help you develop comparable knowledge and experience with respect to the risks of secure computing.

The same thing can be said about computer security in everything from personal devices to complex commercial systems: You start with a few basic terms, principles, and concepts. Then you learn the discipline by seeing those basics reappear in numerous situations, including programs, operating systems, networks, and cloud computing. You pick up a few fundamental tools, such as authentication, access control, and encryption, and you understand how they apply in defense strategies. You start to think like an attacker, predicting the weaknesses that could be exploited, and then you shift to selecting defenses to counter those attacks. This last stage of playing both offense and defense makes computer security a creative and challenging activity.

## USES FOR AND USERS OF THIS BOOK

This book is intended for people who want to learn about computer security; if you have read this far you may well be such a person. This book is intended for three groups of people: college and university students, computing professionals and managers, and users of all kinds of computer-based systems. All want to know the same thing: how to control the risk of computer security. But you may differ in how much information you need about particular topics: Some readers want a broad survey, while others want to focus on particular topics, such as networks or program development.

This book should provide the breadth and depth that most readers want. The book is organized by general area of computing, so that readers with particular interests can find information easily.

## ORGANIZATION OF THIS BOOK

The chapters of this book progress in an orderly manner, from general security concerns to the particular needs of specialized applications, and then to overarching management and legal issues. Thus, this book progresses through six key areas of interest:

1. Introduction: threats, vulnerabilities, and controls
2. The security practitioner's "toolbox": identification and authentication, access control, and encryption
3. Application areas of computer security practice: programs, user–Internet interaction, operating systems, networks, data and databases, and cloud computing
4. Cross-cutting disciplines: privacy, management, law and ethics
5. Details of cryptography
6. Emerging application domains

The first chapter begins like many other expositions: by laying groundwork. In Chapter 1 we introduce terms and definitions, and give some examples to justify how these terms are used. In Chapter 2 we begin the real depth of the field by introducing three concepts that form the basis of many defenses in computer security: identification and authentication, access control, and encryption. We describe different ways of implementing each of these, explore strengths and weaknesses, and tell of some recent advances in these technologies.

Then we advance through computing domains, from the individual user outward. In Chapter 3 we begin with individual programs, ones you might write and those you only use. Both kinds are subject to potential attacks, and we examine the nature of some of those attacks and how they could have been prevented. In Chapter 4 we move on to a type of program with which most users today are quite familiar: the browser, as a gateway to the Internet. The majority of attacks today are remote, carried from a distant attacker across a network, usually the Internet. Thus, it makes sense to study Internet-borne malicious code. But this chapter's focus is on the harm launched remotely, not on the network infrastructure by which it travels; we defer the network concepts to Chapter 6. In Chapter 5 we consider operating systems, a strong line of defense between a user and attackers. We also consider ways to undermine the strength of the operating system itself. Chapter 6 returns to networks, but this time we do look at architecture and technology, including denial-of-service attacks that can happen only in a network. Data, their collection and protection, form the topic of Chapter 7, in which we look at database management systems and big data applications. Finally, in Chapter 8 we explore cloud computing, a relatively recent addition to the computing landscape, but one that brings its own vulnerabilities and protections.

In Chapters 9 through 11 we address what we have termed the intersecting disciplines: First, in Chapter 9 we explore privacy, a familiar topic that relates to most of the six domains from programs to clouds. Then Chapter 10 takes us to the management side of computer security: how management plans for and addresses computer security problems. Finally, Chapter 11 explores how laws and ethics help us control computer behavior.

We introduced cryptography in Chapter 2. But the field of cryptography involves entire books, courses, conferences, journals, and postgraduate programs of study. And this book needs to cover many important topics in addition to cryptography. Thus, we made two critical decisions: First, we treat cryptography as a tool, not as a field of study. An automobile mechanic does not study the design of cars, weighing such factors as aerodynamics, fuel consumption, interior appointment, and crash resistance; a mechanic accepts a car as a given and learns how to find and fix faults with the engine and other mechanical parts. Similarly, we want our readers to be able to use cryptography to quickly address security problems; hence we briefly visit popular uses of cryptography in Chapter 2. Our second critical decision was to explore the breadth of cryptography slightly more in a later chapter, Chapter 12. But as we point out, entire books have been written on cryptography, so our later chapter gives an overview of more detailed work that interested readers can find elsewhere.

Our final chapter detours to four areas having significant computer security hazards. These are rapidly advancing topics for which the computer security issues are much in progress right now. The so-called Internet of Things, the concept of connecting many devices to the Internet, raises potential security threats waiting to be explored. Economics govern many security decisions, so security professionals need to understand how economics and security relate. Convenience is raising interest in using computers to implement elections; the easy steps of collecting vote totals have been done by many jurisdictions, but the hard part of organizing fair online registration and ballot-casting have been done in only a small number of demonstration elections. And the use of computers in warfare is a growing threat. Again, a small number of modest-sized attacks on computing devices have shown the feasibility of this type of campaign, but security professionals and ordinary citizens need to understand the potential—both good and bad—of this type of attack.

## HOW TO READ THIS BOOK

What background should you have to appreciate this book? The only assumption is an understanding of programming and computer systems. Someone who is an advanced undergraduate or graduate student in computing certainly has that background, as does a professional designer or developer of computer systems. A user who wants to understand more about how programs work can learn from this book, too; we provide the necessary background on concepts of operating systems or networks, for example, before we address the related security concerns.

This book can be used as a textbook in a one- or two-semester course in computer security. The book functions equally well as a reference for a computer professional or as a supplement to an intensive training course. And the index and extensive bibliography make it useful as a handbook to explain significant topics and point to key articles in the literature. The book has been used in classes throughout the world; instructors often design one-semester courses that focus on topics of particular interest to the students or that relate well to the rest of a curriculum.

## WHAT IS NEW IN THIS BOOK

This is the fifth edition of *Security in Computing*, first published in 1989. Since then, the specific threats, vulnerabilities, and controls have changed, as have many of the underlying technologies to which computer security applies. However, many basic concepts have remained the same.

Most obvious to readers familiar with earlier editions will be some new chapters, specifically, on user–web interaction and cloud computing, as well as the topics we raise in the emerging topics chapter. Furthermore, pulling together the three fundamental controls in Chapter 2 is a new structure. Those are the big changes, but every chapter has had many smaller changes, as we describe new attacks or expand on points that have become more important.

One other feature some may notice is the addition of a third coauthor. Jonathan Margulies joins us as an essential member of the team that produced this revision. He is currently director of the security practice at Qmulos, a newly launched security consulting practice. He brings many years of experience with Sandia National Labs and the National Institute for Standards and Technology. His focus meshes nicely with our existing skills to extend the breadth of this book.

*This page intentionally left blank*

# Acknowledgments

It is increasingly difficult to acknowledge all the people who have influenced this book. Colleagues and friends have contributed their knowledge and insight, often without knowing their impact. By arguing a point or sharing explanations of concepts, our associates have forced us to question or rethink what we know.

We thank our associates in at least two ways. First, we have tried to include references to their written works. References in the text cite specific papers relating to particular thoughts or concepts, but the bibliography also includes broader works that have played a more subtle role in shaping our approach to security. So, to all the cited authors, many of whom are friends and colleagues, we happily acknowledge your positive influence on this book.

Rather than name individuals, we thank the organizations in which we have interacted with creative, stimulating, and challenging people from whom we learned a lot. These places include Trusted Information Systems, the Contel Technology Center, the Centre for Software Reliability of the City University of London, Arca Systems, Exodus Communications, The RAND Corporation, Sandia National Lab, Cable & Wireless, the National Institute of Standards and Technology, the Institute for Information Infrastructure Protection, Qmulos, and the Editorial Board of *IEEE Security & Privacy*. If you worked with us at any of these locations, chances are high that your imprint can be found in this book. And for all the side conversations, debates, arguments, and light moments, we are grateful.



*This page intentionally left blank*

# About the Authors

**Charles P. Pfleeger** is an internationally known expert on computer and communications security. He was originally a professor at the University of Tennessee, leaving there to join computer security research and consulting companies Trusted Information Systems and Arca Systems (later Exodus Communications and Cable and Wireless). With Trusted Information Systems he was Director of European Operations and Senior Consultant. With Cable and Wireless he was Director of Research and a member of the staff of the Chief Security Officer. He was chair of the IEEE Computer Society Technical Committee on Security and Privacy.

**Shari Lawrence Pfleeger** is widely known as a software engineering and computer security researcher, most recently as a Senior Computer Scientist with the Rand Corporation and as Research Director of the Institute for Information Infrastructure Protection. She is currently Editor-in-Chief of *IEEE Security & Privacy* magazine.

**Jonathan Margulies** is the CTO of Qmulos, a cybersecurity consulting firm. After receiving his master's degree in Computer Science from Cornell University, Mr. Margulies spent nine years at Sandia National Labs, researching and developing solutions to protect national security and critical infrastructure systems from advanced persistent threats. He then went on to NIST's National Cybersecurity Center of Excellence, where he worked with a variety of critical infrastructure companies to create industry-standard security architectures. In his free time, Mr. Margulies edits the "Building Security In" section of *IEEE Security & Privacy* magazine.

*This page intentionally left blank*

# 1

## Introduction

### In this chapter:

- Threats, vulnerabilities, and controls
- Confidentiality, integrity, and availability
- Attackers and attack types; method, opportunity, and motive
- Valuing assets

On 11 February 2013, residents of Great Falls, Montana received the following warning on their televisions [INF13]. The transmission displayed a message banner on the bottom of the screen (as depicted in Figure 1-1).



**FIGURE 1-1** Emergency Broadcast Warning

And the following alert was broadcast:

[Beep Beep Beep: *the sound pattern of the U.S. government Emergency Alert System. The following text then scrolled across the screen:*]

Civil authorities in your area have reported that the bodies of the dead are rising from their graves and attacking the living. Follow the messages on screen that will be updated as information becomes available.

Do not attempt to approach or apprehend these bodies as they are considered extremely dangerous. This warning applies to all areas receiving this broadcast.

[Beep Beep Beep]

The warning signal sounded authentic; it had the distinctive tone people recognize for warnings of serious emergencies such as hazardous weather or a natural disaster. And the text was displayed across a live broadcast television program. On the other hand, bodies rising from their graves sounds suspicious.

What would you have done?

Only four people contacted police for assurance that the warning was indeed a hoax. As you can well imagine, however, a different message could have caused thousands of people to jam the highways trying to escape. (On 30 October 1938 Orson Welles performed a radio broadcast of the H. G. Wells play *War of the Worlds* that did cause a minor panic of people believing that Martians had landed and were wreaking havoc in New Jersey.)

The perpetrator of this hoax was never caught, nor has it become clear exactly how it was done. Likely someone was able to access the system that feeds emergency broadcasts to local radio and television stations. In other words, a hacker probably broke into a computer system.

You encounter computers daily in countless situations, often in cases in which you are scarcely aware a computer is involved, like the emergency alert system for broadcast media. These computers move money, control airplanes, monitor health, lock doors, play music, heat buildings, regulate hearts, deploy airbags, tally votes, direct communications, regulate traffic, and do hundreds of other things that affect lives, health, finances, and well-being. Most of the time these computers work just as they should. But occasionally they do something horribly wrong, because of either a benign failure or a malicious attack.

This book is about the security of computers, their data, and the devices and objects to which they relate. In this book you will learn some of the ways computers can fail—or be made to fail—and how to protect against those failures. We begin that study in the way any good report does: by answering the basic questions of what, who, why, and how.

## 1.1 WHAT IS COMPUTER SECURITY?

Computer security is the protection of the items you value, called the **assets** of a computer or computer system. There are many types of assets, involving hardware, software, data, people, processes, or combinations of these. To determine what to protect, we must first identify what has value and to whom.

A computer device (including hardware, added components, and accessories) is certainly an asset. Because most computer hardware is pretty useless without programs, the software is also an asset. Software includes the operating system, utilities and device handlers; applications such as word processing, media players or email handlers; and even programs that you may have written yourself. Much hardware and software is *off-the-shelf*, meaning that it is commercially available (not custom-made for your purpose) and that you can easily get a replacement. The thing that makes your computer unique and important to you is its content: photos, tunes, papers, email messages, projects, calendar information, ebooks (with your annotations), contact information, code you created, and the like. Thus, data items on a computer are assets, too. Unlike most hardware and software, data can be hard—if not impossible—to recreate or replace. These assets are all shown in Figure 1-2.

These three things—hardware, software, and data—contain or express things like the design for your next new product, the photos from your recent vacation, the chapters of your new book, or the genome sequence resulting from your recent research. All of these things represent intellectual endeavor or property, and they have value that differs from one person or organization to another. It is that value that makes them assets worthy of protection, and they are the elements we want to protect. Other assets—such as access to data, quality of service, processes, human users, and network connectivity—deserve protection, too; they are affected or enabled by the hardware, software, and data. So in most cases, protecting hardware, software, and data covers these other assets as well.

In this book, unless we specifically distinguish between hardware, software, and data, we refer to all these assets as the computer system,

---

**Computer systems—hardware, software, and data—have value and deserve security protection.**

---



**Hardware:**

- Computer
- Devices (disk drives, memory, printer)
- Network gear

**Software:**

- Operating system
- Utilities (antivirus)
- Commercial applications (word processing, photo editing)
- Individual applications

**Data:**

- Documents
- Photos
- Music, videos
- Email
- Class projects

**FIGURE 1-2** Computer Objects of Value

or sometimes as the computer. And because processors are embedded in so many devices, we also need to think about such variations as mobile phones, implanted pace-makers, heating controllers, and automobiles. Even if the primary purpose of the device is not computing, the device's embedded computer can be involved in security incidents and represents an asset worthy of protection.

## Values of Assets


After identifying the assets to protect, we next determine their value. We make value-based decisions frequently, even when we are not aware of them. For example, when you go for a swim you can leave a bottle of water and a towel on the beach, but not your wallet or cell phone. The difference relates to the value of the assets.

The value of an asset depends on the asset owner's or user's perspective, and it may be independent of monetary cost, as shown in Figure 1-3. Your photo of your sister, worth only a few cents in terms of paper and ink, may have high value to you and no value to your roommate. Other items' value depends on replacement cost; some computer data are difficult or impossible to replace. For example, that photo of you and your friends at a party may have cost you nothing, but it is invaluable because there is no other copy. On the other hand, the DVD of your favorite film may have cost a significant portion of your take-home pay, but you can buy another one if the DVD is stolen or corrupted. Similarly, timing has bearing on asset

---

**Assets' values are personal, time dependent, and often imprecise.**

---



**FIGURE 1-3** Values of Assets

value. For example, the value of the plans for a company's new product line is very high, especially to competitors. But once the new product is released, the plans' value drops dramatically.

## The Vulnerability–Threat–Control Paradigm

The goal of computer security is protecting valuable assets. To study different ways of protection, we use a framework that describes how assets may be harmed and how to counter or mitigate that harm.

A **vulnerability** is a weakness in the system, for example, in procedures, design, or implementation, that might be exploited to cause loss or harm. For instance, a particular system may be vulnerable to unauthorized data manipulation because the system does not verify a user's identity before allowing data access.

---

**A vulnerability is a weakness that could be exploited to cause harm.**


---

A **threat** to a computing system is a set of circumstances that has the potential to cause loss or harm. To see the difference between a threat and a vulnerability, consider the illustration in Figure 1-4. Here, a wall is holding water back. The water to the left of the wall is a threat to the man on the right of the wall: The water could rise, overflowing onto the man, or it could stay beneath the height of the wall, causing the wall to collapse. So the threat of harm is the potential for the man to get wet, get hurt, or be drowned. For now, the wall is intact, so the threat to the man is unrealized.

---

**A threat is a set of circumstances that could cause harm.**

---



**FIGURE 1-4** Threat and Vulnerability



However, we can see a small crack in the wall—a vulnerability that threatens the man’s security. If the water rises to or beyond the level of the crack, it will exploit the vulnerability and harm the man.

There are many threats to a computer system, including human-initiated and computer-initiated ones. We have all experienced the results of inadvertent human errors, hardware design flaws, and software failures. But natural disasters are threats, too; they can bring a system down when the computer room is flooded or the data center collapses from an earthquake, for example.

A human who exploits a vulnerability perpetrates an **attack** on the system. An attack can also be launched by another system, as when one system sends an overwhelming flood of messages to another, virtually shutting down the second system’s ability to function. Unfortunately, we have seen this type of attack frequently, as denial-of-service attacks deluge servers with more messages than they can handle. (We take a closer look at denial of service in Chapter 6.)

How do we address these problems? We use a **control** or **countermeasure** as protection. That is, a control is an action, device, procedure, or technique that removes or reduces a vulnerability. In Figure 1-4, the man is placing his finger in the hole, controlling the threat of water leaks until he finds a more permanent solution to the problem. In general, we can describe the relationship between threats, controls, and vulnerabilities in this way:

---

**Controls prevent threats from exercising vulnerabilities.**

---

*A threat is blocked by control of a vulnerability.*

Before we can protect assets, we need to know the kinds of harm we have to protect them against, so now we explore threats to valuable assets.

## 1.2 THREATS

We can consider potential harm to assets in two ways: First, we can look at what bad things can happen to assets, and second, we can look at who or what can cause or allow those bad things to happen. These two perspectives enable us to determine how to protect assets.

Think for a moment about what makes your computer valuable to you. First, you use it as a tool for sending and receiving email, searching the web, writing papers, and performing many other tasks, and you expect it to be available for use when you want it. Without your computer these tasks would be harder, if not impossible. Second, you rely heavily on your computer’s integrity. When you write a paper and save it, you trust that the paper will reload exactly as you saved it. Similarly, you expect that the photo a friend passes you on a flash drive will appear the same when you load it into your computer as when you saw it on your friend’s computer. Finally, you expect the “personal” aspect of a personal computer to stay personal, meaning you want it to protect your confidentiality. For example, you want your email messages to be just between you and

your listed recipients; you don't want them broadcast to other people. And when you write an essay, you expect that no one can copy it without your permission.

These three aspects, confidentiality, integrity, and availability, make your computer valuable to you. But viewed from another perspective, they are three possible ways to make it less valuable, that is, to cause you harm. If someone steals your computer, scrambles data on your disk, or looks at your private data files, the value of your computer has been diminished or your computer use has been harmed. These characteristics are both basic security properties and the objects of security threats.

We can define these three properties as follows.

- **availability:** the ability of a system to ensure that an asset can be used by any authorized parties
- **integrity:** the ability of a system to ensure that an asset is modified only by authorized parties
- **confidentiality:** the ability of a system to ensure that an asset is viewed only by authorized parties

These three properties, hallmarks of solid security, appear in the literature as early as James P. Anderson's essay on computer security [AND73] and reappear frequently in more recent computer security papers and discussions. Taken together (and rearranged), the properties are called the **C-I-A triad** or the **security triad**. ISO 7498-2 [ISO89] adds to them two more properties that are desirable, particularly in communication networks:

- **authentication:** the ability of a system to confirm the identity of a sender
- **nonrepudiation or accountability:** the ability of a system to confirm that a sender cannot convincingly deny having sent something


The U.S. Department of Defense [DOD85] adds auditability: the ability of a system to trace all actions related to a given asset. The C-I-A triad forms a foundation for thinking about security. Authenticity and nonrepudiation extend security notions to network communications, and auditability is important in establishing individual accountability for computer activity. In this book we generally use the C-I-A triad as our security taxonomy so that we can frame threats, vulnerabilities, and controls in terms of the C-I-A properties affected. We highlight one of these other properties when it is relevant to a particular threat we are describing. For now, we focus on just the three elements of the triad.

---

**C-I-A triad: confidentiality, integrity, availability**

---

What can happen to harm the confidentiality, integrity, or availability of computer assets? If a thief steals your computer, you no longer have access, so you have lost availability; furthermore, if the thief looks at the pictures or documents you have stored, your confidentiality is compromised. And if the thief changes the content of your music files but then gives them back with your computer, the integrity of your data has been harmed. You can envision many scenarios based around these three properties.



**FIGURE 1-5** Four Acts to Cause Security Harm

The C-I-A triad can be viewed from a different perspective: the nature of the harm caused to assets. Harm can also be characterized by four acts: **interception**, **interruption**, **modification**, and **fabrication**. These four acts are depicted in Figure 1-5. From this point of view, confidentiality can suffer if someone intercepts data, availability is lost if someone or something interrupts a flow of data or access to a computer, and integrity can fail if someone or something modifies data or fabricates false data. Thinking of these four kinds of acts can help you determine what threats might exist against the computers you are trying to protect.

To analyze harm, we next refine the C-I-A triad, looking more closely at each of its elements.

## Confidentiality

Some things obviously need confidentiality protection. For example, students' grades, financial transactions, medical records, and tax returns are sensitive. A proud student may run out of a classroom screaming "I got an A!" but the student should be the one to choose whether to reveal that grade to others. Other things, such as diplomatic and military secrets, companies' marketing and product development plans, and educators' tests, also must be carefully controlled. Sometimes, however, it is not so obvious that something is sensitive. For example, a military food order may seem like innocuous information, but a sudden increase in the order could be a sign of incipient engagement in conflict. Purchases of food, hourly changes in location, and access to books are not

things you would ordinarily consider confidential, but they can reveal something that someone wants to be kept confidential.

The definition of confidentiality is straightforward: Only authorized people or systems can access protected data. However, as we see in later chapters, ensuring confidentiality can be difficult. For example, who determines which people or systems are authorized to access the current system? By “accessing” data, do we mean that an authorized party can access a single bit? the whole collection? pieces of data out of context? Can someone who is authorized disclose data to other parties? Sometimes there is even a question of who owns the data: If you visit a web page, do you own the fact that you clicked on a link, or does the web page owner, the Internet provider, someone else, or all of you?

In spite of these complicating examples, confidentiality is the security property we understand best because its meaning is narrower than that of the other two. We also understand confidentiality well because we can relate computing examples to those of preserving confidentiality in the real world.

Confidentiality relates most obviously to data, although we can think of the confidentiality of a piece of hardware (a novel invention) or a person (the whereabouts of a wanted criminal). Here are some properties that could mean a failure of data confidentiality:

- An unauthorized person accesses a data item.
- An unauthorized process or program accesses a data item.
- A person authorized to access certain data accesses other data not authorized (which is a specialized version of “an unauthorized person accesses a data item”).
- An unauthorized person accesses an approximate data value (for example, not knowing someone’s exact salary but knowing that the salary falls in a particular range or exceeds a particular amount).
- An unauthorized person learns the existence of a piece of data (for example, knowing that a company is developing a certain new product or that talks are underway about the merger of two companies).

Notice the general pattern of these statements: A person, process, or program is (or is not) authorized to access a data item in a particular way. We call the person, process, or program a **subject**, the data item an **object**, the kind of access (such as read, write, or execute) an **access mode**, and the authorization a **policy**, as shown in Figure 1-6. These four terms reappear throughout this book because they are fundamental aspects of computer security.

One word that captures most aspects of confidentiality is *view*, although you should not take that term literally. A failure of confidentiality does not necessarily mean that someone sees an object and, in fact, it is virtually impossible to look at bits in any meaningful way (although you may look at their representation as characters or pictures). The word view does connote another aspect of confidentiality in computer security, through the association with viewing a movie or a painting in a museum: look but do not touch. In computer security, confidentiality usually means obtaining but not modifying. Modification is the subject of integrity, which we consider in the next section.



FIGURE 1-6 Access Control

## Integrity

Examples of integrity failures are easy to find. A number of years ago a malicious macro in a Word document inserted the word “not” after some random instances of the word “is;” you can imagine the havoc that ensued. Because the document was generally syntactically correct, people did not immediately detect the change. In another case, a model of the Pentium computer chip produced an incorrect result in certain circumstances of floating-point arithmetic. Although the circumstances of failure were rare, Intel decided to manufacture and replace the chips. Many of us receive mail that is misaddressed because someone typed something wrong when transcribing from a written list. A worse situation occurs when that inaccuracy is propagated to other mailing lists such that we can never seem to correct the root of the problem. Other times we find that a spreadsheet seems to be wrong, only to find that someone typed “space 123” in a cell, changing it from a numeric value to text, so the spreadsheet program misused that cell in computation. Suppose someone converted numeric data to roman numerals: One could argue that IV is the same as 4, but IV would not be useful in most applications, nor would it be obviously meaningful to someone expecting 4 as an answer. These cases show some of the breadth of examples of integrity failures.

Integrity is harder to pin down than confidentiality. As Stephen Welke and Terry Mayfield [WEL90, MAY91, NCS91a] point out, integrity means different things in different contexts. When we survey the way some people use the term, we find several

different meanings. For example, if we say that we have preserved the integrity of an item, we may mean that the item is

- precise
- accurate
- unmodified
- modified only in acceptable ways
- modified only by authorized people
- modified only by authorized processes
- consistent
- internally consistent
- meaningful and usable

Integrity can also mean two or more of these properties. Welke and Mayfield recognize three particular aspects of integrity—authorized actions, separation and protection of resources, and error detection and correction. Integrity can be enforced in much the same way as can confidentiality: by rigorous control of who or what can access which resources in what ways.

## Availability

A computer user's worst nightmare: You turn on the switch and the computer does nothing. Your data and programs are presumably still there, but you cannot get at them. Fortunately, few of us experience that failure. Many of us do experience overload, however: access gets slower and slower; the computer responds but not in a way we consider normal or acceptable.

Availability applies both to data and to services (that is, to information and to information processing), and it is similarly complex. As with the notion of confidentiality, different people expect availability to mean different things. For example, an object or service is thought to be available if the following are true:

- It is present in a usable form.
- It has enough capacity to meet the service's needs.
- It is making clear progress, and, if in wait mode, it has a bounded waiting time.
- The service is completed in an acceptable period of time.

We can construct an overall description of availability by combining these goals. Following are some criteria to define availability.

- There is a timely response to our request.
- Resources are allocated fairly so that some requesters are not favored over others.
- Concurrency is controlled; that is, simultaneous access, deadlock management, and exclusive access are supported as required.

- The service or system involved follows a philosophy of fault tolerance, whereby hardware or software faults lead to graceful cessation of service or to work-arounds rather than to crashes and abrupt loss of information. (Cessation does mean end; whether it is graceful or not, ultimately the system is unavailable. However, with fair warning of the system's stopping, the user may be able to move to another system and continue work.)
- The service or system can be used easily and in the way it was intended to be used. (This is a characteristic of usability, but an unusable system may also cause an availability failure.)

As you can see, expectations of availability are far-reaching. In Figure 1-7 we depict some of the properties with which availability overlaps. Indeed, the security community is just beginning to understand what availability implies and how to ensure it.


A person or system can do three basic things with a data item: view it, modify it, or use it. Thus, viewing (confidentiality), modifying (integrity), and using (availability) are the basic modes of access that computer security seeks to preserve.

---

**Computer security seeks to prevent unauthorized viewing (confidentiality) or modification (integrity) of data while preserving access (availability).**

---

A paradigm of computer security is **access control**: To implement a policy, computer security controls all accesses by all subjects to all protected objects in all modes of access. A small, centralized control of access is fundamental to preserving confidentiality and integrity, but it is not clear that a single access control point can enforce availability. Indeed, experts on dependability will note that single points of control can become single points of failure, making it easy for an attacker to destroy availability by disabling the single control point. Much of computer security's past success has focused on confidentiality and integrity; there are models of confidentiality and integrity, for



**FIGURE 1-7** Availability and Related Aspects

example, see David Bell and Leonard La Padula [BEL73, BEL76] and Kenneth Biba [BIB77]. Availability is security's next great challenge.

We have just described the C-I-A triad and the three fundamental security properties it represents. Our description of these properties was in the context of things that need protection. To motivate your understanding we gave some examples of harm and threats to cause harm. Our next step is to think about the nature of threats themselves.

## Types of Threats

For some ideas of harm, look at Figure 1-8, taken from Willis Ware's report [WAR70]. Although it was written when computers were so big, so expensive, and so difficult to operate that only large organizations like universities, major corporations, or government departments would have one, Ware's discussion is still instructive today. Ware was concerned primarily with the protection of classified data, that is, preserving confidentiality. In the figure, he depicts humans such as programmers and maintenance staff gaining access to data, as well as radiation by which data can escape as signals. From the figure you can see some of the many kinds of threats to a computer system.

One way to analyze harm is to consider the cause or source. We call a potential cause of harm a **threat**. Harm can be caused by either nonhuman events or humans. Examples of **nonhuman threats** include natural disasters

---

**Threats are caused both by human and other sources.**

---




FIGURE 1-8 Computer [Network] Vulnerabilities (from [WAR70])



like fires or floods; loss of electrical power; failure of a component such as a communications cable, processor chip, or disk drive; or attack by a wild boar.

**Human threats** can be either benign (nonmalicious) or malicious. **Nonmalicious** kinds of harm include someone's accidentally spilling a soft drink on a laptop, unintentionally deleting text, inadvertently sending an email message to the wrong person, and carelessly typing "12" instead of "21" when entering a phone number or clicking "yes" instead of "no" to overwrite a file. These inadvertent, human errors happen to most people; we just hope that the seriousness of harm is not too great, or if it is, that we will not repeat the mistake.

---

**Threats can be malicious or not.**

---

Most computer security activity relates to **malicious, human-caused harm**: A malicious person actually wants to cause harm, and so we often use the term *attack* for a malicious computer security event. Malicious attacks can be random or directed. In a **random attack** the attacker wants to harm any computer or user; such an attack is analogous to accosting the next pedestrian who walks down the street. An example of a random attack is malicious code posted on a website that could be visited by anybody.

In a **directed attack**, the attacker intends harm to specific computers, perhaps at one organization (think of attacks against a political organization) or belonging to a specific individual (think of trying to drain a specific person's bank account, for example, by impersonation). Another class of directed attack is against a particular product, such as any computer running a particular browser. (We do not want to split hairs about whether such an attack is directed—at that one software product—or random, against any user of that product; the point is not semantic perfection but protecting against the attacks.) The range of possible directed attacks is practically unlimited. Different kinds of threats are shown in Figure 1-9.


---

**Threats can be targeted or random.**

---

Although the distinctions shown in Figure 1-9 seem clear-cut, sometimes the nature of an attack is not obvious until the attack is well underway, or perhaps even ended. A normal hardware failure can seem like a directed, malicious attack to deny access, and hackers often try to conceal their activity to look like ordinary, authorized users. As computer security experts we need to anticipate what bad things might happen, instead of waiting for the attack to happen or debating whether the attack is intentional or accidental.

Neither this book nor any checklist or method can show you *all* the kinds of harm that can happen to computer assets. There are too many ways to interfere with your use of these assets. Two retrospective lists of *known* vulnerabilities are of interest, however. The Common Vulnerabilities and Exposures (CVE) list (see <http://cve.mitre.org/>) is a dictionary of publicly known security vulnerabilities and exposures. CVE's common identifiers enable data exchange between security products and provide a baseline index point for evaluating coverage of security tools and services. To measure the extent of harm, the Common Vulnerability Scoring System (CVSS) (see <http://nvd.nist.gov/cvss.cfm>) provides a standard measurement system that allows accurate and consistent scoring of vulnerability impact.



**FIGURE 1-9** Kinds of Threats

### Advanced Persistent Threat

Security experts are becoming increasingly concerned about a type of threat called **advanced persistent threat**. A lone attacker might create a random attack that snares a few, or a few million, individuals, but the resulting impact is limited to what that single attacker can organize and manage. A collection of attackers—think, for example, of the cyber equivalent of a street gang or an organized crime squad—might work together to purloin credit card numbers or similar financial assets to fund other illegal activity. Such attackers tend to be opportunistic, picking unlucky victims’ pockets and moving on to other activities.

Advanced persistent threat attacks come from organized, well financed, patient assailants. Often affiliated with governments or quasi-governmental groups, these attackers engage in long term campaigns. They carefully select their targets, crafting attacks that appeal to specifically those targets; email messages called spear phishing (described in Chapter 4) are intended to seduce their recipients. Typically the attacks are silent, avoiding any obvious impact that would alert a victim, thereby allowing the attacker to exploit the victim’s access rights over a long time.

The motive of such attacks is sometimes unclear. One popular objective is economic espionage. A series of attacks, apparently organized and supported by the Chinese government, was used in 2012 and 2013 to obtain product designs from aerospace companies in the United States. There is evidence the stub of the attack code was loaded into victim machines long in advance of the attack; then, the attackers installed the more complex code and extracted the desired data. In May 2014 the Justice Department indicted five Chinese hackers in absentia for these attacks.

In the summer of 2014 a series of attacks against J.P. Morgan Chase bank and up to a dozen similar financial institutions allowed the assailants access to 76 million names, phone numbers, and email addresses. The attackers—and even their country of origin—remain unknown, as does the motive. Perhaps the attackers wanted more sensitive financial data, such as account numbers or passwords, but were only able to get the less valuable contact information. It is also not known if this attack was related to an attack a year earlier that disrupted service to that bank and several others.

To imagine the full landscape of possible attacks, you may find it useful to consider the kinds of people who attack computer systems. Although potentially anyone is an attacker, certain classes of people stand out because of their backgrounds or objectives. Thus, in the following sections we look at profiles of some classes of attackers.

## Types of Attackers

Who are attackers? As we have seen, their motivations range from chance to a specific target. Putting aside attacks from natural and benign causes, we can explore who the attackers are and what motivates them.

Most studies of attackers actually analyze computer criminals, that is, people who have actually been convicted of a crime, primarily because that group is easy to identify and study. The ones who got away or who carried off an attack without being detected may have characteristics different from those of the criminals who have been caught. Worse, by studying only the criminals we have caught, we may not learn how to catch attackers who know how to abuse the system without being apprehended.


What does a cyber criminal look like? In television and films the villains wore shabby clothes, looked mean and sinister, and lived in gangs somewhere out of town. By contrast, the sheriff dressed well, stood proud and tall, was known and respected by everyone in town, and struck fear in the hearts of most criminals.

To be sure, some computer criminals are mean and sinister types. But many more wear business suits, have university degrees, and appear to be pillars of their communities. Some are high school or university students. Others are middle-aged business executives. Some are mentally deranged, overtly hostile, or extremely committed to a cause, and they attack computers as a symbol. Others are ordinary people tempted by personal profit, revenge, challenge, advancement, or job security—like perpetrators of any crime, using a computer or not. Researchers have tried to find the psychological traits that distinguish attackers, as described in Sidebar 1-1. These studies are far from conclusive, however, and the traits they identify may show correlation but not necessarily causality. To appreciate this point, suppose a study found that a disproportionate number of people convicted of computer crime were left-handed. Does that result imply that all left-handed people are computer criminals or that only left-handed people are? Certainly not. No single profile captures the characteristics of a “typical” computer attacker, and the characteristics of some notorious attackers also match many people who are not attackers. As shown in Figure 1-10, attackers look just like anybody in a crowd.

---

**No one pattern matches all attackers.**

---



**FIGURE 1-10** Attackers

### SIDEBAR 1-1 An Attacker's Psychological Profile?

Temple Grandin, a professor of animal science at Colorado State University and a sufferer from a mental disorder called Asperger syndrome (AS), thinks that Kevin Mitnick and several other widely described hackers show classic symptoms of Asperger syndrome. Although quick to point out that no research has established a link between AS and hacking, Grandin notes similar behavior traits among Mitnick, herself, and other AS sufferers. An article in *USA Today* (29 March 2001) lists the following AS traits:

- poor social skills, often associated with being loners during childhood; the classic “computer nerd”
- fidgeting, restlessness, inability to make eye contact, lack of response to cues in social interaction, such as facial expressions or body language
- exceptional ability to remember long strings of numbers
- ability to focus on a technical problem intensely and for a long time, although easily distracted on other problems and unable to manage several tasks at once
- deep honesty and respect for laws

(continues)

**SIDEBAR 1-1** *Continued*

Donn Parker [PAR98] has studied hacking and computer crime for many years. He states “hackers are characterized by an immature, excessively idealistic attitude . . . They delight in presenting themselves to the media as idealistic do-gooders, champions of the underdog.”

Consider the following excerpt from an interview [SHA00] with “Mixer,” the German programmer who admitted he was the author of a widespread piece of attack software called Tribal Flood Network (TFN) and its sequel TFN2K:

Q: Why did you write the software?

A: I first heard about Trin00 [another piece of attack software] in July '99 and I considered it as interesting from a technical perspective, but also potentially powerful in a negative way. I knew some facts of how Trin00 worked, and since I didn't manage to get Trin00 sources or binaries at that time, I wrote my own server-client network that was capable of performing denial of service.

Q: Were you involved . . . in any of the recent high-profile attacks?

A: No. The fact that I authored these tools does in no way mean that I condone their active use. I must admit I was quite shocked to hear about the latest attacks. It seems that the attackers are pretty clueless people who misuse powerful resources and tools for generally harmful and senseless activities just “because they can.”

Notice that from some information about denial-of-service attacks, he wrote his own server-client network and then a sophisticated attack. But he was “quite shocked” to hear they were used for harm.

More research is needed before we can define the profile of a hacker. And even more work will be needed to extend that profile to the profile of a (malicious) attacker. Not all hackers become attackers; some hackers become extremely dedicated and conscientious system administrators, developers, or security experts. But some psychologists see in AS the rudiments of a hacker's profile.

---

**Individuals**

Originally, computer attackers were individuals, acting with motives of fun, challenge, or revenge. Early attackers acted alone. Two of the most well known among them are Robert Morris Jr., the Cornell University graduate student who brought down the Internet in 1988 [SPA89], and Kevin Mitnick, the man who broke into and stole data from dozens of computers, including the San Diego Supercomputer Center [MAR95].

**Organized, Worldwide Groups**

More recent attacks have involved groups of people. An attack against the government of the country of Estonia (described in more detail in Chapter 13) is believed to have been an uncoordinated outburst from a loose federation of attackers from around the world. Kevin Poulsen [POU05] quotes Tim Rosenberg, a research professor at George

Washington University, warning of “multinational groups of hackers backed by organized crime” and showing the sophistication of prohibition-era mobsters. He also reports that Christopher Painter, deputy director of the U.S. Department of Justice’s computer crime section, argues that cyber criminals and serious fraud artists are increasingly working in concert or are one and the same. According to Painter, loosely connected groups of criminals all over the world work together to break into systems and steal and sell information, such as credit card numbers. For instance, in October 2004, U.S. and Canadian authorities arrested 28 people from 6 countries involved in an international, organized cybercrime ring to buy and sell credit card information and identities.

Whereas early motives for computer attackers such as Morris and Mitnick were personal, such as prestige or accomplishment, recent attacks have been heavily influenced by financial gain. Security firm McAfee reports “Criminals have realized the huge financial gains to be made from the Internet with little risk. They bring the skills, knowledge, and connections needed for large scale, high-value criminal enterprise that, when combined with computer skills, expand the scope and risk of cybercrime.” [MCA05]

### Organized Crime

Attackers’ goals include fraud, extortion, money laundering, and drug trafficking, areas in which organized crime has a well-established presence. Evidence is growing that organized crime groups are engaging in computer crime. In fact, traditional criminals are recruiting hackers to join the lucrative world of cybercrime. For example, Albert Gonzales was sentenced in March 2010 to 20 years in prison for working with a crime ring to steal 40 million credit card numbers from retailer TJMaxx and others, costing over \$200 million (*Reuters*, 26 March 2010).

Organized crime may use computer crime (such as stealing credit card numbers or bank account details) to finance other aspects of crime. Recent attacks suggest that professional criminals have discovered just how lucrative computer crime can be. Mike Danseglio, a security project manager with Microsoft, said, “In 2006, the attackers want to pay the rent. They don’t want to write a worm that destroys your hardware. They want to assimilate your computers and use them to make money.” [NAR06a] Mikko Hyppönen, Chief Research Officer with Finnish security company f-Secure, agrees that today’s attacks often come from Russia, Asia, and Brazil; the motive is now profit, not fame [BRA06]. Ken Dunham, Director of the Rapid Response Team for VeriSign says he is “convinced that groups of well-organized mobsters have taken control of a global billion-dollar crime network powered by skillful hackers.” [NAR06b]

---

**Organized crime groups are discovering that computer crime can be lucrative.**

---

McAfee also describes the case of a hacker-for-hire: a businessman who hired a 16-year-old New Jersey hacker to attack the websites of his competitors. The hacker barraged the site for a five-month period and damaged not only the target companies but also their Internet service providers (ISPs) and other unrelated companies that used the same ISPs. By FBI estimates, the attacks cost all the companies over \$2 million; the FBI arrested both hacker and businessman in March 2005 [MCA05].

Brian Snow [SNO05] observes that hackers want a score or some kind of evidence to give them bragging rights. Organized crime wants a resource; such criminals want to

stay under the radar to be able to extract profit from the system over time. These different objectives lead to different approaches to computer crime: The novice hacker can use a crude attack, whereas the professional attacker wants a neat, robust, and undetectable method that can deliver rewards for a long time.

## Terrorists

The link between computer security and terrorism is quite evident. We see terrorists using computers in four ways:

- *Computer as target of attack:* Denial-of-service attacks and website defacements are popular activities for any political organization because they attract attention to the cause and bring undesired negative attention to the object of the attack. An example is the massive denial-of-service attack launched against the country of Estonia, detailed in Chapter 13.
- *Computer as method of attack:* Launching offensive attacks requires the use of computers. Stuxnet, an example of malicious computer code called a worm, is known to attack automated control systems, specifically a model of control system manufactured by Siemens. Experts say the code is designed to disable machinery used in the control of nuclear reactors in Iran [MAR10]. The persons behind the attack are unknown, but the infection is believed to have spread through USB flash drives brought in by engineers maintaining the computer controllers. (We examine the Stuxnet worm in more detail in Chapters 6 and 13.)
- *Computer as enabler of attack:* Websites, web logs, and email lists are effective, fast, and inexpensive ways to allow many people to coordinate. According to the Council on Foreign Relations, the terrorists responsible for the November 2008 attack that killed over 200 people in Mumbai used GPS systems to guide their boats, Blackberries for their communication, and Google Earth to plot their routes.
- *Computer as enhancer of attack:* The Internet has proved to be an invaluable means for terrorists to spread propaganda and recruit agents. In October 2009 the FBI arrested Colleen LaRose, also known as JihadJane, after she had spent months using email, YouTube, MySpace, and electronic message boards to recruit radicals in Europe and South Asia to “wage violent jihad,” according to a federal indictment.

We cannot accurately measure the degree to which terrorists use computers, because terrorists keep secret the nature of their activities and because our definitions and measurement tools are rather weak. Still, incidents like the one described in Sidebar 1-2 provide evidence that all four of these activities are increasing.

---

### SIDEBAR 1-2 The Terrorists, Inc., IT Department

In 2001, a reporter for the *Wall Street Journal* bought a used computer in Afghanistan. Much to his surprise, he found that the hard drive contained what appeared to be files from a senior al Qaeda operative. The reporter,

Alan Cullison [CUL04], reports that he turned the computer over to the FBI. In his story published in 2004 in *The Atlantic*, he carefully avoids revealing anything he thinks might be sensitive.

The disk contained over 1,000 documents, many of them encrypted with relatively weak encryption. Cullison found draft mission plans and white papers setting forth ideological and philosophical arguments for the attacks of 11 September 2001. Also found were copies of news stories on terrorist activities. Some of the found documents indicated that al Qaeda was not originally interested in chemical, biological, or nuclear weapons, but became interested after reading public news articles accusing al Qaeda of having those capabilities.

Perhaps most unexpected were email messages of the kind one would find in a typical office: recommendations for promotions, justifications for petty cash expenditures, and arguments concerning budgets.

The computer appears to have been used by al Qaeda from 1999 to 2001. Cullison notes that Afghanistan in late 2001 was a scene of chaos, and it is likely the laptop's owner fled quickly, leaving the computer behind, where it fell into the hands of a secondhand goods merchant who did not know its contents.

But this computer's contents illustrate an important aspect of computer security and confidentiality: We can never predict the time at which a security disaster will strike, and thus we must always be prepared to act immediately if it suddenly happens.

---

If someone on television sneezes, you do not worry about the possibility of catching a cold. But if someone standing next to you sneezes, you may become concerned. In the next section we examine the harm that can come from the presence of a computer security threat on your own computer systems.

## 1.3 HARM

The negative consequence of an actualized threat is **harm**; we protect ourselves against threats in order to reduce or eliminate harm. We have already described many examples of computer harm: a stolen computer, modified or lost file, revealed private letter, or denied access to data. These events cause harm that we want to avoid.

In our earlier discussion of assets, we noted that value depends on owner or outsider perception and need. Some aspects of value are immeasurable, such as the value of the paper you need to submit to your professor tomorrow; if you lose the paper (that is, if its availability is lost), no amount of money will compensate you for it. Items on which you place little or no value might be more valuable to someone else; for example, the group photograph taken at last night's party can reveal that your friend was not where he told his wife he would be. Even though it may be difficult to assign a specific number as the value of an asset, you can usually assign a value on a generic scale, such as moderate or minuscule or incredibly high, depending on the degree of harm that loss or damage to the object would cause. Or you can assign a value relative to other assets,



based on comparable loss: This version of the file is more valuable to you than that version.

In their 2010 global Internet threat report, security firm Symantec surveyed the kinds of goods and services offered for sale on underground web pages. The item most frequently offered in both 2009 and 2008 was credit card numbers, at prices ranging from \$0.85 to \$30.00 each. (Compare those prices to an individual's effort to deal with the effect of a stolen credit card or the potential amount lost by the issuing bank.) Second most frequent was bank account credentials, at \$15 to \$850; these were offered for sale at 19% of websites in both years. Email accounts were next at \$1 to \$20, and lists of email addresses went for \$1.70 to \$15.00 per thousand. At position 10 in 2009 were website administration credentials, costing only \$2 to \$30. These black market websites demonstrate that the market price of computer assets can be dramatically different from their value to rightful owners.

The value of many assets can change over time, so the degree of harm (and therefore the severity of a threat) can change, too. With unlimited time, money, and capability, we might try to protect against all kinds of harm. But because our resources are limited, we must prioritize our protection, safeguarding only against serious threats and the ones we can control. Choosing the threats we try to mitigate involves a process called **risk management**, and it includes weighing the seriousness of a threat against our ability to protect.

---

**Risk management involves choosing which threats to control and what resources to devote to protection.**

---

## Risk and Common Sense

The number and kinds of threats are practically unlimited because devising an attack requires an active imagination, determination, persistence, and time (as well as access and resources). The nature and number of threats in the computer world reflect life in general: The causes of harm are limitless and largely unpredictable. Natural disasters like volcanoes and earthquakes happen with little or no warning, as do auto accidents, heart attacks, influenza, and random acts of violence. To protect against accidents or the flu, you might decide to stay indoors, never venturing outside. But by doing so, you trade one set of risks for another; while you are inside, you are vulnerable to building collapse. There are too many possible causes of harm for us to protect ourselves—or our computers—completely against all of them.

In real life we make decisions every day about the best way to provide our security. For example, although we may choose to live in an area that is not prone to earthquakes, we cannot entirely eliminate earthquake risk. Some choices are conscious, such as deciding not to walk down a dark alley in an unsafe neighborhood; other times our subconscious guides us, from experience or expertise, to take some precaution. We evaluate the likelihood and severity of harm, and then consider ways (called countermeasures or controls) to address threats and determine the controls' effectiveness.

Computer security is similar. Because we cannot protect against everything, we prioritize: Only so much time, energy, or money is available for protection, so we address

some risks and let others slide. Or we consider alternative courses of action, such as transferring risk by purchasing insurance or even doing nothing if the side effects of the countermeasure could be worse than the possible harm. The risk that remains uncovered by controls is called **residual risk**.

A basic model of risk management involves a user's calculating the value of all assets, determining the amount of harm from all possible threats, computing the costs of protection, selecting safeguards (that is, controls or countermeasures) based on the degree of risk and on limited resources, and applying the safeguards to optimize harm averted. This approach to risk management is a logical and sensible approach to protection, but it has significant drawbacks. In reality, it is difficult to assess the value of each asset; as we have seen, value can change depending on context, timing, and a host of other characteristics. Even harder is determining the impact of all possible threats. The range of possible threats is effectively limitless, and it is difficult (if not impossible in some situations) to know the short- and long-term impacts of an action. For instance, Sidebar 1-3 describes a study of the impact of security breaches over time on corporate finances, showing that a threat must be evaluated over time, not just at a single instance.

---

### **SIDEBAR 1-3 Short- and Long-term Risks of Security Breaches**

It was long assumed that security breaches would be bad for business: that customers, fearful of losing their data, would veer away from insecure businesses and toward more secure ones. But empirical studies suggest that the picture is more complicated. Early studies of the effects of security breaches, such as that of Campbell [CAM03], examined the effects of breaches on stock price. They found that a breach's impact could depend on the nature of the breach itself; the effects were higher when the breach involved unauthorized access to confidential data. Cavusoglu et al. [CAV04] discovered that a breach affects the value not only of the company experiencing the breach but also of security enterprises: On average, the breached firms lost 2.1 percent of market value within two days of the breach's disclosure, but security developers' *market* value actually *increased* 1.36 percent.

Myung Ko and Carlos Dorantes [KO06] looked at the longer-term financial effects of publicly announced breaches. Based on the Campbell et al. study, they examined data for four quarters following the announcement of unauthorized access to confidential data. Ko and Dorantes note many types of possible breach-related costs:

“Examples of short-term costs include cost of repairs, cost of replacement of the system, lost business due to the disruption of business operations, and lost productivity of employees. These are also considered tangible costs. On the other hand, long-term costs include the loss of existing customers due to loss of trust, failing to attract potential future customers due to negative reputation

(continues)

**SIDEBAR 1-3** *Continued*

from the breach, loss of business partners due to loss of trust, and potential legal liabilities from the breach. Most of these costs are intangible costs that are difficult to calculate but extremely important in assessing the overall security breach costs to the organization."

Ko and Dorantes compared two groups of companies: one set (the treatment group) with data breaches, and the other (the control group) without a breach but matched for size and industry. Their findings were striking. Contrary to what you might suppose, the breached firms had no decrease in performance for the quarters following the breach, but their return on assets decreased in the third quarter. The comparison of treatment with control companies revealed that the control firms generally outperformed the breached firms. However, the breached firms outperformed the control firms in the fourth quarter.

These results are consonant with the results of other researchers who conclude that there is minimal long-term economic impact from a security breach. There are many reasons why this is so. For example, customers may think that all competing firms have the same vulnerabilities and threats, so changing to another vendor does not reduce the risk. Another possible explanation may be a perception that a breached company has better security since the breach forces the company to strengthen controls and thus reduce the likelihood of similar breaches. Yet another explanation may simply be the customers' short attention span; as time passes, customers forget about the breach and return to business as usual.

All these studies have limitations, including small sample sizes and lack of sufficient data. But they clearly demonstrate the difficulties of quantifying and verifying the impacts of security risks, and point out a difference between short- and long-term effects.

---

Although we should not apply protection haphazardly, we will necessarily protect against threats we consider most likely or most damaging. For this reason, it is essential to understand how we perceive threats and evaluate their likely occurrence and impact. Sidebar 1-4 summarizes some of the relevant research in risk perception and decision-making. Such research suggests that, for relatively rare instances such as high-impact security problems, we must take into account the ways in which people focus more on the impact than on the actual likelihood of occurrence.

---

**SIDEBAR 1-4** **Perception of the Risk of Extreme Events**

When a type of adverse event happens frequently, we can calculate its likelihood and impact by examining both frequency and nature of the collective set of events. For instance, we can calculate the likelihood that it will

rain this week and take an educated guess at the number of inches of precipitation we will receive; rain is a fairly frequent occurrence. But security problems are often extreme events: They happen infrequently and under a wide variety of circumstances, so it is difficult to look at them as a group and draw general conclusions.

Paul Slovic's work on risk addresses the particular difficulties with extreme events. He points out that evaluating risk in such cases can be a political endeavor as much as a scientific one. He notes that we tend to let values, process, power, and trust influence our risk analysis [SLO99].

Beginning with Fischhoff et al. [FIS78], researchers characterized extreme risk along two perception-based axes: the dread of the risk and the degree to which the risk is unknown. These feelings about risk, called *affects* by psychologists, enable researchers to discuss relative risks by placing them on a plane defined by the two perceptions as axes. A study by Loewenstein et al. [LOE01] describes how risk perceptions are influenced by association (with events already experienced) and by affect at least as much if not more than by reason. In fact, if the two influences compete, feelings usually trump reason.

This characteristic of risk analysis is reinforced by prospect theory: studies of how people make decisions by using reason and feeling. Kahneman and Tversky [KAH79] showed that people tend to overestimate the likelihood of rare, unexperienced events because their feelings of dread and the unknown usually dominate analytical reasoning about the low likelihood of occurrence. By contrast, if people experience similar outcomes and their likelihood, their feeling of dread diminishes and they can actually underestimate rare events. In other words, if the impact of a rare event is high (high dread), then people focus on the impact, regardless of the likelihood. But if the impact of a rare event is small, then they pay attention to the likelihood.

---

Let us look more carefully at the nature of a security threat. We have seen that one aspect—its potential harm—is the amount of damage it can cause; this aspect is the **impact** component of the risk. We also consider the magnitude of the threat's **likelihood**. A likely threat is not just one that someone might want to pull off but rather one that could actually occur. Some people might daydream about getting rich by robbing a bank; most, however, would reject that idea because of its difficulty (if not its immorality or risk). One aspect of likelihood is feasibility: Is it even possible to accomplish the attack? If the answer is no, then the likelihood is zero, and therefore so is the risk. So a good place to start in assessing risk is to look at whether the proposed action is feasible. Three factors determine feasibility, as we describe next.

---

**Spending for security is based on the impact and likelihood of potential harm—both of which are nearly impossible to measure precisely.**

---

## Method–Opportunity–Motive

A malicious attacker must have three things to ensure success: method, opportunity, and motive, depicted in Figure 1-11. Roughly speaking, method is the how; opportunity, the when; and motive, the why of an attack. Deny the attacker any of those three and the attack will not succeed. Let us examine these properties individually.

### Method

By **method** we mean the skills, knowledge, tools, and other things with which to perpetrate the attack. Think of comic figures that want to do something, for example, to steal valuable jewelry, but the characters are so inept that their every move is doomed to fail. These people lack the capability or method to succeed, in part because there are no classes in jewel theft or books on burglary for dummies.

Anyone can find plenty of courses and books about computing, however. Knowledge of specific models of computer systems is widely available in bookstores and on

Opportunity



FIGURE 1-11 Method–Opportunity–Motive

the Internet. Mass-market systems (such as the Microsoft or Apple or Unix operating systems) are readily available for purchase, as are common software products, such as word processors or database management systems, so potential attackers can even get hardware and software on which to experiment and perfect an attack. Some manufacturers release detailed specifications on how the system was designed or how it operates, as guides for users and integrators who want to implement other complementary products. Various attack tools—scripts, model programs, and tools to test for weaknesses—are available from hackers’ sites on the Internet, to the degree that many attacks require only the attacker’s ability to download and run a program. The term **script kiddie** describes someone who downloads a complete attack code package and needs only to enter a few details to identify the target and let the script perform the attack. Often, only time and inclination limit an attacker.

### Opportunity

**Opportunity** is the time and access to execute an attack. You hear that a fabulous apartment has just become available, so you rush to the rental agent, only to find someone else rented it five minutes earlier. You missed your opportunity.

Many computer systems present ample opportunity for attack. Systems available to the public are, by definition, accessible; often their owners take special care to make them fully available so that if one hardware component fails, the owner has spares instantly ready to be pressed into service. Other people are oblivious to the need to protect their computers, so unattended laptops and unsecured network connections give ample opportunity for attack. Some systems have private or undocumented entry points for administration or maintenance, but attackers can also find and use those entry points to attack the systems.

### Motive

Finally, an attacker must have a **motive** or reason to want to attack. You probably have ample opportunity and ability to throw a rock through your neighbor’s window, but you do not. Why not? Because you have no reason to want to harm your neighbor: You lack motive.

We have already described some of the motives for computer crime: money, fame, self-esteem, politics, terror. It is often difficult to determine motive for an attack. Some places are “attractive targets,” meaning they are very appealing to attackers. Popular targets include law enforcement and defense department computers, perhaps because they are presumed to be well protected against attack (so they present a challenge and a successful attack shows the attacker’s prowess). Other systems are attacked because they are easy to attack. And some systems are attacked at random simply because they are there.

---

**Method, opportunity, and motive are all necessary for an attack to succeed; deny any of these and the attack will fail.**

---

By demonstrating feasibility, the factors of method, opportunity, and motive determine whether an attack can succeed. These factors give the advantage to the attacker because they are qualities or strengths the attacker must possess. Another factor, this time giving an advantage to the defender, determines whether an attack will succeed: The attacker needs a vulnerability, an undefended place to attack. If the defender removes vulnerabilities, the attacker cannot attack.

## 1.4 VULNERABILITIES

As we noted earlier in this chapter, a **vulnerability** is a weakness in the security of the computer system, for example, in procedures, design, or implementation, that might be exploited to cause loss or harm. Think of a bank, with an armed guard at the front door, bulletproof glass protecting the tellers, and a heavy metal vault requiring multiple keys for entry. To rob a bank, you would have to think of how to exploit a weakness not covered by these defenses. For example, you might bribe a teller or pose as a maintenance worker.

Computer systems have vulnerabilities, too. In this book we consider many, such as weak authentication, lack of access control, errors in programs, finite or insufficient resources, and inadequate physical protection. Paired with a credible attack, each of these vulnerabilities can allow harm to confidentiality, integrity, or availability. Each attack vector seeks to exploit a particular vulnerability.

---

**Vulnerabilities are weaknesses that can allow harm to occur.**

---

Security analysts speak of a system's **attack surface**, which is the system's full set of vulnerabilities—actual and potential. Thus, the attack surface includes physical hazards, malicious attacks by outsiders, stealth data theft by insiders, mistakes, and impersonations. Although such attacks range from easy to highly improbable, analysts must consider all possibilities.

Our next step is to find ways to block threats by neutralizing vulnerabilities.

## 1.5 CONTROLS

A **control** or **countermeasure** is a means to counter threats. Harm occurs when a threat is realized against a vulnerability. To protect against harm, then, we can neutralize the threat, close the vulnerability, or both. The possibility for harm to occur is called risk. We can deal with harm in several ways:

- **prevent** it, by blocking the attack or closing the vulnerability
- **deter** it, by making the attack harder but not impossible
- **deflect** it, by making another target more attractive (or this one less so)
- **mitigate** it, by making its impact less severe
- **detect** it, either as it happens or some time after the fact
- **recover** from its effects

Of course, more than one of these controls can be used simultaneously. So, for example, we might try to prevent intrusions—but if we suspect we cannot prevent all of them, we might also install a detection device to warn of an imminent attack. And we should have in place incident-response procedures to help in the recovery in case an intrusion does succeed.

---

**Security professionals balance the cost and effectiveness of controls with the likelihood and severity of harm.**

---

To consider the controls or countermeasures that attempt to prevent exploiting a computing system's vulnerabilities, we begin by thinking about traditional ways to enhance physical security. In the Middle Ages, castles and fortresses were built to protect the people and valuable property inside. The fortress might have had one or more security characteristics, including

- a strong gate or door to repel invaders
- heavy walls to withstand objects thrown or projected against them
- a surrounding moat to control access
- arrow slits to let archers shoot at approaching enemies
- crenellations to allow inhabitants to lean out from the roof and pour hot or vile liquids on attackers
- a drawbridge to limit access to authorized people
- a portcullis to limit access beyond the drawbridge
- gatekeepers to verify that only authorized people and goods could enter

Similarly, today we use a multipronged approach to protect our homes and offices. We may combine strong locks on the doors with a burglar alarm, reinforced windows, and even a nosy neighbor to keep an eye on our valuables. In each case, we select one or more ways to deter an intruder or attacker, and we base our selection not only on the value of what we protect but also on the effort we think an attacker or intruder will expend to get inside.

Computer security has the same characteristics. We have many controls at our disposal. Some are easier than others to use or implement. Some are cheaper than others to use or implement. And some are more difficult than others for intruders to override. Figure 1-12 illustrates how we use a combination of controls to secure our valuable resources. We use one or more controls, according to what we are protecting, how the cost of protection compares with the risk of loss, and how hard we think intruders will work to get what they want.

In this section, we present an overview of the controls available to us. In the rest of this book, we examine how to use controls against specific kinds of threats.

We can group controls into three largely independent classes. The following list shows the classes and several examples of each type of control.

- **Physical controls** stop or block an attack by using something tangible too, such as walls and fences
  - locks






FIGURE 1-12 Effects of Controls

- (human) guards
- sprinklers and other fire extinguishers
- **Procedural or administrative** controls use a command or agreement that
  - requires or advises people how to act; for example,
  - laws, regulations
  - policies, procedures, guidelines
  - copyrights, patents
  - contracts, agreements
- **Technical controls** counter threats with technology (hardware or software), including
  - passwords
  - program or operating system access controls
  - network protocols
  - firewalls, intrusion detection systems
  - encryption
  - network traffic flow regulators

(Note that the term “logical controls” is also used, but some people use it to mean administrative controls, whereas others use it to mean technical controls. To avoid confusion, we do not use that term.)

As shown in Figure 1-13, you can think in terms of the property to be protected and the kind of threat when you are choosing appropriate types of countermeasures. None of these classes is necessarily better than or preferable to the others; they work in different ways with different kinds of results. And it can be effective to use **overlapping controls** or **defense in depth**: more than one control or more than one class of control to achieve protection.




FIGURE 1-13 Types of Countermeasures

## 1.6 CONCLUSION

Computer security attempts to ensure the confidentiality, integrity, and availability of computing systems and their components. Three principal parts of a computing system are subject to attacks: hardware, software, and data. These three, and the communications among them, are susceptible to computer security vulnerabilities. In turn, those people and systems interested in compromising a system can devise attacks that exploit the vulnerabilities.

In this chapter we have explained the following computer security concepts:

- Security situations arise in many everyday activities, although sometimes it can be difficult to distinguish between a security attack and an ordinary human or technological breakdown. Alas, clever attackers realize this confusion, so they may make their attack seem like a simple, random failure.
- A threat is an incident that could cause harm. A vulnerability is a weakness through which harm could occur. These two problems combine: Either without the other causes no harm, but a threat exercising a vulnerability means damage. To control such a situation, we can either block or diminish the threat, or close the vulnerability (or both).
- Seldom can we achieve perfect security: no viable threats and no exercisable vulnerabilities. Sometimes we fail to recognize a threat, or other times we may be unable or unwilling to close a vulnerability. Incomplete security is not a bad situation; rather, it demonstrates a balancing act: Control certain threats and vulnerabilities, apply countermeasures that are reasonable, and accept the risk of harm from uncountered cases.

- An attacker needs three things: method—the skill and knowledge to perform a successful attack; opportunity—time and access by which to attack; and motive—a reason to want to attack. Alas, none of these three is in short supply, which means attacks are inevitable.

In this chapter we have introduced the notions of threats and harm, vulnerabilities, attacks and attackers, and countermeasures. Attackers leverage threats that exploit vulnerabilities against valuable assets to cause harm, and we hope to devise countermeasures to eliminate means, opportunity, and motive. These concepts are the basis we need to study, understand, and master computer security.

Countermeasures and controls can be applied to the data, the programs, the system, the physical devices, the communications links, the environment, and the personnel. Sometimes several controls are needed to cover a single vulnerability, but sometimes one control addresses many problems at once.

## 1.7 WHAT'S NEXT?

The rest of this book is organized around the major aspects or pieces of computer security. As you have certainly seen in almost daily news reports, computer security incidents abound. The nature of news is that failures are often reported, but seldom successes. You almost never read a story about hackers who tried to break into the computing system of a bank but were foiled because the bank had installed strong, layered defenses. In fact, attacks repelled far outnumber those that succeed, but such good situations do not make interesting news items.

Still, we do not want to begin with examples in which security controls failed. Instead, in Chapter 2 we begin by giving you descriptions of three powerful and widely used security protection methods. We call these three our security toolkit, in part because they are effective but also because they are applicable. We refer to these techniques in probably every other chapter of this book, so we want not only to give them a prominent position up front but also to help lodge them in your brain. Our three featured tools are identification and authentication, access control, and encryption.

After presenting these three basic tools we lead into domains in which computer security applies. We begin with the simplest computer situations, individual programs, and explore the problems and protections of computer code in Chapter 3. We also consider malicious code, such as viruses and Trojan horses (defining those terms along with other types of harmful programs). As you will see in other ways, there is no magic that can make bad programs secure or turn programmers into protection gurus. We do, however, point out some vulnerabilities that show up in computer code and describe ways to counter those weaknesses, both during program development and as a program executes.

Modern computing involves networking, especially using the Internet. We focus first on how networked computing affects individuals, primarily through browsers and other basic network interactions such as email. In Chapter 4 we look at how users can be tricked by skillful writers of malicious code. These attacks tend to affect the protection of confidentiality of users' data and integrity of their programs.

Chapter 5 covers operating systems, continuing our path of moving away from things the user can see and affect directly. We see what protections operating systems can provide to users' programs and data, most often against attacks on confidentiality or integrity. We also see how the strength of operating systems can be undermined by attacks, called rootkits, that directly target operating systems and render them unable to protect themselves or their users.

In Chapter 6 we return to networks, this time looking at the whole network and its impact on users' abilities to communicate data securely across the network. We also study a type of attack called denial of service, just what its name implies, that is the first major example of a failure of availability.

We consider data, databases, and data mining in Chapter 7. The interesting cases involve large databases in which confidentiality of individuals' private data is an objective. Integrity of the data in the databases is also a significant concern.

In Chapter 8 we move even further from the individual user and study cloud computing, a technology becoming quite popular. Companies are finding it convenient and cost effective to store data "in the cloud," and individuals are doing the same to have shared access to things such as music and photos. There are security risks involved in this movement, however.

You may have noticed our structure: We organize our presentation from the user outward through programs, browsers, operating systems, networks, and the cloud, a progression from close to distant. In Chapter 9 we return to the user for a different reason: We consider privacy, a property closely related to confidentiality. Our treatment here is independent of where the data are: on an individual computer, a network, or a database. Privacy is a property we as humans deserve, and computer security can help preserve it, as we present in that chapter.

In Chapter 10 we look at several topics of management of computing as related to security. Security incidents occur, and computing installations need to be ready to respond, whether the cause is a hacker attack, software catastrophe, or fire. Managers also have to decide what controls to employ, because countermeasures cost money that must be spent wisely. Computer security protection is hard to evaluate: When it works you do not know it does. Performing risk analysis and building a case for security are important management tasks.

Some security protections are beyond the scope an individual can address. Organized crime from foreign countries is something governments must deal with, through a legal system. In Chapter 11 we consider laws affecting computer security. We also look at ethical standards, what is "right" in computing.

In Chapter 12 we return to cryptography, which we introduced in Chapter 2. Cryptography merits courses and textbooks of its own, and the topic is detailed enough that most of the real work in the field is done at the graduate level and beyond. We use Chapter 2 to introduce the concepts enough to be able to apply them. In Chapter 12 we expand upon that introduction and peek at some of the formal and mathematical underpinnings of cryptography.

Finally, in Chapter 13 we raise four topic areas. These are domains with an important need for computer security, although the areas are evolving so rapidly that computer

security may not be addressed as fully as it should. These areas are the so-called Internet of Things (the interconnection of network-enabled devices from toasters to automobiles and insulin pumps), computer security economics, electronic voting, and computer-assisted terrorism and warfare.

We trust this organization will help you to appreciate the richness of an important field that touches many of the things we depend on.

## 1.8 EXERCISES

1. Distinguish between vulnerability, threat, and control.
2. Theft usually results in some kind of harm. For example, if someone steals your car, you may suffer financial loss, inconvenience (by losing your mode of transportation), and emotional upset (because of invasion of your personal property and space). List three kinds of harm a company might experience from theft of computer equipment.
3. List at least three kinds of harm a company could experience from electronic espionage or unauthorized viewing of confidential company materials.
4. List at least three kinds of damage a company could suffer when the integrity of a program or company data is compromised.
5. List at least three kinds of harm a company could encounter from loss of service, that is, failure of availability. List the product or capability to which access is lost, and explain how this loss hurts the company.
6. Describe a situation in which you have experienced harm as a consequence of a failure of computer security. Was the failure malicious or not? Did the attack target you specifically or was it general and you were the unfortunate victim?
7. Describe two examples of vulnerabilities in automobiles for which auto manufacturers have instituted controls. Tell why you think these controls are effective, somewhat effective, or ineffective.
8. One control against accidental software deletion is to save all old versions of a program. Of course, this control is prohibitively expensive in terms of cost of storage. Suggest a less costly control against accidental software deletion. Is your control effective against all possible causes of software deletion? If not, what threats does it not cover?
9. On your personal computer, who can install programs? Who can change operating system data? Who can replace portions of the operating system? Can any of these actions be performed remotely?
10. Suppose a program to print paychecks secretly leaks a list of names of employees earning more than a certain amount each month. What controls could be instituted to limit the vulnerability of this leakage?
11. Preserving confidentiality, integrity, and availability of data is a restatement of the concern over interruption, interception, modification, and fabrication. How do the first three concepts relate to the last four? That is, is any of the four equivalent to one or more of the three? Is one of the three encompassed by one or more of the four?
12. Do you think attempting to break in to (that is, obtain access to or use of) a computing system without authorization should be illegal? Why or why not?

13. Describe an example (other than the ones mentioned in this chapter) of data whose confidentiality has a short timeliness, say, a day or less. Describe an example of data whose confidentiality has a timeliness of more than a year.
14. Do you currently use any computer security control measures? If so, what? Against what attacks are you trying to protect?
15. Describe an example in which absolute denial of service to a user (that is, the user gets no response from the computer) is a serious problem to that user. Describe another example where 10 percent denial of service to a user (that is, the user's computation progresses, but at a rate 10 percent slower than normal) is a serious problem to that user. Could access by unauthorized people to a computing system result in a 10 percent denial of service to the legitimate users? How?
16. When you say that software is of high quality, what do you mean? How does security fit in your definition of quality? For example, can an application be insecure and still be "good"?
17. Developers often think of software quality in terms of faults and failures. Faults are problems (for example, loops that never terminate or misplaced commas in statements) that developers can see by looking at the code. Failures are problems, such as a system crash or the invocation of the wrong function, that are visible to the user. Thus, faults can exist in programs but never become failures, because the conditions under which a fault becomes a failure are never reached. How do software vulnerabilities fit into this scheme of faults and failures? Is every fault a vulnerability? Is every vulnerability a fault?
18. Consider a program to display on your website your city's current time and temperature. Who might want to attack your program? What types of harm might they want to cause? What kinds of vulnerabilities might they exploit to cause harm?
19. Consider a program that allows consumers to order products from the web. Who might want to attack the program? What types of harm might they want to cause? What kinds of vulnerabilities might they exploit to cause harm?
20. Consider a program to accept and tabulate votes in an election. Who might want to attack the program? What types of harm might they want to cause? What kinds of vulnerabilities might they exploit to cause harm?
21. Consider a program that allows a surgeon in one city to assist in an operation on a patient in another city via an Internet connection. Who might want to attack the program? What types of harm might they want to cause? What kinds of vulnerabilities might they exploit to cause harm?

# Index

- 1×1 GIF, 254, 628
- 802.11 protocols (WiFi), 376
- Abstraction, in operating system, 289
- Acceptance testing, 211
- Access
  - blocked, 399
  - concurrent, 11
  - controlled, 283
  - exclusiveness, 11
  - log, 74
  - mediation, 152, 155
  - mode, 72
  - point, promiscuous, 386
  - point, undocumented, 157
  - point, wireless, 376
  - rights of individuals, 603
  - simultaneous, 11
  - theft of, 750
  - to data, 8
  - to data, as asset, 3
  - tracking, 546
  - unauthorized physical, 689
- Access control, **12**, 72, 76, 78, 815
  - capability, 82
  - directory, 76 82
  - ticket, 82
  - database, 506, **508**, **511**
  - device, 284
  - failure of, 152, 155
  - file, 284
  - general object, 284
  - granularity of, 287, 511
  - list, 80, 292
  - matrix, 78
  - paradigm, 292
  - physical, 690
  - privacy, 594, 608
  - policy, 9
  - privilege list, 82
  - procedure-oriented, 85
  - propagation, 77, 83
  - revocation, 76
  - role-based, 85–86
  - segmentation, **303**
- Access log, 74
- Accountability
  - for private data collection, 597
  - of asset, **7**
  - versus privacy, 641
- Accumulation, of data, 613
- Accuracy, 55, 62, 242, 488, 531
  - authentication, **56**
  - data, 11, 827
  - data collection, 599
  - elections, 840
  - element, database, 513
  - risk analysis, 685
- ACL, *see* Access control list
- Activation, process, 320
- Ad, third-party, 622
- Add subkey, in AES, 790
- Add-in, browser, 232
- Add-on, security as an, 315
- Address
  - hiding, 303
  - resolution, 414
  - space randomization, 210
  - spoofing, 413
  - translation, page, 306
  - translation, segment, 303
- Addressing 418, 434, 446
  - advertising routing, 410
  - failure of, 408
  - network, 351
  - stealth mode, 487

- Adelman, Leonard, 103, 795
- Administration, of access control, 73
- Administrator, database, 502
- Administrator, system, 358
- Advanced Encryption Standard (AES), *see* AES
- Advanced Persistent Threat, **15**
- Advertiser, 626
- Advertising, and privacy, 629
- Advertising, Internet, 622
- Adware, 170, 629
- Aerospace industry, target of attack, 15
- AES (Advanced Encryption Standard), 98, 393, 439, 779, 789, 803
  - cycle in, 99
  - key length in, 109
  - speed of encryption, 103
  - tamper detection, 113
- Agent, software, 474
- Aggregation, 246
  - data, 640
  - database, 526
  - data mining, 537
  - personal data, 623
  - privacy, 618
- AH (Authentication Header), *see* Authentication Header
- Al Qaeda, 20–21
- Alarm, 691
- Alarm, intrusion detection system, 483, 484
- Alph One, *see* Levy, Elias
- Algebraic inference, database, 525
- Algorithm, encryption, 88
- Algorithm weakness attack, against encryption, 770
- Alias, email, 632
- Allocation,
  - device, 281
  - resource, 286
- Alteration, digital signature, 802
- Alureon, 334, 336
- Amazon GovCloud, 556
- Amazon.com, Inc., 631
- Ames, Stan, 312
- Analysis, of problem, 816
- Analysis, risk, *see* Risk analysis
- Analyzer, code, 150
- Anderson, James P., 7, 75, 172, 318, 733
- Android, 818
- Annenberg Public Policy Center, 631
- Anomaly-based intrusion detection system, 476
- Anonymity, 613
  - email, 634
  - Internet, 620
  - network, 355
  - partial, 606
  - privacy, 605
- Anonymization, 613, 615
  - data, 608
  - Hadoop, 545
  - privacy, 597
- Antivirus tool, 191, 329
- AOL, 527
- Apache Hadoop, 542
- API, 211
- App store, 819
- App, 819
  - review of, 819
  - signed, 819
- Appended virus, 181
- Apple Corp., 818
  - iCloud, 559
  - Mac OS operating system, 291, 302
  - SSL bug, 213
- Application Programming Interface (API), 211
- Application proxy firewall 459, 468
- Application whitelisting, 581
- Application-based network attack, 398
- Approximate value, of data, 9
- Architecture
  - network, 470
  - system, 450
  - tagged, 301, 305
- Arithmetic inference, database, 522
- ARPANET, 143, 508
- Asia, 19
- Asperger syndrome, 17
- Aspidistra, 107
- Assembler language, 150
- Assessment, situation, 488
- Asset, 2
  - access as, 3
  - accountability of, 7
  - auditability of, 7
  - authenticity of, **7**
  - critical, 660
  - data as, 3
  - fabrication of, 8
  - decision-making, 826
  - hardware as, 3
  - harm to, 5, 8
  - intellectual property as, 3
  - interception of, 8
  - interruption of, 8
  - modification of, 7, 8
  - nonrepudiation of, 7
  - property as, 3
  - risk analysis of, 671
  - software as, 3
  - timeliness of, 4
  - use of, 7



- value of, **4**, 5, 6, 21
- viewing of, 7
- Association,
  - hijacking, 386
  - preferred, in wireless network, 386
  - WiFi, 380, 383
- Assurance, 76, 820
  - Common Criteria, 327
  - level, 327
  - operating system design, 312
- Asymmetric cryptography, **89**, 93, 795
  - digital signature, 114
  - key exchange using, 105, 107
  - signing, 116
- Attachment, of malicious code, 178
- Attachment, virus, 188
- Attack, 6
  - capability, 26
  - data driven, **148**
  - denial of service, *see* Denial of service
  - directed, 14, 19, 423
  - feasibility of, 27–28
  - foiled, 32
  - malicious code, 166. *See also* Malicious code
  - man-in-the-middle, 106
  - method, 26
  - multistep, 148
  - of honeypot, 295
  - predicting, 826
  - random, 14
  - reason for, 16
  - source of, 828
  - surface, 28
  - targeted, 14, 19, 423
  - toolkit, 166, 424
  - type, classifying, 829
  - web site defacement, 20
  - zero-day, 172
- Attacker, 18
  - characteristics of, 16
  - motivation of, 16
  - profile of, 16, 17
  - psychology of, 17
- Attractive target, 27
- Attribute
  - database, 504
  - database, hidden, 528
  - personal, for authentication, 611
- Attribution, of attack source, 843, 844
- Audit
  - Asset auditability, 7
  - balloting, 840
  - big data, 546
  - database, 507, **510**
  - log, 74, 292
  - privacy, 608
- Australia, 848
- Authentication, **38**, 108, 240, 569, 610, 816
  - attribute, 611
  - biometrics, **53**
  - challenge–response, 461
  - computer, 241
  - continuous, 245, 817
  - cookie, as basis for, 65
  - database, 507, 512
  - distributed, 357
  - DNA for, 61
  - Extensible Authentication Protocol, 393
  - forgery in, 58–59
  - Header, in IPsec, 445
  - human, 240
  - incomplete, 394
  - IPsec, 446
  - knowledge, as basis for, 40
  - MAC address, used for, 377
  - multifactor, 70
  - network communication, 445
  - nonexistent, in wireless network, 390
  - one-time password, 244
  - operating system, 283
  - password, 40
  - physical characteristic, as basis for, 40, **53**
  - possession, as basis for, 65
  - privacy aspects of, 610, 612
  - puzzle, as basis for, 52
  - questions, as basis for, 39, 52
  - remote, 66
  - replay of credentials, 364
  - request, wireless network, 383
  - something known, as basis for, 40
  - something possessed, as basis for 40
  - strength of, 612, 817, 820
  - success of, 56
  - token, as basis for, 65, **66**
  - trusted path for, 323
  - versus identification, 60, 61
  - weak, 820
  - WiFi, 380
  - wireless network, 385
- Authenticity, **92**, 108, 114, 115, 117, 126
  - digital signature, 802
  - asset, **7**
  - email, 635
- Author, rights of, 705
- Authorization, 8, 11, 574
  - big data applications, 548
- Authorship, 246, 705
- autoexec.bat, 181

- Automobile, 4
- Autonomous mobile agent, 430
- Autorun (automatically executing program), 181
- Availability, 6, 7, 8, **11–13**, 75, 398
  - as asset, 671
  - data, 11
  - database, 507, 512
  - service, 11
  - voting, 834
  - wireless network, 382
- Backdoor, 158, 170, 356, 787, 790, 845
- Background task, 358
- Backup, 198, 421, 694
  - cloud, 697
  - complete, 694
  - offsite, 696
  - periodic, 694
  - revolving, 695
  - selective, 696
- Badge, for authentication, 66
- Bagle, 430
- Ballot, privacy of, 641
- Bandwidth, 490
- Bank, attack on, 16
- Barlow, John Perry, 486
- Base register, 298
- Base station, wireless network, 382
- Bastion host, *see* Application proxy firewall
- Battery, 817
- Bauer, Kenneth, 474
- Beacon, WiFi, 380, 383
- Bell, David, 13
- Bell–La Padula model, 13
- Bellovin, Steven, 417
- Bernstein, Mary, 143, 508
- Best evidence rule, 735
- Best practice, 824
- BetCRIS, 425
- Beth-Israel-Deaconess hospital, 401
- Biba, Kenneth, 13
- Big data, 540
  - access control in, 545
  - access tracking in, 546
  - granularity, 545
  - auditing, 546
  - authentication for, 548
  - data sharing, 543
  - data source provenance, 547
  - data validation for, 547
  - encryption for, 548
  - filtering for, 547
  - integrity of, 547
  - joining fields, 547
  - keys for, 547
  - personal data, 545
  - prediction using, 541
  - privacy, 544
  - proprietary data, 545
  - secure data storage, 546
  - security addition for, 548
  - security monitoring, 546
- Biham, Eli, 788
- BiiN computer, 290, 302
- BIND (Berkeley Internet Name Domain), 414
- Biometrics, **53**
  - disadvantages of, 55
  - speed of, 59, 60
  - template for, 59
- BIOS (Basic I/O System), 292
- Birthday, 615
- Bitcoin, 621
- Black box, airline, 640
- Black hat hacking, 759
- Black-box testing, 214
- Blacklisting, 431, **490**
- Block cipher, *see* Block encryption
- Block encryption, **93**, 96, 792, 795
- Blocked access, denial of service, 399
- Blood vessel, for authentication, 54
- Boneh, Dan, 103
- Book cipher, 775
- Boot sector virus, 187
- Boot, operating system, 280
- Bootstrap loader, 291
- Bootstrap process (system initialization), 187
- Bot, 168, 170, 426
- Botmaster, 427, 429
- Botnet, **426**, 429, 430
- Boundary checking, 149
- Bounded disclosure, 520
- Boxcryptor, 564
- Branch instruction, 136
- Brazil, 19, 743, 835
- Breach,
  - data, 609
  - notification, 740
  - survey, 828
- Break-in, system, 668
- Breaking, encryption, 90, 91, 92
- Britain, 89, 107, 318, 771, 835, 846
- Broadcast mode, wireless network, 384
- Browser, 232
  - encryption in, 437
  - hijacker, 170
  - vulnerability in, 233
- Brute force attack, 791
  - on password, 42, **48**

- BSAFE, RSA cryptographic toolkit, 807
- Buckingham, Earl of, 48–49
- Buffer overflow, 134, 139, 140, 145, 149
- Bug, program, 132
- Business case, for security, 821
- Business continuity plan, **659**, 661
- Business failure, 658
- Byte substitution, in AES, 790
- Bytecode verifier, Java, 295
- Byzantine generals problem, 430
  
- C (programming language), 131, 150
- C++ (programming language), 131, 150
- CA (certification authority), 441
- Cable, network, 343
- Cable, optical fiber, interception from, 346
- California Breach Notification Law, 609, 740
- Call, procedure, 136
- CAN SPAM Act, 740
- Canada, 19, 318, 741, 844
- Canary, stack protection, 150
- Capability, access control mechanism, 82
- Capacity
  - availability attribute, 11
  - network, 398
  - planning, 489
- CAPTCHA, 237
- Caputo, Deanna, 276
- CartManager, 600
- CARVER, 675
- Catastrophe, 659
- Center for Democracy and Technology, 628, 629
- Central key distribution, 124
- CERT (Computer Emergency Response Team), U.S., *see* U.S. Computer Emergency Response Team
- CERT, *see* Incident response team
- Certifiability, reference monitor property, 76
- Certificate, public key, 121, 123, 819
- Certification authority, **122**, 124, 441
- Chain of custody, 735
- Chaining, in cryptography, 113, 363, 784, 786
- Challenge, motive for attack, 18
- Charlotte-Mecklenburg, North Carolina, Police Department, 541
- Check digit, 109
- Checking,
  - access authorization, 156
  - data area boundaries, 149
- Checksum, 109, 112, 113, 251, 429
- Cheswick, Bill, 295
- China, 15, 275, 391, 444, 464, 844
- Chosen plaintext attack, 771
- C–I–A triad, **7–13**, 134, 432, 545
- Cipher suite, in SSL, 439
- Cipher, 769
- Ciphertext, **88**, 103
- Circuit-level gateway firewall, 462
- Civil law, 722
- Classical probability, 676
- Clear GIF, 254, 627
- Clear-box testing, 214
- Clickjacking, 256
- Client–server network, 18
- Clipper, 805
- Clock, controlled access to, 283
- Closed mode, wireless network, 384
- Cloud computing
  - backup, 697
  - characteristics, 551–552
  - deployment models, 552
  - identity management, 568
  - migration, 553
  - platform, 579
  - privacy implications, 642
  - processing, 817
  - provider assessment 554
  - risk analysis, 553
  - security controls, 554
  - service models, 552
  - storage, 557, 561, 580
  - threats, 566
  - vulnerabilities 554
- Code
  - analyzer, static, 150
  - breaking, *see* Encryption, breaking
  - development practices, *see* Program development practices
  - error correction, 516
  - error detecting, *see* Error detecting code
  - error detection, 516
  - hiding, 192
  - library, 189
  - modification checker, 482
  - modification of, 148, 819
  - program, 137
  - review, program assurance technique, 221
  - reviewer, 158
  - signed, 251
- Code Red, 172, 175, 179, 182, 209, 731
- Cohesion, of software, 206
- Cold site, disaster recovery, 698
- Cold, effect on semiconductor, 772
- Collision,
  - in error detection codes, **110**, 800
  - stack and heap, 148
- Colorado State University, 17
- Command sequence, 817
- Command-and-control center, botnet, 245, 426 427, 428

- Commerce, Internet, 630
- Commit, two-phase update, 514
- Common Criteria, 327
- Common Rule, 763
- Common Vulnerabilities and Exposures (CVE), 14
- Common Vulnerability Scoring System (CVSS), 14
- Communication, email, 632
- Communication, interprocess, *see* Interprocess communication
- Community clouds, 552, 555
- Compartment, access control, 80
- Competition, employment contract, 728
- Compiler, 201, 209
  - correct code generation by, 140
  - role in program security, 150
- Complete mediation, design principle, 217, 315
- Completeness
  - mediation, 217, 315
  - operating system, 314, 320
  - operating system design, 314
  - security requirements, 653
  - testing, 214
- Complexity,
  - network, 358
  - operating system, 187
  - operating system design, 291
  - program, 149
  - versus security, 208
- Compliance, 824
- Component failure, 420, 421
- Compromise, 74
- Computability, 218, 219
- Computer,
  - medium of crime, 736
  - security, 2
  - source of attack, 20
  - subject of attack, 736
  - system, **3**
  - target of attack, 20
  - time, theft of, 750
  - tool for attack, 736
- Computer crime, 733
  - complexity, 736, 743
  - criminal, 742
  - evidence, 736
  - evolving laws, 736. *See also* Computer crime laws
  - international aspects, 736, 741
  - prosecution, 736
- Computer crime laws
  - CAN SPAM Act, 740
  - Council of Europe Agreement on Cybercrime, 741
  - E.U. Data Protection Act, 742
  - Freedom of Information Act, 738
  - U.S. Computer Fraud and Abuse Act, 738
  - U.S. Economic Espionage Act, 738
  - U.S. Electronic Communications Privacy Act, 739
  - U.S. Health Insurance Portability and Accountability Act (HIPAA), 739
  - U.S. Privacy Act, 738
  - U.S.A. Patriot Act, 740
- Computer emergency response team (CERT), *see* Incident response team, Security Operations Center
- Computer Emergency Response Team, U.S., *see* U.S. Computer Emergency Response Team
- Computer forensics, 567
- Computer Fraud and Abuse Act, U.S., 620
- Computer security incident response team (CSIRT), *see* Incident response team, Security operations center
- Computer security, 2
- Concealment,
  - data, 529–535
  - malicious code, 178, 189
  - password, 46
- Concurrency, 11, 286
  - control of, 282
  - database, 517
  - Hadoop, 543
- Conficker, 174, 175, 179, 182, 428
- Confidence, in trusted system, 317
- Confidentiality, 6, **7**, **8–10**, 109, 126, 844
  - data, 518
  - database, 512, 529
  - database, 529
  - IPsec, 446
  - network, 441, 443
  - voting, 834
  - wireless network, 381
- Configuration management, 509
- Configuration, firewall, 453 466, 472
- Confinement, program development practice, 207
- Confusion, in cryptography, 774, 808
- Connection failure, physical, 420
- Connection, rogue, 382
- Connectivity, network, 371, 847, 849
- Consequence, of attack, 826
- Consistency,
  - data, 11, 506, 827
  - security requirements, 653
- Content, filtering, 464
- Context, of privacy, 601
- Contingency planning, 688, 694
- Contract
  - acceptance, 723
  - employment, 725, 727
  - information, 724
  - law, 723
  - software, 724
  - suit involving, 725

- validity, 723
- voluntary entry, 723
- Control, 6, 22, **28**, 32
  - access, *see* Access control
  - administrative, 30
  - cost of, 29
  - ease of use, 29
  - logical, *see* Control, technical, and Control, administrative
  - loss of, 814
  - overlapping, 30
  - physical, 29
  - procedural, 30
  - program, 149
  - reducing vulnerability, 670
  - risk, 668
  - security, 653
  - selection, 680
  - technical, 30, 75
- Controlled access, for privacy, 608
- Controlled sharing, 287
- Convention 108, of Council of Europe, 603
- Cookie, 625, 627
  - for authentication, 65
  - for wireless network association, 386
  - third-party, 625
- COPPA, *see* U.S. Children's Online Privacy Protection Act
- COPS (password administration tool), 43, 369
- Copying, of copyrighted material, 707
- Copyright, 704
  - backup of work, 706
  - computer software, 709
  - copying, 707
  - device to counter piracy, 709
  - digital object, 709
  - distribution of work, 706
  - employee's work, 727
  - fair use, 706
  - first sale principle, 708
  - independent work, 709
  - infringement, 709
  - originality of work, 706
  - ownership of, 726
  - personal use doctrine, 708
  - piracy, 707
  - public domain, 705
  - registration of, 708
  - requirement to publish, 709
  - web content, 716
  - work for hire, 726
  - works subject to, 705
- Cornell University, 18
- Correction, of error, 11
- Correctness,
  - data mining, 538
  - data, 616
  - operating system design, 314
  - operating system, 317, 320
  - program, 133, 219
  - proof of program, 219
  - RFID sensor, 639
  - security requirements, 653
  - software, 206
- Correlation, 537, 613, 617, 622
- Corruption, data, 361, 432
- Cost,
  - data loss, 695
  - hidden, 679
  - malicious code, 179
  - security, 657, 824
- Cost-benefit analysis, 669, 681
- Council of Europe Agreement on Cybercrime, 741
- Council of Europe, 603
- Counterattack, 485
- Countermeasure, 6, 22, **28**, 32, *see also* Control
- Coupling, of software, 206
- Coverage, testing, 214
- Covert redirect, 577
- Cowan, Crispin, 150
- Crack (password administration tool), 43
- Cracking, 761
- Credit card theft, 19, 22
- Credit card, disposable, 621
- Crime, computer, *see* Computer crime
- Crime, organized, *see* Organized crime
- Criminal law, 722
- Criminal, 16, 19, 742
- Crisis management, *see* Business continuity plan, Incident response
- Crocker, Stephen, 143, 508
- Crossover, network, 363
- Cross-site scripting, 261
- Cryptanalysis, 90, 769
  - brute force, 791
  - chosen plaintext attack, 771
  - freezing attack, 772
  - frequency analysis attack, 769
  - frequency analysis, 793
  - full plaintext, 770
  - implementation attack, 769
  - in AES, 99
  - inferring the algorithm, 774
  - known plaintext, 770
  - pattern analysis attack, 769
  - plaintext and ciphertext, 770
  - plaintext-only, 768
  - probable plaintext attack, 770

- probable plaintext, 793
- RSA, 797
- statistical analysis, 776
- Cryptographic
  - algorithm, 95
  - checksum, 113
  - side-channel attack, 566
- Cryptography, 86, 90, 768
  - asymmetric, 102
  - authentication using, 817
  - book cipher, 775
  - BSAFE toolkit, 807
  - chaining, 784, 786
  - checksum using, 113
  - confusion, 774, 808
  - differential cryptanalysis, 788
  - diffusion, 774
  - Dual-EC-DBRG, 806
  - El Gamal, 803
  - elliptic curve cryptosystem (ECC), 802
  - export control, 792, 793, 794, 805
  - Keccak, 801
  - key escrow, 805
  - Lucifer algorithm, 780
  - mathematical basis, 778
  - MD4, 800
  - MD5, 800
  - network security control, 433
  - one-time pad, 774
  - product cipher, 782
  - public key, 100, 102
  - public scrutiny of algorithm, 779
  - quantum, 807
  - RC2, 792
  - RC4, 792
  - RC5, 794
  - RC6, 795
  - RSA, 795
  - secret key, 96
  - separation using, 296
  - SHA, 800
  - SHA-3, 801
  - strength of, 817
  - substitution, 774
  - Suite B, 803
  - symmetric, 96
  - transposition, 774
  - Vernam cipher, 775
  - weakness in, 789, 792, 794, 806
- Cryptolocker, 565
- Cryptology, 90
  - and NSA, 805. *See also* U.S. National Security Agency
- Cryptosystem, 87
- CSA STAR (Cloud Security Alliance Security, Trust and Assurance Registry), 555
- CSIRT, *see* Incident response team
- Currency, virtual, 621
- CVE, *see* Common Vulnerabilities and Exposures
- CVSS, *see* Common Vulnerability Scoring System
- Cyber warfare, 842
- Cyber weapon, 847
- Cybercrime, 19
  - Council of Europe Agreement on, 741
- Cyberworthiness, 730
- Cycle,
  - in AES, 98
  - in SHA-3, 601
- Cyclic redundancy check, 111, 516
- Daemon, 352
  - name, 414
- Damage control, in software design, 311
- Damage, from malicious code, 179
- Dark Internet, 444
- Darwin (computer game), 172
- Data
  - access to, 8
  - access to, as asset, 3
  - access, rights of individuals, 603
  - accuracy of, 11
  - anonymization, for privacy, 597
  - approximate value of, 9
  - as asset, 3, 671
  - bias, 759
  - breach law, 609
  - consistency of, 11
  - correctness, 616
  - corruption of, 361
  - critical, 281
  - disclosure of, 8
  - driven attack, 148
  - error, and privacy, 608
  - existence of, 9
  - exposure of, 177
  - integrity of, 10–11
  - irreplaceable, 696
  - loss, cost of, 695
  - meaningful, 11
  - misleading, 759
  - modification of, 11, 529, 597
  - modification, for privacy, 597
  - object, 9
  - ownership of, 8, 596, 608
  - perturbation, database, 534
  - precision of, 11
  - privacy, 736

- private, 587
  - protection of, 687
  - protection, and privacy, 597
  - quality, and privacy, 596, 608
  - replacement, 3, 4
  - retention, limited, 597
  - retraction of, 594
  - sensitive, 587
  - separation of, 11
  - shared access, 287
  - storage, 546
  - storage, for privacy, 608
  - subject, 9
  - suppression, database, 529
  - swapping, database, 535
  - transfer, and privacy, 603
  - unchecked, 153
  - use, government, and privacy, 607
  - use, privacy of, 590
  - use, restricted, 608
  - validation, with big data, 547
  - value of, 736
  - versus instruction, 137
- Data collection,
- accuracy, 599
  - consent, 591
  - control of, 599
  - for specific purpose, 603
  - limit on, 596, 603
  - notice of, 591, 599
  - openness of, 597
  - ownership, 592
  - privacy of, 590, 640
  - security of, 599
- Data mining, 246, 527, 536
- aggregation, 537
  - correctness, 537
  - correlation, 537
  - false negative, 540
  - false positive, 540
  - inference, 537
  - interoperability, 540
  - mistakes, 538
  - privacy, 537, 616
  - privacy-preserving, 617
  - sensitivity, 537
- Data Encryption Standard, *see* DES
- Data Loss Prevention (DLP), 473
- Data Protection Act, 742
- Database Management System (DBMS), 502
- Database, 502
- access control, 508
  - administrator, 502
  - aggregation, 526
  - algebraic inference, 525
  - arithmetic inference, 522
  - auditing, 510
  - authentication, 512
  - availability, 512
  - bounded disclosure, 520
  - concurrency, 517
  - confidentiality, 512
  - data concealing, 529–535
  - data disclosure, 529
  - data perturbation, 529, 534
  - data swapping, 535disclosure, 518
  - element 502
  - element accuracy, 513
  - element integrity, 508
  - element integrity, 513
  - exact disclosure, 519
  - existence disclosure, 520
  - field check, 508
  - field, 502
  - granularity, 512
  - hidden data, 527
  - inference, 511, 521–525
  - integrity, 513
  - integrity, two-phase update, 514
  - join query, 505
  - key, 512, 621
  - limited response suppression, 532
  - mean inference, 523
  - median inference, 523
  - negative disclosure, 520
  - operating system protection, 513
  - performance, 511
  - probable value disclosure, 520
  - project operation, 504
  - protecting data in, 721
  - query, 504
  - query analysis, 535
  - query language, 504
  - random sample disclosure, 534
  - range disclosure, 533
  - record, 502
  - recovery, 516
  - relation, 504
  - reliability, 513
  - rounded disclosure, 533
  - schema, 502
  - sensitive data, 518
  - shadow field, 516
  - small sample concealment, 534
  - SQL query language, 504
  - subschema, 502

- table, 502
- tracker inference, 524
- tuple, 504
- user authentication, 512
- Data-driven attack, 189
- Datagram, 407, 415
- DataNode, in Hadoop, 543
- DBMS, *see* Database Management System (DBMS)
- DDoS attack, *see* Distributed Denial of Service attack
- DEA, encryption algorithm, 780
- DEA1, encryption algorithm, 780
- Deadlock, 11, 282
- DEC VAX computer, 290, 314, 326
- Deception, and privacy, 600
- Deception, email, 740
- Deceptive practice, 630
- Decidability, 190, 218, 219
- Decipherment, 87
- Decision-making, 25, 684, 831
- Decoding, 87
- Decryption, 87
- Defacement, web site, *see* Web site defacement
- Defense in depth, 30, 218, 471
- Defense, Department of, *see* U.S. Department of Defense
- Defensive programming, 222
- Defibrillator, 816
- Deflection, attack countermeasure, 28
- Degauss, magnetic media, 693
- Degradation, graceful, *see* Graceful degradation
- Degraded service, network, 849
- Delay, in access checking, 156
- Deletion, data, 134, 692, 772
- Delphi method, 677, 678
- Demand, network, 398
- Demilitarized zone (DMZ), firewall architecture, 470
- Denial of service, 6, 14, 18, 20, 175, 367, **396**, 753
- Denial of service (DoS) attack, 6, 20, 425, 843
  - access, blocked, 399
  - address resolution, 414
  - address spoofing, 413
  - addressing failure, 408
  - distributed, *see* Distributed denial of service attack
  - DNS, 414
  - DNS cache poisoning, 418
  - DNS spoofing, 409
  - echo-chargen, 404
  - flooding, 398, **402**, 407
  - hardware, 845
  - incident, 401
  - insufficient resources, **402**, 407
  - malicious, 403
  - overload, 399
  - ping of death, 404
  - root name server, 414
  - routing, 409, 413
  - scripted, 423
  - session hijack, 415
  - smurf, 404
  - source routing, 413
  - SYN flood, 405
  - teardrop, 407
  - Tribal flood network, 424
  - volumetric, 399, 423
- Denning, Dorothy, 530
- Denning, Peter, 72, 292
- Deontology, 749
- Department of Defense, *see* U.S. Department of Defense
- Department of Justice, *see* U.S. Department of Justice
- Dependability, 12
- DES (Data Encryption Standard), 95, 439, 779
  - computational limitation of, 98
  - cycle in, 99
  - decryption, 784
  - design secrecy, 787
  - differential cryptanalysis on, 788
  - for tamper detection, 113
  - key length in, 96, 98, 109
  - number of cycles, 788
  - reversibility, 784
  - security of, 98, 787
  - speed of encryption, 103
  - strength of, 789, 805
- Design by contract, program design technique, 223
- Design flaw, 6
- Design principles, 216
- Design, cryptographic algorithm, 779
- Design, layered, 309
- Design, RSA, 797
- Design, simplicity of, 309
- Design, TCB, 321
- Detection,
  - attack countermeasure, 28
  - avoidance, by malicious code, 191
  - error, 11
  - malicious code, 189
  - tamper, 151
- Detector, virus (program), *see* Virus detector
- Deterrence, attack countermeasure, 28
- Development
  - practices, *see* Program development practices
  - program, security in, 158
  - quality software, 816
- Device
  - access control, 284
  - allocation, 281



- driver, 288
- loss, 818
- Dialer program, Microsoft, 135
- Dichotomous test, 56
- Dictionary attack, on password, 43
- Differential cryptanalysis, 788
- Diffie, Whitfield, 98, 101, 645, 791
- Diffie–Hellman key exchange, 446, 803
- Diffusion, in cryptography, 774
- Digital Millennium Copyright Act (DMCA), 704, 709
- Digital Signature Algorithm (DSA), 804
- Digital signature, 109, **113–116**, 118, 121, **124**, 251, 419, 428, 721, 802, 803, 819
- Diplomacy, 848
- Direct inference, database, 521
- Directed attack, 14
- Directive 95/46/EC, of European Union, *see* European Privacy Directive
- Directory, access control, 76
- Disappearing email, 635
- Disassembler, 201
- Disaster, natural, *see* Natural disaster
- Disclosure,
  - bounded, 520
  - data, 736
  - database, 518
  - database, 529
  - exact, 519
  - existence, 520
  - negative, 520
  - of data, 8
  - of vulnerability, 833
  - pacemaker data, 816
  - probable value, 520
  - vulnerability, 185
- Disconnection, network 420
- Discrimination, 605
- Discrimination, price, 631
- Distributed denial of service (DDoS) attack, 421, **423**
- Distribution, encryption key, 93
- Diversity, 558
- Diversity, genetic, *see* Genetic diversity
- DLP, *see* Data Loss Prevention
- DMCA, *see* Digital Millennium Copyright Act
- DMZ, *see*, Demilitarized Zone
- DNA, authentication using, 61
- DNS, 414
  - cache poisoning, 418
  - lookup request, 409
  - record, 419
  - spoofing, **409**
- DNSSEC, (DNS Security extension), 419
- Doctrine, of warfare, 850
- Document virus, 180
- DoD, *see* U.S. Department of Defense
- Domain, 82
  - execution, **286**
  - name, 444
  - switching, 320
- DoS (Denial of Service), *see* Denial of service
- Dot-dot-slash attack, 264
- Double DES, **96**
- DoubleClick, 625
- Download substitution attack, 237
- Download, and privacy, 629
- Drive-by-download, 258
- Dropbox, 561, 563
- Dropper, 170
- Drug trafficking, 19
- DSA, *see* Digital Signature Algorithm
- Dual-EC-DBRG cipher suite, 806
- Dual-homed gateway, 450
- E.U. Data Protection Act, 742
- Ease of use, design principle, 217, 317
- Easter egg, **158**
- Eavesdrop, 243, 343, 354, 432, 808
- ECC, *see* Elliptic curve cryptosystem
- Echo–chargin attack, 404, 477
- Economics, of security, 821
- Economy of mechanism, design principle, 217, 315
- Effectiveness, of testing, 215
- Egoism, 748
- e-Government Act, 599
- Egypt, 847, 849
- El Gamal algorithm, 803, 804
- El Gamal, Taher, 803
- Eleanore (attack toolkit), 166
- Election, fair, 836, 837
- Election, margin of victory, 838
- Electrical use, 817
- Electronic commerce, protection of goods in, 721
- Electronic Communications Privacy Act, U.S., 620, 739
- Electronic publishing, compensation for, 721
- Electronic voting, 835
- Element integrity, database, 507, **508**, 513
- Element, database, 502
- Elliptic curve cryptosystem (ECC), 439, 802, 804, 806
- Email 607
  - accuracy of headers, 273
  - address, disposable, 634
  - alias with, 632
  - authentication, 39
  - deceptive, 740
  - disappearing, 635
  - exposed content of, 632

- filtering, 560
- forged, 267
- forwarding of, 632
- header data, 273
- interception of, 633
- monitoring of, 633
- PGP, 276
- phishing, 274
- S/MIME, 277
- security of, 632
- spam, 740
- spear phishing, 274
- Emanation, electromagnetic, 693
- Embedded device, 4
- Emergency alert system, 1–2
- Employee rights, 725
- Employer rights, 725, 754
- Employment contract, 725, 727
  - non-compete clause, 728
- Encapsulated Security Payload, in IPsec, 445
- Encapsulation, 204
  - by layering, 311
  - of software, 206
- Encipherment, 87
- Encoding, 87
- Encrypted password, 46
- Encrypted virus, 194
- Encryption, 86, 87
  - algorithm design, 433
  - asymmetric, **89**, 93, 795
  - block, **93**
  - breaking, 90, 91
  - chaining, 363
  - end-to-end, **435**, 437, 438
  - exhaustive key search, 395
  - for continuous authentication, 245
  - for privacy, 597
  - in network, 360, 363
  - in the cloud, 561
  - in wireless network, 383
  - initialization vector collision, 389
  - key, 88, 126, 562
  - key length, 388
  - key management, 446
  - key, private, 126
  - keyed, 88
  - keyless, 89
  - link, **433**, 437
  - non-static key, 392
  - protection using, 433
  - speed of, 126
  - static key, 388
  - stream, **93**
  - symmetric, **88**, 92, 779, 786
  - TKIP, 393
  - weak, 388
  - See also* AES, DES, RC2, RC4, RC5, RSA
- End-to-end encryption, **435**, 437, 438
- Enforcement, of integrity, 11
- Engineering, social, *see* Social engineering
- Enigma machine, 771, 774
- Entry point, secret, 27, 158. *See also* Backdoor
- Equipment failure, 420
- Equivalence, of programs, 189, 219
- Erasing, sensitive data, 692
- Error
  - correction, 11
  - detection, 11
  - in data, 608, 617
  - in encryption, 778
  - inadvertent, 14
  - nonmalicious, 133
  - off-by-one, 159
  - program, 132
  - unintentional, 6
- Error correction code, 516. *See also* Error detection code
- Error detection code, **109**, 111, 251, 516
- Escrow, encryption key, 805
- ESP (Encapsulated Security Payload), *see* Encapsulated Security Payload
- Espionage, 171, 668, 738
- Estimation technique, 676
- Estimation, Delphi method, 678
- Estonia, 18, 2, 391, 396, 641, 838, 842, 843, 846
- Ethical hacking, *see* Penetration testing
- Ethical system, 745
- Ethics, 744
  - analysis, 746
  - and religion, 746
  - consequence-based, 748
  - consequence-based, 749
  - context of action, 753
  - deontology, 749
  - egoism, 748
  - fair sharing, 753
  - intrinsic goodness, 749
  - of privacy, 752
  - overriding principles, 748
  - pluralism, 746
  - privacy and, 752
  - religion and, 746
  - rule-deontology, 749
  - teleology, 748
  - to justify a position, 748
  - to make a reasoned choice, 748
  - utilitarianism, 749
  - variability, 746
  - versus law, 744

- Euler totient function, 797
- Europe, Council of, 603
- European Privacy Directive, **603–604**, 605, 849
- European Union, 596, 603
  - data breach laws, 609
- Even parity, 111
- Evidence,
  - authenticity, 735
  - chain of custody, 735
  - computer output as, 734
  - incident, 664
  - rule of, 734
- Exact disclosure, 519
- Exchange, cryptographic key, 104
- Exclusiveness, of access, 11
- Executable code, hiding, 192
- Executive, operating system, 280, **285**
- Exfiltration, of sensitive data, 474, 845
- Exhaustive attack, on password, 48
- Exhaustive key search, 395
- Existence,
  - disclosure, 520
  - of data, 9
- Expected loss, 678
- Experimentation, informed consent, 763
- Exploitation, vulnerability, 419
- Export control, of cryptography, 562, 792, 793, 794, 805
- Exposure, risk, *see* Risk exposure
- Extensible Authentication Protocol (EAP), 393
- Externality, 834
  
- Fabrication, 87, 107
  - air defense signal, 844
  - asset, 8
  - encrypted data, 785
  - network data, 361
- Facebook, 526, 594, 635, 696, 762
- Facial recognition, for authentication, 55
- Factoring, in encryption, 103, 795, 797
- Failure modes and effects analysis, 673
- Failure reporting, 729
- Failure, 2
  - business, 658
  - component, 420
  - component, in network, 368
  - hardware, 6, 368, 421, 659
  - program, 132
  - software, 6, 728, 816
  - system, 74
  - transmission, 420
- Fair election, 836, 837
- Fair Information Practices, 596
- Fair use, 706
- Fairness, 11, 281
  
- Fake email, 267
- False
  - acceptance, *see* False positive
  - accusation, 608
  - alarm, 824
  - negative, **55**, 56, 62, 64, 488, 540
  - positive, **55**, 56, 62, 64, 488, 540, 824
  - reading, 55
  - reject, *see* False negative
- Farmer, Dan 369
- Fault tolerance, 12
- Fault tree analysis, 673
- Fault, program, **132**, 136
- FBI, *see* U.S. Federal Bureau of Investigation
- Feasibility, of attack, 27–28
- Federal Bureau of Investigation, *see* U.S. Federal Bureau of Investigation
- Federal Information Processing Standard 197 (FIPS 197), 99
- Federal Trade Commission (FTC), 630, 635
- Federated identity management, 68, 569
- FedRAMP (Federal Risk and Automation Management Program), 555
- Fence, 297
- Fence register, 298
- FidM, *see* Federated identity management
- Field check, database, 508
- Field, database, 502
- File, 320
- File access control, 284
- File sharing, peer-to-peer, 629
- File tag, 528
- Filter, packet; *see* Packet filtering gateway
- Filter, polarizing, 808
- Filtering, 486
- Filtering, in big data, 547
- Fingerprint,
  - for authentication 53, 59, 60, 62, 63, 64
  - in error detection codes, 111
  - of malicious code, 192, 198, 200
- Finland, 641
- Fire, 659, 687
- Firesheep, browser extension, 386
- Firewall, 448, **452**, 492
  - application proxy, 459
  - circuit-level gateway, 462
  - demilitarized zone, 470
  - Great Firewall of China, 464
  - guard, 463
  - packet filtering gateway, 456
  - personal, 464
  - stateful inspection, 458
- First sale, principle of, 708
- Fit for use, 730

- Flaw
  - design, 6
  - impact of, 134
  - program, **133**, 184
  - reporting, 731
- Floating-point error, Intel Pentium chip, 10
- Flood, 686
- Flooding attack, 479, 840
  - in denial of service, 399, 479
- FOIA, *see* U.S. Freedom of Information Act
- Forensic analysis, 74, 202, 736
- Forgery,
  - digital signature, 802
  - in authentication, 58–59, 65, 66
  - protection against, 116
- Formal methods, program assurance technique, 220
- Forwarding, email, 632, 634
- Frame,
  - Data-link, 352
  - SSID in, 384
  - WiFi, 379
- Framing, web page, 258
- France, 318, 846
- Fraud, 19, 22, 722, 757
- Free public WiFi, 392
- Frequency
  - analysis, against encryption, 769, 793
  - distribution, in cryptanalysis, 777
  - probability, 676
- Front end (database management system), 502
- Front-end (intrusion detection system), 480
- f-Secure Corp., 19
- Full disclosure, of software flaws, 731, 760
- Full plaintext attack, 700
- Function testing, 211
- Functionality, in Common Criteria, 328
  
- Gasser, Morrie, 314
- Gateway, application proxy, *see* Application proxy firewall
- Geer, Daniel, 209, 210
- Genetic diversity, program environment characteristic, 209
- Geographic diversity, 558
- Geography, and cyber warfare, 850
- Geotag, 528
- Germany, 107, 318, 431, 668, 771
- Get\_root exploit, 291
- Ghostery, 623
- Gong, Li, 295
- Gonzales, Albert, 19, 391
- Good, greatest for greatest number, 762
- Goodness, program characteristic, 218
- Google, 818, 820
  - docs, 697
  - Street View project, 378
- GOTO Fail bug, 213
- Government data use, 607
- Graceful degradation, 12
- Graham, Scott, 72, 292
- Gramm–Leach–Bliley Act, 598, 739
- Grandin, Temple, 17
- Granularity,
  - database, 512
  - in big data, 545
  - of access control, **74**, 75, 287, 297
- Great Falls, Montana, 1
- Great Firewall of China, 464
- Greece, 356
- GrIDSure authentication system, 52
- Group, access control, 80
- Guard firewall, 463
- Guard, human, 680, 690
  
- Hachette, 631
- Hacker, 15, 18, 19, 759. *See also* Malicious code attack
- Hacking, black hat, 759
- Hacking, white hat, 759
- Hadoop, 542
  - anonymization for, 545
  - concurrency, 543
  - DataNode, 543
  - map–reduce, 543
  - NameNode, 543
  - privacy for, 544
  - redundancy, 543
  - secure mode, 548
  - sharing, 543
  - trusted users, 543
- Halme, Larry, 474
- Halting problem, 218, 219
- Hamming code, 799
- Hand geometry, for authentication, 54
- Hard problems, cryptographic, 92
- Hardware,
  - as asset, 3, 671
  - failure, 6, 420, 398, 421, 772
  - interface to, 282
  - loss of, 691
  - malicious, 845
  - modification of, 845
- Harm, 6, 13, 23, 28
  - causes of, 22
  - from buffer overflow, 138
  - from computer attack, **21–25**
  - from malicious code, 176, 179
  - from vulnerability search, 762
  - likelihood of, 22
  - limitation of, 845
  - malicious, 14

- measurement of, 14
  - potential, 764
  - severity of, 22
  - stopping, 845
  - to asset, 5, 8
  - types of, 14
- Hash code, 109, **112**, 116, 125, 428, 799
- Hash function, *see* Hash code
- Hastiness, in faulty error analysis, 816
- Hazard analysis, 672
- Hazard and operability study, 673
- Header, packet, 458
- Healthcare data, 739
- Heap, **147**
- Heap, memory, 136, 139
- Hellman, Martin, 96, 98, 101, 791
- Heuristic intrusion detection system, 476
- Hiding,
  - address, 303
  - malicious code, 192
- Hierarchical design, 311
- Hijack attack, 242
- HIPAA, *see* U.S. Health Insurance Portability and Accountability Act
- Hoare, Anthony (C.A.R.), 149
- Hoax, 2, 176
- Honan, Mat, 559
- Honeypot, **295**, 668
- Hooking, to operating system, **288**, 337, 465
- Hop, 413
- Host scanning, 566
- Host-based firewall, *see* Personal firewall
- Host-based intrusion detection system (HIDS), 476, 480
- Hostile mobile agent, 170
- Hot site, disaster recovery, 698
- Hot spot, wireless, 382
- HTTPS (HTTP Secure) protocol, *see* SSL
- Human error, in encryption, 771
- Human subjects, 762
- Human, threat from, 13–14
- Human–computer interaction (HCI), 654
- Hybrid clouds, 553, 555
- Hypervisor, **292**
- Hyppönen, Mikko, 19
- IaaS (Infrastructure as a Service), 552, 558, 579, 580
- IBM Corp. 95, 97, 290, 779, 788, 789
- ICD, 816, 817
- Iceland, 613
- Identification versus authentication, 60, 61
- Identification, **38**, 243, 610, 617, 815, 816
  - only when necessary, 603
  - unique, 610
  - versus authentication, 38
  - voluntary, 638
  - weak, 820
- Identity, **38**, 122
  - card, for authentication, 66
  - documents, 612
  - group, 611
  - linking, 606
  - management, cloud, 568
  - management, federated, *see* Federated identity management
  - multiple, 606
  - non-unique, 611
  - records confirming, 49
  - theft, 609
  - uniqueness of, 606
- IDS (Intrusion Detection System), *see* Intrusion Detection System
- IEEE (Institute of Electrical and Electronics Engineers), 132
- IETF (Internet Engineering Task Force), 444
- Iframe, web page, 258
- IKE, *see* Internet Security Association Key Management Protocol Key Exchange
- ILoveYou (malicious code), 172, 175, 179
- ImageShield, authentication system, 52
- Immunity, from malicious code infection, 195, 200
- Impact,
  - of attack, 831
  - of computer failure, 660
  - of security incident, 25
  - risk, 668
- Impersonation, 107, 474
- Implantable Cardioverter Defibrillator, *see* ICD
- Implanting, of malicious code, 186
- Implementation weakness, against encryption, 770
- Implementation, TCB, 322
- In-the-clear, message, 434
- Incident cost, 828
- Incident response, 567
  - action, 662
  - coordination, 666
  - declaring an incident, 662
  - national, 666
  - plan, 662
  - post-incident review, 665
  - taking charge, 662
  - team membership, 665
  - team, 397, 665
- Incident survey, 828
- Incident, security, 25
- Incomplete mediation, 152
- Independence, program quality, 204
- Independent testing, 215
- India, 743

- Individual, versus identity, 611, 612
- Inductance, network, 343
- Infection, malicious code, 186, 194, 430
- Infection, spread of (malicious code), 185
- Inference engine, intrusion detection, 476
- Inference, database, 511, 521–525
- Inference
  - in data mining, 537
  - in intrusion detection system, 478
- Information
  - as an object, 717
  - commerce, 720
  - cost of, 718
  - depletion of, 718
  - disclosure of, 739
  - hiding, of software, 204, 206
  - replication of, 718
  - transfer of, 719
  - value of, 719
- Informed consent, 763
- Infowar, 486
- Infrastructure
  - ownership of, 849, 850
  - shared, 566, 580
  - virtual, 581
- Infringement
  - copyright, 709
  - patent, 712–713
- Initialization vector, 786, 793
- Injection attack, 839
- Injection, SQL, attack, 263
- Input validation, 153
- Input, unchecked, 154
- Insecure APIs, 566
- Insertion, in network communication, 364
- Insider, 474
- Insider threat, 357
- Installation
  - malicious code, 186
  - program, 237
  - testing, 211
- Instruction, machine, 136
- Insurance, 23, 669, 688, 695
- Integer overflow, 160
- Integrated vulnerability assessment, 675
- Integration testing, 211
- Integrity, 6, 7, 8, 117, 251, 758
  - big data, 547
  - check, 109, 112
  - code, 151, 482
  - computation, 133
  - contextual, 602
  - data **10–11**, 506
  - database, 507
  - enforcement by operating system, 317
  - enforcement of, 11
  - failure from race condition, 165
  - failure of, 109
  - faulty check in wireless network, 390
  - inaccurate linking, 608
  - incorrect form, 608
  - network communications, 366
  - protecting, 109
  - protection in WPA, 393
  - stack, 151
  - voting, 834
  - wireless network, 381
- Intel, 10
- Intellectual property, 705
  - as asset, 3
- Intent, two-phase update, 514
- Interception, 87, 236, 808, 845
  - air defense signal, 844
  - asset, **8**
  - authentication data, 243
  - cryptographic key, 105, 107
  - encryption, 91
  - Internet, 635
  - lawful, 355
  - network, 354
  - network, 360
  - pacemaker signal, 816
  - personal data, 820
  - signal, 344
  - WiFi communication, 364, 391
  - WiFi, 364
- Interface design, 654
- Interface, usability, 840
- Internal intrusion detection system, 480
- Internet, the
  - governing, 419
  - international nature of, 741
  - payments using, 621
  - privacy and, 619
  - site registration on, 622
  - user ID, 622
- Internet access, free, *see* Public hot spot
- Internet of things, 814
- Internet Security Association Key Management Protocol
  - Key Exchange (IKE), 446, 447
- Internet Service Provider, *see* ISP
- Internet Society, 124
- Internet-enabled product, 814
- Interpreted language, 189
- Interpreter, 189
- Interprocess communication, 281, 320
- Interruption,
  - access, 849

- network communication, 366
- of asset, **8**
- Intrusion Detection System (IDS), 474
  - anomaly-based, 476
  - false alarm, 824
  - front-end, 480
  - heuristic, 476
  - host-based (HIDS), 476, 480
  - inference engine, 476
  - internal, 480
  - model-based, 478
  - network-based (NIDS), 476, 480
  - response, 483
  - signature-based, 476
  - situation assessment, 488
  - state-based, 478
  - stateful protocol analysis, 479
  - stealth mode, 487
- Intrusion Prevention System (IPS), 474, 482
- Intrusion, system, 668
- Invention, patent for, 711
- Inverse,
  - of a function, 112
  - of encryption, 103
- Investigation, security, 426
- iOS (Apple operating system), 818
- IP fragmentation attack, 407
- IPS (Intrusion Prevention System), *see* Intrusion Prevention System
- IPsec (IP security protocol suite), 444
  - authentication header, 444
  - security association in, 444
- IPv4, 444
- IPv6, 444
- Iran, 368, 444, 843, 847
- ISAKMP (Internet Security Association Key Management Protocol), *see* Internet Security Association Key Management Protocol
- ISO 7489-2, 7
- Isolation, 204
  - in operating system design, 311
  - malicious code countermeasure, 195
- of potential malicious code, 197ISP (Internet Service Provider), 19, 425, 633
- Israel, 843, 844, 845
- Iteration, in DES, 96
- J.P. Morgan Chase, 16
- Japan, 741, 772
- Jaschen, Sven, 430
- Java script attack, 262
- Java, sandbox in, 294
- Jet Blue, 601
- JihadJane, 20
- Join query, database, 505
- Join, in big data, 547
- Justice, Department of, *see* U.S. Department of Justice
- Justification, with risk analysis, 684
- Kahn, David, 90, 771, 774
- Kahneman, Daniel, 25
- Karger, Paul, 172, 219, 314
- Kaspersky Labs (security research firm), 169
- Keccak, 801
- Kerberos, in big data application, 548
- Kerckhoffs, Auguste, 227
- Kernel
  - operating system, 284, **312**, 334
  - security, *see* Security kernel
- Kernell, David, 39
- Key
  - asymmetric, 796
  - change, 771
  - cryptographic, 96, 103, 777
  - database, 512, 621
  - deduction, against encryption, 770
  - derivation functions, 562
  - distribution, 93, 124
  - encryption, **88**, 789
  - encryption, sharing, 92
  - escrow, encryption, 805
  - exchange, 104
  - exchange, Diffie–Hellman, 446
  - exchange, with asymmetric cryptography, 105, 107
  - for RC4, 793, 794
  - in big data, 547
  - length, 96, 97, 109, 792, 805
  - length, in AES, 791
  - management, encryption, 93, 433, 446
  - physical, security properties of, 184
  - recovery, 805
  - search, exhaustive, 395
- Keys (cryptographic), proliferation of, 102
- Keystroke logger, 236, 442, 628
- Kill switch, 845, 848
- Known plaintext attack, 770
- Koobface, botnet, 426
- Korea, victim of phishing attack, 275
- Krebs, Brian, 159
- 10pht computer group, 139–140
- La Padula, Leonard, 13
- LAN (Local Area Network), 343
- Landau, Susan, 645
- Language,
  - interpreted, 189
  - programming, 150
  - safe, 149

- Laptop, loss of, 691
- Lastpass 564
- Law,
  - as security protection 426
  - civil, 722
  - conflict between, 604
  - contract, 722
  - court decisions, 723
  - criminal, 722
  - data breach, 609
  - E.U. Data Protection, *see* European Privacy Directive
  - security control, 426
  - tort, 722
  - versus ethics, 744
- Layered protection, 471
- Layering, 310
- Leakage, data, 474, 620
- Least common mechanism, design principle, 217, 317
- Least privilege, 73, 216, 218, 316, 358
- Legal
  - action, 485
  - countermeasure, 426
  - issue, incident, 664
  - protection, 703
- Leverage, risk, 669
- Leveson, Nancy, 815
- Levy, Elias, 145
- License, software, 727
- Likelihood,
  - of event, 668
  - of exploitation, 675
  - of harm, 22
  - of security incident, 25
- Limitation on data collection, 596
- Limitations of testing, 215
- Limited privilege, 317. *See also* Least privilege
- Limited response suppression, 532
- Link encryption, **433**, 437, 447
- Linking, personal data, 627
- Linux operating system, 291
- List, access control, *see* Access control list
- Litchfield, David, 134, 174, 732
- LMS (Learning Management System), 570
- Load balancing, 431, 489, 492
- Local data, 141
- Location-sensing, 820
- Lock, physical, 680, 690
- Log analysis *see* SIEM
- Log data, *see* System log
- Log, access, *see* Access log
- Log, audit, *see* Audit log
- Logarithm, 802
- Logger, keystroke, 236, 628
- Logic bomb, 170
- Logical integrity, database, 507
- Lookup, DNS, 409
- Loss, 5
  - data, 695
  - expected, 678
  - from security incident, 668
  - power, 688
  - service, 366
- Lucifer, encryption algorithm, 780, 788, 789
- Lyon, Barrett, 425
- MAC (Media Access Control), 343, 351, 377
- MAC address, 378, 380
  - changing, 385
  - spoofing, 394
- MAC header, WiFi, 379
- Mach, 302
- Macro, 189
- Macro virus, 10
- Mafia, 769
- Magnetic media, destruction of, 692
- Magnetic remanence, 325
- Maintenance, software, 205
- Malfunction, device, 815
- Malicious code, 166–196, **167**
  - addressing failure, 408
  - adware, 170
  - Alureon, 334, 336
  - antivirus detector (program), 191
  - appended virus, 181
  - attachment of, 178
  - attack toolkit, 419, 424
  - backdoor, 170
  - Bagle, 430
  - boot sector virus, 187
  - bot, 170
  - browser hijacker, 170
  - Code Red, 172, 175, 179, 182, 209, 731
  - concealment of, 178, 189
  - Conficker, 174, 179, 182, 428
  - destructive, 176
  - detection avoidance by, 191
  - detection of, 189
  - disassembly of, 201
  - DNS spoofing, 409
  - dropper, 170
  - echo–chargen, 404
  - encrypting virus, 194
  - encryption of, 194
  - fingerprint of, 192, 198, 200
  - flooding, 403, 407
  - forensic analysis of, 202
  - harm from, 176
  - hijacker, 629



- history of, 172
- hostile mobile agent, 170
- ILoveYou, 172, 175, 179
- immunity from, 195, 200
- implant of, 186, 760
- infection by, 194
- isolation, as countermeasure, 195
- keystroke logger, 236
- logic bomb, 170
- malware detector (program), 191
- man-in-the-browser, 234
- Melissa, 172, 175
- memory-resident virus, 188
- mobile agent, 430
- mobile agent, hostile, 170
- Morris worm, 172, 175, 209
- multipartite virus, 178
- MyDoom, 430
- NIMDA, 172
- pattern matching to detect, 192, 198, 200
- pattern recognition, 192
- ping of death, 404
- polymorphic, 193
- prevention of, 197
- propagation of, 180
- rabbit, 170
- Remote access Trojan horse (RAT), 170
- replacement virus, 182
- rootkit, 170, 329, 334, 336
- Sasser, 431
- scareware, 170, 195
- script kiddie, 196
- separation as countermeasure, 195
- session hijack, 415
- signature, recognition by, 192, 198, 200
- Slammer, 172, 175
- smurf, 404
- SoBig, 172, 175
- source of, 845
- spyware, 170, 628
- stealth, 189, 190
- steganography and, 192
- Stuxnet, 174, 175, 368, 843
- SYN flood, 405
- TDL-3, 334
- teardrop, 407
- TFN, 424
- TFN2K, 424
- time bomb, 170
- tool, 170
- toolkit, 170, 196, 336
- transmission of, 180
- trapdoor, 170
- Tribal flood network, 424
- Trin00, 424
- Trojan horse, 169
- user-in-the-middle, 237
- virus, **167**
- volume of, 196
- Waladec, 429
- worm, 168
- zero-day attack, 172, **419**
- Zeus, 245
- zombie, 170
- Malicious threat, 14
- Malicious web activity,
  - clickjacking, 256
  - cross-site scripting, 261
  - dot-dot-slash, 264
  - drive-by-download, 258
  - server-side include, 265
  - SQL injection attack, 263
  - web site defacement, 246
- Malware, 10, 166–196, **167**.
  - see also* Malicious code
  - Android phone, 819
  - detector (program), 191
  - scanner, 465
  - smartphone, 818
  - toolkit, 196
- Man in the middle, 460
- Management, 75
  - encryption key, 93
  - network, 489
  - risk, *see*, Risk management
  - security, 657
- Manager, 657
- Man-in-the-browser attack, 234, 442
- Man-in-the-middle attack, 106, 409, 394, 840
- Man-in-the-mobile attack, 245
- Many-to-one function, 110
- Map–reduce, in Hadoop, 543
- Mash, in encryption, 792
- Masquerading, 432
- Matrix, access control, *see* Access control matrix
- Mayfield, Terry, 10–11
- McAfee (security firm), 19
- MD4, 428
- MD5, 800
- MD6, 429
- Mean inference, database, 523
- Measurement
  - harm, 14
  - security, 825
- Mechanism,
  - access control, 76
  - security, 75
- Median inference, database, 523

- Mediation, complete, 154
- Mediation, incomplete, 152, 155
- Medical device, 815, 820
- Medical record, 613, 638, 758
- Medium Access Code (MAC), *see* MAC
- Melissa, 172, 175
- Memory allocation, 136
- Memory management,
  - paging, 306
  - segmentation, 303
  - virtual memory, 303
- Memory protection, 284, 297, 320, 321
  - base/bounds, 298
  - fence, 297
  - paging, 306, 307
  - segmentation, 303
  - tagged, 301
  - virtual memory, 303
- Memory, system space, 138
- Memory-resident virus, 188
- Merchants, Internet, 630
- Merkle, Ralph, 96, 121
- Message digest, 109, 112, 125, 799
  - MD4, 428, 800
  - MD5, 800
  - MD6, 429, 800
  - SHA, 800
- Message, protection of, 434
- Metadata, 529
- Method, of attack, 26
- Method–opportunity–motive, **26–28**, 837
- Microkernel, 289
- Microscope and tweezers, 202, 735
- Microsoft, 222, 818
- Microsoft Trustworthy Computing Initiative, 326
- Microwave signal, 346
- Minimality, 212
- Minimization, data, for privacy, 608
- Misidentification, 815
- Missile attack, 844
- Mission creep, 608
- Mistakes, in data mining, 538
- Misuse, system, 74
- Mitigation, attack countermeasure, 28
- Mitnick, Kevin, 17, 18
- Mitre Corp., 14
- Mix, in encryption, 792
- Mix columns, in AES, 790
- Mixmaster remailer, 634
- Mixer (German hacker), 18
- Mobile agent, hostile, 170, 430
- Mobile phone, 4, 818
- Mode, of access, 9, 72
- Model-based intrusion detection system, 478
- Modification, 87
  - asset, 7, **8**
  - code, 819
  - data, 11, 529
  - network, 361
  - program file, 177
  - protection against, 110, 113
  - sensitive data, 820
- Modularity,
  - in program design, 203, 204
  - in operating system design, 312
  - in operating system implementation, 322
- Money laundering, 19
- Monitor,
  - operating system, 285
  - reference, *see* Reference monitor
  - virtual machine, 292
- Monitoring, 474, 483, 484
  - and privacy, 620
  - implanted medical device, 816
  - real-time, 546
  - security, 475
- Moore’s Law, 92
- Morris Worm, 172, 175, 179, 209
- Morris, Robert T., Jr., 18, 172, 179
- Morris, Robert T., Sr., 43, 172, 417
- Motivation, of attacker, 16, 19, 773, 837
- Motive, 18, 19, **26**, 816
- Mudge, *see* Zatko, Peter
- Mulligan, Deirdre, 605
- Multics, 80, 85, 216, 219, 290, 307, 326
- Multifactor authentication, 70
- Multipartite virus, 178
- Multiple remailer, 634
- Multiplexing, network, 345, 363
- Multiprogramming, 285
- Multistep attack, 148
- Multitasking, 283
- Murder, by computer, 816
- Music-sharing service, 629
- Mutual authentication, 561
- Mutual suspicion, software characteristic, 207
- MyDoom, 430
- Name server, 414, 419
- Name, domain, 444
- named* (name daemon), 414
- NameNode, in Hadoop, 543
- Napster, 707
- NAT, *see* Network Address Translation
- National Bureau of Standards, *see* U.S. National Bureau of Standards
- National Institute of Standards and Technology, *see* U.S. National Institute of Standards and Technology

- National Security Agency (NSA), *see* U.S. National Security Agency
- NATO, 845, 849
- Natural disaster, 6, 13, 22, 686
  - building collapse, 687
  - fire, 687
  - flood, 686
  - water, 686
  - weather event, 687
- NBS (National Bureau of Standards), *see* U.S. National Bureau of Standards
- Need to know, 739
- Negative disclosure, 520
- Netherlands, 318, 641
- NetSky, 430
- Network, 342
  - client–server, 18
  - communication, confidential, 443
  - data loss prevention, 474
  - design, 401
  - interception in , 343–346
  - monitoring, 560
  - penetration of, 844
  - port scan, 456
  - traffic flow, 401
  - transmission media, 343
- Network Address Translation (NAT), 472
- Network attack,
  - component failure, 368
  - denial-of-service, 367
  - insertion, 364
  - interception, 354, 355
  - loss of service, 366
  - port scan, 369
  - replay, 364
  - routing, 367
  - sequencing, 363
  - substitution, 363
- Network Interface Card (NIC), 351, 376, 380
- Network management, 489
  - addressing, 490
  - bandwidth allocation, 490
  - blacklisting, 490
  - capacity planning, 489
  - load balancing, 489
  - rate limiting, 490
  - shunning, 490
  - sinkholing, 490
  - tuning, 490
- Network-based intrusion detection system (NIDS), 476, 480
- Networked storage, for backup, 697
- Neumann, Peter, 311
- NIC (Network Interface Card), **351**, 376, 380
- NIMDA, 172
- Nissenbaum, Helen, 601
- NIST (National Institute of Standards and Technology), *see* U.S. National Institute of Standards and Technology
- Nixon, Richard, 596
- Nmap, scanning tool, 369
- Noise,
  - for privacy, 545
  - in communication, 109
- Nonce, 108, 278, 793
- Non-compete clause, employment contract, 728
- Nonmalicious threat, **14**, 420
- Nonrandom attack, *see* Targeted attack
- Nonrepudiation, **7**, 115
- Nothing up my sleeve numbers, 806
- Notice, privacy, 600
- Notification, of data breach, 609
- Novelty, patent requirement, 712, 713
- NSA (National Security Agency), *see* U.S. National Security Agency
- Numbering, sequence, 419
- OAuth 573
  - Access token, 574
  - Authorization server, 574
  - Client secret, 575
  - Client, 574
  - Refresh token, 576
  - Request token, 575
  - Resource owner, 574
  - Resource server, 574
  - Token, *see* OAuth access token
- Object, 72
  - access control, 284
  - data as, 9
  - name, 77
  - reuse, 325
- Obscurity, security through (by), 185, 226, 356, 836
- Odd parity, 111
- Off-by-one error, 159
- Offset, page, 306
- Off-the-shelf, **3**
- OIDC (OpenID Connect), 577
- One-time pad, 774, 807
- One-time password, 52, 67, 244
- One-way hash function, 799
- Onion Routing, 443, 635
- Online profile, 627
- Open design, design principle, 217, 315
- Open mode, wireless network, 384
- Open System Interconnection (OSI) model, *see* OSI
- Openness, of private data collection, 597
- Operating system, 136, 279–340, 513
  - abstraction in, 289

- Apple iOS, 302
- Apple Mac OS, 291
- Audit in, 292
- authentication by, 283
- boot, 280
- complexity of design, 291
- complexity of, 187, 309
- concurrency in, 286
- correctness, 314
- DEC VAX, 314
- design of, 308, 820
- device control, 283
- device driver, 288
- domain, 286
- DOS, 302
- for smartphone, 818
- hierarchical design in, 311
- history, 284
- hypervisor, 292
- kernel, 284, 312
- layered design, 309
- Linux, 291
- loading in stages, 291
- Mach, 302
- monitor, 285
- multiprogramming, 285
- multitasking, 283
- process, 286
- resource allocation, 286
- rootkit, 329
- Scomp, 323
- security kernel, 312
- self-protection of, 290
- simplicity of design, 309
- single-user, 284
- smartphone, 818
- startup, 280
- task, 286
- thread of execution, 286
- trusted system, **316**
- Unix, 291
- virtualization, 292
- Windows, 291, 302
- Opportunity, of attack, **26**
- Optical fiber cable, interception from, 346
- Opt-in botnet, 430
- Orange Book, *see Trusted Computer System Evaluation Criteria*
- Organized crime, 15, **19**, 177
- Original work of authorship, 705
- Originality, and copyright, 706
- OSI (Open System Interconnection) model, 350, 433, 435, 439, 455, 462
- Out-of-band communication, 244
- Overflow,
  - buffer, *see* Buffer overflow
  - data, 149
  - integer, 160
  - parameter, 140
  - segment, 306
  - table, 143
- Overload, denial of service, 11, 399
- Oversight, of data collection, 603
- Ownership, of data, 8, 594, 596
- PaaS (Platform as a Service), 552, 557
- Pacemaker, 4, 816
- Packet, **351**, 415, 458, 477
- Packet filtering gateway, 456, 461, 467
- Packet sniffer, 343
- Page, offset in, 306
- Page, size of, 307
- Page-in-the-middle attack, 237
- Paging, **306**
  - combined with segmentation, 307
  - memory protection in, 307
- Palin, Sarah, 39, 52
- Parameter overflow, 140
- Parameter, mismatch of, 162
- Parity, **110**
  - check, 109
  - even, 111
  - odd, 111
- Parker, Donn, 18
- Partial plaintext attack, 770
- Passenger Name Record (PNR), 604
- Password(s), **40–51**, 266, 568, 610, 657, 738, 794, 844
  - attack on 42
  - choosing, 48
  - common, 45
  - concealment of, 46
  - database, 266
  - dictionary attacks on, 43
  - disclosure of, 41
  - forgotten, 42
  - guessing attack, 42–45
  - guessing, 761
  - inference of, 41, 43
  - loss of, 42
  - manager, 564
  - one-time, *see* One-time password
  - reuse of, 266
  - revocation of, 42
  - selection, 48
  - shared, 569
  - table, 46
  - use of, 41
  - variations of, 50

- weak, 568
- written 50, 51
- Patch, 419
  - hasty, 816
  - penetrate and, *See* Penetrate-and-patch
  - program, 172, 184, 731, 733
  - timeliness, 732
- Patent, 711
  - employment and, 727
  - enforcement, 713
  - for software, 713
  - infringement, 712–713
  - invalidation of, 713
  - license of technology, 712
  - nonobviousness requirement, 712
  - novelty requirement, 712
  - of employee's invention, 727
  - of RSA, 802
  - ownership of, 726
  - prior invention, 713
  - registration of, 712
  - RSA algorithm, 802
  - search of previous inventions, 712
  - software, 713
  - tangible invention, 711
- Path, network, 359
- Pattern analysis, against encryption, 769
- Pattern, malicious code, 192, 198, 200
- Pattern-matching
  - for intrusion detection, 477, 479
  - for malicious code, 192, 198, 200
- PayPal, 621
- PBKDF2, 562, 564
- P-box, in DES, 787
- PCI DSS (Payment Card Industry Data Security Standard), 555
- Peer-to-peer file sharing, 629, 707
- Penetrate-and-patch, program assurance myth, 224, 336, 733, 816
- Penetration testing, 218
- Pentium chip, Intel, floating-point error, 10
- People, as asset, 671
- Performance testing, 211
- Performance, database, 511
- Perimeter,
  - network, 359
  - security, 354, 471
- Permission, for data access, 596
- Permission-based, design principle, 217, 218, 316
- Permutation step, in DES, 96
- Permutation, in cryptography, 782
- Persistent cross-site scripting attack, 262
- Persistent virus, 168
- Personal computer, backup, 696
- Personal data, 820
- Personal firewall, 464
- Perturbation, data, 529, 534, 617
- Petmail, 240
- PGP, 276, 633
- Phishing, 274, 635
- Phishing attack,
  - G20 summit partners, 275
  - Korean diplomats, 275
  - RSA Corp., 275
  - White House staffers, 275
- Phone, mobile, 4
- Photon
  - gun, 811
  - orientation of, 807
  - reception of, 808
- Physical access, 773
- Physical access, unauthorized, 689
- Physical connection failure, 420
- Physical integrity, database, 507
- Physical protection, of computer, 284
- Physical security, 447
- Physical security, for separation, 296
- PIN, in authentication, 40, 67, 244
- Ping of death, 404
- Ping, 477
- Piracy, of intellectual property, 707
- Plaintext, **88**, 96, 103, 434
- Plaintext and ciphertext attack, 770
- Plaintext-only attack, 770
- Plan, incident response, *see* Incident response plan
- Plan, security, *see* Security plan
- Planning, contingency, 694
- Point-to-point communication, 633
- Poisoning, DNS cache, 418
- Polarizing filter, 808
- Policy, 72
  - access control, 9, 12
  - privacy, 600, 601, 609, 626
  - security, 453, 466, 649
- Politics, and cyberwarfare, 850
- Polymorphic virus, 193
- Poor programming practice, 158
- POP (Post Office Protocol), 353, 370
  - server, 633
- Pop-up ad, 630
- Porras, Phil, 428
- Port, **353**, 370, 472
- Port scan, network, 369, 450, 456, 476
- Post Office Protocol (POP), *see* POP
- Power
  - consumption, 817
  - loss, 688
  - spike, 688

- supply, uninterruptible, 688
- surge, 688
- Precaution, 22
- Precision, of data, 11, 530
- Precision, with risk analysis, 684
- Predictability, in Dual-EC, 806
- Prediction, from RFID sensor, 639
- Predictive value, in authentication, 57
- Preferred association, in wireless network, 386
- Pretty Good Privacy, *see* PGP
- Prevalence, in authentication, **56**
- Prevention, attack countermeasure, 28
- Price
  - of computer objects, 833
  - on the Internet, 631
- Primary Colors*, 246
- Privacy Act (U.S.), *see* U.S., Privacy Act
- Privacy officer, 739
- Privacy, **586**
  - access control for, 594
  - accuracy of data, 596, 599, 603, 608
  - adware, 629
  - affected parties, 589
  - anonymity and, 605
  - anonymization, 597, 613
  - breach notification law, 740
  - children's web access, 598
  - cloud computing, 642
  - collection limitation, 596
  - commerce and, 604
  - context of data use, 588, 601
  - controlled disclosure, 587
  - cookie, 627
  - correctness, data, 596, 599, 608
  - data accuracy, 596, 599, 603, 608
  - data collection by government, 738
  - data mining, 537
  - data modification, 597
  - data ownership, 592
  - data quality, 596, 599, 603, 608
  - data retraction, 594
  - deception prohibited, 600
  - determining sensitivity, 587
  - disappearing email, 635
  - disclosure, controlled, 587
  - E.U. Data Protection Act, 742
  - economics and, 832
  - email monitoring and, 632, 633
  - email remailer, 634
  - encryption and, 597
  - erroneous data, 608
  - ethical aspect of, 752
  - Europe, 603
  - expectation of, 633
  - fair market, 632
  - financial service organization, 598
  - government data misuse and, 607
  - government surveillance and, 645
  - Gramm–Leach–Bliley Act, 739
  - Hadoop, 544
  - Internet user ID, 622
  - laws, 597, 736
  - limited data collection, 603
  - limited data retention, 597
  - limited use, 597
  - linking of identities, 613
  - loss of, 814
  - medical data, 598, 739
  - new technology and, 643
  - notice of collection, 599, 600
  - online profile, 627
  - ownership, data, 592
  - permission for access, 596
  - policy statement of, 598
  - RFID tag, 638
  - safeguards for, 597
  - security of collected data, 599
  - specific purpose for use, 596, 603
  - spyware, 629
  - student records, 598
  - telephony, 642
  - U.S. e-Government Act, 599
  - U.S. government websites, 599
  - U.S. Privacy Act, 738
  - versus confidentiality, 589
  - voting, 641
  - web bug, 628
- Privacy-preserving data mining, 617
- Private cloud, 552, 555
- Private key, in cryptography, 101, 102, 109, 126
- Privilege, 73, 85, 158
  - escalation, **139**, 145, 165
  - least, *see* Least privilege
  - list, in access control, 82
  - limited, 75
  - limited, in operating system, 317
  - operating system, 139
  - root, 329
  - rootkit, 333
  - separation of, design principle, 217, 317
- Probability,
  - classical, 676
  - frequency, 676
  - subjective, 676
- Probable plaintext attack, against encryption, 770, 793
- Probable value disclosure, 520
- Procedure call, 136
- Procedure oriented access control, 85

- Process, 286, 320
- Process activation, in operating system, 320
- Processor, controlled access to, 283
- Product cipher, encryption, 782
- Product failure, redress for, 728
- Profile,
  - online, 627
  - protection, *see* Protection profile
  - user, 68
- Profit, motive for attack, 19
- Program assurance myth,
  - penetrate-and-patch, 224
  - penetration testing, 218
  - security through (by) obscurity, 185, 226, 356, 836
- Program assurance technique,
  - code review, 221
  - formal methods, 220
  - penetration testing, 218
  - proof of correctness, 219
  - testing, 211
  - validation, 221
- Program complexity, 149
- Program counter,
  - modification of, 136, 148, 149
  - protection of, 150
  - vulnerability of, 147
- Program design
  - complete mediation, 217, 316
  - defense in depth, 218
  - defensive programming, 222
  - Design by contract, 223
  - ease of use, 217, 317
  - economy of mechanism, 217, 316
  - least common mechanism, 217, 317
  - least privilege, 216, 218, 316
  - open design, 217, 316
  - permission-based, 217, 218, 317
  - separation of privilege, 217, 317
  - simplicity, 217
  - validate input, 217
- Program development practices, 216
  - cohesion, 206
  - encapsulation, 204, 206
  - information hiding, 204, 206
  - isolation, 203
  - modularity, 203, 204
  - mutual suspicion, 207
- Program equivalence, 189, 218, 219
- Program file, modification of, 177
- Program flaw, 184
- Program implementation, 150. *See also* Program development practices
- Program use, responsibility for use, 758
- Program verification, 219
- Program, resident, 188
- Program, shared access to, 287
- Program, terminate-and-stay-resident, 188
- Programmer, responsibility for program use, 758
- Programming error,
  - buffer overflow, 134, 139, 145
  - faulty serialization, 163
  - input validation failure, 152
  - off-by-one, 159
  - race condition, 163
  - synchronization, 163
  - time-of-check to time-of-use, 159
  - unchecked data, 153
- Programming language, 150
- Programming practice, poor 158
- Project, database operation, 504
- Promiscuous access point, 386
- Proof of correctness, program assurance technique, 219
- Propagation,
  - access right, 77, 83
  - encryption error, 778
  - malicious code, 180
- Property, as asset, 3
- Property, legal rules of, 734
- Proprietary software, 756
- Prosecution, 426
- Protected speech, 595
- Protection, 3, 6, 75, 87
  - consumer financial, 621
  - cookie data, 625
  - copyright, 704
  - critical data, 281
  - data, 11
  - differentiated, 305
  - for computer objects, 716, 717, 721
  - inadequate, 608
  - layered, 471
  - memory, 284, 321
  - mobile agent, 430
  - of critical data, 281
  - of data, 11
  - of implanted medical device, 817
- Protection profile, 328
- Protocol, 351
- Protocol, cryptographic key exchange, 105, 107
- Protocol, WiFi, 376
- Protocol analysis, stateful, 479
- Proxy, application, *see* Application proxy firewall
- Pseudonym
  - and privacy, 606, 613
  - for email, 634
  - of an object, 77
- PSOS (Provably Secure Operating System), 311, 326
- Psychology, of attacker, 16–17

- Public cloud, 552, 555, 561
- Public domain, 705, 755
  - ECC in the, 802
- Public hot spot, wireless, 382, 383
- Public key cryptography, **89**, 93, 100, 101, 102, 109, 118, 795, 802
  - for digital signature, 114, 116, 118
- Public scrutiny, of cryptographic algorithm, 779
- Pull, command-and-control update, 428
- Purpose for data use, and privacy, 597
- Push, command-and-control update, 428
  
- Qualitative risk analysis, 677
- Quality
  - of data, and privacy, 608
  - of service, as asset, 3
  - of software, 733, 816
- Quantification, of security, 825
- Quantitative risk analysis, 677
- Quantum cryptography, 807
- Quantum physics, 807
- Query analysis, database, 535
- Query language, database, 504
- Query, database, 504
  
- Rabbit, 170
- Race condition, 163, 815
- RACS (Redundant Array of Cloud Storage), 557
- Radar, jamming, 844
- Radiation therapy machine, 815
- Radiation, for network interception, 343
- Radio frequency identification, *see* RFID
- Rainbow table, **47**
- Randell, Brian, 296
- Random attack, 14
- Random number generator, 775, 786, 792, 806
- Random sample disclosure, database, 534
- Randomization, of address space, 210
- Range disclosure, database, 533
- Ransom, 400, 425
- Rate limiting, 490
- Rationality, 831
- RC2, 792
- RC4, 389, 393, 792
- RC5, 794
- RC6, 795
- Realm discovery, 571
- Rearrangement, encrypted data, 786
- Reasoning, ethical, 747
- Record, database, 502
- Record-keeping, incident, 664
- Recovery, 198
  - attack countermeasure, 28
  - database, 516
  - from malicious code attack, 179
  - system, 74
- Redirection
  - browser, 237
  - traffic, 413
- Redundancy, 421, 428
  - backup and, 697
  - database, 506
  - Hadoop and, 543
  - network design, 367
  - testing, 109
- Reference monitor, **76**, 155, **313**, 454
- Reflections on Trusting Trust, 172
- Register,
  - base, 298
  - bounds, 298
  - fence, 298
  - program counter, 136
  - stack pointer, 136, 146
- Registration,
  - copyright, 708
  - patent, 712
- Regression testing, 213
- Regularity, in cryptography, 774
- Regulation, 834
- Relation, database, 504
- Reliability, 421
  - data, 827
  - database, 513
  - software, 185
- Relocation, program, 301
- Remailer,
  - email, 634
  - multiple, 634
- Remanence, magnetic, 325
- Remote access Trojan horse (RAT), 170
- Remote wipe, 559
- Rent-a-bot, 429
- Repetition, in cryptanalysis, 776
- Replacement, of data, 3, 4
- Replacement virus, 182
- Replay attack, 432
  - authentication credentials, 365
  - network communication, 364
- Replication, data, 697
- Reputation, as asset, 671
- Requirements, security, 212, 649, 651
- Resident routine, 188
- Resident virus, 168
- Residual risk, 23
- Resilience, network, 847
- Resolution, addressing, 414
- Response team, 663
- Response, timeliness of, 11



- Responsibility, for security implementation, 650, 653
- Retraction, data, 594
- Return address
  - spoofing (network), 406
  - subprocedure, 139
- Reuse,
  - authentication data, 243
  - digital signature, 802
  - object, 325
  - serial, 287
  - software 206
- Reuters*, 19
- Reverse engineering, 714, 817
- Review, program, 158, 819
- Revocation, of access, 76
- Revolving backup, 695
- RFID, 636
  - device, 817
  - reader, 638
  - tag, 529, 636
- Right versus wrong, 747
- Rights of individuals to privacy, 597
- Rijndael, 98, 790. *See also* AES
- Ripple effect, 827
- Risk, 824
  - analysis, *see* Risk analysis
  - assumption of, 669
  - avoidance of, 669
  - communication of, 831
  - data access and, 607
  - exposure, 669
  - extreme events, 24–25
  - leverage, 669
  - management, 22
  - perception of, 25, 831
  - residual, *see* Residual risk
  - transfer of, 669
- Risk analysis, 23, 650, **668**
  - accuracy of, 685
  - benefits, 684
  - control selection, 680
  - difficulty to perform, 685
  - disadvantages, 684
  - exposure, 681
  - lack of accuracy, 685
  - likelihood estimation, 676
  - qualitative, 677
  - quantitative, 677
- Rivest, Ronald, 103, 107, 792, 795, 800
- Rivest–Shamir–Adelman cryptographic algorithm (RSA),
  - see* RSA
- Robustness, network, 847
- Rogue access point, 383
- Rogue host, in wireless network, 384
- Rogue network connection, 382
- Rogue program, 167
- Role-based access control, 85–86
- root* (Unix identity), 329
- Root name server (Internet), 414, 419
- Rootkit, 170, 465, 474, 612
  - Alureon, 334, 336
  - detection of, 334
  - eradication of, 334
  - in operating system, 329
  - in phone, 329
  - integration of, 332
  - mobile phone, 329
  - operating system, 329
  - Sony XCP, 335
  - stealth, 333, 335
  - TDL-3, 334
- Round, in AES, 98
- Rounded disclosure, 533
- Router, 351, 352, 401, 492. *See also* Routing
- Router, screening, *see* Packet filtering gateway
- Routing, 352, 355, 359, 367, 410, 413, 434, 436
- RSA Corp., 275, 439, 779, 795, 804
- RSA encryption
  - algorithm, 102
  - cryptanalysis of, 103
  - key selection in, 798
  - speed of encryption, 103
- Rule of engagement, 848
- Rule of evidence, 734
- Rushby, John, 296
- Russia, 19, 391, 397, 743, 843, 845
  
- S/MIME, 277, 633
- SaaS (Software as a Service), 552, 557
- Safe harbor, 604, 742
- Safe language, 149
- Safeguards, privacy, 597
- Safety, 815
- Salt, password table, 47
- Saltzer, Jerome, 75, 202, 216, 315, 735
- SAML (Security Assertion Markup Language), 570
  - Asserting Party, *see* IdP
  - Assertion, 572
  - Authentication Request, 572
  - Authentication Response, 572
  - IdP (Identity Provider), 571
  - Relying Party, *see* SP
  - SP (Service Provider), 571
  - Subject, 571
  - Token, *see* Authentication Response
- Sample size concealment, database, 534
- Sampling, 55
- Sampling, statistical, 532

- San Diego Supercomputer Center, 18
- Sandbox, **294**
- Sanitization, object, 325
- Sasser, 431
- SATAN (password administration tool), 43, 369
- Satellite communication, network, 346
- S-box, in DES, 787, 789
- Scan, port, 369, 456
- Scareware, 170, 195
- Schaefer, Marv, 221
- Schell, Roger, 172, 219, 225
- Schema, database, 502
- Schneier, Bruce, 801
- Schroeder, Michael, 75, 216, 315
- Scomp, 323, 326
- Scope, incident, 667
- Screening router, *see* Packet filtering gateway
- Script(ed) attack, 261, 423, 839
- Script kiddies, 196
- Seal, tamper detecting, 108, 112, 113
- Secrecy,
  - assurance myth, 227
  - code, 158, 185, 846
  - communication, 116
  - encryption, 777
  - programming, 184
  - security weakness of, 158, 185, 836
  - voting, 837
- Secret key encryption, *see* Symmetric encryption
- Secret, shared, in authentication, 243
- Secure Hash Standard (SHS), *see* SHS
- Secure programming, *see also* Program development practices
- Secure Socket Layer (SSL), *see* SSL
- SecurID authentication token, 67, 244, 275
- Security
  - add-on, 364
  - association, in IPsec, 444
  - computer, 2
  - cost of, 171
  - designing for, 212
  - kernel, 287, **312**, 322
  - operations center (SOC), 397, 492, 666
  - perimeter, 354
  - physical, 447
  - policy, 72, 466
  - program development, 158
  - quantifying, 825
  - software design and, 310
  - success of, 32
  - through (by) obscurity, 185, 226, 356, 836
- Security Essentials, Microsoft security tool, 250
- Security Information and Event Management (SIEM), 492, 493, 560, 568
- Security plan, 648, 668
  - acceptance of, 656
  - controls, 653
  - extensibility, 655
  - maintenance of, 655
  - requirements, 653
  - responsibility for implementation, 653
  - risk analysis, 668
  - team members, 656
  - timetable, 655
- Segment, offset in, 304
- Segment, size of, 305, 307
- Segmentation, combined with paging, 307
- Segmentation, memory, **303**
- Selective backup, 696
- Self-protection, of operating system, 290
- Sensitive data, 587
  - access from smartphone, 818
  - control of, 814
  - database, 518, 529
  - disposal of, 692, 772
  - exposure of, 177, 818
  - interception of, 236, 692, 772
  - protection of, 603
  - RFID tags and, 638
  - timeliness of, 844
- Sensitive information, subject to Freedom of Information act, 738
- Sensitivity, in authentication, **56**
- Sensitivity, in data mining, 537
- Sensor, 640, 815
- Separation, 72, 259, 296, 305
  - code from data, 150
  - controlled, 296
  - cryptographic, 296
  - data, 11
  - layering, 310
  - logical, 296
  - malicious code countermeasure, 195
  - physical 296, 688
  - potential malicious code, 197
  - privilege, design principle, 217, 316
  - security kernel, 312
  - TCB from non-TCB code, 320
  - temporal, 296
  - using firewall, 452
  - virtualization, 292
- Sequencing attack, 363
- Sequencing, TCP, 415
- Serial reuse, 287
- Serialization flaw, 163
- Server, 286
- Server-side include, 265
- Service, degradation of, 849

- Service, denial of, *see* Denial of service
- Service, theft of, 750
- Session hijack attack, 386, 394, 415
- Session, wireless communication, 393
- Severity, of harm, 22
- SHA, 113, 800
- SHA-2, 800
- SHA-256 564
- SHA-3, 801
- Shadow field, database, 516
- Shakespeare, 246
- Shamir, Adi, 103, 107, 788, 795
- Shannon, Claude, 90, 777
- Shared data space, 141
- Shared infrastructure, 566, 580
- Shared key, encryption, 92
- Shared passwords, 569
- Shared secret, in authentication, 243
- Shared use, operating system, 285
- Sharing, 74
  - controlled, 287, 296
  - data, 287
  - enforced, 281
  - fair, 753
  - incident response information, 667
  - programs, 287
  - resource, 358
  - total, 296
- Shielding, blocking electronic emanation, 693
- Shift row, in AES, 790
- Shneiderman, Ben, 654
- Shock, electrical, 816, 817
- Shopping, on the Internet, 630
- Shredding, paper, 692
- SHS ((Secure Hash Standard), *see* SHA
- Shunning, 431, **490**
- SIEM, *see* Security Information and Event Management
- Signature, digital, *see* Digital signature
- Signature, malicious code, 192, 198, 200
- Signature-based intrusion detection system, 476, 494
- Signed code, 251
- Silent Banker, 234
- Simple Mail Transfer Protocol (SMTP), *see* SMTP
- Simplicity,
  - encryption process, 778
  - program design principle, 217
  - program quality, 205
- Simultaneous access, 11
- Simultaneous execution, 286
- Single point of failure, 55, 557
- Single sign-on, 68, 461, 569
- Single-key encryption, *see* Symmetric encryption
- Single-user computer, 284
- Sinkholing, 490
- Situation assessment, by intrusion detection
  - system, 488
- Size, of ciphertext, 778
- Skimmer, 324
- Skimming, of authentication tokens, 67
- Skype, 642
- SLA (Service Level Agreement), 555, 567
- Slammer, 172, 175
- Small sample concealment, database, 534
- Smart device, 814
- Smartphone, 817
- SMTP (Simple Mail Transfer Protocol), 273
- SMTP server, 633
- Smurf attack, 404
- Snapchat, 635
- Sniffer, 343, 345
- Snow, Brian, 19
- SoBig, 172, 175
- SOC, *see*, Security Operations Center
- Social engineering, 50, 844
- Software,
  - as asset, 3, 671
  - as asset, 671
  - cohesion of, 206
  - correctness of, 206, 728, 729
  - coupling, 206
  - encapsulation of, 206
  - failure, 6, 730
  - failure, 728
  - flaw reporting, 731
  - information hiding in, 206
  - license of, 727, 756
  - maintenance of, 205
  - ownership of, 725, 754
  - patching, 731, 733
  - proprietary, 756
  - quality of, 733
  - quality, 210, 221
  - reliability, 815
  - return of defective, 730
  - reuse of, 206
  - shrink-wrapped, 729
  - usability, 728
- Software as a Service (SaaS), 552, 557
- Software design, 310
  - damage control in, 311
  - hierarchical, 311
  - security kernel, 312
- Software development practices, *see* Program development
  - practices
- Sony XCP rootkit, 335
- Source address spoofing, 404
- Source, in big data, 547
- Spafford, Eugene, 761

- Spam, 431, 633, 635, 740
  - advertising with, 270
  - fee to send, 273
  - laws, 271
  - links to malicious code sites, 271
  - outside legal jurisdictions, 271
  - pattern recognition, 272
  - pharmaceuticals, 270
  - pump-and-dump, 270
  - stocks, 270
  - U.S. Can Spam Act, 272
  - unreliable source address, 272
  - volume limitation, 272
  - volume of, 268
- Spear phishing, 274, 844
- Special operations, 842
- Specificity, in authentication, **56**
- Speech. Protected, 595
- Speed, of encryption, 126
- Splicing,
  - cable, 344, 363
  - code modification, 337
- Spoof(ing), 844
  - address, 413, 490
  - DNS, 409
  - email, 635
  - source address, 404
- Spying, 92, 845
- Spyware, 170, 628, 630
- SQL, 504
- SQL injection attack, 263
- Square, payment scheme, 621
- SSH (Secure shell) encryption, 438
- SSID (Security Set Identifier), 378, **381**, 383
  - cloaking, 384
  - automatic connection to, 387
- SSL (Secure Socket Layer) encryption, 235, 387, **438**, 444, 561, 794
  - Apple bug, 213
  - big data applications. 548
  - lack of diversity in implementation of, 210
  - session in, 439
- STaaS (Storage as a Service), *see* Cloud storage
- Stack, 146
- Stack frame, 146
- Stack frame, protection of, **150**
- Stack memory, 136, 139
- Stack pointer, 136, 146
- Stack pointer, protection of, 150
- Stack smashing, 145, 148
- StackGuard (stack protection software), 150
- Stalker, 820
- Startup (automatically executing program), 181, 189
- Startup, operating system 280, 323
- State machine, 479
- State-based intrusion detection system, 478
- Stateful inspection firewall, 458
- Stateful protocol analysis, 479
- Statistical analysis, 477
  - in cryptanalysis, 776
- Statistical sampling, 532
- Statistics, web use, 626
- Statute, *see* Law
- Stealth, 487
  - mode, wireless network, 384
  - malicious code, 189, 190 428
- Steganography, 192
- Stoll, Cliff, 295, 667
- Storage, networked, for backup, 697
- Strategy, business continuity, 660
- strcpy, string copy utility, 162
- Stream cipher, 793
- Stream encryption, **93**
- Street View, Google, 378
- Strength, of encryption, 97, 777
- String copy program, 162
- String
  - length, 161
  - null-terminated, 161
  - termination, 161
- strncpy, string copy utility, 162
- STU-III secure telephone, 244
- Stuxnet, 20, 174, 175, 368, 843, 847
- Subject, **38**, 72
- Subject, data, 9
- Subjective probability, 676
- Subnet, 450
- Subprocedure, 139
- Subschema, database, 502
- Substitution, 363
  - attack, 363
  - encrypted data, 786
  - in AES, 98
  - in cryptography, 95, 103, 774
  - step, in DES, 96
- Subtask, 204
- Subversion, 815
- Suit, contract law, 725
- Suite B, cryptographic algorithms, 803
- Supervisor, operating system, 136, 280
- Suppression, data, 529
- Suppression, limited response, 532
- Surface, attack, *see* Attack surface
- Surfing, and privacy, 624
- Surge suppressor, 688
- Surveillance, government, and privacy, 645
- Survey results, comparability of, 830
- Swapping, 303

- database, 535
  - value, 618
- Sweeney, Latanya, 527, 615
- Switching cloud providers, 556
- Symmetric cipher, 789
- Symmetric encryption, **88**, 92, 96, 786
- SYN flood attack, 405
- SYN packet, 406
- SYN-ACK, 406
- Synchronization, 281
  - program, 163
  - TCP, 416
- Syria, 844, 845
- System log, 567, 582
- System, computer, **3**
- System, trusted, *see* Trusted system
- System, usability of, 12
- Syveron, Paul, 443
  
- Tablet computer, 818
- Tag, RFID, 636
- Tagged architecture, 301, 305
- Tamper detection, 151
- Tampering, data, 109
- Tampering, protection against, 113
- Tamperproof, reference monitor property, 76
- Tamper-resistant seal, 840
- Target, attractive, 27
- Target Corp., 609, 616
- Targeted attack, 14, 19
- Targeting, behavioral, 626
- Task, **286**
  - background, 358
- TCP connection, 415
- TCP/IP, 439
- TCSEC (Trusted Computer System Evaluation Criteria),
  - see* *Trusted Computer System Evaluation Criteria*
- TDL-3 (malicious code), 334
- TDSS rootkit, 336
- Teardrop attack, 407
- Telecommuter, 449
- Teleology, 748
- Telephony, privacy and, 642
- Television, 1
- Temperature, effect on semiconductor, 772
- Tempest, 693
- Template, for biometric authentication, 59, 62
- Temporal Key Integrity Program (TKIP), 393
- Terminate-and-stay-resident routine, 188
- Terms of service, 643
- Terms of use, 592, 763
- Terrorism, 20–21
  - and privacy, 607
- Testing, 210, 221
  - acceptance, 211
  - black-box, 214
  - clear-box, 214
  - completeness of, 214
  - coverage of, 214
  - effectiveness of, 215
  - function, 211
  - independent, 215
  - installation, 211
  - integration, 211
  - limitations of, 215
  - penetration, 218
  - performance, 211
  - regression, 213
  - unit, 211
- TFN, *see* Tribal flood network
- TFN2K, *see* Tribal flood network 2000, *The Cuckoo's Egg*, 668
- Theft, 689, 692, 734
  - credit card, 19, 22
  - detering, 692
  - identity, 609
- Therac 25, 815
- Third-party ad, 622
- Third-party cookie, 625
- Thompson, Ken, 43, 172
- Thread, 163, **286**
- Threat, **5**, **6**, 8, 13, 25
  - Threat, **6**, 8
    - Advanced Persistent, *see* Advanced Persistent Threat
    - for decision-making, 826
    - malicious, **14**
    - network disconnection, 849
    - nonmalicious, **14**, 420
- Threat surface, 820
- Threshold, 55
- Ticket, access control mechanism, 82
- Tiger team analysis, *see* Penetration testing
- Time bomb, 170
- Time
  - theft of, 750
  - response *see* Response time
  - value of, 824
  - wait, *see* Wait time
- Timeliness, 777
  - data, 827
  - response, 11
  - sensitive data, 844
  - value of asset, 4
- Time-of-check to time-of-use (TOCTTOU) error, **155**
- TJMaxx, data theft, 19, 391
- TKIP (Temporal Key Integrity Program), 393
- TLS (Transport Layer Security) encryption, *see* SSL
- TNO (Trust No One), 562, 564

- TOCTTOU error, *see* Time-of-check to time-of-use error
- Toilet sensor, 592
- Token,  
     active, **66**  
     dynamic, **67**  
     for authentication, 65, **66**  
     passive, **66**  
     RFID, 636  
     static, **66**
- Tolerance, fault, *see* Fault tolerance
- Toolkit, 166, 170, 196
- Top level domain, 414
- Topology, network, 849
- TOR (The Onion Router), *see* Onion routing
- Tort law, 722
- Totient function, Euler, 797
- Tracker  
     inference in database, 524  
     web page, 623
- Tracking  
     active, 628  
     Internet, 254, 620, 622, 623, 627  
     passive, 627  
     RFID tag, 638
- Tracking bug, 254
- Trade secret, 714, 720, 734  
     enforcement, 714  
     improper access to, 714  
     ownership of, 727  
     reverse engineering, 714  
     secrecy of, 714
- Trademark, 717
- Traffic redirection, 413
- Transfer, of risk, 669
- Transient virus, 168
- Translation, address, *see* Address translation
- Transmission  
     error, 361  
     failure, 420  
     of malicious code, 180
- Transparency, and privacy, 629
- Transparent image, Internet, 629
- Transport mode, in IPsec, 446
- Transposition, in cryptography, 95, 103, 774
- Trapdoor, 158, 170, 356, 787, 790, 845
- Treaty, 848
- Trespassing, 761
- Triad, C-I-A, *see* C-I-A triad
- Triage, incident response, 664
- Tribal flood network (TFN), 18, 424
- Tribal flood network year 2000 edition (TFN2K), 18, 424
- Trin00 (malicious software), 18, 424
- Triple DES, **96–97**, 98
- Triple, access control, 78–79, 81
- Tripwire (modification detection program), 112, 165, 251, 481
- Trojan horse, 169, 170, 423. *See also* Malicious code
- Trope, Roland, 730
- Trust, 76, 117, 172, 288, 310, 316, 409, 412, 454, 818, 838
- Trusted code, 289
- Trusted Computer System Evaluation Criteria*, 318, 323, **327**, 651
- Trusted Computing Base (TCB), 318, **319**
- Trusted path, 323
- Trusted system, 316
- Trustworthy Computing Initiative, Microsoft, 222, 326
- Truth, 747, 762
- Tuning, network, 431, 489
- Tunnel mode, in IPsec, 446
- Tunnel, encrypted, 448
- Tuple, database, 504
- Turn, Rein, 597
- Tversky, Amos, 25
- Twitter, 595
- Two-factor authentication, 70
- Two-phase update, database, 514
- U.S. Children's Online Privacy Protection Act (COPPA), 598
- U.S. Computer Emergency Response Team (CERT), 424
- U.S. Computer Fraud and Abuse Act, 738
- U.S. Department of Defense, 7, 608, 694, 842
- U.S. Department of Health, Education and Welfare, 596
- U.S. Department of Justice, 15, 19, 610
- U.S. Economic Espionage Act, 738
- U.S. Federal Bureau of Investigation (FBI), 19, 20, 21, 61, 64
- U.S. Federal Educational Rights and Privacy Act, 598
- U.S. Federal Trade Commission, 599, 601, 610
- U.S. Freedom of Information Act (FOIA), 738
- U.S. Health Insurance Portability and Accountability Act (HIPAA), 598, 739, 753
- U.S. National Bureau of Standards (NBS) 95, 97, 779, 788.  
     *See also* U.S. National Institute of Standards and Technology
- U.S. National Institute of Standards and Technology (NIST) 14, 95, 98, 429, 789, 800, 801, 806, 811.  
     *See also* U.S. National Bureau of Standards
- U.S. National Security Agency (NSA), 97, 781, 787, 788, 794, 801, 803, 805, 806
- U.S. Privacy Act, 597, 738
- U.S. Uniform Commercial Code (UCC), 729
- U.S.A. Patriot Act, 740
- UCC, *see* U.S. Uniform Commercial Code
- Ukraine, 166, 845
- Unchecked data, 153
- Undecidability, *see* Decidability
- Undocumented access point, 27, 157. *See also* Backdoor

- Unintentional error, 6, 420
- Uninterruptible power supply, 688
- Unique identity, 606
- Unit testing, 211
- United States, 15, 19, 211, 743, 772, 843, 846
- Unix, 81, 291, 329
- Unsafe code, 150
- Unterminated string, 161
- Usability, 51, 75, 242
  - in the large, 51, 52
  - in the small, 51, 52
  - system 12
  - voting system, 841
- Use,
  - asset, 7
  - data, 11, 608
- User, 72
- User interface, 815, 840
- User-in-the-middle, 237
- Utilitarianism, 749
- Utility program, 284
  
- Validation, program assurance technique, 221
- Value swapping, 618
- Value, of asset, **4**, 6, 21
- Value, of data, 736
- Vandalism, 689
- Variability, in biometric authentication, 55, 59, 64
- VAX, DEC computer, 290
- Vendor lock-in, 556
- Venema, Wietse, 369
- Verifiability, reference monitor property, 76
- Verification, program, *see* Program verification
- Verizon Breach Report, 171
- Vernam cipher, 775
- Viewing, data, 9
- Viewing, asset, 7
- Virginia, 421
- Virtual infrastructure, 581
- Virtual machine, **292**, 579
- Virtual memory, 303
- Virtual private network (VPN), **447**, 492, 633
- Virtualization, in operating system, **292**
- Virus, **167**, 329
  - appended, 181
  - attachment of, 188
  - boot sector, 187
  - destructive, 176
  - detector, 198–199, 295
  - document, 180
  - encrypting, 194
  - hoax, 176
  - memory-resident, 188
  - multipartite, 178
  - persistent, 168
  - polymorphic, 193
  - resident, 168
  - transient, 168
  - See also* Malicious code
- VM (Virtual Machine), 558, 567, 579
- Voice over IP, *see* VOIP
- VoIP, 642
- Volume-based attack, denial of service, *see* Volumetric attack
- Volumetric attack, 398, 399, 423
- Voting, electronic,
  - casting a ballot, 834
  - counting ballots, 836
  - privacy, 641
- VPN, *see* Virtual private network
- Vulnerability, **5**, 6, **28**
  - backdoor, 158
  - disclosure of, 731–733, 760, 833
  - disclosure, full, 760
  - disclosure, partial, 760
  - electronic voting, 834
  - exploitation, 419
  - finding, 760
  - for decision-making, 826
  - paper-based election, 834
  - race condition, 163
  - reporting, responsible, 732
  - risk analysis, 672
  - scanning, 431, 482
  - search for, 761
  - toolkit, 166, 419
  - trapdoor, 158
  - undocumented entry, 158
  - zero-day, 172
- Vulnerability–threat–control paradigm, 5
  
- Wait time, 11
- Waladec, spam network, 269, 429
- War driving, network, 382
- War of the Worlds*, 2
- Ware, Willis, 13, 172, 318, 596, 597
- Warfare, conventional, 842, 846
- Warfare, cyber, *see* Cyber warfare
- Watergate burglary, 596
- Watermark, digital, 710
- Weak encryption, 388
- Weak passwords, 568
- Weakness, 5
  - in cryptography, 806
- Weapon,
  - cyber, 847
  - kinetic, 847
- Web [the], *see* Internet

## Web

- bug, 254, 627
- content, false, 246
- hosting, 566
- page, fake, 117
- site defacement, 20, 246
- site, fake, 249
- site, privacy of, 599, 600

Welke, Stephen, 10–11

Welles, Orson, 2

Wells, H. G., 2

WEP (Wired Equivalent Privacy), 379, 388, 398, 794

- weaknesses in, 389–390

Whistle blower, 613

White hat hacking, 759

White House, victim of phishing attack, 275

Whitelisting, application, 581

Whittaker, James, 210, 211, 214

## WiFi

- communication, 364, *see also* Wireless network
- frame, 379
- signal interception, 391

WikiLeaks, 473, 486, 595, 620

Wild card, in access control, **81**

Windows operating system, 291, 302, 339, 818

Wireless client, 364

Wireless communication, 364, 376, 816. *See also* WiFi  
communication

## Wireless network

- association, 380
- authentication, 380
- authentication, 385
- availability in, 382
- base station, 382
- broadcast mode, 384
- closed mode, 384
- confidentiality, 381
- encryption in, 383
- integrity in, 381
- open mode, 384
- rogue access point, 383
- rogue host in, 384
- stealth mode, 384

Wireless network vulnerability,

- association hijacking, 386
- authentication, nonexistent, 390

availability, 382

confidentiality, 381

encryption initialization vector collision, 389

faulty integrity check, 390

incomplete authentication, 394

integrity, 381

integrity check, 390

integrity failure, 395

MAC address spoofing, 394

man-in-the-middle, 394

no authentication, 390

promiscuous access point, 386

rogue host, 384

session hijack, 394

short encryption key, 388

static encryption key, 388

weak encryption, 388

Wiretap attack, 242, 343, 344, 354, 355, 360, 628, 739,  
770, 771

Word macro virus, 10

Work factor, 227

Work factor, cryptographic, 91, 97

Work for hire, 726

World Intellectual Property Organization Treaty of 1996,  
705

World War II, 89, 107, 771, 772

Worm, 168. *See also* Malicious codeWorm, Morris, *see* Morris worm

WPA (WiFi Protected Access), 390, 794

WPA attack,

- MAC address spoofing, 394
- man-in-the-middle, 394

XCP, Sony rootkit, 335

XMLDSig (XML digital signature), 572

x-ray, 815

Yes-or-no test, in authentication, 56, 62

Yoran, Amit, 209

Zatko, Peter (Mudge), 139–140

Zero-day exploit, 172 **419**

Zeus, vulnerability toolkit, 245, 419

Zip code, U.S. 615

Zombie, 170, 423, 426