QC CERTIFICATE · SPEC SHEET

AB1-RN-S-07 · version 1

RING · Category C · QC passed 2026-11-02 23:04 UTC

Measured specification

Minimum wall	0.90 mm · required 0.80 mm
Minimum prong	0.85 mm · required 0.80 mm
Ring size	US 6.5
Inner diameter	—
Mesh tolerance	0.005 mm max distance / edge
Open edges	0

QC stage 1 · Designer check

#	CHECK	RESULT	MARKED (UTC)
01	Size and all measurements	Pass	11-02 23:04
02	Diamond sizes, colours and count	Pass	11-02 23:04
03	Setting type	Pass	11-02 23:04
04	Metal colour and karat	Pass	11-02 23:04
05	Client's special remarks	Pass	11-02 23:04
06	Overall design look, every measurement marked	Pass	11-02 23:04
07	No open or naked edges	Pass	11-02 23:04
08	STL mesh	Pass	11-02 23:04
09	Files exported	Pass	11-02 23:04

QC stage 2 · QC manager check

#	CHECK	RESULT	MARKED (UTC)
01	Overall design look	Pass	11-02 23:04
02	Diamond sizes, shapes and colours	Pass	11-02 23:04
03	All measurements	Pass	11-02 23:04
04	Setting type, metal colour and karat	Pass	11-02 23:04
05	Client's special remarks	Pass	11-02 23:04

Sign-off

Designer	DSG-0001
QC manager	Pod lead · Pod One
Status	Approved · 2026-11-02 23:04 UTC

Files and fingerprints (SHA-256)

3DM	RN-S-07_3DM_v1.3dm	ae26a36821ef10c489337125af81f4cd0fe27edb14184289503f26759d3ff60b
RENDER	RN-S-07_RENDER_v1.png	d3537af34b1f905df9ea185cc9131995ca8f1142022979677912644 1c5b34628

STL	RN-S-07_STL_v1.stl	6e785567bf1ef0ab6a04453b5a4abc71bab07f55a11395c28df0e87ed8aa9c4a
TECH	RN-S-07_TECH_v1.png	4cae0b4809b5fb9ad547c66acf6fc2b697716a0d9a822e1e1c7e86bb681151c4

A file whose fingerprint differs from the one listed here has been edited after delivery.