

Tables

New tables

Table	Purpose
M_RFIDTag	Tag lifecycle master (Unused/Assigned/Lost/Damaged/Retired), independent of any file
Tra_RFIDScan	Raw log of every reader ping, whether or not it caused a location change

Altered tables

Table	Columns added
Mst_RFIDCaseListDetails	TagID, CaseType, CaseYear, CaseNo, CourtID, LastSeenOn, LastSeenReaderID, UpdatedOn
M_RFIDReader	LocationID, ReaderType
Tra_FileMovement	ScanID, TransactionStatus
Missing_File	ExpectedLocationID, DispatchMovementID, LastSeenReaderID, IsAutoDetected, FoundLocationID, FoundReaderID, ClosedDate, ClosedBy
Alert_Master	ReaderID, LocationID
CauseList_File	Cino, CheckedOn, CheckedBy
M_Court	CourtNo widened to VARCHAR(200)

Deleted tables

Table	Reason
Case_Master (local)	Confirmed unused — real flow keys off Cino against ccms3 directly

Untouched (reviewed, left as-is): File_Master, M_User, M_Role, M_Section, Case_Type_Master, Case_Year_Master, Notification_Log, Audit_Log

Views (all new)

View	Purpose
V_FileCurrentStatus	One row per file — tag, location, status, last seen — for quick lookups
V_OpenMissingFiles	Currently open missing-file cases with last-known location
V_ReaderHealth	Computes ONLINE/WARNING/OFFLINE/NO HEARTBEAT from each reader's last heartbeat

Stored Procedures

New

Proc	Purpose
SP_RecordRFIDScan	Core transaction: logs a scan, moves the file if location changed, raises alerts, auto-resolves missing status
SP_DetectMissingFiles	Scheduled job — flags files not scanned anywhere for 24h since their last movement
SP_SyncCourtMaster	Copies court list from <code>ccms3.court_room_master</code> into local <code>M_Court</code>
SP_SyncCauseList	Pulls today's hearing list from <code>ccms3.Cause_List</code> , resolves court + computes real Available status

Rewritten (same name, replaced logic)

Proc	What changed
SP_AssignRFIDToFile	Now creates a row in <code>M_RFIDTag</code> instead of just writing a number onto the file
SP_CheckRFIDUniqueness	Checks <code>M_RFIDTag</code> instead of raw <code>RFIDTagNo</code> text
SP_GenerateRFID	Now a thin wrapper that generates a number then calls <code>SP_AssignRFIDToFile</code>

Proc	What changed
SP_GetTodayCauseListStatus	Replaced the old <code>ia_flag</code> /hardcoded-location-9 logic with the real "seen + not missing + correct courtroom" rule
SP_GetCourtWiseFileStatus	Same rewrite, broken out per court
SP_GetDashboardStats	Repointed off <code>TagID</code> instead of raw <code>RFIDTagNo</code> ; missing-file check now matches 'OPEN' status
SP_GetRecentFileMovements	Repointed <code>CaseNo</code> off <code>Mst_RFIDCaseListDetails</code> instead of the dropped <code>Case_Master</code>
SP_GetMissingFilesHighPriority	Same repoint
SP_GetFileMovementDashboard	Same repoint (<code>CaseNo</code> , <code>CaseType</code>)
SP_GetRFIDDashboard	<code>Readers / RecentScans</code> branches repointed to <code>M_RFIDReader.LocationID</code> and <code>Tra_RFIDScan</code> instead of the old text <code>LocationName / Tra_FileMovement</code>
SP_GetDropdownData	<code>CASE_STATUS</code> branch repointed to <code>Mst_RFIDCaseListDetails.FileStatus</code> (was reading the dropped <code>Case_Master</code>)

Deleted

Proc	Reason
SP_Case_Search_Optimized	Only queried the dropped <code>Case_Master</code> — confirmed unused

Untouched: `SP_GetReaderStatus`, `SP_GetFileDistributionByCourt`, `SP_GetFileDistributionBySection`, `SP_GetFileMovementTrend`, `SP_SearchFilesV2`, `SP_sync_case_no_to_RFID`

Key relationships (foreign keys added)

From → To	What it enforces
<code>Tra_FileMovement.FileID</code> → <code>Mst_RFIDCaseListDetails.FileID</code>	A movement must belong to a real file (<i>previously missing entirely</i>)

From → To	What it enforces
Missing_File.FileID → Mst_RFIDCaseListDetails.FileID	Same (<i>previously missing</i>)
Alert_Master.FileID → Mst_RFIDCaseListDetails.FileID	Same (<i>previously missing</i>)
CauseList_File.FileID → Mst_RFIDCaseListDetails.FileID	Same (<i>previously missing</i>)
Alert_Master.ResolvedBy → M_User.UserID	Who resolved an alert (<i>never existed, even originally</i>)
Mst_RFIDCaseListDetails.TagID → M_RFIDTag.TagID	A file's tag must be a real registered tag
Mst_RFIDCaseListDetails.CourtID → M_Court.CourtID	
Mst_RFIDCaseListDetails.LastSeenReaderID → M_RFIDReader.ReaderID	
M_RFIDTag.AssignedFileID → Mst_RFIDCaseListDetails.FileID	
M_RFIDReader.LocationID → M_Location.LocationID	Reader belongs to a location (flipped from the old Location→Reader direction, which forced one reader per room)
Tra_RFIDScan.FileID / .ReaderID → Mst_RFIDCaseListDetails / M_RFIDReader	
Tra_FileMovement.ScanID → Tra_RFIDScan.ScanID	Traces every movement back to the scan that caused it
Missing_File.ExpectedLocationID, .FoundLocationID, .FoundReaderID, .LastSeenReaderID, .DispatchMovementID, .ClosedBy → respective tables	Full lifecycle trail for a missing-file case
Alert_Master.ReaderID, .LocationID → respective tables	Where an alert was raised
CauseList_File.CheckedBy → M_User.UserID	Who verified a listed file's availability

Constraint added: UQ_File_Cino — unique index on Mst_RFIDCaseListDetails.Cino, enforcing your rule of one file per case.