## CS1571 Fall 2019 12/2 In-Class Worksheet

Name: Simran Gidwani

Where were you sitting in class today: Center right

## A. Pre-Reflection

On a scale of 1-5, with 5 being most confident, how well do you think you could execute these learning objectives:

■ 21.3 Execute a Naïve Bayes classification

22.1 Describe the components of Q-learning

## **B.** Q-Learning

1. Explain the different components of the following equation.

$$Q_{\text{sample}}(s,a) = r + \gamma \max_{a'} Q_{\text{old}}(s',a')$$

The q value of taking action a in state s = Qsample(s, a) ==

The reward r you get from taking action a in state s (new information you get from taking that action in that state) + discount factor of future rewards \* max future utility of taking an action in state s' (the state you arrived in)

Gamma – value between 0 and 1 that discounts the future rewards

Qold – represents previously computed value of Q that is computed using dynamic programming – iterating over all the a'

2. Explain the different components of the following equation. What do you think is going on?

$$Q_{new}(s,a) \leftarrow Q_{old}(s,a) + \alpha*(Q_{sample}(s,a) - Q_{old}(s,a))$$

Creates weighted average that balances new info with the old

A\* -- learning rate

	T	4	$\mathbf{r}$	a			
<b>C</b> .	PA	st-	ĸ	4 T	<b>ው</b> ሮ1	tır	m
$\sim$	1 0	-טפי	77		·	uu	,,,

On a scale of 1-5, with 5 being most confident, how well do y	ou think you could execute
these learning objectives:	
21.3 Evacuta a Naïva Bayas classification	

<ul> <li>21.3 Execute a Naïve Bayes classification</li> </ul>

-	22.1 Describe the components of Q-learning	
---	--	--