

Multiclass Support Vector Machine exercise

In this exercise you will:

- implement a fully-vectorized **loss function** for the SVM
- implement the fully-vectorized expression for its **analytic gradient**
- **check your implementation** using numerical gradient
- use a validation set to **tune the learning rate and regularization** strength
- **optimize** the loss function with **SGD**
- **visualize** the final learned weights

In [1]:

```
# Run some setup code for this notebook.

import random
import numpy as np
from cs175.data_utils import load_CIFAR10
import matplotlib.pyplot as plt

from __future__ import print_function

# This is a bit of magic to make matplotlib figures appear inline in the
# notebook rather than in a new window.
%matplotlib inline
plt.rcParams['figure.figsize'] = (10.0, 8.0) # set default size of plots
plt.rcParams['image.interpolation'] = 'nearest'
plt.rcParams['image.cmap'] = 'gray'

# Some more magic so that the notebook will reload external python modules;
# see http://stackoverflow.com/questions/1907993/autoreload-of-modules-in-ipython
%load_ext autoreload
%autoreload 2
```

CIFAR-10 Data Loading and Preprocessing

In [2]:

```
# Load the raw CIFAR-10 data.
cifar10_dir = 'cs175/datasets/cifar-10-batches-py'
X_train, y_train, X_test, y_test = load_CIFAR10(cifar10_dir)

# As a sanity check, we print out the size of the training and test data.
print('Training data shape: ', X_train.shape)
print('Training labels shape: ', y_train.shape)
print('Test data shape: ', X_test.shape)
print('Test labels shape: ', y_test.shape)
```

```
Training data shape: (50000, 32, 32, 3)
Training labels shape: (50000,)
Test data shape: (10000, 32, 32, 3)
Test labels shape: (10000,)
```

In [3]:

```
# Visualize some examples from the dataset.
# We show a few examples of training images from each class.
classes = ['plane', 'car', 'bird', 'cat', 'deer', 'dog', 'frog', 'horse', 'ship', 'truck']
num_classes = len(classes)
samples_per_class = 7
for y, cls in enumerate(classes):
    idxs = np.flatnonzero(y_train == y)
    idxs = np.random.choice(idxs, samples_per_class, replace=False)
    for i, idx in enumerate(idxs):
        plt_idx = i * num_classes + y + 1
        plt.subplot(samples_per_class, num_classes, plt_idx)
        plt.imshow(X_train[idx].astype('uint8'))
        plt.axis('off')
        if i == 0:
            plt.title(cls)
plt.show()
```



In [4]:

```
# Split the data into train, val, and test sets. In addition we will
# create a small development set as a subset of the training data;
# we can use this for development so our code runs faster.
num_training = 49000
num_validation = 1000
num_test = 1000
num_dev = 500

# Our validation set will be num_validation points from the original
# training set.
mask = range(num_training, num_training + num_validation)
X_val = X_train[mask]
y_val = y_train[mask]

# Our training set will be the first num_train points from the original
# training set.
mask = range(num_training)
X_train = X_train[mask]
y_train = y_train[mask]

# We will also make a development set, which is a small subset of
# the training set.
mask = np.random.choice(num_training, num_dev, replace=False)
X_dev = X_train[mask]
y_dev = y_train[mask]

# We use the first num_test points of the original test set as our
# test set.
mask = range(num_test)
X_test = X_test[mask]
y_test = y_test[mask]

print('Train data shape: ', X_train.shape)
print('Train labels shape: ', y_train.shape)
print('Validation data shape: ', X_val.shape)
print('Validation labels shape: ', y_val.shape)
print('Test data shape: ', X_test.shape)
print('Test labels shape: ', y_test.shape)
```

```
Train data shape: (49000, 32, 32, 3)
Train labels shape: (49000,)
Validation data shape: (1000, 32, 32, 3)
Validation labels shape: (1000,)
Test data shape: (1000, 32, 32, 3)
Test labels shape: (1000,)
```

In [5]:

```
# Preprocessing: reshape the image data into rows
X_train = np.reshape(X_train, (X_train.shape[0], -1))
X_val = np.reshape(X_val, (X_val.shape[0], -1))
X_test = np.reshape(X_test, (X_test.shape[0], -1))
X_dev = np.reshape(X_dev, (X_dev.shape[0], -1))


# As a sanity check, print out the shapes of the data
print('Training data shape: ', X_train.shape)
print('Validation data shape: ', X_val.shape)
print('Test data shape: ', X_test.shape)
print('dev data shape: ', X_dev.shape)
```

```
Training data shape: (49000, 3072)
Validation data shape: (1000, 3072)
Test data shape: (1000, 3072)
dev data shape: (500, 3072)
```

In [6]:

```
# Preprocessing: subtract the mean image
# first: compute the image mean based on the training data
mean_image = np.mean(X_train, axis=0)
print(mean_image[:10]) # print a few of the elements
plt.figure(figsize=(4,4))
plt.imshow(mean_image.reshape((32,32,3)).astype('uint8')) # visualize the mean i
mage
plt.show()
```

```
[130.64189796 135.98173469 132.47391837 130.05569388 135.34804082
 131.75402041 130.96055102 136.14328571 132.47636735 131.48467347]
```



In [7]:

```
# second: subtract the mean image from train and test data
X_train -= mean_image
X_val -= mean_image
X_test -= mean_image
X_dev -= mean_image
```

In [8]:

```
# third: append the bias dimension of ones (i.e. bias trick) so that our SVM
# only has to worry about optimizing a single weight matrix W.
X_train = np.hstack([X_train, np.ones((X_train.shape[0], 1))])
X_val = np.hstack([X_val, np.ones((X_val.shape[0], 1))])
X_test = np.hstack([X_test, np.ones((X_test.shape[0], 1))])
X_dev = np.hstack([X_dev, np.ones((X_dev.shape[0], 1))])

print(X_train.shape, X_val.shape, X_test.shape, X_dev.shape)
```

```
(49000, 3073) (1000, 3073) (1000, 3073) (500, 3073)
```

SVM Classifier

Your code for this section will all be written inside **cs175/classifiers/linear_svm.py**.

As you can see, we have prefilled the function `compute_loss_naive` which uses for loops to evaluate the multiclass SVM loss function.

In [9]:

```
# Evaluate the naive implementation of the loss we provided for you:
from cs175.classifiers.linear_svm import svm_loss_naive
import time

# generate a random SVM weight matrix of small numbers
W = np.random.randn(3073, 10) * 0.0001

loss, grad = svm_loss_naive(W, X_dev, y_dev, 0.000005)
print('loss: %f' % (loss, ))
```

```
loss: 8.975407
```

The grad returned from the function above is right now all zero. Derive and implement the gradient for the SVM cost function and implement it inline inside the function `svm_loss_naive`. You will find it helpful to interleave your new code inside the existing function.

To check that you have correctly implemented the gradient correctly, you can numerically estimate the gradient of the loss function and compare the numeric estimate to the gradient that you computed. We have provided code that does this for you:

In [10]:

```
# Once you've implemented the gradient, recompute it with the code below
# and gradient check it with the function we provided for you

# Compute the loss and its gradient at W.
loss, grad = svm_loss_naive(W, X_dev, y_dev, 0.0)

# Numerically compute the gradient along several randomly chosen dimensions, and
# compare them with your analytically computed gradient. The numbers should match
h
# almost exactly along all dimensions.
from cs175.gradient_check import grad_check_sparse
f = lambda w: svm_loss_naive(w, X_dev, y_dev, 0.0)[0]
grad_numerical = grad_check_sparse(f, W, grad)

# do the gradient check once again with regularization turned on
# you didn't forget the regularization gradient did you?
loss, grad = svm_loss_naive(W, X_dev, y_dev, 5e1)
f = lambda w: svm_loss_naive(w, X_dev, y_dev, 5e1)[0]
grad_numerical = grad_check_sparse(f, W, grad)
```

numerical: 5.452293 analytic: 5.452293, relative error: 9.367385e-11
numerical: -19.565726 analytic: -19.565726, relative error: 9.166351e-12
numerical: -17.780532 analytic: -17.780532, relative error: 5.160872e-12
numerical: -28.739971 analytic: -28.739971, relative error: 2.145735e-11
numerical: -12.207504 analytic: -12.207504, relative error: 2.104780e-12
numerical: -3.642083 analytic: -3.642083, relative error: 9.603972e-12
numerical: -8.588827 analytic: -8.588827, relative error: 6.950765e-12
numerical: -10.077323 analytic: -10.077323, relative error: 1.018918e-11
numerical: -34.820867 analytic: -34.820867, relative error: 8.770658e-12
numerical: 7.105618 analytic: 7.105618, relative error: 2.207735e-11
numerical: -7.620453 analytic: -7.619434, relative error: 6.686054e-05
numerical: -27.968442 analytic: -27.963746, relative error: 8.395620e-05
numerical: -9.587827 analytic: -9.587417, relative error: 2.139413e-05
numerical: -19.252627 analytic: -19.253781, relative error: 2.997435e-05
numerical: 35.304743 analytic: 35.303370, relative error: 1.944763e-05
numerical: 42.305025 analytic: 42.308084, relative error: 3.615000e-05
numerical: -31.571840 analytic: -31.564771, relative error: 1.119598e-04
numerical: -8.161366 analytic: -8.160050, relative error: 8.063040e-05
numerical: -9.447753 analytic: -9.445924, relative error: 9.678954e-05
numerical: 10.964797 analytic: 10.966333, relative error: 7.002237e-05

Inline Question 1:

It is possible that once in a while a dimension in the gradcheck will not match exactly. What could such a discrepancy be caused by? Is it a reason for concern? What is a simple example in one dimension where a gradient check could fail? *Hint: the SVM loss function is not strictly speaking differentiable*

Your Answer: *SVM loss function is not differentiable at hinge loss. Since gradient is taking the derivative, the hinge loss $\max(0, 1-x)$ does not at certain points i.e when $x=1$. Similarly, the gradient will be different based on the direction. The discrepancy is not for reason of concern because it is caused by the differentiability of loss function.

In [11]:

```
# Next implement the function svm_loss_vectorized; for now only compute the loss
;
# we will implement the gradient in a moment.
tic = time.time()
loss_naive, grad_naive = svm_loss_naive(W, X_dev, y_dev, 0.000005)
toc = time.time()
print('Naive loss: %e computed in %fs' % (loss_naive, toc - tic))

from cs175.classifiers.linear_svm import svm_loss_vectorized
tic = time.time()
loss_vectorized, _ = svm_loss_vectorized(W, X_dev, y_dev, 0.000005)
toc = time.time()
print('Vectorized loss: %e computed in %fs' % (loss_vectorized, toc - tic))

# The losses should match but your vectorized implementation should be much faster.
print('difference: %f' % (loss_naive - loss_vectorized))
```

Naive loss: 8.975407e+00 computed in 0.065717s
Vectorized loss: 8.975407e+00 computed in 0.005323s
difference: -0.000000

In [12]:

```
# Complete the implementation of svm_loss_vectorized, and compute the gradient
# of the loss function in a vectorized way.

# The naive implementation and the vectorized implementation should match, but
# the vectorized version should still be much faster.
tic = time.time()
_, grad_naive = svm_loss_naive(W, X_dev, y_dev, 0.000005)
toc = time.time()
print('Naive loss and gradient: computed in %fs' % (toc - tic))

tic = time.time()
_, grad_vectorized = svm_loss_vectorized(W, X_dev, y_dev, 0.000005)
toc = time.time()
print('Vectorized loss and gradient: computed in %fs' % (toc - tic))

# The loss is a single number, so it is easy to compare the values computed
# by the two implementations. The gradient on the other hand is a matrix, so
# we use the Frobenius norm to compare them.
difference = np.linalg.norm(grad_naive - grad_vectorized, ord='fro')
print('difference: %f' % difference)
```

Naive loss and gradient: computed in 0.062188s
Vectorized loss and gradient: computed in 0.004839s
difference: 0.000000

Stochastic Gradient Descent

We now have vectorized and efficient expressions for the loss, the gradient and our gradient matches the numerical gradient. We are therefore ready to do SGD to minimize the loss.


In [13]:

```
# In the file linear_classifier.py, implement SGD in the function  
# LinearClassifier.train() and then run it with the code below.  
from cs175.classifiers import LinearSVM  
svm = LinearSVM()  
tic = time.time()  
loss_hist = svm.train(X_train, y_train, learning_rate=1e-7, reg=2.5e4,  
                      num_iters=1500, verbose=True)  
toc = time.time()  
print('That took %fs' % (toc - tic))
```

```
iteration 0 / 1500: loss 789.448019  
iteration 100 / 1500: loss 473.747724  
iteration 200 / 1500: loss 285.618708  
iteration 300 / 1500: loss 174.405367  
iteration 400 / 1500: loss 107.181009  
iteration 500 / 1500: loss 67.094431  
iteration 600 / 1500: loss 41.567173  
iteration 700 / 1500: loss 27.532363  
iteration 800 / 1500: loss 18.736417  
iteration 900 / 1500: loss 13.567887  
iteration 1000 / 1500: loss 9.557464  
iteration 1100 / 1500: loss 8.876452  
iteration 1200 / 1500: loss 7.179011  
iteration 1300 / 1500: loss 6.162728  
iteration 1400 / 1500: loss 6.228678  
That took 4.377493s
```

In [14]:

```
# A useful debugging strategy is to plot the loss as a function of
# iteration number:
plt.plot(loss_hist)
plt.xlabel('Iteration number')
plt.ylabel('Loss value')
plt.show()
```



In [15]:

```
# Write the LinearSVM.predict function and evaluate the performance on both the
# training and validation set
y_train_pred = svm.predict(X_train)
print('training accuracy: %f' % (np.mean(y_train == y_train_pred), ))
y_val_pred = svm.predict(X_val)
print('validation accuracy: %f' % (np.mean(y_val == y_val_pred), ))
```

```
training accuracy: 0.380694
validation accuracy: 0.370000
```

In [16]:

```
# Use the validation set to tune hyperparameters (regularization strength and
# learning rate). You should experiment with different ranges for the learning
# rates and regularization strengths; if you are careful you should be able to
# get a classification accuracy of about 0.4 on the validation set.
learning_rates = [1e-7, 5e-5]
regularization_strengths = [2.5e4, 5e4]

# results is dictionary mapping tuples of the form
# (learning_rate, regularization_strength) to tuples of the form
# (training_accuracy, validation_accuracy). The accuracy is simply the fraction
# of data points that are correctly classified.
results = {}
best_val = -1 # The highest validation accuracy that we have seen so far.
best_svm = None # The LinearSVM object that achieved the highest validation rate
```

```
#####
# TODO: #
# Write code that chooses the best hyperparameters by tuning on the validation #
# set. For each combination of hyperparameters, train a linear SVM on the #
# training set, compute its accuracy on the training and validation sets, and #
# store these numbers in the results dictionary. In addition, store the best #
# validation accuracy in best_val and the LinearSVM object that achieves this #
# accuracy in best_svm. #
# #
# Hint: You should use a small value for num_iters as you develop your #
# validation code so that the SVMs don't take much time to train; once you are #
# confident that your validation code works, you should rerun the validation #
# code with a larger value for num_iters. #
#####

for lr in learning_rates:
    for reg in regularization_strengths:
        svm=LinearSVM()
        svm.train(X_train, y_train, learning_rate=lr, reg=reg, num_iters=800)

        y_train_pred = svm.predict(X_train)
        y_val_pred=svm.predict(X_val)

        accuracy_train=np.mean(y_train==y_train_pred)
        accuracy_val=np.mean(y_val==y_val_pred)

        results[(lr, reg)] = (accuracy_train, accuracy_val)

        if accuracy_val > best_val:
            best_val = accuracy_val
            best_svm = svm

#####
#                                     END OF YOUR CODE #
#####

# Print out results.
for lr, reg in sorted(results):
    train_accuracy, val_accuracy = results[(lr, reg)]
    print('lr %e reg %e train accuracy: %f val accuracy: %f' % (
        lr, reg, train_accuracy, val_accuracy))

print('best validation accuracy achieved during cross-validation: %f' % best_val
)
```


```
lr 1.000000e-07 reg 2.500000e+04 train accuracy: 0.366510 val accuracy: 0.362000
lr 1.000000e-07 reg 5.000000e+04 train accuracy: 0.369898 val accuracy: 0.382000
lr 5.000000e-05 reg 2.500000e+04 train accuracy: 0.134755 val accuracy: 0.152000
lr 5.000000e-05 reg 5.000000e+04 train accuracy: 0.060898 val accuracy: 0.059000
best validation accuracy achieved during cross-validation: 0.382000
```

In [17]:

```
# Visualize the cross-validation results
import math
x_scatter = [math.log10(x[0]) for x in results]
y_scatter = [math.log10(x[1]) for x in results]

# plot training accuracy
marker_size = 100
colors = [results[x][0] for x in results]
plt.subplot(2, 1, 1)
plt.scatter(x_scatter, y_scatter, marker_size, c=colors)
plt.colorbar()
plt.xlabel('log learning rate')
plt.ylabel('log regularization strength')
plt.title('CIFAR-10 training accuracy')

# plot validation accuracy
colors = [results[x][1] for x in results] # default size of markers is 20
plt.subplot(2, 1, 2)
plt.scatter(x_scatter, y_scatter, marker_size, c=colors)
plt.colorbar()
plt.xlabel('log learning rate')
plt.ylabel('log regularization strength')
plt.title('CIFAR-10 validation accuracy')
plt.show()
```



In [18]:


```
# Evaluate the best svm on test set
y_test_pred = best_svm.predict(X_test)
test_accuracy = np.mean(y_test == y_test_pred)
print('linear SVM on raw pixels final test set accuracy: %f' % test_accuracy)
```

linear SVM on raw pixels final test set accuracy: 0.355000

In [19]:

```
# Visualize the learned weights for each class.
# Depending on your choice of learning rate and regularization strength, these may
# or may not be nice to look at.
w = best_svm.W[:-1,:] # strip out the bias
w = w.reshape(32, 32, 3, 10)
w_min, w_max = np.min(w), np.max(w)
classes = ['plane', 'car', 'bird', 'cat', 'deer', 'dog', 'frog', 'horse', 'ship', 'truck']
for i in range(10):
    plt.subplot(2, 5, i + 1)

    # Rescale the weights to be between 0 and 255
    wimg = 255.0 * (w[:, :, :, i].squeeze() - w_min) / (w_max - w_min)
    plt.imshow(wimg.astype('uint8'))
    plt.axis('off')
    plt.title(classes[i])
```



Inline question 2:

Describe what your visualized SVM weights look like, and offer a brief explanation for why they look the way that they do.

Your answer: Within a class there are different types of images for example in class car there are different types of car regarding make, model, color. Linear SVM generates the weight vector that takes the best generalizes all the image matrices within the class.

In []: