Administrasi Medika

CUSTOMER HOST: API JSON

***Rust** Version 1.0*

BUSINESS PROCESS FLOW

RE_PRINT_OUT

Gateway@AdMedika via JSON

Table of Contents

1 Introduction and Scope 3
1.1 General 3
1.2 Communication 3
1.3 Security 3
1.4 File Formats 4
1.5 Authentication 4
1.6 Example XML and JSON Request..... 5
1.7 Duplicate Checking 5
1.7 Expiration of request message 5
1.8 Benefits at a Glance 5

2 Web Service 5
2.1 API Address 5
2.2 Request 5
2.3 Response.....5
2.4 Example of complete JSON request and response 6

3 Available Service ID..... 6
3.1 HELLO_WORLD for testing purposes 7
3.2 RE_PRINT_OUT..... 8

4 Response Code 9

1. Introduction and Scope

1.1 General

Gateway@AdMedika is the global file transfer platform developed by PT. Administrasi Medika (AdMedika) that provides for bi-directional transfer of data files from a customer's host system to AdMedika's processing systems and vice versa in a secure manner. The document explains the Gateway@ AdMedika component that enables customer and explain the various connectivity options that our customer have for to establish the file transfer link with the server in a secure manner via internet for sending and receiving files. However, this will not cover all the technical details necessary to establish the Host to Host (H2H) connection. The idea of this guide is provide all necessary information in order to allow our customers to validate, if and how they can connect to Gateway@AdMeidka infrastructure.

In order to allow a centralized H2H connection and integration of the customer's request transaction files, our solution is based on a central H2H platform linked to all these request services.

There are seven main aspects to our solution

- Communication
- Security
- File Format
- Authentication
- Duplicate Checking
- Expiration of request message
- Benefits at a Glance

1.2 Communication

Customer may connect to Gateway@AdMedika using any of the following protocols

- https (JSON)

1.3 Security

In order to provide the highest possible standard of security, we have added state-of-the-art security features to our communication options to assure authentication, confidentiality (symmetric encryption) and integrity of the data transferred to Gateway@AdMedika.

Gateway@AdMedika expects customers to connect using SSL based protocol with client authentication enabled. This ensures that the channel is authenticated and also encrypted.

In addition to the SSL based encryptions for XML and JSON, Gateway@AdMedika supports the hashing SHA-256.

1.4 File Formats

In order to facilitate our customers' implementation of the desired H2H connection, the file format is XML/JSON supported by AdMedika in line with your requirements.

1.5 Authentication

XML/JSON document always has to contain information that will let XML or JSON API server to authenticate requesting user. This document will contain Customer ID and other information that will help server to accurately identify the user submitting request. Every server request to XML or JSON API has to contain the following authentication information:

- API's Secret word. Depending on a function, customer ID may be specified in various parts of XML/JSON document.
- AdMedika Customer ID.
- Authentication token, this parameter consists of hashed line of text, formed by the concatenation of API's Customer ID, secret word, UTC dateTime, Request ID and Service ID.

Creation of authentication token

You need to create authentication token with the following procedure:

1. Obtain by concatenation the following line:
    a. SHA256(**customerID**: SHA256(**securityword**):**Date** UTC in YYYYMMDDHHMMSS format: **requestID**: **serviceID)**
2. Get hash of above line by SHA256. For example:
    a. Customer ID – **MY_CUSTOMER_ID**
    b. security word - **MySecurityWordHere**
    c. date UTC – **20171108181756** (YYYYMMDDHHMMSS 24h format)
    d. Request ID – **51515** (5digits. It could be your unique Request ID)
    e. Service ID - **HELLO_WORLD**
3. Concatenation of parameters:
    a. SHA256(**MY_CUSTOMER_ID**:SHA256(**MySecurityWordHere**):**20171108181756**:**51515**:**HELLO_WORLD)**
    b. Hash SHA256 for above created line:
    0f58fb94999566130f8b4cce6408473968403684fc6db24ac142b6a33d908bfe

1.7 Duplicate Checking

Gateway@AdMedika server has the capability to check for duplicate request.

1.8 Expiration of request message

The request message will expired in 60 seconds. Need to create new authentication token for every request to avoid just copying the request message and made changes to it.

1.8 Benefits at a Glance

AdMedika comprehensive H2H solution enables our customers to: Transmit a XML or JSON file formats without any conversion requirements on the customer side. The files are directly exported from the customer system and transmitted to AdMedika in JSON format.

Ensure a maximum level of security through a web-services communication covering confidentiality, integrity and authentication of transaction details.

Obtain full account information for direct integration into other systems for automated.

2 Web Service

This following description provides Web Service detail of Gateway@AdMedika system.

2.1 API Address:

- ***Prod:*** ***https://adcpslite.admedika.co.id:553/admedgateway/services/customerhost***
- ***Dev:*** ***https://adcpslite.admedika.co.id:553/admedgateway/services/customerhost_dev***

2.2 Request:

Key	Data Type	Value
tokenAuth	String	SHA256(**MY_CUSTOMER_ID**:SHA256(**MySecurityWordHere**): **20171108181756**: **51515**: **HELLO_WORLD**)
serviceID	String	Depends on service. Refer to 3 Service ID
customerID	String(7)	Customer ID
requestID	String(5)	Must be unique each request
txnData	String	Depends on service (Refer to 3 Service ID)
txnRequestDateTime	String(14)	yyyyMMddHHmmss

2.3 Response:

Key	Data Type	Value
referenceID	String(20)	Reference ID
statusCode	String(3)	00 : Success, XXX : fail (See response code)
statusMsg	String	Depends on statusCode refer to 4.0 Response code
format	String(5)	API use format message

txnData	String	Depends on service
txnResponseDateTime	String(14)	yyyyMMddHHmmss

2.3 Example of COMPLETE JSON **HELLO_WORLD** request and response.

HELLO_WORLD request.


```
{
   "input": {
      "tokenAuth": "0f58fb94999566130f8b4cce64084739684036 84fc6db24ac142b6a33d908bfe",
      "serviceID": "HELLO_WORLD",
      "customerID": "MY_CUSTOMER_ID",
      "requestID": "51515",
      "txnData": {
         "helloRequest": {
            "customerID": "MY_CUSTOMER_ID"
         }
      },
      "txnRequestDateTime": "20171108181756"
   }
}
```


HELLO_WORLD response.


```
{
   "output": {
      "referenceID": "586",
      "statusCode": "00",
      "statusMsg": "Successful ",
      "format": "JSON",
      "txnData": {
         "helloResponse": {
            "hello": {
               "message": "Hello there JAMINAN KESEHATAN (ADMEDKA) and Welcome to Gateway@AdMedika",
               "apiName": "Gateway@AdMedika (Powered by Rustlang)",
               "apiVersion": "Rust 1.0.1"
            }
         }
      },
      "txnResponseDateTime": "20171121145633"
   }
}
```

3 Service ID

3.1 Hello World: *For client development purposes*

Request Format:

Service ID: HELLO_WORLD

txnData:
{"helloRequest":{"customerID":"MY_CUSTOMER_ID"}}

Field	Data Type	Value
customerID	String(7)	Customer ID (given by AdMedika)

Response Format:

Success

txnData:


```
{
  "helloResponse": {
    "hello": {
      "message": "Hello there JAMINAN KESEHATAN (ADMEDKA) and Welcome to Gateway@AdMedika",
      "apiName": "Gateway@AdMedika",
      "apiVersion": "Rusty 1.0.1"
    }
  }
}
```


Field	Data Type	Value
message	string	Welcome and its successful
apiName	string	Api Name
apiVersion	string	Api Version

Failed

txnData: Nothing to show here and no validation on txnData, If error please refer to **4.0 Response Code**

Option

R = required / mandatory
O = Optional

3.2 RE_PRINT_OUT - To Re-Print the LOA, LOC or the LOR

Request Format:

Service ID: RE_PRINT_OUT

txnData:

```
{
  "rePrintOutRequest": {
    "rePrintOut": {
      "clID": "150XXXXXX",
      "rePrintType": "D"
    }
  }
}
```

txnData Format

Field	Data Type	Opt	Value
clID	String	R	Claims id
rePrintOut	String(1)	R	Default value for : **E** = Letter of Authorization (LOA) **D** = Letter of Confirmation (LOC) **X** = Letter of Rejection (LOR)

Response Format:

Success

txnData:

```
{
  "rePrintOutResponse": {
    "rePrintOut": {
      "printOut": "PENGESAHAN & TAGIHAN\r\nDUMMY Insurance Indonesia\r\nPT TESLA TRANSPORTASI INDONESIA
TBK\r\nDIAG:I10 IZIN SAKIT:0\r\nB. ADMIN                    15,000.00\r\nB.DR.SPES
125,000.00\r\nB.DR.UMUM                       0.00\r\nDIAGNOSTIK                55,000.00\r\nB.OBAT
2,437,900.00\r\nFISIOTHERAPI                    0.00\r\nKONST+OBAT                     0.00\r\nIMUNISASI
0.00\r\n**********************************\r\nJUM.BIAYA :            2,892,900.00\r\nJUM.DIBYR ASS:
2,632,900.00\r\nDIBYR PASIEN:            260,000.00\r\n**********************************\r\nEKSES TAGIH DI
TEMPAT TERMASUK\r\nNON MEDIS DAN PENGECUALIAN POLIS\r\nEFEKTIF PER TANGGAL 1 AGUSTUS 2025\r\nPELAYANAN KEPADA
PESERTA MENGGUNAKAN\r\nTARIF LAYANAN SESUAI KETENTUAN YANG\r\nTELAH DISEPAKATI BERSAMA ADMEDIKA\r\n"
    }
  }
}
```

Failed

txnData:

```
{
  "rePrintOutResponse": {
    "rePrintOut": {
      "errorCode": 1997,
      "errorDesc": "Invalid rePrintType [S]. Default value [E = ELIGIBILITY (LOA)] [D = DISCHARGE (LOC)] [X =
REJECT (LOR)]"
    }
  }
}
```

Field	Data Type	Value
errorCode	String(4)	Refer to response code (4.0)
errorDesc	String(255)	Error description

4.0 Response Code

Status Code			tnxData Validation	
Code	**Description**		**Code**	**Description**
00	Successful		1810	Not Match
500	Request messages length was too short		~~1809~~	Amount total approved of HEADER not equal to details
501	Syntax error, malformed JSON		1811	corporateID not found.
502	Unexpected control character found		1812	Member not found
503	Undefined json key		1813	provider terminal not found!
601	Authentication code was empty		1814	Admission date is not a valid date (format should be DDMMYYYY)
602	error in processing request (invalid authentication code)		1815	Discharge date is not a valid date (format should be DDMMYYYY)
603	Customer is not registered		1816	Admission and Discharge cannot be greater than today date
604	Customer not active		1817	Admission date cannot be greater than Discharge date
605	Invalid customer description		1818	Invalid claimsType. Valid claimsType are [R=REIMBURSEMENT | M=NORMAL CLAIMS]
611	Security word's locked		1819	Plan code was not found
612	Request message is expired		1820	Coverage code is invalid
615	Service ID was empty		1821	No plan policy date for this admissionDate
616	Invalid service ID (unknown service)		1829	not a valid date (format should be DDMMYYYY)
617	txnData is empty			
618	XML is Invalid		1830	diagnosisCodeList was empty
910	error on txnData. see the description		~~1831~~	icd10 in diagnosisCodeList was not found!
910	No response data found		~~1832~~	Icd is pre-existing disease
999	Error, see the description		~~1833~~	Icd is exclusion
			1834	admedikaClaimsID must be a number
			1835	modeNo 1 (New Claims) : payorClaimsID cannot be empty. payorClaimsID is your claims transaction reference id and it must be a unique for each claims
			1836	modeNo 1 (New Claims) : ClaimsID is already in the system. To avoid duplicate transaction. Please check the payorClaimsID. Or use modeNo for Claims adjustment instead
			1837	Member has a pending claims transaction, close this pending before you can add more claims to this member.
			1838	Claims ID not found. Please check the payorClaimsID.
			1839	benefitCode/claimsID not found
			1840	Not found! (see addition description)
			1841	terminalID cannot be found
			1842	Inpatient Claim assessment is still on progress
			1843	No final bill statement found!
			1844	No daily claims monitoring details found!
			1822	Member not active
			1823	Policy expired
			1824	Policy suspended
			1871	Invalid Mode number. unknown modeNo
			1880	eDocs Upload Error
			1990	Host no response. Please inform AdMedika
			1997	Invalid (See additional description given)
			1998	Rejected (See addition info on the response msg)
			1999	Cannot be empty (See addition info on the response msg)