MAHATMA GANDHI UNIVERSITY, KOTTAYAM

MGU-UGP (Honours)/ MGU-BBA (Honours)/ MGU-BCA (Honours) REGULAR EXAMINATION October 2026

Fifth SEMESTER

Skill Enhancement Course (SEC) - MG5SECECT300, MG5SECECC300 - RESPONSIVE WEB DESIGN AND FRONTEND DEVELOPMENT

(2024 ADMISSION ONWARDS)

PART A

1. [c] [U][CO1]
2. [d] <td> [K][CO1]
3. [d] <fieldset> [K][CO1]
4. [d] submit [K][CO1]
5. [c] vw [K][CO1]
6. [b] :hover [U][CO1]
7. [b] href [K][CO1]
8. [b] Cloud hosting [U][CO1]
9. [a] Hyper Text Markup Language [U][CO1]
10. [b] Shared hosting [U][CO1]
11. [a] [K][CO1]
12. [a] <meta> [U][CO1]
13. [c] value() [U][CO2]
14. [a] email [U][CO2]
15. [b] To simplify JavaScript programming [K][CO2]
16. [c] $("#myForm") [K][CO2]
17. [a] attr() [U][CO2]
18. [a] jquery.js [U][CO2]
19. [b] click [K][CO2]
20. [a] after() [U] [CO2]

21. [b] Animation and effects [K][CO2]

22. [b] . [U][CO2]

23. [d] remove() [U][CO2]

24. [a] submit() [U][CO2]

25. Give mark if attempted [U][CO4]

26. [b] .nav-link [U][CO4]

27. [b] It provides ready-made and responsive navbar classes and components [U][CO3]

28. (c) Ready-made styles and components [K][CO3]

29. (a) Bootstrap provides predefined button styles. [U][CO4]

30. (c) Container → Row → Column [K][CO3]

31. (b) .text-end [U][CO4]

32. (a) 6 out of 12 columns [U][CO4]

33. (a) CDN [U][CO3]

34. (d) Designing responsive page layouts [U][CO3]

35. (c) Bootstrap provides responsive layout tools and ready-made components. [U][CO3]

PART B

Answer any three questions. Each question carries 5 marks.

36. Inline CSS is written directly inside an HTML element using the style attribute.
Example:
HTML
Wrap linesCopy codePreview
Hello World
Internal CSS is written inside the <style> tag within the <head> section of an HTML document.
Example:
HTML
Wrap linesCopy codePreview

```
<head>
  <style>
    p { color: blue; }
  </style>
</head>
```

External CSS is written in a separate .css file and linked to the HTML document using the <link> tag.
Example:
HTML
Wrap linesCopy codePreview
<link rel="stylesheet" href="style.css">
Inline CSS styles a single element, internal CSS styles elements within one HTML page, and external CSS can style multiple web pages. Inline CSS is useful for quick styling, internal CSS is suitable for single-page styling, and external CSS improves reusability and maintainability. [An][CO1]

37. HTTP stands for Hyper Text Transfer Protocol. It is used for communication between a web browser and a web server. The browser sends an HTTP request to the web server to access a webpage or resource. The web server processes the request and sends an HTTP response containing the requested data or a status code. HTTP transfers web content such as HTML pages, images, CSS files, and JavaScript files. HTTP is stateless, meaning each request is handled independently. HTTPS is the secure version of HTTP that uses encryption to protect data. [U][CO1]

38. Syntax: The basic syntax of jQuery is:
$(selector).action();
$ Symbol: The $ symbol is used to access the jQuery library.
Selector: It selects the HTML element to which the action is applied.
Action: It performs an operation such as hiding, showing, or changing an element.
Example:
HTML
Wrap linesCopy codePreview

```
<p id="demo">Hello World!</p>
<button id="btn">Click Me</button>

<script>
$(document).ready(function(){
  $("#btn").click(function(){
    $("#demo").hide();
  });
});
</script>
```

[K][CO2]

39. parent(): Selects the immediate parent element of the selected element.
parents(): Selects all ancestor elements of the selected element.
children(): Selects all direct child elements of the selected element.
find(): Selects all matching descendant elements at any level inside the selected element.
Example:
$("p").parent() – Selects the immediate parent of <p>.
$("p").parents() – Selects all ancestors of <p>.
$("div").children() – Selects direct children of .
$("div").find("p") – Selects all descendant <p> elements inside . [U][CO2]

40. Bootstrap forms are used to collect user information through input fields, buttons, checkboxes, and other controls. Bootstrap provides classes like .form-control for text fields and .form-select for dropdown lists. The <label> element is used to identify form fields clearly. Bootstrap forms automatically adapt to different screen sizes using its grid system and responsive classes. Bootstrap provides built-in validation styles and classes to create attractive, user-friendly forms. [U][CO3]