QP CODE: 25900320

DISCIPLINE SPECIFIC ELECTIVE (DSE) - MG3DSEBCA202 – WEB PROGRAMMING - I

ANSWER KEY- OCTOBER 2025 (2024 ADMISSION ONWARDS)

Part A - Answer all questions. Each question carries 2 marks

1. **Discuss the term URL with an example**. [U] / [CO1]

   URL (Uniform Resource Locator): Address used to locate a resource on the internet. [1 mark]

   Example: https://www.example.com/page.php [1 mark]

2. **Explain how array_shift() differs from array_pop().** [U] / [CO1]

   array_shift(): Removes and returns first element, reindexes numeric keys. [1 mark]

   array_pop(): Removes and returns last element, no reindexing needed. [1 mark]

   Difference in position & reindexing.

3. **Explain the working of a do while loop with a sample code.** [A] / [CO2]

```
do {
  body of the loop
} while(condition);
```

   Executes at least once.

   Explain with an example give 2 marks. Syntax only gives 1 mark

4. **What are the key components of XAMPP?** [K] / [CO1]

   XAMPP Components: Apache, MySQL, PHP, Perl. Brief role of each. (0.5*4 =2)

5. **Write a PHP code to loop through an associative array using foreach.** [A] / [CO2]

```
<?php
$arr = ['a'=>1, 'b'=>2];
foreach ($arr as $k => $v) {
 echo "$k: $v"; }
?>
```

   Correctly declares an associative array and uses the foreach($array as $key => $value) syntax to iterate and display/use the elements give 2 marks.

6. **Write a PHP program to check if a number is positive, negative, or zero using if-else statements and explain the code.** [A] / [CO2]

```
<?php
$num = 5;
if($num > 0) echo "Positive";
else if($num < 0) echo "Negative";
else echo "Zero";
?>
```

   Correct code [1 mark], Explanation [1 mark]

7. **What is the difference between ++$x and $x++ in PHP?** [A] / [CO2]

   ++$x: Pre-increment → increment then use

   $x++: Post-increment → use then increment

Example: $x=5; echo ++$x; //6, echo $x++; //5

Definition [1 mark] , Example [1 mark]

8. **Write a PHP code to access a global variable inside a function using $_GLOBALS.** [A] / [CO2]

```
<?php
$x = 10;
function test() { echo $GLOBALS['x']; }
test(); //10
?>
```

Code correctly defines a global variable, a function, and inside the function, uses $_GLOBALS['varname'] to access and use the variable give 2 marks

9. **Write the syntax of mysqli_query() and briefly explain its parameters.** [A] / [CO2, CO3]

Syntax: mysqli_query($conn, $sql)
Parameters:
• $conn: Connection object
• $sql: SQL query string
Syntax 1 mark, Parameters explained 1 mark

10. **Why is it considered good practice to close a MySQL connection in PHP?** [A] / [CO2, CO3]

Frees server resources, prevents memory leaks, improves performance, security (prevents connection hijacking). Any two valid reason give 2 marks

Part B: Short Answer Questions (3 x 5 = 15 Marks)

Answer any 3 questions. Answers require more detail and structure.

11. **Illustrate all the compound datatypes of php with a sample code.** [U] / [CO1]

1. Array – indexed/assoc/multidimensional

2. Object – class instance

Lists all compound datatypes (array, object) (2 marks); Sample code for each (3 marks, 1.5 each if both code and output explained)

12. **Explain variable and different rules for PHP variable with example.** [U] / [CO1]

Variable: Named memory location.
Rules:
• Starts with $
• Letter or underscore
• No spaces, case-sensitive
• Valid: $name, $_age
• Invalid: $2var, $my var
Examples.
Definition 1 mark , any 4 rules 2 marks, Example 2 marks

13. **State the difference between echo and print with example.** [K] / [CO1]

echo: Language construct, faster, multiple params, no return.
print: Function, returns 1, single argument.
Example:
echo "A","B"; → AB
print "A"."B"; → AB Differences 3 marks, Example 2 marks

14. **Write a PHP script to perform the operations Delete and Select on a students table.** [A] / [CO2, CO3]

Database Connection (1 mark): *mysqli_connect()*

DELETE Operation (2 marks): *SQL DELETE query (e.g., with a WHERE clause) executed using mysqli_query().*

SELECT Operation (2 marks): *SQL SELECT query executed, and results are fetched (e.g., using mysqli_fetch_assoc()) and displayed in a loop.*

15. **List and explain any four file inclusion functions in PHP with their purpose.** [K] / [CO2]

Key functions are:

1. include(): Includes and evaluates a file, produces a warning on failure.
2. require(): Identical to include(), but produces a fatal error on failure, halting the script.
3. include_once(): Ensures the file is included only once, avoiding redeclaration errors.
4. require_once(): Ensures the file is required only once, avoiding redeclaration errors.

Give 1.25 marks for correctly naming and explaining the purpose of each function.