File Edit View Run Kernel LaTeX Tabs Settings Help

CPU Usage | Disk Usage | Kernels

Anaconda Toolbox v4.54.0

Tools for easy setup and effortless collaboration.
Create, share, sync work anywhere.

Projects

Manage Projects

Code Snippets

Manage Code Snippets

AI Assistant

Chat-based Python Help

Untitled.ipynb | python basic programs.ipynb

Code | Notebook | anaconda-2022.05-py39

[20]:
```
def trap(height):
    left, right = 0, len(height) - 1
    left_max = right_max = 0
    water = 0

    while left < right:
        if height[left] < height[right]:
            if height[left] >= left_max:
                left_max = height[left]
            else:
                water += left_max - height[left]
            left += 1
        else:
            if height[right] >= right_max:
                right_max = height[right]
            else:
                water += right_max - height[right]
            right -= 1

    return water


arr = [0,1,0,2,1,0,1,3,2,1,2,1]
print(trap(arr))
```

```
6
```

[ ]:

File Edit View Run Kernel LaTeX Tabs Settings Help

CPU Usage | Disk Usage | Kerne

Anaconda Toolbox v4.54.0

Projects

Manage Projects

Code Snippets

Manage Code Snippets

AI Assistant

Chat-based Python Help

Untitled.ipynb | python basic programs.ipynb

Code | Notebook | anaconda-2022.05-py39

[6]:
```
def two_sum(nums, target):
    num_map = {}

    for i, num in enumerate(nums):
        complement = target - num

        if complement in num_map:
            return [num_map[complement], i]

        num_map[num] = i

    return []


arr = [2, 7, 11, 15]
target = 9

result = two_sum(arr, target)
print(result)
```

```
[0, 1]
```

[7]:
```
def length_of_longest_substring(s):
    char_set = set()
    left = 0
    max_length = 0

    for right in range(len(s)):
        while s[right] in char_set:
            char_set.remove(s[left])
            left += 1

        char_set.add(s[right])
        max_length = max(max_length, right - left + 1)
```

Simple | 2 | anaconda-2022.05-py39 | Idle | Submit a Request | Help | Mode: Edit | Ln 1, Col 1

File Edit View Run Kernel LaTeX Tabs Settings Help

CPU Usage | Disk Usage | Kern

Anaconda Toolbox v4.54.0

Tools for easy setup and effortless collaboration.
Create, share, sync work anywhere.

Projects

Manage Projects

Code Snippets

Manage Code Snippets

AI Assistant

Chat-based Python Help

Untitled.ipynb | python basic programs.ipynb

Code | Notebook | anaconda-2022.05-py39

```
        char_set.add(s[right])
        max_length = max(max_length, right - left + 1)

    return max_length


s = "abcabcbb"
print(length_of_longest_substring(s))
```

```
3
```

[8]:
```
def merge_intervals(intervals):

    intervals.sort(key=lambda x: x[0])

    merged = []

    for interval in intervals:

        if not merged or merged[-1][1] < interval[0]:
            merged.append(interval)
        else:

            merged[-1][1] = max(merged[-1][1], interval[1])

    return merged


intervals = [[1,3],[2,6],[8,10]]
print(merge_intervals(intervals))
```

Simple | 2 | anaconda-2022.05-py39 | Idle

Submit a Request | Help | Mode: Edit | Ln 1, Col 1

File Edit View Run Kernel LaTeX Tabs Settings Help

CPU Usage | Disk Usage | Kerne

Anaconda Toolbox v4.54.0

Tools for easy setup and effortless collaboration.
Create, share, sync work anywhere.

Projects

Manage Projects

Code Snippets

Manage Code Snippets

AI Assistant

Chat-based Python Help

Untitled.ipynb | python basic programs.ipynb

Code | Notebook | anaconda-2022.05-py39

```
[[1, 6], [8, 10]]
```

[9]:
```
def product_except_self(nums):
    n = len(nums)
    result = [1] * n


    prefix = 1
    for i in range(n):
        result[i] = prefix
        prefix *= nums[i]


    suffix = 1
    for i in range(n - 1, -1, -1):
        result[i] *= suffix
        suffix *= nums[i]

    return result



nums = [1, 2, 3, 4]
print(product_except_self(nums))
```

```
[24, 12, 8, 6]
```

[10]:
```
def is_valid(s):
    stack = []
    mapping = {
        ')': '(',
        '}': '{',
        ']': '['
```

Simple | 2 | anaconda-2022.05-py39 | Idle | Submit a Request | Help | Mode: Edit | Ln 1, Col 1

File Edit View Run Kernel LaTeX Tabs Settings Help

CPU Usage | Disk Usage | Kernels

Anaconda Toolbox v4.54.0

Tools for easy setup and effortless collaboration.
Create, share, sync work anywhere.

Projects

Manage Projects

Code Snippets

Manage Code Snippets

AI Assistant

Chat-based Python Help

Untitled.ipynb | python basic programs.ipynb

Code | Notebook | anaconda-2022.05-py39

```
    for char in s:
        if char in mapping:
            top = stack.pop() if stack else '#'
            if mapping[char] != top:
                return False
        else:
            stack.append(char)

    return len(stack) == 0



s = "({[]})"
print(is_valid(s))
```

```
True
```

[11]:
```
import heapq

def find_kth_largest(nums, k):
    heap = []

    for num in nums:
        heapq.heappush(heap, num)

        if len(heap) > k:
            heapq.heappop(heap)

    return heap[0]



nums = [3,2,1,5,6,4]
```

Simple | 2 | anaconda-2022.05-py39 | Idle

Submit a Request | Help | Mode: Edit | Ln 1, Col 1

File Edit View Run Kernel LaTeX Tabs Settings Help

CPU Usage | Disk Usage | Kerne

Anaconda Toolbox v4.54.0

Tools for easy setup and effortless collaboration.
Create, share, sync work anywhere.

Projects

Manage Projects

Code Snippets

Manage Code Snippets

AI Assistant

Chat-based Python Help

Untitled.ipynb | python basic programs.ipynb

Code | Notebook | anaconda-2022.05-py39

```
            platforms -= 1
            j += 1

    return max_platforms



arr = [900, 940, 950, 1100, 1500, 1800]
dep = [910, 1200, 1120, 1130, 1900, 2000]

print(min_platforms(arr, dep))
```

```
3
```

[16]:

```
class ListNode:
    def __init__(self, val=0, next=None):
        self.val = val
        self.next = next


def has_cycle(head):
    slow = head
    fast = head

    while fast and fast.next:
        slow = slow.next          # moves 1 step
        fast = fast.next.next     # moves 2 steps

        if slow == fast:
            return True

    return False
```

Simple | 2 | anaconda-2022.05-py39 | Idle | Submit a Request | Help | Mode: Edit | Ln 1, Col 1

File Edit View Run Kernel LaTeX Tabs Settings Help

CPU Usage | Disk Usage | Kerne

Anaconda Toolbox v4.54.0

Tools for easy setup and effortless collaboration.
Create, share, sync work anywhere.

Projects

Manage Projects

Code Snippets

Manage Code Snippets

AI Assistant

Chat-based Python Help

Untitled.ipynb | python basic programs.ipynb

Code | Notebook | anaconda-2022.05-py39

[17]:
```
import heapq
from collections import Counter

def top_k_frequent(nums, k):
    freq = Counter(nums)

    heap = []


    for num, count in freq.items():
        heapq.heappush(heap, (count, num))

        if len(heap) > k:
            heapq.heappop(heap)


    return [num for count, num in heap]



nums = [1,1,1,2,2,3]
k = 2
print(top_k_frequent(nums, k))
```

```
[2, 1]
```

[18]:
```
def word_break(s, wordDict):
    word_set = set(wordDict)
    n = len(s)

    dp = [False] * (n + 1)
    dp[0] = True
```

Simple | 2 | anaconda-2022.05-py39 | Idle | Submit a Request | Help | Mode: Edit | Ln 1, Col 1

File Edit View Run Kernel LaTeX Tabs Settings Help

CPU Usage | Disk Usage | Kernels

Anaconda Toolbox v4.54.0

Tools for easy setup and effortless collaboration.
Create, share, sync work anywhere.

Projects

Manage Projects

Code Snippets

Manage Code Snippets

AI Assistant

Chat-based Python Help

Untitled.ipynb | python basic programs.ipynt

Code | Notebook | anaconda-2022.05-py39

```
    for i in range(1, n + 1):
        for j in range(i):
            if dp[j] and s[j:i] in word_set:
                dp[i] = True
                break

    return dp[n]



s = "applepenapple"
wordDict = ["apple", "pen"]
print(word_break(s, wordDict))
```

```
True
```

[19]:
```
def longest_palindrome(s):
    if not s:
        return ""

    start = end = 0

    def expand(l, r):
        while l >= 0 and r < len(s) and s[l] == s[r]:
            l -= 1
            r += 1
        return l + 1, r - 1

    for i in range(len(s)):

        l1, r1 = expand(i, i)
```

Simple | 2 | anaconda-2022.05-py39 | Idle

Submit a Request | Help | Mode: Edit | Ln 1, Col 1

File Edit View Run Kernel LaTeX Tabs Settings Help

CPU Usage | Disk Usage | Kern

Anaconda Toolbox v4.54.0

Projects

Manage Projects

Code Snippets

Manage Code Snippets

AI Assistant

Chat-based Python Help

Untitled.ipynb | python basic programs.ipynb

Code | Notebook | anaconda-2022.05-py39

```
k = 2
print(find_kth_largest(nums, k))
```

```
5
```

[12]:
```
def search(nums, target):
    left, right = 0, len(nums) - 1

    while left <= right:
        mid = (left + right) // 2

        if nums[mid] == target:
            return mid


        if nums[left] <= nums[mid]:
            if nums[left] <= target < nums[mid]:
                right = mid - 1
            else:
                left = mid + 1

        else:
            if nums[mid] < target <= nums[right]:
                left = mid + 1
            else:
                right = mid - 1

    return -1



nums = [4,5,6,7,0,1,2]
target = 0
print(search(nums, target))
```

Simple | 2 | anaconda-2022.05-py39 | Idle

Submit a Request | Help | Mode: Edit | Ln 1, Col 1

File Edit View Run Kernel LaTeX Tabs Settings Help

CPU Usage | Disk Usage | Kerne

Anaconda Toolbox v4.54.0

Projects

Manage Projects

Code Snippets

Manage Code Snippets

AI Assistant

Chat-based Python Help

Untitled.ipynb | python basic programs.ipynb

Code | Notebook | anaconda-2022.05-py39

```
4
```

[13]:
```python
from collections import defaultdict

def group_anagrams(strs):
    anagrams = defaultdict(list)

    for word in strs:

        key = ''.join(sorted(word))
        anagrams[key].append(word)

    return list(anagrams.values())



words = ["eat","tea","tan","ate","nat","bat"]
print(group_anagrams(words))
```

```
[['eat', 'tea', 'ate'], ['tan', 'nat'], ['bat']]
```

[14]:
```python
from collections import deque

def max_sliding_window(nums, k):
    dq = deque()
    result = []

    for i in range(len(nums)):

        while dq and dq[0] < i - k + 1:
            dq.popleft()
```

Simple | anaconda-2022.05-py39 | Idle

File Edit View Run Kernel LaTeX Tabs Settings Help

CPU Usage | Disk Usage | Kerne

Anaconda Toolbox v4.54.0

Tools for easy setup and effortless collaboration.
Create, share, sync work anywhere.

Projects

Manage Projects

Code Snippets

Manage Code Snippets

AI Assistant

Chat-based Python Help

Untitled.ipynb | python basic programs.ipynb

Code | Notebook | anaconda-2022.05-py39

```
        while dq and nums[dq[-1]] < nums[i]:
            dq.pop()

        dq.append(i)


        if i >= k - 1:
            result.append(nums[dq[0]])

    return result



nums = [1,3,-1,-3,5,3,6,7]
k = 3
print(max_sliding_window(nums, k))
```

```
[3, 3, 5, 5, 6, 7]
```

[15]:
```
def min_platforms(arr, dep):
    n = len(arr)


    arr.sort()
    dep.sort()

    i = j = 0
    platforms = max_platforms = 0

    while i < n and j < n:

        if arr[i] <= dep[j]:
            platforms += 1
```

Simple | 2 | anaconda-2022.05-py39 | Idle | Submit a Request | Help | Mode: Edit | Ln 1, Col 1