Equality Donation Distribution Model using Penalty function method

Worameth Chinchuthakun*, Athasit Surarerks and Laokhwan Ngamprasit Mahidol Wittayanusorn School, Nakhon Pathom, Thailand *email hw.55.m.woramet@gmail.com



Abstract

When an emergency incident happens, it is literally difficult to maintain fair distribution of donations. To improve efficiency of distribution, an optimization model for equality donation distribution is established. The model's objective is to find an optimal strategy to distribute donations. Constraints of the model include demand of victims, quality and quantity of donations in multi-category, and structure of the disaster area. Transportation route for each pair of nodes is the shortest path. Penalty function method was applied to transform the model into a simpler problem,

and then greedy algorithm was applied. Algorithm's time complexity is $O\left(T\left(\beta\epsilon + (C+N)\left(\log(C+N) + |V|\left(\epsilon + \alpha + \frac{1}{C+N}\right)\right)\right)\right)$ where C, N,

|V| and T are number of vehicle, number of donations, number of victims, and time interval of the incident, respectively. The experiment result shows that the algorithm can distribute donations while maintain equality.

- To establish an optimization model represent equality donation distribution problem
- To develop an efficient algorithm for distribute donation equally

Conclusion and Further Development

According to the result from 8,168 test cases, mean, median, and mode of error from optimal solution and model solution is 9.06%, 5.40%, and 0.00%, respectively. Error from optimal solution and model solution resembles exponential distribution. Thus, the algorithm can distribute donations while maintain equality.


For further development, there are 2 important things to develop,

• Adjust function f to decrease error, on the other word, develop function $h: \mathbb{R}_0^+ \to \mathbb{R} - \{0\}$ such that

$$f_{u}(t, y, \bar{l}) = \frac{K^{2} - \max^{2}(0, K - b_{y})}{h(l_{y})}$$

where $K = A_{u}(t, y, \overline{I})$


 Test algorithm with test cases consist of dynamic graph and nonpolynomial penalty demand function



Error of algorithm is calculated by percentage error of objective function (δ)

$$\delta = \left(\frac{P_{\text{model}}(t) - P_{\text{global}}(t)}{P_{\text{reference}}(t) - P_{\text{global}}(t)}\right) \times 100\%$$

According to 8,168 generated test cases, & values are shown below



[1] Chunquanq, C., Xiaoyu, S., Lijie, W., Bo, G. (2010). 2010 International Conference on Logistics Systems and Intelligent Management. A Multi-category Emergency Goods Distribution Model and Its Algorithm, 1490-1494.

[2] Demetrescut, C., Italiano, G. F. (2006). Fully dynamic all pairs shortest paths with real edge weights. Journal of Computer and System Sciences, 813-837.

[3] Impact Forecasting. (2012). 2011 Thailand Floods Event Recap Report. [Online]. Available http://docplayer.net/601894-2011-thailand-floods-event-recap-report-impactforecasting-march-2012.html

[4] King, V. (1999). Fully dynamic algorithms for maintaining all-pairs shortest paths and transitive closure in digraphs. Foundations of Computer Science, 1999. 40th Annual Symposium on. Institute of Electrical and Electronics Engineers.

[5] Nijenhui, A., Wilf, H. (1975). A Method and Two Algorithms on the Theory of Partitions. Journal of Combinatorial Theory, 219-222.























