In [2]:
```
import qiskit
```

In [3]:
```
qiskit.__version__
```

Out[3]:
```
'1.4.2'
```

In [4]:
```
token = "MK9bZuASn2QEw3VvroU7qg3AVjaRfq07O4U6qsJwPZ5F"
```

In [5]:
```
from qiskit_ibm_runtime import QiskitRuntimeService

service = QiskitRuntimeService.save_account(
    channel="ibm_cloud",    # or "ibm_quantum"
    token=token,            # IBM Cloud API key
    instance="instance1",       # <-- this should be your *CRN* or instance name
    name="default",      # optional
    set_as_default=True,
    overwrite=True
)
```

In [6]:
```
service = QiskitRuntimeService()
print(service.backends())
```

```
[<IBMBackend('ibm_brisbane')>, <IBMBackend('ibm_torino')>]
```

In [7]:
```
service.backends(simulator=False, operational=True, min_num_qubits=5)
```

Out[7]:
```
[<IBMBackend('ibm_brisbane')>, <IBMBackend('ibm_torino')>]
```

In [8]:
```
service.least_busy(operational=True, min_num_qubits=5)
```

Out[8]:
```
<IBMBackend('ibm_torino')>
```

In [9]:
```
backend = service.backend("ibm_brisbane")

print(
    f"Name: {backend.name}\n"
    f"Version: {backend.version}\n"
    f"No. of qubits: {backend.num_qubits}\n"
)
```

```
Name: ibm_brisbane
Version: 2
No. of qubits: 127
```