

# Quality & Features

---

Dr. Tushar Sandhan

# What is the need

---

- Quantitative assessment
  - performance evaluation of image processing algorithms
    - e.g. denoising, compression
- Quantitative achievement
  - performance improvement via optimization based methods
    - e.g. enhance images to minimize MSE or improve PSNR



# What is the need

---

- Quantitative assessment
  - performance evaluation of image processing algorithms
    - e.g. denoising, compression
- Quantitative achievement
  - performance improvement via optimization based methods
    - e.g. enhance images to minimize MSE or improve PSNR



# PSNR

---

- Full reference measure

- need a clear GT or reference image

- Generic error

- $p$  – norm
- minkowski norm

$$d_p(\mathbf{x}, \mathbf{y}) = \left( \sum_{i=1}^N |e_i|^p \right)^{1/p} \quad \text{where } e_i = x_i - y_i$$

- Mean sq error (MSE)

- PSNR

- $L$  is dynamic range

# PSNR

---

- Full reference measure

- need a clear GT or reference image

- Generic error

- $p$  – norm
- minkowski norm

$$d_p(\mathbf{x}, \mathbf{y}) = \left( \sum_{i=1}^N |e_i|^p \right)^{1/p} \quad \text{where } e_i = x_i - y_i$$

- Mean sq error (MSE)

$$\text{MSE}(\mathbf{x}, \mathbf{y}) = \frac{1}{N} \sum_{i=1}^N (x_i - y_i)^2$$

- PSNR

- $L$  is dynamic range

# PSNR

---

- Full reference measure

- need a clear GT or reference image

- Generic error

- $p$  – norm
- minkowski norm

$$d_p(\mathbf{x}, \mathbf{y}) = \left( \sum_{i=1}^N |e_i|^p \right)^{1/p} \quad \text{where } e_i = x_i - y_i$$

- Mean sq error (MSE)

$$\text{MSE}(\mathbf{x}, \mathbf{y}) = \frac{1}{N} \sum_{i=1}^N (x_i - y_i)^2$$

- PSNR

- $L$  is dynamic range

$$\text{PSNR} = 10 \log_{10} \frac{L^2}{\text{MSE}}$$

# MSE

---

- Good metric for optimization based methods
  - MSE: convex and differentiable
  - parameter-free, memoryless
  - energy minimization methods: relation to energy
- Uniformity with data communication signal measurements
- Distance metric

# MSE

---







- Good metric for optimization based methods
  - MSE: convex and differentiable
  - parameter-free, memoryless
  - energy minimization methods: relation to energy
- Uniformity with data communication signal measurements
- Distance metric
  - nonnegativity:  $d_p(\mathbf{x}, \mathbf{y}) \geq 0$
  - symmetry:  $d_p(\mathbf{x}, \mathbf{y}) = d_p(\mathbf{y}, \mathbf{x})$
  - identity:  $d_p(\mathbf{x}, \mathbf{y}) = 0$  if and only if  $\mathbf{x} = \mathbf{y}$
  - triangular inequality:  $d_p(\mathbf{x}, \mathbf{z}) \leq d_p(\mathbf{x}, \mathbf{y}) + d_p(\mathbf{y}, \mathbf{z})$



# PSNR

---


reference  
image



# Image features

- Image representation

- summarize image content via set of numbers (e.g. a vector)
- capture important image properties
  - object recognition
  - image matching
  - segmentation (via supervised learning)




# Image features

## ■ Image representation

- summarize image content via set of numbers (e.g. a vector)
- capture important image properties
  - object recognition
  - image matching
  - segmentation (via supervised learning)

## ■ Type of features


- local, global
- capture only certain property
  - texture, color, shape
  - deformation, object relative relations
  - motion



# Feature matching


---

- Panorama



# Feature matching


- Panorama







# Feature matching

- Depth estimation



# Feature matching

- Depth estimation



# Feature matching

---

- Object tracking






# Feature matching

---

- Segmentation



# Image features

---

- Feature detector
  - for a given image, outputs interesting locations (e.g. x, y)
  - tells nothing about the image properties at that region
  - capture important regions
    - corner detector

# Image features

---

- Feature detector

- for a given image, outputs interesting locations (e.g. x, y)
- tells nothing about the image properties at that region
- capture important regions
  - corner detector


- Feature descriptor

- for a given image, outputs interesting properties via feature vector
- encode interesting info into a series of stable numbers
  - stability in the sense that those numbers do not change drastically over image transformations (invariant)
  - e.g. scale, rotation invariance
- capture important properties of regions
  - Local binary pattern

# Image features

## ■ Feature detector

- for a given image, outputs interesting locations (e.g. x, y)
- tells nothing about the image properties at that region
- capture important regions
  - corner detector




## ■ Feature descriptor

- for a given image, outputs interesting properties via feature vector
- encode interesting info into a series of stable numbers
  - stability in the sense that those numbers do not change drastically over image transformations (invariant)
  - e.g. scale, rotation invariance
- capture important properties of regions
  - Local binary pattern

# Image features


- Without feature detector
  - uniform sampling



# Image features

- Without feature detector

- uniform sampling



- Feature combination

- local to global transition

# Feature detector

---

- Interest points


- robust to

- noise
    - distortions
    - transformations

- distinctive

- why are they located mostly at

- line endings
    - intersection of edges
    - local extrema points




# Image features


Extract keypoints





Feature descriptors



Clustering



Visual vocabulary






# LBP

---

- Local Binary Pattern


- texture and local pattern detection
- textures have no specific definition
  - complex patterns having more sub-patterns



# LBP


## Local Binary Pattern

- texture and local pattern detection
- textures have no specific definition
  - complex patterns having more sub-patterns



The value of the LBP code of a pixel  $(x_c, y_c)$  is given by:


$$LBP_{P,R} = \sum_{p=0}^{P-1} s(g_p - g_c) 2^p \quad s(x) = \begin{cases} 1, & \text{if } x \geq 0; \\ 0, & \text{otherwise.} \end{cases}$$



# LBP


## Local Binary Pattern

- texture and local pattern detection
- textures have no specific definition
  - complex patterns having more sub-patterns



The value of the LBP code of a pixel  $(x_c, y_c)$  is given by:

$$LBP_{P,R} = \sum_{p=0}^{P-1} s(g_p - g_c) 2^p \quad s(x) = \begin{cases} 1, & \text{if } x \geq 0; \\ 0, & \text{otherwise.} \end{cases}$$



$$1*1 + 1*2 + 1*4 + 1*8 + 0*16 + 0*32 + 0*64 + 0*128 = 15$$

# LBP


---

- Invariant to

- illumination

- shadow, reflection, brightness
    - relative difference between intensities remain same

- rotation?





# LBP

## ■ Invariant to

### ○ illumination

- shadow, reflection, brightness
- relative difference between intensities remain same

### ○ rotation?






# LBP

## ■ Invariant to

### ○ illumination

- shadow, reflection, brightness
- relative difference between intensities remain same

### ○ rotation?






# LBP

## ■ Invariant to

### ○ illumination

- shadow, reflection, brightness
- relative difference between intensities remain same

### ○ rotation?



# LBP

---


- Local Binary Pattern
  - 8 neighborhood gives 256 possible LBP codes
    - each pixel gets one of the codes
  - LBP histogram 256D
    - probability of occurrence of each LBP code



# LBP


## ■ Local Binary Pattern

- 8 neighborhood gives 256 possible LBP codes
  - each pixel gets one of the codes
- LBP histogram 256D
  - probability of occurrence of each LBP code




# LBP

- LBP to global descriptor





# LBP

---




# LBP




# Haar features

- Face detection



Haar feature:  $f(x, y) = \sum I(R_{white}) - \sum I(R_{black})$



Haar filters  
(based on Haar wavelets)

# Conclusion

- Statistical descriptors
- LBP
- Haar

