

Denoise:

Non-linear filtering

Dr. Tushar Sandhan

Introduction

- Image noise
 - a random variation of pixel values (RGB)
 - causes: sensor (quality, heat), camera parameters, environment, read noise

Introduction

- Image noise
 - a random variation of pixel values (RGB)
 - causes: sensor (quality, heat), camera parameters, environment, read noise

impulse



Introduction

- Image noise
 - a random variation of pixel values (RGB)
 - causes: sensor (quality, heat), camera parameters, environment, read noise

impulse



diffused impulses



Introduction

- Image noise
 - a random variation of pixel values (RGB)
 - causes: sensor (quality, heat), camera parameters, environment, read noise

impulse



diffused impulses



imperceptible



Introduction

- Image noise

- a random variation of pixel values (RGB)
- causes: sensor (quality, heat), camera parameters, environment, read noise

impulse



diffused impulses



imperceptible



salt & pepper



Gaussian filter

- Spatial averaging (linear) filter
 - noise looks high freq, so LPF
 - local neighbourhood of pixels has roughly similar color
 - while averaging, central pixels are weighted higher than far pixels
 - weights are fixed & don't depend on image content

Gaussian filter

- Spatial averaging (linear) filter
 - noise looks high freq, so LPF
 - local neighbourhood of pixels has roughly similar color
 - while averaging, central pixels are weighted higher than far pixels
 - weights are fixed & don't depend on image content

$$G[I]_{\mathbf{p}} = \sum_{\mathbf{q} \in \mathcal{S}} G_{\sigma}(\|\mathbf{p} - \mathbf{q}\|) I_{\mathbf{q}},$$

Gaussian filter

- Spatial averaging (linear) filter
 - noise looks high freq, so LPF
 - local neighbourhood of pixels has roughly similar color
 - while averaging, central pixels are weighted higher than far pixels
 - weights are fixed & don't depend on image content

$$G[I]_{\mathbf{p}} = \sum_{\mathbf{q} \in \mathcal{S}} G_{\sigma}(\|\mathbf{p} - \mathbf{q}\|) I_{\mathbf{q}},$$

$$G_{\sigma}(x) = \frac{1}{2\pi\sigma^2} \exp\left(-\frac{x^2}{2\sigma^2}\right)$$

Gaussian filter


- Spatial averaging (linear) filter
 - noise looks high freq, so LPF
 - local neighbourhood of pixels has roughly similar color
 - while averaging, central pixels are weighted higher than far pixels
 - weights are fixed & don't depend on image content

$$G[I]_{\mathbf{p}} = \sum_{\mathbf{q} \in \mathcal{S}} G_{\sigma}(\|\mathbf{p} - \mathbf{q}\|) I_{\mathbf{q}},$$


$$G_{\sigma}(x) = \frac{1}{2\pi\sigma^2} \exp\left(-\frac{x^2}{2\sigma^2}\right)$$

$$\frac{1}{256} \begin{bmatrix} 1 & 4 & 6 & 4 & 1 \\ 4 & 16 & 24 & 16 & 4 \\ 6 & 24 & 36 & 24 & 6 \\ 4 & 16 & 24 & 16 & 4 \\ 1 & 4 & 6 & 4 & 1 \end{bmatrix}$$

Gaussian filter




Gaussian filter



Unsharp masking

- Fill back the lost edges
 - an image sharpening method
 - amplifies high freq.


$$f_{sharp}(x, y) = I(x, y) + \alpha * (I(x, y) - G_{\sigma}(I(x, y)))$$



Unsharp masking

- Fill back the lost edges
 - an image sharpening method
 - amplifies high freq.


$$f_{sharp}(x, y) = I(x, y) + \alpha * (I(x, y) - G_{\sigma}(I(x, y)))$$



Unsharp masking

- Fill back the lost edges
 - an image sharpening method
 - amplifies high freq.


$$f_{sharp}(x, y) = I(x, y) + \alpha * (I(x, y) - G_{\sigma}(I(x, y)))$$



Unsharp masking


- Fill back the lost edges
 - an image sharpening method
 - amplifies high freq.

$$f_{sharp}(x, y) = I(x, y) + \alpha * (I(x, y) - G_{\sigma}(I(x, y)))$$




Gaussian filter

- Fixed kernel everywhere
 - edges are lost
 - averaging across edges



Dynamic filter

- Non-fixed kernel everywhere
 - edges are not lost
 - no averaging across edges
 - non-linear




Median filter

- Non-linear filter
- Replace each pixel by the median over a range N (e.g. $N = 5$)

$$\text{Median}([1\ 7\ 1\ 5\ 1]) = 1$$

- Spike noise




- Monotonic edges




Median filter

- 2D
 - $N \rightarrow k \times k$ (e.g. $k = 3$)
 - k is window size



Median filter

- 2D
 - $N \rightarrow k \times k$ (e.g. $k = 3$)
 - k is window size




```
1  do
2  {
3      while (a[i] < x) i++;
4      while (a[j] > x) j--;
5      int t = a[i];
6      a[i] = a[j];
7      a[j] = t;
8  } while (i < j);
```

Median filter

- 2D

- $N \rightarrow k \times k$ (e.g. $k = 3$)
- k is window size


- partitioning around pivot
- do it till pivot is at $N/2$ location



```
1  do
2  {
3      while (a[i] < x) i++;
4      while (a[j] > x) j--;
5      int t = a[i];
6      a[i] = a[j];
7      a[j] = t;
8  } while (i < j);
```

Median filter

- Effect of window size
 - best k depends upon image content, noise level & applications




input



$k = 3$

Median filter

- Effect of window size
 - best k depends upon image content, noise level & applications



input




$k = 3$



$k = 5$

Median filter

- Effect of window size
 - best k depends upon image content, noise level & applications



input



$k = 3$



$k = 5$



$k = 7$

Median filter



- Impulse noise

Median filter




■ Impulse noise





■ Salt & pepper noise

Hybrid median filter



Hybrid median filter



courtesy: G. Umamaheswari

Burst mean filter

- Average across M images
 - fix the camera parameters

$$g(x, y, t_M) = \frac{1}{M} \sum_{k=0}^{M-1} f(x, y, t_k)$$

Burst mean filter

- Average across M images
 - fix the camera parameters

$$g(x, y, t_M) = \frac{1}{M} \sum_{k=0}^{M-1} f(x, y, t_k)$$



Burst mean filter

- Average across M images
 - fix the camera parameters

$$g(x, y, t_M) = \frac{1}{M} \sum_{k=0}^{M-1} f(x, y, t_k)$$



k=0

k=M-1

Burst mean filter

- Average across M images
 - fix the camera parameters

$$g(x, y, t_M) = \frac{1}{M} \sum_{k=0}^{M-1} f(x, y, t_k)$$



k=0

k=M-1



k=0

k=M-1

Burst mean filter

- Average across M images
 - fix the camera parameters

$$M = 1$$



Burst mean filter

- Average across M images
 - fix the camera parameters

$M = 1$



$M = 3$



Burst mean filter

- Average across M images
 - fix the camera parameters

$M = 1$



$M = 3$



$M = 5$




Bilateral filter

- Varying filter kernel
 - kernel depends upon image content
- 1D image



Bilateral filter


- Varying filter kernel
 - kernel depends upon image content
- 1D image



Bilateral filter

- Gaussian

- kernel depends upon spatial dist



$$I_{\mathbf{p}}^b = \sum_{\mathbf{q} \in \mathcal{S}} \underbrace{G_{\sigma_s}(\|\mathbf{p} - \mathbf{q}\|)}_{\text{space}} I_{\mathbf{q}}$$


- Bilateral

- kernel depends upon spatial + intensity range dist

Bilateral filter

- Gaussian


- kernel depends upon spatial dist




$$I_{\mathbf{p}}^b = \sum_{\mathbf{q} \in \mathcal{S}} \underbrace{G_{\sigma_s}(\|\mathbf{p} - \mathbf{q}\|)}_{\text{space}} I_{\mathbf{q}}$$

- Bilateral

- kernel depends upon spatial + intensity range dist



$$I_{\mathbf{p}}^{\text{bf}} = \underbrace{\frac{1}{W_{\mathbf{p}}^{\text{bf}}}}_{\text{normalization}} \sum_{\mathbf{q} \in \mathcal{S}} \underbrace{G_{\sigma_s}(\|\mathbf{p} - \mathbf{q}\|)}_{\text{space}} \underbrace{G_{\sigma_r}(|I_{\mathbf{p}} - I_{\mathbf{q}}|)}_{\text{range}} I_{\mathbf{q}}$$



Bilateral filter

$$BF[I]_{\mathbf{p}} = \frac{1}{W_{\mathbf{p}}} \sum_{\mathbf{q} \in \mathcal{S}} G_{\sigma_s}(\|\mathbf{p} - \mathbf{q}\|) G_{\sigma_r}(|I_{\mathbf{p}} - I_{\mathbf{q}}|) I_{\mathbf{q}},$$

where


$$W_{\mathbf{p}} = \sum_{\mathbf{q} \in \mathcal{S}} G_{\sigma_s}(\|\mathbf{p} - \mathbf{q}\|) G_{\sigma_r}(|I_{\mathbf{p}} - I_{\mathbf{q}}|)$$

- BF


- Amount of filtering is controlled via σ_s, σ_r
- Spatial: σ_s – controls the influence of distant pixels
- Range: σ_r – controls the influence of pixel intensity change

Bilateral filter

- Influence of pixels
 - pixels close in space as well as in range are the influencers, others are ignored




Bilateral filter




Bilateral filter

- Summary



Bilateral filter


- Parameter effect



courtesy: Paris et al.

Bilateral filter


- Parameter effect



courtesy: Paris et al.

Bilateral filter

- Parameter effect



courtesy: Paris et al.

Bilateral filter

- Multiple iterations



input



BF iter-1



BF iter-5

Cartoon rendition

- $\sigma_s \uparrow$ & iterate



References

- Denoising by filtering

References

- Denoising by filtering

- ❑ CF Wstin Ron Kikiniis, H Knutsson, “Handbook of medical imaging”, 2000
- ❑ J Joseph, BN Anoop, J Williams, “A modified unsharp masking with adaptive threshold...”, Multimedia tools and applications, 2018
- ❑ Y Zhu and C Huang, “An improved median filtering algorithm for image noise reduction”, SSDMS Procedia 2012
- ❑ TS Huang, GJ Yang, GY Tang, “A fast two-dimensional median filtering algorithm”, IEEE Tran ASSP, 1979
- ❑ C. Tomasi and R. Manduchi, “Bilateral filtering for gray and color imaegs”, IEEE ICCV 1998
- ❑ S. Paris and F. Durand, “A fast approximation of the bilateral filter using a signal processing approach”, ECCV 2006
- ❑ Q. Yang, KH Tan, N. Ahuja, “Real time $O(1)$ bilateral filtering”, IEEE CVPR, 2009
- ❑ H Winnemoller, SC Olsen, B Gooch, (Cartoon rendition) “Real time video abstraction”, SIGGRAPH, 2006