SIMPLEX · BETALBATIM PUB · KITCHEN

Bill of quantities (BOQ)

90 priced lines in 8 trades, numbered A.01 to H.06, taken from the model and the two A3 sheets. Suppliers fill the rate, make and model for each line; the Excel file multiplies and totals. Quantities marked “measure on site” are estimates for pricing. Concept drawings for briefing suppliers, not construction drawings.

Item	Description and specification	Unit	Qty	Rate ₹	Amount ₹	Drawing
A	**Stainless steel fabrication (SS 304 throughout)** Worktops 1.2 mm or thicker, bodies 1.0 mm, legs 38 mm tube, welded and polished joints, adjustable feet. Supplier confirms or corrects the gauges.					
A.01	Non-veg prep bench 800 × 650 × 900 mm, open undershelf for the board rack, 100 mm back upstand	nos	1			Sheet 1
A.02	Dumpling and veg prep bench 800 × 650 × 900 mm, top over the under-counter freezer (B.07), two wall shelves over	nos	1			Sheet 1
A.03	Pass counter 650 × 650 × 900 mm with heat-lamp bracket and hatch ledge 700 mm through the wall	nos	1			Sheet 1
A.04	Dish sink, 2 bowls, 800 × 650 × 900 mm, pre-rinse spray bracket, undershelf, legs	nos	1			Sheet 1
A.05	Wall shelf 1,400 × 350 mm over the dish line: one plain, one slatted for bamboo steamer baskets	nos	2			Sheet 1
A.06	Veg and herb wash sink, single bowl, 450 × 500 × 900 mm, legs, undershelf	nos	1			Sheet 1
A.07	Back-up sauce and oil wall shelf 900 × 300 mm at 1.45 m	nos	1			Sheet 1
A.08	Wok seasoning rail 440 × 220 mm at 1.0 m with 8 lidded pots and a squeeze-bottle rack for 8 bottles	set	1			Sheet 1
A.09	Wok tool rail 470 mm at 1.4 m with 4 hooks	nos	1			Sheet 1
A.10	Chilled mise-en-place counter-top rail 760 × 260 × 220 mm for 5 pans	nos	1			Sheet 1
A.11	Dip and garnish rail 650 × 120 mm with 5 inserts, on the pass	nos	1			Sheet 1
A.12	Ticket rail 650 mm above the pass hatch	nos	1			Sheet 1
A.13	Magnetic knife strip 400 mm	nos	2			Sheet 1
A.14	Colour-coded cutting-board rack, slots for 4 boards, under the non-veg bench	nos	1			Sheet 1
A.15	Floor channel drain with SS grating 3,150 × 80 mm, falls to the grease trap	m	3.15			Sheet 1

Item	Description and specification	Unit	Qty	Rate ₹	Amount ₹	Drawing
A.16	Canopy hood 3,350 × 950 × 550 mm, bottom edge 2.05 m, baffle filters, grease cup, LED lights; 0.20 m overhang at the open end, 0.15 m over the wok range	nos	1			Sheet 2
A.17	Exhaust ductwork 400 × 400 mm SS at 2.35 to 2.75 m: hood collar, wall penetration, along the back wall, round the corner, to the ESP, fan and discharge; with brackets, bends and access doors	m	5			Sheet 2 · measure on site
A.18	Discharge elbow 400 × 400 mm at about 2.6 m pointing away from the building, with bird mesh and rain cowl	nos	1			Sheet 2
A.19	Storage deck racking, SS or galvanised, 3 tiers: 450 × 2,050 mm, 1,900 × 450 mm, 800 × 450 mm	nos	3			Model
A.20	Ceiling hatch frame 600 × 800 mm with fold-down loft ladder	nos	1			Sheet 1
B	**Cooking, cold and kitchen equipment (branded)** State make and model, kW or litres, and who services it in Goa. Sizes are the space available; do not quote a wider unit.					
B.01	Chinese wok range, 2 burners, LPG, 1,200 × 800 × 800 mm (0.75 to 0.9 m deep acceptable, aisle is 0.95 m at the range)	nos	1			Sheet 1
B.02	Dim sum steamer, 2 holes, LPG, 600 × 700 × 800 mm, with water top-up	nos	1			Sheet 1
B.03	Twin-tank fryer, LPG, 600 × 700 × 900 mm, two tanks (veg and non-veg oil)	nos	1			Sheet 1
B.04	Stock range, 2 burners, LPG, 600 × 700 × 850 mm	nos	1			Sheet 1
B.05	Reach-in, 2 doors, dual temperature (fridge door front, freezer door back), 950 × 750 × 2,000 mm, about 800 L, doors open into the aisle; state litres of each side	nos	1			Sheet 1
B.06	Under-counter fridge for the pass, about 600 × 550 × 700 mm; state litres	nos	1			Sheet 1
B.07	Under-counter freezer, 2 doors, to fit under the 800 × 650 mm bench; state litres (target about 650 L of freezer in all)	nos	1			Sheet 1
B.08	Under-counter dishwasher 600 × 650 × 900 mm with drainboard and its own booster heater	nos	1			Sheet 1
B.09	Rice cooker, 5 L (jasmine, sticky)	nos	2			Sheet 1
B.10	Mixer-grinder, commercial	nos	1			Sheet 1
B.11	Kitchen blowtorch	nos	1			Sheet 1

Item	Description and specification	Unit	Qty	Rate ₹	Amount ₹	Drawing
B.12	Storage water heater 35 L, 3 kW, 70 °C, high on the left wall over the dish line	nos	1			Sheet 2
B.13	Water heater 6 L for a hand-wash basin	nos	2			Sheet 2
B.14	Insect killer 500 × 180 mm over the kitchen door	nos	1			Sheet 1
B.15	Heat lamp over the pass, on its own switch	nos	2			Sheet 1
B.16	Electrostatic precipitator with carbon odour filter, about 500 × 1,000 × 900 mm, at 2.05 to 2.95 m outside	nos	1			Sheet 2
B.17	Inline exhaust fan Ø 440 mm, 4,000 to 5,000 m³/h, on anti-vibration mounts, with speed control	nos	1			Sheet 2
B.18	Fresh-air intake fan 500 × 480 mm, high on the back wall, interlocked with the exhaust	nos	1			Sheet 2
B.19	Make-up air diffuser, perforated, low velocity, 600 × 500 mm, in the kitchen ceiling	nos	2			Sheet 2
B.20	Make-up air cooling coil 1.5 TR with condenser unit on the right side wall at about 3.0 m	set	1			Sheet 2
B.21	Goods hoist, electric, 200 kg, over the ceiling hatch, with limit switch	nos	1			Sheet 2
B.22	Smallware, to the chef's list: carbon-steel woks, ladle, spatula, spider, wok brush, pans, food pans, knives, boards, stone mortar	lot	1			Chef
B.23	Bamboo steamer stacks (3 baskets and a lid), Ø 260 mm, for the drying shelf (the steamer comes with its own baskets, B.02)	nos	3			Sheet 1
C	**Gas installation (licensed contractor, for the fire NOC)** Pressure test and a written certificate are part of the work.					
C.01	LPG cage, locked and ventilated, 350 × 1,700 × 1,600 mm, on the right strip	nos	1			Sheet 2
C.02	LPG cylinders 19 kg with changeover manifold and regulator (4 on line and 1 spare, 95 kg in all)	nos	5			Sheet 2
C.03	Copper pipe with clamps and sleeves: along the right outside wall at 1.3 m, into the kitchen at the back corner, drop to the manifold at 0.4 m, along the back of the hot line (size by the contractor from the burner kW)	m	9			Sheet 2 · measure on site
C.04	Gas solenoid valve, weatherproof, outside on the entry; closes with the exhaust fan or the hood suppression	nos	1			Sheet 2
C.05	Ball valve, one per appliance, on the manifold	nos	6			Sheet 2

Item	Description and specification	Unit	Qty	Rate ₹	Amount ₹	Drawing
C.06	Flexible gas hose, certified, one per appliance	nos	6			Sheet 2
C.07	LPG leak detector with cut-off signal, low on the right wall	nos	1			Sheet 2
C.08	Pressure test, commissioning and certificate	lot	1			
D	**Plumbing and drainage** Sizes and fittings by the plumber. All kitchen drains go to the grease trap, then the grey-water line (never the biodigester).					
D.01	Water sump, buried, 1,000 L, 1.3 × 1.0 × 0.8 m, with lid and tanker inlet, under the garden	nos	1			Plan
D.02	Pressure pump set 0.5 HP, with sediment filter and softener, in the right-hand water cabinet 450 × 800 × 1,500 mm	set	1			Sheet 2
D.03	Water cabinet, 450 × 800 × 1,500 mm, ventilated, on the right strip (the fabrication is part of the cabinet item)	nos	1			Sheet 2
D.04	Cold and hot water pipe (CPVC or PPR) with fittings and isolation valves: cabinet to the kitchen along the strip and the hot-water run to the sink and dishwasher	lot	1			Sheet 2 · about 20 m
D.05	Hand-wash basin, wall-mounted, hands-free tap, soap dispenser: 330 × 400 mm at the door and 250 × 250 mm at the prep corner	nos	2			Sheet 1
D.06	Tall swan-neck wok tap, wall-mounted, at the wok range	nos	1			Sheet 2
D.07	Tall mixer tap for the veg sink; sink mixer tap with pre-rinse spray for the dish sink	set	1			Sheet 2
D.08	Pot filler, wall-mounted swing arm, cold, over the stock range	nos	1			Sheet 2
D.09	Steamer water feed with isolation valve at the back wall	nos	1			Sheet 2
D.10	Grease trap 450 × 450 mm, outside back corner, with cover	nos	1			Sheet 2
D.11	Drain pipe uPVC 100 mm with fittings: floor channel, sinks, hand-wash basins and dishwasher to the grease trap and grey-water line	m	12			Sheet 2 · measure on site
D.12	Floor trap with grating, SS	nos	2			Sheet 2
E	**Electrical** Three-phase supply about 15 to 20 kW. The fridges, exhaust fan, ESP, lights and water pump are on the power backup. Point numbers are on sheet 2.					

Item	Description and specification	Unit	Qty	Rate ₹	Amount ₹	Drawing
E.01	Socket or switch points 1 to 14 as marked on sheet 2 (fridge, freezer, rice cookers, mise-en-place rail, heat lamps, dishwasher, insect killer, hood and panel, pass fridge, grinder, heater isolator, hand-wash heaters, hoist), with their own MCBs where marked	nos	14			Sheet 2
E.02	Kitchen sub-distribution board with RCCB and MCBs, earthing and labelling	nos	1			Sheet 1
E.03	Exhaust fan and ESP control panel with hood-light switch and interlocks (fan, make-up air, gas solenoid, suppression)	nos	1			Sheet 2
E.04	LED hood light, 300 × 200 mm, vapour-proof	nos	3			Sheet 2
E.05	LED ceiling panel 600 × 600 mm	nos	3			Model
E.06	Cable, conduit, trunking and fixings for all kitchen points	lot	1			
E.07	Emergency light and EXIT sign at the rear door	set	1			Sheet 1
E.08	Testing and commissioning of all circuits	lot	1			
F	**Civil and finishes** Quantities from the 4.9 × 2.4 m kitchen; add wastage as usual. Ceiling must be non-combustible (no PVC).					
F.01	Wall tiles, white glazed 75 mm, to 2.1 m on the left wall and the partition, 0.85 to 2.1 m on the back and right walls, with grout and corner trims	m²	22.4			Model
F.02	Anti-slip epoxy floor with falls to the channel drain, grey	m²	11.8			Model
F.03	Non-combustible cement-board ceiling at 2.70 m with frame and white paint	m²	11.8			Model
F.04	Double-acting kitchen door 800 × 2,050 mm, stainless, spring pivots, vision panel, push plates and kick plate	nos	1			Sheet 1
F.05	Rear exit door 800 × 2,100 mm, opening outward, with closer, rubber sweep, PVC strip curtain and panic bar	set	1			Sheet 1
F.06	Cutting and making good: duct opening 400 × 400 mm in the back wall, gas and water sleeves, fan and intake openings	lot	1			Sheet 2
F.07	Storage deck over the kitchen, plywood on steel joists, 4.9 × 2.4 m, rated for storage only	m²	11.8			Model

Item	Description and specification	Unit	Qty	Rate ₹	Amount ₹	Drawing
G	**Fire and safety** Needed for the fire NOC.					
G.01	Wet-chemical hood suppression with nozzles over each appliance, manual pull and automatic gas cut-off	set	**1**			Sheet 2
G.02	Extinguisher, wet chemical (Class K) 6 L, on the back wall at the end of the hot line	nos	**1**			Sheet 1
G.03	Extinguisher, CO_2 4.5 kg, beside the electrical board at the kitchen door	nos	**1**			Model
G.04	Fire blanket in a wall box	nos	**1**			Sheet 1
G.05	First-aid box on the wall	nos	**1**			Model
G.06	Heat detector on the kitchen ceiling, wired to the alarm panel	nos	**1**			Sheet 2
H	**Outside, bins and housekeeping**					
H.01	Bin store 450 × 900 × 1,000 mm, timber slats, on the right strip	nos	**1**			Plan
H.02	Wheeled bin 60 L (wet, dry, glass)	nos	**3**			Plan
H.03	Foot-pedal bin Ø 200 × 600 mm (wet under the veg sink, dry by the rear door)	nos	**2**			Sheet 1
H.04	Steel bollard Ø 130 × 900 mm on the edge of the strip	nos	**6**			Plan
H.05	Apron hook rail, 3 hooks, above the prep-corner hand-wash	nos	**1**			Sheet 1
H.06	Dirty-linen bag with lid, and used-oil can 20 L with spill tray	set	**1**			Sheet 1

Every quote must state

- Steel grade and thickness (304 stainless only); make and model of every branded item.
- Price ex-GST, itemised, with the GST rate shown separately; delivery to Betalbatim and unloading; installation and connections, included or extra.
- Lead time, payment schedule, warranty and who services it in Goa, and how long the quote is valid.