SIMPLEX · BETALBATIM PUB · KITCHEN

BOQ: kitchen equipment and exhaust

44 lines in 3 sections: stainless steel fabrication, cooking and cold equipment, and the hood, exhaust and ventilation. Sizes are in feet and inches with millimetres alongside, sheet in SWG, hood and benches by the running foot, duct by the square foot, airflow in CFM, cooling in TR, cold units in litres. These are the units Indian commercial-kitchen quotes usually use; I could not confirm them with a Goa vendor, so the millimetre column is there if they prefer it. Gas, plumbing, electrical, civil and fire work are in the main BOQ. Concept drawings for briefing suppliers, not construction drawings.

No.	Item / type	Size W × D × H (ft-in)	Size (mm)	Gauge, capacity, specification	Unit	Qty	Per-foot basis	Rate ₹	Main BOQ
	Stainless steel fabrication SS 304. Worktops 18 SWG (1.2 mm), bodies and shelves 19 SWG (1.0 mm), legs 1½" (38 mm) tube, welded and polished joints, adjustable feet. Vendor confirms or corrects the gauge and states it on the quote.								
1	**Non-veg prep bench**	2'-7½" × 2'-1½" × 2'-11½"	800 × 650 × 900	Open undershelf for the board rack, 100 mm back upstand	nos	1	2.6 run ft		A.01
2	**Dumpling and veg prep bench**	2'-7½" × 2'-1½" × 2'-11½"	800 × 650 × 900	Top over the under-counter freezer (B.07); two wall shelves over	nos	1	2.6 run ft		A.02
3	**Pass counter**	2'-1½" × 2'-1½" × 2'-11½"	650 × 650 × 900	Heat-lamp bracket; hatch ledge 700 mm through the wall	nos	1	2.1 run ft		A.03
4	**Dish sink, 2 bowls**	2'-7½" × 2'-1½" × 2'-11½"	800 × 650 × 900	Pre-rinse spray bracket, undershelf, legs	nos	1	2.6 run ft		A.04
5	**Wall shelf over the dish line**	4'-7" × 1'-2"	1,400 × 350	One plain, one slatted for bamboo steamer baskets	nos	2	9.2 run ft		A.05
6	**Veg and herb wash sink**	1'-5½" × 1'-7½" × 2'-11½"	450 × 500 × 900	Single bowl, legs, undershelf	nos	1	1.5 run ft		A.06
7	**Sauce and oil wall shelf**	2'-11½" × 1'-0"	900 × 300	Back-up stock, fixed at 1.45 m	nos	1	3 run ft		A.07
8	**Wok seasoning rail**	1'-5½" × 8½"	440 × 220	At 1.0 m; 8 lidded pots and a rack for 8 squeeze bottles	set	1	1.4 run ft		A.08
9	**Wok tool rail**	1'-6½" long	470 long	At 1.4 m with 4 hooks	nos	1	1.5 run ft		A.09
10	**Chilled mise-en-place rail**	2'-6" × 10" × 8½"	760 × 260 × 220	Counter-top unit for 5 pans	nos	1	2.5 run ft		A.10
11	**Dip and garnish rail**	2'-1½" × 4½"	650 × 120	5 inserts, on the pass	nos	1	2.1 run ft		A.11
12	**Ticket rail**	2'-1½" long	650 long	Above the pass hatch	nos	1	2.1 run ft		A.12

No.	Item / type	Size W × D × H (ft-in)	Size (mm)	Gauge, capacity, specification	Unit	Qty	Per-foot basis	Rate ₹	Main BOQ
13	**Magnetic knife strip**	1'-3½" long	400 long		nos	2	2.6 run ft		A.13
14	**Cutting-board rack**	11" × 1'-4½" × 1'-4½"	280 × 420 × 420	Slots for 4 colour-coded boards, under the non-veg bench	nos	1			A.14
15	**Floor channel drain**	10'-4" × 3"	3,150 × 80	SS grating, falls to the grease trap (3.15 m)	run ft	10.3			A.15
16	**Storage deck racking**	1'-5½" × 6'-8½" · 6'-3" × 1'-5½" · 2'-7½" × 1'-5½"	450 × 2,050 · 1,900 × 450 · 800 × 450	SS or galvanised, 3 tiers, one rack of each size	nos	3			A.19
17	**Ceiling hatch frame with fold-down ladder**	1'-11½" × 2'-7½" opening	600 × 800 opening	For light goods; heavy stock goes on the hoist (B.21)	nos	1			A.20
	Cooking, cold and kitchen equipment (branded) State make and model, burner rating in kW (or kcal/hr), litres for each cold unit, and who services it in Goa. Sizes are the space available: do not quote a wider unit.								
18	**Chinese wok range, 2 burners**	3'-11" × 2'-7½" × 2'-7½"	1,200 × 800 × 800	LPG; state burner kW. 750 to 900 mm deep is acceptable (aisle is 0.95 m at the range)	nos	1			B.01
19	**Dim sum steamer, 2 holes**	1'-11½" × 2'-3½" × 2'-7½"	600 × 700 × 800	LPG; with water top-up	nos	1			B.02
20	**Twin-tank fryer**	1'-11½" × 2'-3½" × 2'-11½"	600 × 700 × 900	LPG; two tanks (veg and non-veg oil)	nos	1			B.03
21	**Stock range, 2 burners**	1'-11½" × 2'-3½" × 2'-9½"	600 × 700 × 850	LPG; for 20 L stock pots	nos	1			B.04
22	**Reach-in, 2 doors, dual temperature**	3'-1½" × 2'-5½" × 6'-6½"	950 × 750 × 2,000	About 800 L: fridge door at the front, freezer door at the back, doors open into the aisle; state litres of each side	nos	1			B.05
23	**Under-counter fridge (pass)**	1'-11½" × 1'-9½" × 2'-3½"	600 × 550 × 700	Sauce bases and cut veg; state litres	nos	1			B.06
24	**Under-counter freezer, 2 doors**	fits under 2'-7½" × 2'-1½"	fits under 800 × 650	State litres (target about 650 L of freezer in all with the reach-in)	nos	1			B.07
25	**Under-counter dishwasher**	1'-11½" × 2'-1½" × 2'-11½"	600 × 650 × 900	With drainboard and its own booster heater	nos	1			B.08
26	**Rice cooker**	Ø 10"	Ø 260	5 L; one for jasmine, one for sticky rice	nos	2			B.09
27	**Mixer-grinder**			Commercial, for sauces and batter	nos	1			B.10
28	**Kitchen blowtorch**				nos	1			B.11

No.	Item / type	Size W × D × H (ft-in)	Size (mm)	Gauge, capacity, specification	Unit	Qty	Per-foot basis	Rate ₹	Main BOQ
29	**Storage water heater**	Ø 1'-1" × 1'-7½"	Ø 330 × 500	35 L, 3 kW, 70 °C, high on the left wall over the dish line	nos	1			B.12
30	**Water heater for a hand-wash basin**			6 L, under each basin	nos	2			B.13
31	**Insect killer**	1'-7½" × 7"	500 × 180	Over the kitchen door	nos	1			B.14
32	**Heat lamp over the pass**			On its own switch	nos	2			B.15
33	**Goods hoist**			Electric, 200 kg, over the ceiling hatch, with limit switch	nos	1			B.21
34	**Smallware**			To the chef's list: carbon-steel woks, ladle, spatula, spider, wok brush, pans, food pans, knives, boards, stone mortar	lot	1			B.22
35	**Bamboo steamer stack**	Ø 10"	Ø 260	3 baskets and a lid, for the drying shelf (the steamer comes with its own baskets, B.02)	nos	3			B.23
	Hood, exhaust and ventilation Exhaust about 2,400 to 3,000 CFM (4,000 to 5,000 m³/h) for the whole hood; make-up air about 80% of it. No roof stack: apartment above and parking behind, so the duct goes out through the back wall, along it and up the right side, with an ESP before the fan. Vendor states the static pressure the fan is selected for.								
36	**Canopy hood, wall type, with baffle filters**	11'-0" × 3'-1½" × 1'-9½"	3,350 × 950 × 550	SS 304, 20 SWG (0.9 mm); SS baffle filters, grease cup, LED lights; bottom edge 6'-9" (2.05 m) above the floor; overhang 8" at the open end, 6" over the wok range. Priced per running foot or per hood: state which	nos	1	11 run ft		A.16
37	**Exhaust ducting, rectangular**	16" × 16" section	400 × 400 section	SS 304, 20 SWG (0.9 mm), at 7'-8" to 9'-0" above the floor: hood collar, wall opening, along the back wall, round the corner, to the ESP, fan and discharge; brackets, bends, access doors. Sheet area 86 sq ft (about 95 sq ft with bends)	run ft	16.4	95 sq ft		A.17
38	**Discharge elbow**	16" × 16" section	400 × 400 section	About 8'-6" above the floor, pointing away from the building; bird mesh and rain cowl	nos	1			A.18
39	**ESP with carbon odour filter**	1'-7½" × 3'-3½" × 2'-11½"	500 × 1,000 × 900	Outside, 6'-9" to 9'-8" above the floor; rated for 2,400 to 3,000 CFM; state kW and filter life	nos	1			B.16
40	**Inline exhaust fan**	Ø 17½"	Ø 440	2,400 to 3,000 CFM at the static pressure you state (duct + ESP + discharge); belt or direct drive, motor HP stated; anti-vibration mounts, speed control	nos	1			B.17
41	**Fresh-air intake fan**	1'-7½" × 1'-7"	500 × 480	High on the back wall (about 10'-10"); about 1,900 to 2,400 CFM; interlocked with the exhaust	nos	1			B.18
42	**Make-up air diffuser, perforated, low velocity**	1'-11½" × 1'-7½"	600 × 500	In the kitchen ceiling, about 950 to 1,200 CFM each	nos	2			B.19

No.	Item / type	Size W × D × H (ft-in)	Size (mm)	Gauge, capacity, specification	Unit	Qty	Per-foot basis	Rate ₹	Main BOQ
43	**Make-up air cooling coil with condenser**	condenser 2'-7½" × 1'-9½" × 1'-0"	condenser 800 × 550 × 300	1.5 TR; condenser on the right side wall at about 9'-10" above the floor	set	1			B.20
44	**Exhaust fan and ESP control panel**			With hood-light switch and interlocks (fan, make-up air, gas solenoid, suppression)	nos	1			E.03

Every quote must state

- Steel grade and SWG for each part; make and model, kW or litres for every branded item; the static pressure the exhaust fan is selected for.
- Price ex-GST with the GST rate separate; delivery to Betalbatim and unloading; installation and connections included or extra; whether the hood and benches are priced per unit or per running foot, and the duct per square foot.
- Lead time, payment schedule, warranty and who services it in Goa, and how long the quote is valid.