

Chapter → 09

Access Modifiers & Constructors

Access Modifiers

- 1) Private :
- 2) Default :
- 3) Protected :
- 4) Public :

Getters and Setters

Getters → Returns the value (accessors)

Setters → Sets/updates the value (mutators)

Example:

```

class Employee {
    private int id;
    private String name;

    public String getName() {
        return name;
    }

    public String void setName(String n) {
        return name = n;
    }

    public int getId() {
        return id;
    }

    public void setId(id) (int i) {
        id = i;
    }
}
  
```



```

public class ch9 {
    public static void main (String [] args)
    {
        Employee malip = new Employee ();
        malip.setName ("Code with malip");
        System.out.println (malip.getName());

        malip.setId (55);
        System.out.println (malip.getId());
    }
}

```

Constructors in Java

A member function used to initialise an object ~~while~~ while creating it.

```

Employee malip = new Employee ();
malip.setName ("Malip bhar");

```

In order to write our own constructor, we define a method with name same as class name.

```

public Employee () {
    name = "your name";
}

```


Quiz: Overload the Employee constructor to initialize the salary to Rs. 10000.

Class MyEmployee1

{

private int id;

private String name;

private double salary;

public MyEmployee1 (int id, String name, double s

{

this.id = id;

this.name = name;

this.salary = salary;

}

public MyEmployee1 (int id, String name)

{

this.id = id;

this.name = name;

salary = 10000;

}

public void setId (int i)

{

id = i;

}

public ~~void~~ int getId ()

{

return id;

}


```
public void setName (String n)
```

```
{
```

```
    name = n;
```

```
}
```

```
public String getName ( )
```

```
{
```

```
    return name;
```

```
}
```

```
public void setSalary (double sal)
```

```
{
```

```
    salary = sal;
```

```
}
```

```
public double getSalary ( )
```

```
{
```

```
    return salary;
```

```
}
```

```
}  
public class CH-9-CONSTRUCTOR-QUIZ
```

```
{
```

```
    public static void main (String [] args)
```

```
{
```

```
        MyEmployee1 emp = new MyEmployee1 ("Mahip",  
                                                4,25000);
```

```
        System.out.println ( emp.getName ( ) );
```

```
        cout ( emp.getId ( ) );
```

```
        cout ( emp.getSalary ( ) );
```

```
        MyEmployee1 emp1 = new MyEmployee1 ("Mahit",  
                                                45);
```

```
        System.out.println ( emp1.getName ( ) );
```

```
        cout ( emp1.getId ( ) );
```

```
        cout ( emp1.getSalary ( ) );
```

```
}
```

```
}
```