

Contents

- 0.1 删除同字
- 0.2 滑窗

0.1 删除同字

```

1 #include<bits/stdc++.h>
2 using namespace std;
3
4 struct node{
5     int leng,idx;
6     bool operator<(const node& other) const {
7         if (leng!=other.leng) return leng<other.leng;
8         return idx>other.idx;
9     }
10 };
11
12 int main(){
13     int n;
14     cin>>n;
15     vector<int> tbl(n);
16     for(auto &i:tbl) cin>>i;
17     vector<int> num,len;
18     int siz=0;
19     num.push_back(tbl[0]);
20     len.push_back(0);
21     for(int i=0;i<n;i++){
22         if(tbl[i]==num[siz]) len[siz]++;
23         else{
24             siz++;
25             num.push_back(tbl[i]);
26             len.push_back(1);
27         }
28     }
29     siz=num.size();
30     vector<int> L,R,alive(siz,1);
31     for(int i=0;i<siz;i++){
32         L.push_back(i-1);
33         R.push_back(i+1);
34     }
35     priority_queue<node> pq;
36     for(int i=0;i<siz;i++) pq.push({len[i],i});
37     int ans=0;
38     while(!pq.empty()){
39         auto [currentL,idx]=pq.top();
40         pq.pop();
41
42         if(!alive[idx] || currentL!=len[idx]) continue;
43         ans++;
44         alive[idx]=0;
45         int l=L[idx],r=R[idx];
46         if(l>=0) R[l]=r;
47         if(r<siz) L[r]=l;
48
49         if(l>=0 && r<siz && alive[l] && alive[r] &&
50             num[l]==num[r]){
51             len[l]+=len[r];
52             alive[r]=0;
53             R[l]=R[r];
54             if(R[r]<siz) L[R[r]]=l;
55             pq.push({len[l],l});
56         }
57     }
58     cout<<ans;
59 }

```

0.2 滑窗

```

1 #include<bits/stdc++.h>
2 using namespace std;
3 multiset<int> l,r;
4 int tbl[200005];
5 void resort(){
6     while(l.size()<r.size()){
7         l.insert(*r.begin());
8         r.erase(r.begin());
9     }
10    while(l.size()>r.size()+1){
11        r.insert(*l.rbegin());
12        l.erase(prev(l.end()));
13    }
14 }
15 void insert_num(int num){
16     if(l.empty() || num<=*l.rbegin()) l.insert(num);
17     else r.insert(num);
18     resort();
19 }
20 void erase_num(int num){
21     if(l.find(num)!=l.end()) l.erase(l.find(num));
22     else r.erase(r.find(num));
23     resort();
24 }
25 int main(){
26     int n,x;
27     cin>>n>>x;
28     for(int i=0;i<n;i++) cin>>tbl[i];
29     for(int i=0;i<x;i++) insert_num(tbl[i]);
30     cout<<*l.rbegin()<<" ";
31     for(int i=x;i<n;i++){
32         insert_num(tbl[i]);
33         erase_num(tbl[i-x]);
34         cout<<*l.rbegin()<<" ";
35     }
36 }

```