Microcontroller and Microprocessors
Experiment - 2
Equation Solving and Boolean Reduction

Varun Singh Inda
16BEE0023

Equation Solving

Aim :- To solve the given equation ($5x^2 + 6xy + y^2 + 8$)

Procedure :-
1. Launch Keil uVision
2. Create a new project and load the NXP microcontroller P895V1RD2
3. Create a blank document and save the file with extension .asm
4. Load the saved .asm file under the target folder for the ongoing project.
5. Type the code and save the file once again
6. Build the target to check if there are any errors or warnings
7. If there are any errors, debug them and continue with step 8
8. Debug the program and note the values of accumulator and corresponding registers
9. Run the program and verify the updated values of the accumulator and corresponding registers

Code :-

```
MOV A, 20H
MOV B, A
MUL AB
MOV R0, B
MOV B, #05
MUL AB
MOV R0, B
MOV R1, A
MOV A, 20H
MOV B, 21H
MUL AB
MOV B, #06
MUL AB
MOV R2, B
MOV R3, A
```

```
MOV A, 21H
MOV B, A
MUL AB
MOV B, #07
MUL AB
MOV R4, B
MOV R5, A
MOV A, R1
ADD A, R3
ADDC A, R5
MOV R6, A
MOV A, R0
ADDC A, R2
ADDC A, R4
MOV R7, A
MOV A, R6
ADDC A, #08
MOV 22H, A
MOV A, R7
SUBB A, #0
MOV 23H, A
END
```

Pictures :-





Lab Pictures



Conclusion :- Through Keil we can see that equation solving is not a big task and can be done in seconds using different values. The program ran successfully and the results were same as of theory.

Boolean Reduction

Aim :- To solve the given boolean expression using keil.



Procedure :-

1. Launch Keil uVision
2. Create a new project and load the NXP microcontroller P895V1RD2
3. Create a blank document and save the file with extension .asm
4. Load the saved .asm file under the target folder for the ongoing project.
5. Type the code and save the file once again
6. Build the target to check if there are any errors or warnings
7. If there are any errors, debug them and continue with step 8
8. Debug the program and note the values of accumulator and corresponding registers
9. Run the program and verify the updated values of the accumulator and corresponding registers

Logic :-

- Compute all the logic gates and store them in accumulators for further operations

For OR and NOR gates:

- Use ORL command to perform OR logic between A and B (A + B)
- Use CPL command after ORL command to obtain NOR logic ((A + B)')

For AND and NAND gates:

- Use ANL command to perform AND logic between A and B (AB)
- Use CPL command after ANL command to obtain NAND logic ((AB)')

For XOR gates:

- Use CPL command to obtain A' and B' and store them in 2 new Accumulators.
- Use ANL command to perform AND logic between A' and B and A and B' and obtain A'B and B'A and store them in Accumulators
- Use ORL command to perform OR logic between A'B and B'A to get the final XOR gate (A'B + B'A).

Code :-

```
Setb acc.0
Setb b.0
clr b.0 ;Value setting
mov c,b.0
anl c,b.0
cpl c
cpl c
mov acc.1,c ;Module 1
```

```
mov c,b.0
orl c,acc.0
cpl c ;Module 2
cpl b.0
orl c,b.0
orl c,acc.1; Module 3 and 4
cpl c
end; Module 5
```

Pictures :-





Lab Pictures





Conclusion :- The boolean reduction was done easily using Keil and the result matches with the theoretical result.