



**Business Gateway  
Developer pack**

**Schema explain**

**Search of the index map – SIM V2.1**

Data Input Field (from LR Test Harness)	Extract of relevant code from Schema	Description	Mandatory	Min Value	Max Value	Has a pattern constraint	XML Datatype
User Credentials							
User Id							
Password							
Locale							
RequestSearchOfIndexMapV2_1	<pre>&lt;xs:complexType   name="RequestSearchOfIndexMapV2_1Type"&gt;   &lt;xs:sequence&gt;     &lt;xs:element name="ID"       type="Q1IdentifierType"       minOccurs="1" maxOccurs="1" /&gt;     &lt;xs:element name="Product"       type="Q1ProductType"       minOccurs="1" maxOccurs="1"&gt;      &lt;xs:element name="SearchOfIndexMap"       type="Q1SearchOfIndexMapType"       minOccurs="1" maxOccurs="1"&gt;      &lt;xs:element name="AlternativeDespatchDetails"       type="Q1AlternativeDespatchDetailsType"       minOccurs="0" maxOccurs="1" /&gt;      &lt;xs:complexType name="Q1SearchOfIndexMapType"&gt;       &lt;xs:element name="WithoutAttachedPlan"         type="Q1WithoutAttachedPlanType"         minOccurs="1" maxOccurs="1" /&gt;       &lt;xs:element name="WithAttachedPlan"         type="Q1WithAttachedPlanType"         minOccurs="1" maxOccurs="1" /&gt;        &lt;xs:complexType name="Q1WithAttachedPlanType"&gt;         &lt;xs:sequence&gt;           &lt;xs:element name="Plan"             type="Q1PlanType"             minOccurs="1" maxOccurs="1" /&gt;           &lt;xs:element name="WithPlanAddressDetails"             type="Q1WithPlanAddressDetailsType"             minOccurs="1" maxOccurs="1" /&gt;          &lt;xs:complexType name="Q1WithoutAttachedPlanType"&gt;           &lt;xs:sequence&gt;             &lt;xs:element               name="WithoutPlanAddressDetails"               type="Q1WithoutPlanAddressDetailsType"               minOccurs="1" maxOccurs="1" /&gt;            </pre>	<p>Main element of the schema, creating a message id and a product type to carry the necessary data for the SIM.</p> <p>NOTE: The address elements are only explained once.</p>					

Data Input Field (from LR Test Harness)	Extract of relevant code from Schema	Description	Mandatory	Min Value	Max Value	Has a pattern constraint	XML Datatype
	<pre> &lt;xs:complexType name="Q1WithoutPlanAddressDetailsType"&gt;   &lt;xs:choice&gt;     &lt;xs:element name="AddressWithPostcode"       type="Q1AddressWithPostcodeType"       minOccurs="0" maxOccurs="1" /&gt;     &lt;xs:element name="AddressWithoutPostcode"  type="Q1WithoutPlanWithoutPostcodeType"       minOccurs="0" maxOccurs="1" /&gt;  &lt;xs:complexType name="Q1WithPlanAddressDetailsType"&gt;   &lt;xs:choice&gt;     &lt;xs:element name="AddressWithPostcode"       type="Q1AddressWithPostcodeType"       minOccurs="1" maxOccurs="1" /&gt;     &lt;xs:element name="AddressWithoutPostcode"  type="Q1WithPlanWithoutPostcodeType"       minOccurs="1" maxOccurs="1" /&gt; </pre>						
Message Id	<pre> &lt;xs:complexType name="Q1IdentifierType"&gt;   &lt;xs:sequence&gt;     &lt;xs:element name="MessageID"       type="Q1TextType"       minOccurs="1" maxOccurs="1"&gt;       &lt;xs:annotation&gt;         &lt;xs:documentation&gt;A character string (i.e. a finite set of characters) generally in the form of words of a language.  &lt;xs:complexType name="Q1TextType"&gt;   &lt;xs:annotation&gt;     &lt;xs:documentation&gt;A character string (i.e. a finite set of characters) generally in the form of words of a language. &lt;/xs:documentation&gt; &lt;/xs:annotation&gt; &lt;xs:simpleContent&gt;   &lt;xs:extension base="Q1TextContentType" /&gt;  &lt;xs:simpleType name="Q1TextContentType"&gt;   &lt;xs:restriction base="xs:string"&gt;     &lt;xs:minLength value="5" /&gt;     &lt;xs:maxLength value="50" /&gt; </pre>	<p>Each application must have a message id. There can only be one message Id for each application.</p> <p>The message Id is a string with a minimum length of 5 characters and a maximum length of 50 characters.</p> <p>The message id has a constraint on its pattern value [a-zA-Z0-9][a-zA-Z0-9\-\]* This constrains the message id to begin with a-z (lowercase), A-Z(uppercase) or 0-9 and can then be followed with a-z (lowercase), A-Z(uppercase) , 0-9 or a hyphen (as long as the input meets the field's length criteria).</p> <p>All of the XML elements that are relevant for the message id are shown, text in bold to help show the links within the XML.</p>	Y	5	50	Y	xs:string

Data Input Field (from LR Test Harness)	Extract of relevant code from Schema	Description	Mandatory	Min Value	Max Value	Has a pattern constraint	XML Datatype
	<pre>&lt;xs:pattern value="[a-zA-Z0-9][a-zA-Z0-9\-\ ]*" /&gt; &lt;/xs:restriction&gt;</pre>						

Data Input Field (from LR Test Harness)	Extract of relevant code from Schema	Description	Mandatory	Min Value	Max Value	Has a pattern constraint	XML Datatype
Gross Price Amount	<pre> &lt;xs:element name="ExpectedPrice"   type="Q1ExpectedPriceType"   minOccurs="0" maxOccurs="1"&gt;    &lt;xs:complexType name="Q1ExpectedPriceType"&gt;     &lt;xs:element name="GrossPriceAmount"       type="AmountType"       minOccurs="0" maxOccurs="1"&gt;       &lt;xs:annotation&gt;         &lt;xs:documentation&gt;The gross price is the price including the VAT. If the VAT is zero then the Gross and Net Price will be the same &lt;/xs:documentation&gt;          &lt;xs:element name="NetPriceAmount"           type="AmountType"           minOccurs="0" maxOccurs="1"&gt;           &lt;xs:annotation&gt;             &lt;xs:documentation&gt;The Net Price is the amount before the VAT is added on. If the VAT is zero then the Gross and Net Price will be the same              &lt;xs:element name="VATAmount"               type="AmountType"               minOccurs="0" maxOccurs="1"&gt;               &lt;xs:annotation&gt;                 &lt;xs:documentation&gt;This is the amount of the VAT                &lt;/xs:documentation&gt;             &lt;/xs:element&gt;           &lt;/xs:annotation&gt;         &lt;/xs:documentation&gt;       &lt;/xs:annotation&gt;     &lt;/xs:complexType&gt;   &lt;/xs:element&gt; &lt;/pre&gt; </pre>	<p>Carries the customers expected fee value.</p> <p>NetPriceAmount and VATAmount are not currently used.</p>					xs:decimal

Data Input Field (from LR Test Harness)	Extract of relevant code from Schema	Description	Mandatory	Min Value	Max Value	Has a pattern constraint	XML Datatype
Continue If Actual Fee Exceeds Expected Fee Indicator	<pre> &lt;xs:element name= "ContinueIfActualFeeExceedsExpectedFeeIndicator"   type="IndicatorType"   minOccurs="1" maxOccurs="1"&gt;   &lt;xs:documentation&gt; A list of two mutually exclusive          Boolean values that express the            only possible states of a Property.  &lt;xs:complexType name="IndicatorType"&gt;   &lt;xs:annotation&gt;     &lt;xs:documentation&gt;A list of two mutually exclusive          Boolean values that express the only            possible states of a Property. &lt;xs:simpleContent&gt;   &lt;xs:extension base="xs:boolean" /&gt; &lt;/xs:simpleContent&gt; </pre>	<p>The documentation text does not clearly explain its element.</p> <p>If true, tells LR to continue with search even if the actual cost of the search is greater than the cost expected by the CMS.</p> <p>If false and the actual fee is greater than the fee input by the customer an error message will be returned and the search will not be performed.</p>	Y				xs:boolean
External Reference	<pre> &lt;xs:element name="ExternalReference"   type="Q1ExternalReferenceType"   minOccurs="1" maxOccurs="1"&gt;   &lt;xs:documentation&gt;Reference associated with a          case in Case Management System  &lt;xs:complexType name="Q1ExternalReferenceType"&gt;   &lt;xs:documentation&gt;A unique reference given to identify           a particular request, order or instruction in the          system of the organisation allocating it with the          ability to associate the name of the          Company that has allocated it.  &lt;xs:sequence&gt;   &lt;xs:element name="Reference"     type="ReferenceTextContentType"     minOccurs="1" maxOccurs="1"&gt;     &lt;xs:documentation&gt;A unique reference given to           identify a particular request, order or instruction           in the system of the organisation allocating it.  &lt;xs:simpleType name="ReferenceTextContentType"&gt;   &lt;xs:restriction base="xs:string"&gt; </pre>	<p>To carry the external reference to LR, external ref is created by the CMS.</p>	Y	1	25	Y	xs:string

Data Input Field (from LR Test Harness)	Extract of relevant code from Schema	Description	Mandatory	Min Value	Max Value	Has a pattern constraint	XML Datatype
	<pre>&lt;xs:minLength value="1" /&gt; &lt;xs:maxLength value="25" /&gt; &lt;xs:pattern value="[A-Za-z0-9\s~!&amp;quot;@#\$%'\(\)\*\+\,\-\.\/:;=&amp;gt;\?[\[\]\_{}\^&amp;#xa3;]*" /&gt; &lt;/xs:restriction&gt; &lt;/xs:simpleType&gt;</pre>						

Data Input Field (from LR Test Harness)	Extract of relevant code from Schema	Description	Mandatory	Min Value	Max Value	Has a pattern constraint	XML Datatype
Customer Reference	<pre> &lt;xs:element name="CustomerReference"   type="Q1CustomerReferenceType"   minOccurs="1" maxOccurs="1"&gt;   &lt;xs:documentation&gt;Reference of the person for                                 whom the remortgage is performed.  &lt;xs:complexType name="Q1CustomerReferenceType"&gt;   &lt;xs:documentation&gt;Provides a unique reference to                                 identify a particular request, order or instruction                                 or object in the system of the organisation                                 allocating it.    &lt;xs:sequence&gt;     &lt;xs:element name="Reference"       type="ReferenceTextContentType"       minOccurs="1" maxOccurs="1"&gt;       &lt;xs:documentation&gt;A unique reference given to                                 identify a particular request, order or instruction                                 in the system of the organisation allocating                                 it with the ability to associate the name of the                                 Company that has allocated it.  &lt;xs:simpleType name="ReferenceTextContentType"&gt;   &lt;xs:restriction base="xs:string"&gt;     &lt;xs:minLength value="1" /&gt;     &lt;xs:maxLength value="25" /&gt;     &lt;xs:pattern value="[A-Za-z0-9\s~!&amp;quot;@#\$\$%\(\)\*\+\,\- \./:;=&amp;gt;\?[\[\]\_{}\^&amp;#xa3;]*" /&gt;   &lt;/xs:restriction&gt; &lt;/xs:simpleType&gt; </pre>	To carry the Customer reference to LR, customer ref is created/provided by the CMS.	Y	1	25	Y	xs:string



Data Input Field (from LR Test Harness)	Extract of relevant code from Schema	Description	Mandatory	Min Value	Max Value	Has a pattern constraint	XML Datatype
Contact Name	<pre> &lt;xs:element name="Contact"   type="Q1ContactType" minOccurs="1"   maxOccurs="unbounded"&gt;   &lt;xs:documentation&gt;The information relevant to a               person or organization that acts as a               point of contact with another person or organization.&lt;/xs:documentation&gt;  &lt;xs:complexType name="Q1ContactType"&gt;   &lt;xs:documentation&gt;The information relevant to a               person or organization that acts as a               point of contact with another person or organization.&lt;/xs:documentation&gt;        &lt;xs:element name="Name"         type="Q3TextType"         minOccurs="1" maxOccurs="1"&gt;         &lt;xs:documentation&gt;The name of this contact person                                 or department.  &lt;xs:complexType name="Q3TextType"&gt;   &lt;xs:documentation&gt;A character string (i.e. a finite set                                 of characters) generally in the form                                 of words of a language. &lt;xs:simpleContent&gt;   &lt;xs:extension base="Q3TextContentType" /&gt;  &lt;xs:simpleType name="Q3TextContentType"&gt;   &lt;xs:restriction base="xs:string"&gt;     &lt;xs:pattern value=".*\S.*"/&gt;   &lt;/xs:restriction&gt; </pre>	Carries the contact name of the person sending the request for OS.	Y			Y	xs:string

Data Input Field (from LR Test Harness)	Extract of relevant code from Schema	Description	Mandatory	Min Value	Max Value	Has a pattern constraint	XML Datatype
Telephone Number	<pre> &lt;/xs:element&gt;   &lt;xs:element name="Communication"     type="Q1CommunicationType"     minOccurs="1" maxOccurs="1"&gt;     &lt;xs:documentation&gt;The information relevant to methods of communication for this Contact.  &lt;xs:complexType name="Q1CommunicationType"&gt;   &lt;xs:documentation&gt;Provides details of any other form of communication   &lt;xs:element name="Telephone"     type="Q3TextType"     minOccurs="1" maxOccurs="1"&gt;  &lt;xs:complexType name="Q3TextType"&gt;   &lt;xs:documentation&gt;A character string (i.e. a finite set of characters) generally in the form of words of a language. &lt;xs:simpleContent&gt;   &lt;xs:extension base="Q3TextContentType" /&gt;  &lt;xs:simpleType name="Q3TextContentType"&gt;   &lt;xs:restriction base="xs:string"&gt;     &lt;xs:pattern value=".*\S.*"/&gt;   &lt;/xs:restriction&gt; &lt;/xs:simpleType&gt; </pre>	Carries the telephone number of the person submitting the application	Y			Y	xs:string
<b>SIM - No Attachment; No Postcode</b>	<pre> &lt;xs:complexType name=   "Q1WithoutPlanWithoutPostcodeType"&gt;   &lt;xs:sequence&gt; </pre>	This type is the overall container for sending a request without a plan and without a postcode					
<b>SIM with Attachment; No Postcode</b>	<pre> &lt;xs:complexType name=   "Q1WithPlanWithoutPostcodeType"&gt;   &lt;xs:sequence&gt; </pre>	This type is the overall container for sending a request with a plan but without a postcode					

Data Input Field (from LR Test Harness)	Extract of relevant code from Schema	Description	Mandatory	Min Value	Max Value	Has a pattern constraint	XML Datatype
Attachment	<pre> &lt;xs:complexType name="Q1PlanType"&gt;   &lt;xs:element name="PlanDetailsAttachment"     type="Q1PlanDetailsAttachmentType"     minOccurs="1" maxOccurs="1"&gt;      &lt;xs:complexType       name="Q1PlanDetailsAttachmentType"&gt;         &lt;xs:element name="EmbeddedFileBinaryObject"           type="BinaryObjectType"           minOccurs="1" maxOccurs="1"&gt;            &lt;xs:complexType name="BinaryObjectType"&gt;             &lt;xs:documentation&gt;A set of finite-             length sequences                                 of             binary octets.              &lt;xs:simpleContent&gt;               &lt;xs:extension base="xs:base64Binary"&gt;                 &lt;xs:attribute name="filename"                   type="xs:string"                   use="optional"&gt;                   &lt;xs:annotation&gt;                     &lt;xs:documentation&gt; Must be the full                     filename including                                 the extension                     (Reference IETF RFC 2045,                                 2046, 2047) </pre>	These elements carry the file upload					xs:base64Binary
Identifier	<pre> &lt;xs:element name="Title"   type="Q3TextType"   minOccurs="0" maxOccurs="1"&gt;   &lt;xs:documentation&gt;Title or Caption for   the attached                                 file   or document    &lt;xs:complexType name="Q3TextType"&gt;     &lt;xs:documentation&gt;A character string     (i.e. a finite set of     characters) generally in the form of                                 words of a     language.     &lt;xs:simpleContent&gt;       &lt;xs:extension base="Q3TextContentType" /&gt;     &lt;/xs:simpleContent&gt;   &lt;/xs:complexType&gt;    &lt;xs:simpleType name="Q3TextContentType"&gt;     &lt;xs:restriction base="xs:string"&gt;       &lt;xs:pattern value=".*\S.*"/&gt;     &lt;/xs:restriction&gt;   &lt;/xs:simpleType&gt; </pre>	Carries the title/description of the file uploaded				Y	xs:string
Local Authority	This set of elements/attributes is used with either of the SIM with No Postcode types above						

Data Input Field (from LR Test Harness)	Extract of relevant code from Schema	Description	Mandatory	Min Value	Max Value	Has a pattern constraint	XML Datatype
Property Identifier	<pre> &lt;xs:element name="PropertyIdentifier"   type="Q1Len50TextType"   minOccurs="1" maxOccurs="1"&gt;   &lt;xs:documentation&gt;This field could be a Land Identifier, House Number or House Name e.g. 'Land to the left of 15 The Mews'  &lt;xs:complexType name="Q1Len50TextType"&gt;   &lt;xs:annotation&gt;     &lt;xs:documentation&gt;A character string (i.e. a finite set of characters) generally in the form of words of a language. &lt;xs:simpleContent&gt;   &lt;xs:extension base="Q1Len50TextContentType" /&gt;  &lt;xs:simpleType name="Q1Len50TextContentType"&gt;   &lt;xs:restriction base="xs:string"&gt;     &lt;xs:minLength value="1" /&gt;     &lt;xs:maxLength value="50" /&gt;     &lt;xs:pattern value=".*\S.*"/&gt;   &lt;/xs:restriction&gt; </pre>	House number or name carried by this element	Y	1	50	Y	xs:string
Sub Building Name	<pre> &lt;xs:element name="SubBuildingName"   type="Q1Len100TextType"   minOccurs="0" maxOccurs="1"&gt;   &lt;xs:documentation&gt;A character string (i.e. a finite set of characters) generally in the form of words of a language. &lt;/xs:element&gt;  &lt;xs:complexType name="Q1Len100TextType"&gt;   &lt;xs:documentation&gt;A character string (i.e. a finite set of characters) generally in the for of words of a language. &lt;xs:simpleContent&gt;   &lt;xs:extension base="Q1Len100TextContentType" /&gt; &lt;/xs:simpleContent&gt; &lt;/xs:complexType&gt;  &lt;xs:simpleType name="Q1Len100TextContentType"&gt;   &lt;xs:restriction base="xs:string"&gt; </pre>	To carry the Sub building name, eg: Purple Brick Building,		1	100	Y	xs:string

Data Input Field (from LR Test Harness)	Extract of relevant code from Schema	Description	Mandatory	Min Value	Max Value	Has a pattern constraint	XML Datatype
	<pre> &lt;xs:minLength value="1" /&gt; &lt;xs:maxLength value="100" /&gt; &lt;xs:pattern value=".*\S.*"/&gt; &lt;/xs:restriction&gt; &lt;/xs:simpleType&gt; </pre>						
Street Name	<pre> &lt;xs:element name="StreetName"   type="Q1Len50TextType"   minOccurs="1" maxOccurs="1"&gt;   &lt;xs:documentation&gt;A character string (i.e. a finite set                                 of characters) generally in the form                                 of words of a language. &lt;/xs:element&gt;  &lt;xs:complexType name="Q1Len50TextType"&gt;   &lt;xs:documentation&gt;A character string (i.e. a finite set                                 of characters) generally in the form                                 of words of a language. &lt;xs:simpleContent&gt;   &lt;xs:extension base="Q1Len50TextContentType" /&gt; &lt;/xs:simpleContent&gt; &lt;/xs:complexType&gt;  &lt;xs:simpleType name="Q1Len50TextContentType"&gt;   &lt;xs:restriction base="xs:string"&gt;     &lt;xs:minLength value="1" /&gt;     &lt;xs:maxLength value="50" /&gt;     &lt;xs:pattern value=".*\S.*"/&gt; </pre>	To carry the street name	Y	1	50	Y	xs:string

Data Input Field (from LR Test Harness)	Extract of relevant code from Schema	Description	Mandatory	Min Value	Max Value	Has a pattern constraint	XML Datatype
	<pre> &lt;/xs:restriction&gt; &lt;/xs:simpleType&gt; </pre>						
Town Name	<pre> &lt;xs:element name="TownName"   type="Q1Len35TextType"   minOccurs="1" maxOccurs="1"&gt;    &lt;xs:documentation&gt;A character string (i.e. a finite set                         of characters) generally in the form                         of words of a language. &lt;/xs:element&gt;  &lt;xs:complexType name="Q1Len35TextType"&gt;   &lt;xs:documentation&gt;A character string (i.e. a finite set                         of characters) generally in the form                         of words of a language. &lt;xs:simpleContent&gt;   &lt;xs:extension base="Q1Len35TextContentType"   /&gt;   &lt;/xs:simpleContent&gt; &lt;/xs:complexType&gt;  &lt;xs:simpleType name="Q1Len35TextContentType"&gt;   &lt;xs:restriction base="xs:string"&gt;     &lt;xs:minLength value="1" /&gt;     &lt;xs:maxLength value="35" /&gt; </pre>	To carry the town name	Y	1	35	Y	xs:string

Data Input Field (from LR Test Harness)	Extract of relevant code from Schema	Description	Mandatory	Min Value	Max Value	Has a pattern constraint	XML Datatype
	<pre> &lt;xs:pattern value=".*\S.*"/&gt; &lt;/xs:restriction&gt; &lt;/xs:simpleType&gt; </pre>						
Locality	<pre> &lt;xs:element name="Locality"   type="Q1Len35TextType"   minOccurs="0" maxOccurs="1"&gt;   &lt;xs:documentation&gt;A character string (i.e. a finite set                                 of characters) generally in the form                                 of words of a language.   &lt;/xs:element&gt;  &lt;xs:complexType name="Q1Len35TextType"&gt;   &lt;xs:documentation&gt;A character string (i.e. a finite set                                 of characters) generally in the form                                 of words of a language.   &lt;xs:simpleContent&gt;     &lt;xs:extension base="Q1Len35TextContentType"   /&gt;     &lt;/xs:simpleContent&gt;   &lt;/xs:complexType&gt;  &lt;xs:simpleType name="Q1Len35TextContentType"&gt;   &lt;xs:restriction base="xs:string"&gt;     &lt;xs:minLength value="1" /&gt;     &lt;xs:maxLength value="35" /&gt;     &lt;xs:pattern value=".*\S.*"/&gt; </pre>	To carry the Locality		1	35	Y	xs:string

Data Input Field (from LR Test Harness)	Extract of relevant code from Schema	Description	Mandatory	Min Value	Max Value	Has a pattern constraint	XML Datatype
	<pre> &lt;/xs:restriction&gt; &lt;/xs:simpleType&gt; </pre>						
County	<pre> &lt;xs:element name="CountyName"   type="Q1Len35TextType"   minOccurs="0" maxOccurs="1"&gt;   &lt;xs:documentation&gt;A character string (i.e. a finite set                                 of characters) generally in the form                                 of words of a language. &lt;/xs:element&gt;  &lt;xs:complexType name="Q1Len35TextType"&gt;   &lt;xs:documentation&gt;A character string (i.e. a finite set                                 of characters) generally in the form                                 of words of a language. &lt;xs:simpleContent&gt;   &lt;xs:extension base="Q1Len35TextContentType" /&gt;   &lt;/xs:simpleContent&gt; &lt;/xs:complexType&gt;  &lt;xs:simpleType name="Q1Len35TextContentType"&gt;   &lt;xs:restriction base="xs:string"&gt;     &lt;xs:minLength value="1" /&gt;     &lt;xs:maxLength value="35" /&gt;     &lt;xs:pattern value=".*\S.*"/&gt; </pre>	To carry the county name		1	35	Y	xs:string



Data Input Field (from LR Test Harness)	Extract of relevant code from Schema	Description	Mandatory	Min Value	Max Value	Has a pattern constraint	XML Datatype
	<pre> &lt;/xs:restriction&gt; &lt;/xs:simpleType&gt; </pre>						
Local Authority	<pre> &lt;xs:element name="LocalAuthority"   type="Q1Len50TextType"   minOccurs="1" maxOccurs="1"&gt;   &lt;xs:documentation&gt;A character string (i.e. a finite set                         of characters) generally in the form                         of words of a language. &lt;/s:element&gt;  &lt;xs:complexType name="Q1Len50TextType"&gt;   &lt;xs:documentation&gt;A character string (i.e. a finite set                         of characters) generally in the form                         of words of a language. &lt;xs:simpleContent&gt;   &lt;xs:extension base="Q1Len50TextContentType" /&gt; &lt;/xs:simpleContent&gt; &lt;/xs:complexType&gt;  &lt;xs:simpleType name="Q1Len50TextContentType"&gt;   &lt;xs:restriction base="xs:string"&gt;     &lt;xs:minLength value="1" /&gt;     &lt;xs:maxLength value="50" /&gt;     &lt;xs:pattern value=".*\S.*"/&gt; </pre>	To carry the Local Authority Name	Y	1	50	Y	xs:string

Data Input Field (from LR Test Harness)	Extract of relevant code from Schema	Description	Mandatory	Min Value	Max Value	Has a pattern constraint	XML Datatype
	<pre> &lt;/xs:restriction&gt; &lt;/xs:simpleType&gt; </pre>						
OS Map Reference	<pre> &lt;xs:element name="OSMapReference"   type="Q1Len8TextType"   minOccurs="0" maxOccurs="1"&gt;   &lt;xs:documentation&gt;A character string   (i.e. a finite set                                 of characters) generally in the form                                 of words of a language.   &lt;/xs:element&gt; &lt;/xs:sequence&gt;  xs:complexType name="Q1Len8TextType"&gt;   &lt;xs:documentation&gt;A character string   (i.e. a finite set                                 of characters) generally in the form                                 of words of a language. &lt;xs:simpleContent&gt;   &lt;xs:extension base="Q1Len8TextContentType"   /&gt;   &lt;/xs:simpleContent&gt; &lt;/xs:complexType&gt;  &lt;xs:simpleType name="Q1Len8TextContentType"&gt;   &lt;xs:restriction base="xs:string"&gt;     &lt;xs:minLength value="1" /&gt;     &lt;xs:maxLength value="8" /&gt; </pre>	Carries the OS map reference		1	8	Y	xs:string

Data Input Field (from LR Test Harness)	Extract of relevant code from Schema	Description	Mandatory	Min Value	Max Value	Has a pattern constraint	XML Datatype
	<pre>&lt;xs:pattern value=".*\S.*"/&gt; &lt;/xs:restriction&gt; &lt;/xs:simpleType&gt;</pre>						
<i><b>SIM - Address with Postcode</b></i>	<pre>&lt;xs:complexType name="Q1AddressWithPostcodeType"&gt;   &lt;xs:sequence&gt;</pre>	Contents of type as above with extra postcode element.					

Data Input Field (from LR Test Harness)	Extract of relevant code from Schema	Description	Mandatory	Min Value	Max Value	Has a pattern constraint	XML Datatype
Postcode	<pre> xs:element name="PostcodeZone"   type="Q1PostcodeZoneType"   minOccurs="1" maxOccurs="1"&gt;   &lt;xs:documentation&gt;The identifier for one or more  properties according to the UK service; a group of letters numbers added to the postal address to assist in the sorting of as defined by the Royal Mail. &lt;/xs:element&gt;  &lt;xs:complexType name="Q1PostcodeZoneType"&gt;   &lt;xs:documentation&gt;The identifier for one or more properties according to the UK postal group of letters and to the postal address the sorting of mail, as Royal Mail.   &lt;xs:sequence&gt;     &lt;xs:element name="Postcode"       type="Q3TextType"       minOccurs="1" maxOccurs="1"&gt;&gt;       &lt;xs:documentation&gt;A full or partial UK Postcode     &lt;/xs:element&gt;   &lt;/xs:sequence&gt; &lt;/xs:complexType&gt;  &lt;xs:complexType name="Q3TextType"&gt;   &lt;xs:documentation&gt;A character string (i.e. a finite set of characters) generally in the form of language. &lt;xs:simpleContent&gt;   &lt;xs:extension base="Q3TextContentType" /&gt; &lt;/xs:simpleContent&gt; &lt;/xs:complexType&gt;  &lt;xs:simpleType name="Q3TextContentType"&gt;   &lt;xs:restriction base="xs:string"&gt;   &lt;xs:pattern value=".*\S.*"/&gt; </pre>	Carries the postcode	Y			Y	xs:string

Data Input Field (from LR Test Harness)	Extract of relevant code from Schema	Description	Mandatory	Min Value	Max Value	Has a pattern constraint	XML Datatype
	<div>&lt;/xs:restriction&gt; &lt;/xs:simpleType&gt;</div>						

Data Input Field (from LR Test Harness)	Extract of relevant code from Schema	Description	Mandatory	Min Value	Max Value	Has a pattern constraint	XML Datatype
Alternative Despatch address	<pre> &lt;xs:complexType name="Q1AlternativeDespatchDetailsType"&gt; &lt;xs:sequence&gt;  &lt;xs:element name="AlternativeDespatchAddress" type="Q1AlternativeDespatchAddressType" minOccurs="0" maxOccurs="1"&gt; &lt;xs:documentation&gt; The type of address to be used on results. &lt;/xs:element&gt;  &lt;xs:complexType name="Q1AlternativeDespatchAddressType"&gt; &lt;xs:choice&gt; &lt;xs:element name="PostalAddress"  type="Q1AlternativePostalAddressType" minOccurs="0" maxOccurs="1"&gt; &lt;xs:documentation&gt; A specific Address that can be used for the delivery of physical mail. &lt;/xs:element&gt; &lt;xs:element name="DXDetails" type="Q1DXDetailsType" minOccurs="0" maxOccurs="1" /&gt;  &lt;/xs:choice&gt; &lt;/xs:complexType&gt; </pre>	Main element enabling/enforcing a choice between postal or DX delivery address.					
Despatch Name	<pre> &lt;xs:element name="AlternativeDespatchName" type="DespatchNameTextContentType" minOccurs="0" maxOccurs="1"&gt; &lt;xs:documentation&gt; Name of firm/company results will be addressed to. &lt;/xs:element&gt;  &lt;xs:simpleType name="DespatchNameTextContentType"&gt; &lt;xs:restriction base="xs:string"&gt; &lt;xs:minLength value="1" /&gt; &lt;xs:maxLength value="70" /&gt; &lt;xs:pattern value="[A-Za-z0-9\s~!&amp;quot;@#\$\$%\(\)\*\+\,\-\\./:;=&amp;gt;\\?\\[\\]\\_\\{\\}\\^&amp;#xa3;]*" /&gt; &lt;/xs:restriction&gt; &lt;/xs:simpleType&gt; </pre>	Words say name of firm/company, however it is possible it could be a private individual		1	70	Y	xs:string

Data Input Field (from LR Test Harness)	Extract of relevant code from Schema	Description	Mandatory	Min Value	Max Value	Has a pattern constraint	XML Datatype
Despatch Reference	<pre> &lt;xs:element name ="AlternativeDespatchReference"   type="Q4TextContentType"   minOccurs="0" maxOccurs="1"&gt;   &lt;xs:annotation&gt;     &lt;xs:documentation&gt; Text reference to be     displayed                                 on     results.   &lt;/xs:documentation&gt;   &lt;/xs:annotation&gt; &lt;/xs:element&gt;  &lt;xs:simpleType name="Q4TextContentType"&gt;   &lt;xs:restriction base="xs:string"&gt;     &lt;xs:minLength value="1" /&gt;     &lt;xs:maxLength value="25" /&gt;     &lt;xs:pattern value="[A-Za-z0-9\s~!&amp;quot;@#\$\$%'\(\)\*\+\,\-\ \.\/:;=&gt;\?\\[\\]\_\\{\}\^&amp;#xa3;]*" /&gt;   &lt;/xs:restriction&gt; &lt;/xs:simpleType&gt; </pre>	Carries a reference for the alternative despatch.		1	25	Y	xs:string
Line 1	<pre> &lt;xs:element name="AddressLine"   type="Q3TextType"   minOccurs="0" maxOccurs="unbounded"&gt;   &lt;xs:annotation&gt;     &lt;xs:documentation&gt;A line of the     address for the     alternative despatch location.   &lt;/xs:documentation&gt;   &lt;/xs:annotation&gt; &lt;/xs:element&gt;  &lt;xs:complexType name="Q3TextType"&gt;   &lt;xs:annotation&gt;     &lt;xs:documentation&gt;A character string     (i.e. a finite set                                 of     characters) generally in the form of                                 words of a     language.   &lt;/xs:documentation&gt;   &lt;/xs:annotation&gt;   &lt;xs:simpleContent&gt;     &lt;xs:extension base="Q3TextContentType" /&gt;   &lt;/xs:simpleContent&gt; &lt;/xs:complexType&gt;  &lt;xs:simpleType name="Q3TextContentType"&gt;   &lt;xs:restriction base="xs:string"&gt;     &lt;xs:pattern value=".*\S.*"/&gt;   &lt;/xs:restriction&gt; &lt;/xs:simpleType&gt; </pre>	Start of the alternative despatch address				y	xs:string
Line 2	As line 1						

Data Input Field (from LR Test Harness)	Extract of relevant code from Schema	Description	Mandatory	Min Value	Max Value	Has a pattern constraint	XML Datatype
Line 3	As line 1						
Line 4	As line 1						
Line 5	As line 1						
Postcode	<pre> &lt;xs:element name="Postcode"   type="Q3TextType"   minOccurs="0" maxOccurs="1"&gt;   &lt;xs:annotation&gt;     &lt;xs:documentation&gt;A valid postcode for the alternative address.     &lt;/xs:documentation&gt;   &lt;/xs:annotation&gt; &lt;/xs:element&gt;  &lt;xs:complexType name="Q3TextType"&gt;   &lt;xs:annotation&gt;     &lt;xs:documentation&gt;A character string (i.e. a finite set of characters) generally in the form of words of a language.     &lt;/xs:documentation&gt;   &lt;/xs:annotation&gt; &lt;xs:simpleContent&gt;   &lt;xs:extension base="Q3TextContentType" /&gt; &lt;/xs:simpleContent&gt; &lt;/xs:complexType&gt;  &lt;xs:simpleType name="Q3TextContentType"&gt;   &lt;xs:restriction base="xs:string"&gt;     &lt;xs:pattern value=".*\S.*"/&gt;   &lt;/xs:restriction&gt; &lt;/xs:simpleType&gt; </pre>	Field to carry the postcode.				Y	xs:string
OR							



Data Input Field (from LR Test Harness)	Extract of relevant code from Schema	Description	Mandatory	Min Value	Max Value	Has a pattern constraint	XML Datatype
DX number	<pre>&lt;xs:element name="DXNumber"   type="Q3TextType"   minOccurs="1" maxOccurs="1"&gt;   &lt;xs:annotation&gt;     &lt;xs:documentation&gt;A unique     identifier for a delivery     point for     organisations using the     Document     Exchange service.   &lt;/xs:documentation&gt;   &lt;/xs:annotation&gt; &lt;/xs:element&gt;  &lt;xs:complexType name="Q3TextType"&gt;   &lt;xs:annotation&gt;     &lt;xs:documentation&gt;A character string     (i.e. a finite set     of     characters) generally in the form of     words of a     language.   &lt;/xs:documentation&gt;   &lt;/xs:annotation&gt; &lt;xs:simpleContent&gt;   &lt;xs:extension base="Q3TextContentType" /&gt; &lt;/xs:simpleContent&gt; &lt;/xs:complexType&gt;  &lt;xs:simpleType name="Q3TextContentType"&gt;   &lt;xs:restriction base="xs:string"&gt;     &lt;xs:pattern value=".*\S.*"/&gt;   &lt;/xs:restriction&gt; &lt;/xs:simpleType&gt;</pre>	Field to carry the DX number				Y	xs:string

Data Input Field (from LR Test Harness)	Extract of relevant code from Schema	Description	Mandatory	Min Value	Max Value	Has a pattern constraint	XML Datatype
DX exchange	<pre>&lt;xs:element name="ExchangeName"   type="Q3TextType"   minOccurs="1"  maxOccurs="1"&gt;   &lt;xs:annotation&gt;     &lt;xs:documentation&gt;A character string     (i.e. a finite set                                 of characters) generally in the form of                                 words of a language.     &lt;/xs:documentation&gt;   &lt;/xs:annotation&gt; &lt;/xs:element&gt;  &lt;xs:complexType name="Q3TextType"&gt;   &lt;xs:annotation&gt;     &lt;xs:documentation&gt;A character string     (i.e. a finite set                                 of characters) generally in the form                                 of words of a language.     &lt;/xs:documentation&gt;   &lt;/xs:annotation&gt; &lt;xs:simpleContent&gt;   &lt;xs:extension base="Q3TextContentType" /&gt; &lt;/xs:simpleContent&gt; &lt;/xs:complexType&gt;  &lt;xs:simpleType name="Q3TextContentType"&gt;   &lt;xs:restriction base="xs:string"&gt;     &lt;xs:pattern value=".*\S.*"/&gt;   &lt;/xs:restriction&gt; &lt;/xs:simpleType&gt;</pre>	Field to carry the DX exchange				Y	xs:string