



Mobile Phone Security





Dr. Digvijaysinh Rathod
Associate Professor
(Cyber Security and Digital Forensics)
Institute of Forensic Science
Gujarat Forensic Sciences University

digvijay.rathod@gfsu.edu.in

Android boot process



Reference



Android boot process

✓ When an Android device is first powered on, there is a sequence of steps that are executed, helping the device to load necessary firmware, OS, application data, and so on into memory.

Android boot process

✓ The sequence of steps involved in Android boot process is as follows:

✓ 1. Boot ROM code execution

✓ 2. The boot loader


✓ 3. The Linux kernel

✓ 4. The init process


✓ 5. Zygote and Dalvik

✓ 6. The system server

Android boot process



Android boot process




execution shifts to the code loaded into the RAM.

Android boot process – Boot Loader

- ✓ The boot loader is a piece of program that is executed before the operating system starts to function.
- ✓ there are two stages—
 - ✓ initial program load (IPL)
 - ✓ second program load (SPL).

Android boot process – Boot Loader



Android boot process – Linux Kernal

- ✓ The Linux kernel is the heart of the Android operating system and is responsible for **process management**, **memory management**, and enforcing security on the device.
- ✓ After the kernel is loaded,
- ✓ it mounts the root file system (rootfs) and provides access to system and user data.

1. When the memory management units and **caches have been initialized**, the system can use virtual memory and launch user space processes.
2. The kernel will look in the **rootfs for the init process** and launch it as the **initial user space process**.

Android boot process – The init process

1. The **init** is the very **first process** that starts and is the root process of all other processes - (**init.rc**).
2. The init process will **parse** the **init.rc** script and launch the system service processes.
3. At this stage, you will see the **Android logo** on the device screen.

Android boot process – Zygote and Dalvik

- ✓ Zygote is one of the first init processes created after the device boots.
- ✓ It initializes the Dalvik virtual machine and tries to create multiple instances to support each android process.
- ✓ Zygote facilitates using a shared code across the VM, thus helping to save the memory and reduce the burden on the system.

Android boot process – System server

- ✓ All the core features of the device such as telephony, network, and other important functions, are started by the system server

Android boot process – System server

- ✓ The following core services are started in this process:
- ✓ Start Power Manager
- ✓ Create Activity Manager
- ✓ Start Telephony Registry
- ✓ Start Package Manager
- ✓ Set Activity Manager Service as System Process
- ✓ Start Context Manager etc.,



Mobile Phone Security



Dr. Digvijaysinh Rathod
Associate Professor
(Cyber Security and Digital Forensics)
Institute of Forensic Science
Gujarat Forensic Sciences University

digvijay.rathod@gfsu.edu.in