



Mobile Phone Security





Dr. Digvijaysinh Rathod
Associate Professor
(Cyber Security and Digital Forensics)
Institute of Forensic Science
Gujarat Forensic Sciences University

digvijay.rathod@gfsu.edu.in

Intent



Reference




www.developer.google.com

<https://data-flair.training/blogs/android-service-tutorial/>

The application framework : Intent

✓ There are two types of intents:

1. **Explicit** This intent satisfies the request within the application component. It takes the fully qualified class name of activities or services that we want to start.
2. **Implicit Intent:** This intent does not specify the component name. It invokes the component of another app to handle it.



Intent

- ✓ **Intent** – Communication object.
- ✓ Intent Filter tells Android that which activity handle which action.
- ✓ Whenever Android is given an Intent, It has to figure out which activity or activities can handles it.
- ✓ This process is known as Intent Resolution.

The application framework : Intent

✓ There are two types of intents:

1. **Explicit** This intent satisfies the request within the application component. It takes the fully qualified class name of activities or services that we want to start.

Syntax

Starting the Activity

```
Intent intent = new Intent(getApplicationContext(), ActivityT  
wo.class);  
  
startActivity(intent);
```

The application framework : Intent

- ✓ There are two types of intents:

Syntax

Starting the Service

```
Intent intent = new Intent(this, HelloService.class);  
startService(intent);
```

Syntax

Delivering Broadcast Receive

```
Intent intent = new Intent ("unique name");  
context.sendBroadcast(intent);
```

- 1. Implicit Intent:** This intent does not specify the component name. It invokes the component of another app to handle it.

Syntax

Starting the Activity

```
Intent intent = new Intent();
```

```
intent.setAction(Intent.ACTION_DIAL);
```

```
intent.setAction(Intent.ACTION_VIEW);
```

```
intent.setAction(Intent.ACTION_CALL);
```


The application framework : Intent



The application framework : Intent

✓ Demonstration of two project

(Intro_demo_android_master)

1. Explicit Intent
2. Implicit Intent

Ref: https://github.com/codepath/intro_android_demo



Mobile Phone Security



Dr. Digvijaysinh Rathod
Associate Professor
(Cyber Security and Digital Forensics)
Institute of Forensic Science
Gujarat Forensic Sciences University

digvijay.rathod@gfsu.edu.in

Intent Component & Intent Filter


The application framework : Intent

```
Intent intent = new Intent();
```

```
intent.setAction(Intent.ACTION_DIAL);
```

```
intent.setAction(Intent.ACTION_VIEW);
```

```
intent.setAction(Intent.ACTION_CALL);
```



The application framework : Intent

```
Intent i = new Intent(android.content.Intent.ACTION_VIEW,  
    Uri.parse("http://www.example.com"));  
startActivity(i);
```



```
<activity android:name="com.gfsu.intentfilter_demo.CustomActivity_1">  
  <intent-filter>  
    <action android:name="android.intent.action.VIEW" />  
    <action android:name="com.gfsu.intentfilter_demo.LAUNCH" />  
    <category android:name="android.intent.category.DEFAULT" />  
    <category android:name="android.intent.category.BROWSABLE" />  
    <data android:scheme="http" />  
  </intent-filter>  
</activity>  
</application>
```

```
Intent i = new Intent("com.gfsu.intentfilter_demo.LAUNCH",  
    Uri.parse("http://www.example.com"));  
startActivity(i);
```



```
<activity android:name="com.gfsu.intentfilter_demo.CustomActivity_2">  
  <intent-filter>  
    <action android:name="android.intent.action.VIEW" />  
    <action android:name="com.gfsu.intentfilter_demo.LAUNCH" />  
    <category android:name="android.intent.category.DEFAULT" />  
    <category android:name="android.intent.category.BROWSABLE" />  
    <data android:scheme="https" />  
  </intent-filter>  
</activity>  
</application>
```

✓ Intent Filters

- ✓ Basically, Intent Filters can define the **behavior of Intents** using three Elements, that are-
- ✓ <actions> – Action name defines the intent action that it'll accept.
- ✓ <data> – Data defines the data that is acceptable.
- ✓ <category> – Category defines the name of the Intent Category that is acceptable.

✓ Intent Filters

- ✓ You have seen how an Intent has been used to call an another activity.
- ✓ Android OS uses filters to pinpoint the set of Activities, Services, and Broadcast receivers that can handle the Intent with help of **specified set of action, categories, data scheme** associated with an Intent.
- ✓ You will use **<intent-filter>** element in the manifest file to list down actions, categories and data types associated with any activity, service, or broadcast receiver.

The application framework : Intent

- ✓ **Intent Filters**
- ✓ Demo (IntentFilter_demo)

The application framework : Intent

- ✓ Any Intent object contains the following six things :
 1. Component Name
 2. Action
 3. Data
 4. Category
 5. Extras
 6. Flag

The application framework : Intent

- ✓ Any Intent object contains the following six things :

1. **Component Name:**

The intent object holds the name of the component of the Android application. Using component names, the system delivers an intent to a particular application component.

- ✓ `setComponent()`
- ✓ `setClass()`
- ✓ `setClassName()`
- ✓ Demo of the application (ImplicitIntentOne.apk)

Ref: <https://www.codota.com/code/java/methods/android.content.Intent/setComponent>

- ✓ Any Intent object contains the following six things :

2. Action

Action defines the general task that is to be performed on components. Now, these actions directly target Activities, Services or Broadcast Receivers. Let's see a few actions that an intent object stores:

The application framework : Intent

- ✓ Any Intent object contains the following six things :

2. Action

- ✓ ACTION_VIEW content://contacts/people/1 -- Display information about the person whose identifier is "1".
- ✓ ACTION_DIAL content://contacts/people/1 -- Display the phone dialer with the person filled in.
- ✓ ACTION_DIAL tel:123 -- Display the phone dialer with the given number filled in.

Ref: <https://developer.android.com/reference/android/content/Intent>

- ✓ Any Intent object contains the following six things :

2. Action

- ✓ ACTION_VIEW tel:123 -- Display the phone dialer with the given number filled in. Note how the VIEW action does what is considered the most reasonable thing for a particular URI.
- ✓ ACTION_EDIT content://contacts/people/1 -- Edit information about the person whose identifier is "1".

- ✓ Any Intent object contains the following six things :

2. Action

- ✓ ACTION_VIEW content://contacts/people/ -- Display a list of people, which the user can browse through. This example is a typical top-level entry into the Contacts application, showing you the list of people.

- ✓ Any Intent object contains the following six things :

3. Category

- ✓ This contains some additional information about what kind of object should hold the intent. An intent object can contain any number of type of categories.
- ✓ This field is optional in an IntentObject.

- ✓ Any Intent object contains the following six things :
 3. **Category** : Some of the categories included are as follows :
 - ✓ BROWSABLE: The target components can be invoked in browsers to display data or message.
 - ✓ ALTERNATIVE: This means the component should be added in the list of alternative actions that the user performs on some data.
 - ✓ GADGET: This activity can be added inside some other components that host the gadgets.

The application framework : Intent

- ✓ Any Intent object contains the following six things :
 - 3. **Category** : Some of the categories included are as follows :
 - ✓ HOME: This displays the home page of the user's device.
 - ✓ LAUNCHER: The target can be an initial task and listed on the top of the application launcher.



Mobile Phone Security



Dr. Digvijaysinh Rathod
Associate Professor
(Cyber Security and Digital Forensics)
Institute of Forensic Science
Gujarat Forensic Sciences University

digvijay.rathod@gfsu.edu.in