

Assignment 0

Your last recorded submission was on 2024-01-17, 16:49

IST

1) 1 point

Which of the following is/are example(s) of distributed systems?

- a. Web browser
- b. E-commerce platforms
- c. Amazon Web Services
- d. Email


- ☐ a.
- ☒ b.
- ☒ c.
- ☐ d.

Yes, the answer is correct.

Score: 1

Accepted Answers:

b.
c.



2) 1 point

Consider the fork() system call in Unix-based operating systems. How many processes are created from the following executions of the fork() system call?

```
int main() {  
    fork();  
    fork();  
    return 0;  
}
```

- ☐ a.
- ☒ b.
- ☐ c.
- ☐ d.

Yes, the answer is correct.

Score: 1

Accepted Answers:

b.

3) 1 point

What is the output of the following piece of code written in C programming language?

```
int swap(int a, int b) {  
    int temp;  
    temp = a;  
    a = b;  
    b = temp;  
}  
  
int main() {  
    int x = 10, y = 20;  
    swap(x, y);  
    printf("%d %d", x, x);  
    return 0;  
}
```

- ☐ a. 10 20
- ☐ b. 20 10
- ☒ c. 10 10
- ☐ d. 20 20

- ☐ a.
- ☐ b.
- ☒ c.
- ☐ d.

Yes, the answer is correct.

Score: 1

Accepted Answers:

c.

4) 1 point

Which of the following network protocols is used to get the MAC address of a network interface from its IP address?

- a. DNS
- b. ARP
- c. RARP
- d. TELNET

- ☐ a.
- ☒ b.
- ☐ c.
- ☐ d.

Yes, the answer is correct.

Score: 1

Accepted Answers:

b.

5) 1 point

Consider that the IP address of a network is 202.141.80.20 and the subnet mask is 255.255.255.0. How many hosts are supported by this network?

- a. 256
- b. 254
- c. 128
- d. 126

- ☐ a.
- ☒ b.
- ☐ c.
- ☐ d.

Yes, the answer is correct.

Score: 1

Accepted Answers:

b.

6) 1 point

Which of the following is/are used in operating systems to solve the mutual exclusion problems for critical sections?

- a. Semaphore
- b. Spinlocks
- c. Process states
- d. Deadlock detection

- ☒ a.
- ☒ b.
- ☐ c.
- ☐ d.

Yes, the answer is correct.

Score: 1

Accepted Answers:

a.
b.

7) 1 point

What is Belady's anomaly?

- a. Increase in a process's time quanta will increase in deadlock possibility
- b. Increase in a process's time quanta will decrease in deadlock possibility
- c. Increase in the number of pages will increase the page fault
- d. Increase in the number of pages will decrease the page fault

- ☐ a.
- ☐ b.
- ☒ c.
- ☐ d.

Yes, the answer is correct.

Score: 1

Accepted Answers:

c.

8) 1 point

What is the default port address for HTTPS?

- a. TCP port 8080
- b. UDP port 80
- c. TCP port 443
- d. UDP port 443

- ☐ a.
- ☐ b.
- ☒ c.
- ☐ d.

Yes, the answer is correct.

Score: 1

Accepted Answers:

c.

9) 1 point

Which of the following IP addresses cannot be used to host a web server that needs access from a public Internet?

- a. 202.141.80.9
- b. 10.10.178.2
- c. 152.58.9.9
- d. 8.8.8.8

- ☐ a.
- ☒ b.
- ☐ c.
- ☐ d.

Yes, the answer is correct.

Score: 1

Accepted Answers:

b.

10) 1 point

What is the purpose of the connect() system call?

- a. To accept an incoming TCP connection
- b. To accept an incoming UDP connection
- c. To create a TCP connection to a given IP address/Port
- d. To create a UDP connection to a given IP address/Port

- ☐ a.
- ☐ b.
- ☒ c.
- ☐ d.

Yes, the answer is correct.

Score: 1

Accepted Answers:

c.

Check Answers and Submit

Your score is: 10/10

Week 1 : Assignment 1

The due date for submitting this assignment has passed.
Due on 2024-02-07, 23:59 IST.

Assignment submitted on 2024-02-06, 13:46 IST

1) 1 point

What are the features of a hash function?

- a. Puzzle-friendly
- b. Collision-resistance
- c. Deterministic
- d. Post image resistance

- ☒ a.
- ☒ b.
- ☒ c.
- ☐ d.

Yes, the answer is correct.

Score: 1

Accepted Answers:

- a.
- b.
- c.

2) 1 point

For a SHA 256 bit hash function, the attacker needs to compute how many hash operations in order to find two matching outputs?

- a. 0.3×2^{128}
- b. 0.2×10^{50}
- c. 0.25×2^{130}
- d. 1×2^{256}

- ☐ a.
- ☐ b.
- ☒ c.
- ☐ d.

Yes, the answer is correct.

Score: 1

Accepted Answers:

- c.

3) 1 point

What is the hash value of 6666 if SHA-256 is used?

- a. d7697570462f7562b83e81258de0f1e41832e98072e44c36ec8efec46786e24e
- b. d7597570462f7562b83e81258de0g1e41832e98072e44c36ec8efec46786e24e
- c. c7697570462f7562b83e81258de0f1c41832e98072e44c36ec8efec46786e24e
- d. d7697570462f7562m83e81258de0f1e41832e98072e44c36ec8efec46786e24es

- ☒ a.
- ☐ b.
- ☐ c.
- ☐ d.

Yes, the answer is correct.

Score: 1

Accepted Answers:

- a.

4) 1 point

Which of the statements below is/are true for decentralized distributed systems?

- a. Players may or may not trust each other
- b. Players must trust each other
- c. Central body should govern the communication
- d. None of the above

- ☒ a.
- ☐ b.
- ☐ c.
- ☐ d.

Yes, the answer is correct.

Score: 1

Accepted Answers:

- a.

5) 1 point

Miner nodes only execute new transactions but can not verify previous transaction hash?

- a. True
- b. False

- ☐ a.
- ☒ b.

Yes, the answer is correct.

Score: 1

Accepted Answers:

- b.

6) 1 point

Which of the following is/are true for blockchains?

- a. Works based on Push technique
- b. Existing data can be deleted easily
- c. Tamper-proof
- d. None of the above

- ☐ a.
- ☐ b.
- ☒ c.
- ☐ d.

Partially Correct.

Score: 0.5

Accepted Answers:

- a.
- c.

7) 1 point

Where are the ledger logs stored in a blockchain?

- a. On a SQL Database
- b. On a central immutable ledger
- c. On a metadata table
- d. In ledger of each peer

- ☐ a.
- ☐ b.
- ☐ c.
- ☒ d.

Yes, the answer is correct.

Score: 1

Accepted Answers:

- d.

8) 1 point

Which of the following is an avalanche effect to a cryptographic hash function?

- a. given the same message the hash function would not return the same hash
- b. it is not very difficult to generate the original message from the hash
- c. a small change in the message, impacts large change the hash value
- d. None of the above

- ☐ a.
- ☐ b.
- ☒ c.
- ☐ d.

Yes, the answer is correct.

Score: 1

Accepted Answers:

- c.

9) 1 point

Genesis blocks may not contain the

- a. First transaction
- b. First transaction block
- c. Last transaction block
- d. None of the above

- ☐ a.
- ☐ b.
- ☒ c.
- ☐ d.

Yes, the answer is correct.

Score: 1

Accepted Answers:

- c.

10) 1 point

Which of the below is/are blockchain based app examples?

- a. Cross-border payments
- b. Supply chain
- c. Anti-money laundering tracking system
- d. UTXO

- ☒ a.
- ☒ b.
- ☒ c.
- ☐ d.

Yes, the answer is correct.

Score: 1

Accepted Answers:

- a.
- b.
- c.

Week 2 : Assignment 2

The due date for submitting this assignment has passed.
Due on 2024-02-07, 23:59 IST.

Assignment submitted on 2024-02-07, 22:18 IST

1)

Alice employs the RSA cryptosystem with the prime numbers $p = 7$ and $q = 17$ to derive her public and private keys. Given that Alice's public key is 11, her corresponding private key is _____.

35

Yes, the answer is correct.

Score: 1

Accepted Answers:

(Type: String) 35

1 point

2)

0 points

Bob wishes to send a lengthy message to Alice with the requirement that Alice can verify its origin and Bob cannot later disown the message. They also want to ensure the confidentiality of the message. Alice and Bob decide to employ public key cryptography and cryptographic hashing techniques. Let the key pairs for Alice and Bob be (Pub A, Pri A) and (Pub B, Pri B) respectively, and let E, D, and H denote the encryption, decryption, and hash functions respectively. M represents the message, and H(M) is its digest. Which of the following outlines the correct sequence of steps for Alice to send the digitally signed message?

- i. At Bob: $M' = E(M, K_{pubA})$
- ii. At Alice: $M = E(M', K_{priA})$
- iii. Bob sends the message M' to Alice
- iv. The signature along with the message is sent to Alice (M, M')
- v. Bob: $M' = E(M, K_{priB})$
- vi. Signing the message with his private key: $S = E(H(M), K_{priB})$
- vii. $M = E(M', K_{pubB})$

- a. v, vii, ii, i, iii, iv, vi
- b. i, iii, ii, v, iv, vii, vi
- c. i, ii, iii, iv, v, vi, vii
- d. vii, vi, v, iv, iii, ii, i

- ☐ a.
- ☒ b.
- ☐ c.
- ☐ d.

Yes, the answer is correct.

Score: 0

Accepted Answers:

b.

3)

1 point

The act of digitally signing transactions by the sender in Blockchain ensures the resolution of repudiation/verifiability problems.

- a. True
- b. False

- ☒ a.
- ☐ b.

Yes, the answer is correct.

Score: 1

Accepted Answers:

a.

4)

1 point

Which of the following is used to point to a block in the blockchain:

- a. Hash Pointer
- b. User ID
- c. Transaction ID
- d. Timestamp

- ☒ a.
- ☐ b.
- ☐ c.
- ☐ d.

Yes, the answer is correct.

Score: 1

Accepted Answers:

a.

5)

1 point

Suppose you have 6 data points -- A to F. The post-order traversal of the Merkle Tree is given by (here A means hash of A, DC means the combined hash of D and C, and so on):

- a. {ABCDEFEF, ABCD, EFEF, AB, CD, EF, EF, A, B, C, D, E, F}
- b. {A, AB, B, C, D, CD, ABCD, E, F, EF, ABCDEF}
- c. {A, B, AB, C, D, CD, ABCD, E, F, EF, GH, EFGH, ABCDEFGH}
- d. {A, B, AB, C, D, CD, ABCD, E, F, EF, EF, EFEF, ABCDEFEF}

- ☐ a.
- ☐ b.
- ☐ c.
- ☒ d.

Yes, the answer is correct.

Score: 1

Accepted Answers:

d.

6)

0 points

Which of the following is true for using a digital signature in blockchain?

- a. To check the validity of the source of a transactions
- b. None of the above.
- c. It will ensures that no one can deny of their own transaction
- d. It supports user authentication

- ☒ a.
- ☐ b.
- ☒ c.
- ☒ d.

No, the answer is incorrect.

Score: 0

Accepted Answers:

a.

c.

7)

1 point

Which are the main Consensus Algorithms?

- a. Proof of Work
- b. Proof of Wager
- c. Proof of Stake
- d. Proof of Mining

- ☒ a.
- ☐ b.
- ☒ c.
- ☐ d.

Yes, the answer is correct.

Score: 1

Accepted Answers:

a.

c.

8)

0 points

Why is consensus hard in an asynchronous system?

- I. No notion of global time
- II. faults in network
- III. nodes may crash/ faulty nodes

- a. II, III
- b. I, II
- c. I, III
- d. I, II, III

- ☐ a.
- ☐ b.
- ☐ c.
- ☒ d.

Yes, the answer is correct.

Score: 0

Accepted Answers:

d.

9)

1 point

The Liveliness property ensures the output should be produced within a finite time limit?

- a. False
- b. True

- ☐ a.
- ☒ b.

Yes, the answer is correct.

Score: 1

Accepted Answers:

b.

10)

1 point

Paxos consensus support(s) which of the below properties

- a. Liveliness
- b. Safety
- c. Both
- d. None of the above

- ☐ a.
- ☒ b.
- ☐ c.
- ☐ d.

Yes, the answer is correct.

Score: 1

Accepted Answers:

b.

Week 3 : Assignment 3

The due date for submitting this assignment has passed.
Due on 2024-02-14, 23:59 IST.

Assignment submitted on 2024-02-14, 23:04 IST

1) Inspect and explore block #828070 using [this link](#) to solve the below question. What is the hash of the previous block for Bitcoin block #828070? **1 point**

- a. 0000000000000000000000000246ef8870310474e18acbd1fd8453abb6f367f74816f

b. 0000000000000000000000001d857c22ab5211e2173e4f970eb15f04f64e692587aa1

c. 000000000000000000000000034511894ee97dfa62803bb338335a12e40f6e5a451720

d. 0000000000000000000000002c2c0e69e794d1968382626109ed1d6441020105e7d4e

- ☒ a.

☐ b.

☐ c.

☐ d.

Yes, the answer is correct.
Score: 1

Accepted Answers:

a.

2) **1 point**

- Which of the following Bitcoin scripts will generate a **TRUE** outcome?

a. scriptSig: <sig>
scriptPubKey: <pubKey> OP_DUP OP_HASH256 <pubKeyHash> OP_EQUAL OP_VERIFY OP_CHECKSIG

b. scriptSig: <pubKey>
scriptPubKey: OP_HASH160 <pubKeyHash> OP_EQUAL

c. scriptSig: <pubKey>
scriptPubKey: <pubKey> OP_EQUALVERIFY

d. scriptSig: <sig>
scriptPubKey: <pubKey> OP_CHECKSIG

A. a, b, c
B. c, d
C. a, b, d
D. a, c, d

- ☐ A.

☐ B.

☒ C.

☐ D.

Yes, the answer is correct.
Score: 1

Accepted Answers:

C.

3) **1 point**

- In the Bitcoin block header, the block identifier is calculated

a. Using SHA256 on the current block header

b. Using Double SHA256 on the previous block hash

c. Using Double SHA256 on the Difficulty bits

d. Using Double SHA256 on the current block header

- ☐ a.

☐ b.

☐ c.

☒ d.

Yes, the answer is correct.
Score: 1

Accepted Answers:

d.

4) **1 point**

- If the six-byte difficulty bits in the hexadecimal form are 0x1a05f20881ab, and the target value is calculated using $X * 2^Y$, what are the values for X and Y respectively?

a. X = 0x5f20881ab, Y = 0x1a

b. X = 0x1a05f2, Y = 0x0881ab

c. X = 0x1a05f2, Y = 0x18

d. X = 0x5f20881ab, Y = 0x1a0

- ☒ a.

☐ b.

☐ c.

☐ d.

Yes, the answer is correct.
Score: 1

Accepted Answers:

a.

5) **1 point**

- DLT can be used to maintain financial information only.

a. False

b. True

- ☒ a.

☐ b.

Yes, the answer is correct.
Score: 1

Accepted Answers:

a.

6) **1 point**

- Which one of the following opcodes is needed to remove the second-to-top stack item?

a. OP_DELETE

b. OP_2POP

c. OP_DEQUE

d. OP_NIP

- ☐ a.

☐ b.

☐ c.

☒ d.

Yes, the answer is correct.
Score: 1

Accepted Answers:

d.

7) **1 point**

- Bitcoin Scripting Language:

a. Not Turing Complete

b. Supports Cryptography

c. Queue Based

d. Supports infinite time/memory

- ☒ a.

☒ b.

☐ c.

☐ d.

Yes, the answer is correct.
Score: 1

Accepted Answers:

a.

b.

8) **1 point**

- Permissioned blockchain is regarded as more secure than open blockchain as the participants are known beforehand and pre-authenticated.

a. True

b. False

- ☒ a.

☐ b.

Yes, the answer is correct.
Score: 1

Accepted Answers:

a.

9) **1 point**

- What is nonce?

a. The transaction ID number

b. A miner ASIC chip array

c. The generator point used in elliptic curve cryptography

d. The number miners run through to generate a correct hash

- ☐ a.

☐ b.

☐ c.

☒ d.

Yes, the answer is correct.
Score: 1

Accepted Answers:

d.

10) **1 point**

- Which of these fields is present in a Bitcoin block summary?

a. Nonce

b. Gas Used

c. Gas Limit

d. Private Key of the Sender

- ☒ a.

☐ b.

☐ c.

☐ d.

Yes, the answer is correct.
Score: 1

Accepted Answers:

a.

Week 4 : Assignment 4

The due date for submitting this assignment has passed.

Due on 2024-02-21, 23:59 IST.

Assignment submitted on 2024-02-20, 12:13 IST

1) 1 point

After a hard fork, the emerging two chains are incompatible. True or False?

- a. True
b. False

- ☒ a.
☐ b.

Yes, the answer is correct.

Score: 1

Accepted Answers:

a.

2) 1 point

Which is/are the possible example/s of a double-spending attack?

- a. Sammy has a total of 90 unspent bitcoins from two different transactions with an equal amount of bitcoins each. He tries to send the entire amount at a time each to Nikita and Ayush as transactions
- b. Brady bought a car using 'm' bitcoins. On delivery, the bitcoins are transferred from his wallet to the dealer's wallet.
- c. Karan has 180 unspent bitcoins. He sends the equal amount each to Dev and Tarun one by one
- d. Deepak has 20 unspent bitcoins. He tries to transfer those 20 bitcoins to his two each of his friends simultaneously.

- ☒ a.
☐ b.
☒ c.
☒ d.

No, the answer is incorrect.

Score: 0

Accepted Answers:

a.

d.

3) 1 point

Blocks of a blockchain?

- a. Transaction data
b. Hash
c. Time stamp
d. None of the above

- ☒ a.
☒ b.
☒ c.
☐ d.

Yes, the answer is correct.

Score: 1

Accepted Answers:

a.

b.

c.

4) 1 point

What are some Bitcoin exchanges available in India:

- a. BuyUCoin
b. ZebPay
c. WazirX
- i. a and b
ii. b and c
iii. a and c
iv. a, b and c

- ☐ i
☐ ii
☐ iii
☒ iv

Yes, the answer is correct.

Score: 1

Accepted Answers:

iv

5) 1 point

"We can achieve consensus with a single crash failure in a perfect asynchronous network." This scenario is _____?

- a. Always true
b. Sometimes true
c. Can't say
d. Impossible

- ☐ a.
☐ b.
☐ c.
☒ d.

Yes, the answer is correct.

Score: 1

Accepted Answers:

d.

6) 1 point

What is the correct order of adding a new block to blockchain

- i. Block Mining
ii. Block propagation
iii. Block Flooding
iv. Transaction Flooding
- a. iii, iv, ii, i
b. iv, i, iii, ii
c. iv, iii, ii, i
d. ii, i, iii, iv

- ☐ a.
☒ b.
☐ c.
☐ d.

Yes, the answer is correct.

Score: 1

Accepted Answers:

b.

7) 1 point

Double spending is reusing digital assets intentionally or inadvertently. True or False?

- a. True
b. False

- ☒ a.
☐ b.

Yes, the answer is correct.

Score: 1

Accepted Answers:

a.

8) 1 point

The primary difference between the permissionless and permissioned blockchain is _____?

- a. Hash Algorithms
b. Confidentiality
c. Availability
d. Access control for the participants in the blockchain network

- ☐ a.
☐ b.
☐ c.
☒ d.

Yes, the answer is correct.

Score: 1

Accepted Answers:

d.

9) 1 point

What is an advantage of a permissionless blockchain?

- a. It does not use disinterested third parties to secure blocks, as all participants have a vested interest.
- b. It is open to everyone in the world without permission and approval requirements.
- c. It is more resilient against fraud because it uses federated nodes to combat fraud.
- d. Its networks are built by for-profit companies and the working of the network is guaranteed.

- ☐ a.
☒ b.
☐ c.
☐ d.

Yes, the answer is correct.

Score: 1

Accepted Answers:

b.

10) 1 point

Bitcoin protocol directly runs over

- i. TCP
ii. HTTP
iii. HTTPS
- a. i, ii, iii
b. Only ii
c. Only i
d. All of the above

- ☐ a.
☐ b.
☒ c.
☐ d.

Yes, the answer is correct.

Score: 1

Accepted Answers:

c.

Week 5 : Assignment 5

The due date for submitting this assignment has passed.
Due on 2024-02-28, 23:59 IST.

Assignment submitted on 2024-02-28, 17:12 IST

1) 1 point

The height of the block is the ____ in the chain between it and the genesis block.

- a. Metafiles
- b. Hash
- c. Log size
- d. Number of blocks

- ☐ a.
- ☐ b.
- ☐ c.
- ☒ d.

Yes, the answer is correct.

Score: 1

Accepted Answers:

d.

2) 1 point

What is the CLI command used to send ethers after the nodes have been initialized?

- a. eth.submitTransaction()
- b. eth.sendTransaction()
- c. eth.sendIBANTransaction()
- d. eth.sendRawTransaction()

- ☐ a.
- ☒ b.
- ☐ c.
- ☐ d.

Yes, the answer is correct.

Score: 1

Accepted Answers:

b.

3) 1 point

Which of the following syntax is correct to write data in a smart contract using solidity

- a. myContract.methods.store("55").set()
- b. myContract.methods.write("55").send()
- c. myContract.methods.store("55").send()
- d. myContract.methods.write("55").set()

- ☐ a.
- ☐ b.
- ☒ c.
- ☐ d.

Yes, the answer is correct.

Score: 1

Accepted Answers:

c.

4) 1 point

What is the limitation of using the consensus algorithm Proof of Work (PoW)?

- a. A lot of mining power is wasted as only one gets success in mining at a time
- b. PoW is used for permissioned blockchain
- c. It is used for blockchain mining
- d. High transaction throughput

- ☒ a.
- ☐ b.
- ☐ c.
- ☐ d.

Yes, the answer is correct.

Score: 1

Accepted Answers:

a.

5) 1 point

Which statement(s) is/are true for PoS(Proof of Stake) consensus?

- a. Depends on the work done by the miner
- b. Depends on the amount of crypto currency the miner holds
- c. Provides less protection in general
- d. None of the above

- ☐ a.
- ☒ b.
- ☐ c.
- ☐ d.

Yes, the answer is correct.

Score: 1

Accepted Answers:

b.

6) 1 point

Which of the following is/are applicable for PoET(Proof of Elapsed Time) consensus

- a. Each participant in the blockchain network waits a random amount of time
- b. The first participant to finish becomes the follower for the new block
- c. Trusted execution platform and attestation are used to verify that the proposer has really waited
- d. The first participant to finish becomes the leader for the new block.

- ☒ a.
- ☐ b.
- ☒ c.
- ☒ d.

Yes, the answer is correct.

Score: 1

Accepted Answers:

a.

c.

d.

7) 1 point

Proof of Burn consensus algorithms also consider virtual resources or digital coins for participating in the mining activity?

- a. True
- b. False

- ☒ a.
- ☐ b.

Yes, the answer is correct.

Score: 1

Accepted Answers:

a.

8) 1 point

15 ether equals

- a. $15 \times (10^{16})$ wei
- b. $15 \times (10^{18})$ wei
- c. $15 \times (10^6)$ wei
- d. $15 \times (10^8)$ wei

- ☐ a.
- ☒ b.
- ☐ c.
- ☐ d.

Yes, the answer is correct.

Score: 1

Accepted Answers:

b.

9) 1 point

How an attacker could manipulate the transaction history of an existing blockchain

- a. The attacker hard-forked the network and created a new blockchain network.
- b. The attacker modified the smart contract and recovered the investor's cryptocurrency.
- c. The attacker gained control of more than 51% of the network's computing power.
- d. The attacker gained control of less than 49% of the network's computing power.

- ☐ a.
- ☐ b.
- ☒ c.
- ☐ d.

Yes, the answer is correct.

Score: 1

Accepted Answers:

c.

10) 1 point

What library/API is used for smart contract deployment and invocation from Dapp ?

- a. Contract
- b. web3
- c. admin
- d. eth

- ☐ a.
- ☒ b.
- ☐ c.
- ☐ d.

Yes, the answer is correct.

Score: 1

Accepted Answers:

b.

Week 6 : Assignment 6

The due date for submitting this assignment has passed.
Due on 2024-03-06, 23:59 IST.

Assignment submitted on 2024-03-04, 11:20 IST

1) 1 point

If there are 25 faulty nodes (crash fault) in asynchronous CFT, at least how many nodes needed to reach consensus

a. 48

b. 49

c. 50

d. 51

- ☐ a.
- ☐ b.
- ☐ c.
- ☒ d.

Yes, the answer is correct.

Score: 1

Accepted Answers:

d.

2) 1 point

In Paxos, a node can have only one role among the three roles at a time. True or False

- a. False
- b. True

- ☒ a.
- ☐ b.

Yes, the answer is correct.

Score: 1

Accepted Answers:

a.

3) 1 point

If there are 25 faulty nodes in, at least how many nodes needed to reach consensus in the Byzantine Fault Tolerance (BFT) system.

- a. 72
- b. 76
- c. 77
- d. 79

- ☐ a.
- ☒ b.
- ☐ c.
- ☐ d.

Yes, the answer is correct.

Score: 1

Accepted Answers:

b.

4) 0 points

Which are the properties of an asynchronous consensus:

- a. Validity
- b. Agreement
- c. Termination
- d. Integrity

- ☒ a.
- ☒ b.
- ☒ c.
- ☒ d.

Yes, the answer is correct.

Score: 0

Accepted Answers:

a.

b.

c.

d.

5) 1 point

Can we reach a consensus when there is one commander, one good lieutenant, and one faulty lieutenant in a Byzantine Generals Problem. Yes, or No?

- a. Yes
- b. No

- ☐ a.
- ☒ b.

Yes, the answer is correct.

Score: 1

Accepted Answers:

b.

6) 1 point

Which are the examples of the synchronous consensus techniques?

- a. RAFT
- b. PAXOS
- c. Byzantine General Model
- d. Practical Byzantine General Model

- ☒ a.
- ☒ b.
- ☒ c.
- ☒ d.

Yes, the answer is correct.

Score: 1

Accepted Answers:

a.

b.

c.

d.

7) 1 point

Suppose you execute your tasks distributedly from six different systems at six different locations. For maintaining the consensus among the systems, you are using the BFT model. You found that one system is permanently failed due to a hardware fault and another system is compromised by an attacker. Does your system correctly work at all?

- a. No
- b. Yes, with the remaining nodes
- c. Yes, with all the nodes

- ☒ a.
- ☐ b.
- ☐ c.

Yes, the answer is correct.

Score: 1

Accepted Answers:

a.

8) 0 points

Which of the statements are true?

- a. Paxos is based on state-machine replication
- b. In Paxos, Proposers and Learners maintain a state of the running epochs
- c. In a Paxos, once a consensus is reached, Paxos cannot progress to another consensus
- d. Paxos works in two rounds

- ☒ a.
- ☐ b.
- ☒ c.
- ☒ d.

Yes, the answer is correct.

Score: 0

Accepted Answers:

a.

c.

d.

9) 0 points

State machine replication-based consensus is used over permissioned blockchains. Select the suitable reason(s)?

- a. The network is closed, and the nodes know each other, hence state replication is possible among the known nodes
- b. Not need to spend power, time, or bitcoin
- c. Machines can behave maliciously, hence consensus is required
- d. State machine replication-based consensus is not recommended to use over permissioned blockchains.

- ☒ a.
- ☒ b.
- ☐ c.
- ☐ d.

Yes, the answer is correct.

Score: 0

Accepted Answers:

a.

b.

10) 1 point

The following code snippet from paxos algorithm belongs to which phase?

```
is the ID the largest I have seen so far, max_id == N?
if yes
    reply with an ACCEPTED message & send ACCEPTED(ID, VALUE) to
    all learners
if no
    do not respond (or respond with a "fail" message)
```

- a. PREPARE-PROMISE
- b. PROPOSE-ACCEPT

- ☐ a.
- ☒ b.

Yes, the answer is correct.

Score: 1

Accepted Answers:

b.

Week 7 : Assignment 7

The due date for submitting this assignment has passed.
Due on 2024-03-13, 23:59 IST.

Assignment submitted on 2024-03-13, 22:45 IST

1) 1 point

Which statement(s) are true about Byzantine Dissemination Quorum:

- a. Any two quorums have at least one correct replica in common
- b. There is always a quorum available with no faulty replicas
- c. Any two quorums have at most one correct replica in common
- d. There is always a quorum available with some faulty replicas

☒ a.

☒ b.

☐ c.

☐ d.

Yes, the answer is correct.

Score: 1

Accepted Answers:

a.

b.

2) 1 point

If you have f number of faulty nodes, then you need at least how many replicas to reach consensus irrespective of crash fault or byzantine fault.

- a. $2f + 1$
- b. $3f + 1$
- c. $f + 1$
- d. $3f$

☐ a.

☒ b.

☐ c.

☐ d.

Yes, the answer is correct.

Score: 1

Accepted Answers:

b.

3) 0 points

What is the correct sequence of operations in PBFT algorithm

- i. Prepare
 - ii. Reply
 - iii. Commit
 - iv. Pre-Prepare
- a. iv, i, ii, iii
 - b. iv, i, iii, i
 - c. i, iv, ii, iii
 - d. I, ii, iv, iii

☐ a.

☒ b.

☐ c.

☐ d.

Yes, the answer is correct.

Score: 0

Accepted Answers:

b.

4) 1 point

PBFT is safe under _____ quorum over an asynchronous environment

- a. $2f + 1$
- b. $3f + 1$
- c. $f + 1$
- d. f

☒ a.

☐ b.

☐ c.

☐ d.

Yes, the answer is correct.

Score: 1

Accepted Answers:

a.

5) 1 point

What are Hyperledger frameworks used for?

- a. Hyperledger frameworks are primarily used for building permissioned blockchains for organizations.
- b. Hyperledger frameworks are primarily used for building public blockchains.
- c. Hyperledger frameworks are used for only building smart contracts for IBM's blockchain.
- d. Hyperledger frameworks are primarily used for building smart contracts for public blockchains

☒ a.

☐ b.

☐ c.

☐ d.

Yes, the answer is correct.

Score: 1

Accepted Answers:

a.

6) 1 point

Which of the following(s) is/are benefits of Blockchain for Business

- a. Reduced transaction time from days to near instantaneous
- b. Removes intermediaries overheads and cost
- c. Enables NewBusiness Models such as IoT Integration into supply chain
- d. All of the above

☐ a.

☐ b.

☐ c.

☒ d.

Yes, the answer is correct.

Score: 1

Accepted Answers:

d.

7) 1 point

Which of the following is an open source, enterprise-grade Permissioned DLT platform

- a. Hyperledger Fabric
- b. Hyperledger Explorer
- c. Hyperledger Burrow
- d. Hyperledger Indy

☒ a.

☐ b.

☐ c.

☐ d.

Yes, the answer is correct.

Score: 1

Accepted Answers:

a.

8) 1 point

Which of the following abstractions in Hyperledger Fabric provide confidentiality to individual ledgers ?

- a. Ordering Services
- b. Peers
- c. Channels
- d. Endorsement Policies

☐ a.

☐ b.

☒ c.

☐ d.

Yes, the answer is correct.

Score: 1

Accepted Answers:

c.

9) 1 point

Suppose there are 5 channels present in a Hyperledger Fabric network, each of them has access to 3 chaincodes A, B and C. How many containers will run in each peer for running this system?

- a. 5
- b. 1
- c. 3
- d. 15

☐ a.

☐ b.

☒ c.

☐ d.

Yes, the answer is correct.

Score: 1

Accepted Answers:

c.

10) 1 point

Hyperledger Fabric only allows Proof of Work consensus to be plugged in to ensure a high degree of trustworthiness. True or False

- a. False
- b. True

☒ a.

☐ b.

Yes, the answer is correct.

Score: 1

Accepted Answers:

a.

Week 8 : Assignment 8

The due date for submitting this assignment has passed

Due on 2024-03-20, 23:50



Assignment submitted on 2024-03-20, 23:14 IST

1) 1 point

Which of the following is an open, scalable consensus algorithm having low transaction throughput?

- a. PoW
- b. PoS
- c. PBFT
- d. PoL

- ☒ a.
- ☐ b.
- ☐ c.
- ☐ d.

Yes, the answer is correct.

Score: 1

Accepted Answers:

a.

2) 1 point

Running a chaincode in hyperledger fabric internally involves the following steps even if all the steps are not explicitly done by the user in the latest versions.

- i. Instantiation of Chaincode of Channel
- ii. Creation of Channel
- iii. Configuring Orderer and Peer nodes
- iv. Adding members to Channel
- v. Installing chaincode on peers

Which of the following sequence of steps is valid?

- a. ii, iv, iii, i
- b. iv, iii, v, i
- c. v, i, ii, iv
- d. iii, v, ii, iv, i

- ☐ a.
- ☐ b.
- ☐ c.
- ☒ d.

Yes, the answer is correct.

Score: 1

Accepted Answers:

d.

3) 1 point

Hyperledger Fabric only allows Proof of Work consensus to be plugged in to ensure a high degree of trustworthiness. True or False

- a. True
- b. False

- ☐ a.
- ☒ b.

Yes, the answer is correct.

Score: 1

Accepted Answers:

b.

4) 1 point

Traditional methods for centralized digital identity management do NOT have which of the following characteristics?

- a. Identity holder can easily decide with whom to share the identity and which part of it
- b. Identity theft can occur and remain undetected
- c. Restricting components of identity to be revealed to different verifiers is difficult
- d. An attacker can capture the presented identity

- ☒ a.
- ☐ b.
- ☐ c.
- ☐ d.

Yes, the answer is correct.

Score: 1

Accepted Answers:

a.

5) 1 point

Which of the following statements is/are FALSE regarding PBFT and PoW?

- a. PoW can be executed over both public and private blockchain networks.
- b. PBFT can be executed over a private blockchain network, but not chosen to be executed over a public blockchain network in general.
- c. PBFT can be generally preferred to be executed for both public and private blockchain networks
- d. PoW can be executed over a private blockchain network but can not be executed over a public blockchain network

- ☒ a.
- ☐ b.
- ☒ c.
- ☒ d.

No, the answer is incorrect.

Score: 0

Accepted Answers:

c.

d.

6) 0 points

Which of the following is/are true for Proof Of Work (PoW) protocol

- a. Generally used in Open environment
- b. Scalable
- c. Transaction Per second (TPS) is low in general
- d. All of the above

- ☐ a.
- ☐ b.
- ☐ c.
- ☒ d.

Partially Correct.

Score: 0

Accepted Answers:

a.

b.

c.

d.

7) 1 point

PBFT has higher transaction throughput than PoW

- a. False
- b. True

- ☐ a.
- ☒ b.

Yes, the answer is correct.

Score: 1

Accepted Answers:

b.

8) 1 point

Which of the below statements is true?

- a. PoW is a non-randomized protocol
- b. Pow can always ensure consensus finality
- c. BFT protocols ensure total ordering of transactions
- d. None of the above

- ☐ a.
- ☐ b.
- ☒ c.
- ☐ d.

Yes, the answer is correct.

Score: 1

Accepted Answers:

c.

9) 1 point

BFT protocol ensures finality in general.

- a. False
- b. True

- ☐ a.
- ☒ b.

Yes, the answer is correct.

Score: 1

Accepted Answers:

b.

10) 1 point

Which of the following is/are true for scalable witness cosigning protocol?

- a. protect authorities and their clients from undetected misuse
- b. ensuring that every authoritative statement is validated
- c. It is used to sign a message by multiple authorities collectively
- d. none of the above

- ☒ a.
- ☒ b.
- ☒ c.
- ☐ d.

Yes, the answer is correct.

Score: 1

Accepted Answers:

a.

b.

c.

Week 9 : Assignment 9

The due date for submitting this assignment has passed.
Due on 2024-03-27, 23:59 IST.

Assignment submitted on 2024-03-27, 21:37 IST

1) 1 point

Which of the following is true about Single Sign-on

- The same identity can be used to access multiple services
- Decentralized providers always maintain the identity of individuals participating in single sign-on
- All individuals use a fixed same identity for every one of them
- All identity holders are also identity providers

- ☐ a.
- ☐ b.
- ☐ c.
- ☐ d.

Yes, the answer is correct.

Score: 1

Accepted Answers:

a.

2) 1 point

Which of the following sequence of steps is valid for Algorand?

- A block is prepared
- Run Byzantine agreement on the block
- Prepare the digital signature and propagate
- Block is propagated through gossiping

- i, ii, iv, iii
- i, ii, iii, iv
- i, iv, ii, iii
- I, iii, ii, iv

- ☐ a.
- ☐ b.
- ☒ c.
- ☐ d.

Yes, the answer is correct.

Score: 1

Accepted Answers:

c.

3) 1 point

Which of the following statements regarding Solidity is true?

- Solidity is compiled to bytecode which is executed by Ethereum Virtual Machine.
- Solidity interpreter executes the program by Ethereum Virtual Machine.
- Solidity interpreter executes smart contracts in Ethereum nodes.
- Solidity is compiled to bytecode which is executed by Ethereum node's interpreter.

- ☒ a.
- ☐ b.
- ☐ c.
- ☐ d.

Yes, the answer is correct.

Score: 1

Accepted Answers:

a.

4) 1 point

Which of the following can be used for setting up Verifiable Credentials?

- Hyperledger Aries
- Litecoin
- Ethereum
- Solidity

- ☒ a.
- ☐ b.
- ☐ c.
- ☐ d.

Yes, the answer is correct.

Score: 1

Accepted Answers:

a.

5) 1 point

Which of the following is true about the selection of the random committee in the Algorand network?

- There is a dedicated node which chooses the nodes to form the committee
- A distributed algorithm decides the list of nodes participating in the committee
- A specific pool of node choose are given the responsibility of forming the committee
- The nodes elect themselves as a committee member by winning a local computation

- ☐ a.
- ☐ b.
- ☐ c.
- ☒ d.

Yes, the answer is correct.

Score: 1

Accepted Answers:

d.

6) 1 point

Which of the following is not a valid distinct component in Distributed Identifiers(DID) Architecture.

- DID Controller
- Verifiable Data Registry
- DID Subject
- DID Randomizer

- ☐ a.
- ☐ b.
- ☐ c.
- ☒ d.

Yes, the answer is correct.

Score: 1

Accepted Answers:

d.

7) 1 point

Consider the following statement - "Say Alice has generated two Distributed Identifiers (DID) DID1 and DID2 for her pairwise relationships maintained in Hyperledger Indy". Which part of the above statement is false with respect to the concepts of Hyperledger Indy?

- Generation of DID by Alice
- Assignment of SEED to Steward
- Acceptance of incoming invitation by Alice
- None of the above

- ☐ a.
- ☒ b.
- ☐ c.
- ☐ d.

No, the answer is incorrect.

Score: 0

Accepted Answers:

d.

8) 1 point

In Verifiable Credential (VC), a claim is a statement about a non participant.

- True
- False

- ☐ a.
- ☒ b.

Yes, the answer is correct.

Score: 1

Accepted Answers:

b.

9) 1 point

Which of the following statement(s) is/are true

- In Hyperledger Indy, any authorised party can read the ledger.
- In Hyperledger Indy, only registered parties and can write to the ledger.

- I
- I, II
- II
- None of the above

- ☐ a.
- ☒ b.
- ☐ c.
- ☐ d.

Yes, the answer is correct.

Score: 1

Accepted Answers:

b.

10) 1 point

Data transfer is an important aspect of interoperability in which of the following blockchains?

- Hyperledger Indy
- Corda
- Hyperledger Fabric
- None

- ☐ a.
- ☒ b.
- ☐ c.
- ☐ d.

No, the answer is incorrect.

Score: 0

Accepted Answers:

c.

Week 10 : Assignment 10

The due date for submitting this assignment has passed.
Due on 2024-04-03, 23:59 IST.

Assignment submitted on 2024-04-02, 12:27 IST

1)

1 point

Which of the following statements is true for PBFT. Choose the best possible answer

a. It requires a core non consensus group

b. For scalability, it always requires $O(n)$ for communication complexity

c. It is not possible to create multiple pseudonymous identities to subvert the 3f+1 requirements of PBFT

d. None of the above

☐

a.

☐

b.

☒

c.

☐

d.

No, the answer is incorrect.

Score: 0

Accepted Answers:

d.

2)

1 point

Alice has an account in the Ethereum network and wants to transfer ETH to Bob who has an account in the bitcoin network. Is it possible to do so?

a. Yes, it is always possible without any external help

b. No it is not possible

c. Yes, possible via a trusted third party

d. None of the above

☐

a.

☐

b.

☒

c.

☐

d.

Yes, the answer is correct.

Score: 1

Accepted Answers:

c.

3)

1 point

Which of the following denotes properties of Hashed Timelock Contracts?

a. If the secret is not revealed, the transaction creator cannot get back the fund even after timeout

b. Spending of fund is blocked till the secret is publicly revealed or timeout occurs

c. If timeout occurs, all the parties have distributed the funds equally

d. Fund goes to the intended fund recipient after timeout occurs If the secret is not revealed

☐

a.

☒

b.

☐

c.

☐

d.

Yes, the answer is correct.

Score: 1

Accepted Answers:

b.

4)

1 point

One of the advantages of centralized TTP-based Asset Transfer is it is very secure and always considered reliable. True or False?

a. True

b. False

☐

a.

☒

b.

Yes, the answer is correct.

Score: 1

Accepted Answers:

b.

5)

1 point

What are some of the issues that exist in Asset Exchange?

a. Synchronization problem among sender and receiver networks

b. Agreement of exchange rates

c. Denial of Service

d. All of the above

☐

a.

☐

b.

☐

c.

☒

d.

Yes, the answer is correct.

Score: 1

Accepted Answers:

d.

6)

1 point

What is an escrow? Select the best possible and concrete answer

a. Escrow is an agreement in which assets are held and distributed when conditions are met

b. Escrow is payment for smart contracts

c. Escrow is a permissioned blockchain

d. Escrow is cost of execution of smart contracts

☒

a.

☐

b.

☐

c.

☐

d.

Yes, the answer is correct.

Score: 1

Accepted Answers:

a.

7)

1 point

Which of the following are guaranteed in the ideal atomic swap protocol ?

a. All swaps will take place only when all parties conform to the protocol

b. If some parties deviate from the protocol, then all conforming party ends up worse off

c. No coalition has an incentive to deviate from the protocol

d. All of the above

☒

a.

☐

b.

☒

c.

☐

d.

Yes, the answer is correct.

Score: 1

Accepted Answers:

a.

c.

8)

1 point

Can Alice send 1 BTC to her own account using a time locked contract.

a. No the target account should be always different from the sender

b. Yes she can send to her own account

c. Only possible if she wants to send more than 1 BTC

d. It depends on the time value mentioned in the contract.

☐

a.

☒

b.

☐

c.

☐

d.

Yes, the answer is correct.

Score: 1

Accepted Answers:

b.

9)

1 point

Suppose Alice has a time locked contract with a target account as:

Funding Contract - 1 BTC

Hash: ...Fa4509

Timeout: 2Δ

What will happen if Alice refuses to reveal the key and timeout occurs?

a. 1 BTC refunded to Alice

b. 1 BTC transferred to target account

c. BTC less than 1 refunded to Alice as Some BTC deducted as penalty.

d. BTC less than 1 transferred to target account

☒

a.

☐

b.

☐

c.

☐

d.

Yes, the answer is correct.

Score: 1

Accepted Answers:

a.

10)

1 point

Which of the following is used as a public permissioned ledger based DID registry?

a. Hyperledger Indy

b. Bitcoin

c. Ethereum

d. Sidetree

☒

a.

☐

b.

☐

c.

☐

d.

Yes, the answer is correct.

Score: 1

Accepted Answers:

a.

Week 11 : Assignment 11

The due date for submitting this assignment has passed.

Due on 2024-04-10, 23:59 IST.

Assignment submitted on 2024-04-10, 23:18 IST

1)

1 point

If an attacker initially populates the victim node's peer tables with attacker's IP addresses in blockchain network, this attack is known as:

- a. Sybil Attack
- b. Eclipse Attack
- c. Selfish Mining Attack
- d. 51% Attack

- ☐ a.
- ☒ b.
- ☐ c.
- ☐ d.

Yes, the answer is correct.

Score: 1

Accepted Answers:

b.

2)

1 point

Which of the following can be used to identify a good blockchain use-case? (Mark multiple options if applied)

- a. Participants
- b. Assets
- c. Transactions
- d. Independent of everything

- ☒ a.
- ☒ b.
- ☐ c.
- ☐ d.

Partially Correct.

Score: 0.66

Accepted Answers:

a.

b.

c.

3)

1 point

Alice is performing an Eclipse Attack, and If her IP replaces another attacker IP, the evicted IP is resent and eventually replaced by honest IP. Is this a valid statement?

- a. Yes
- b. No

- ☒ a.
- ☐ b.

Yes, the answer is correct.

Score: 1

Accepted Answers:

a.

4)

1 point

In a decentralized blockchain network, which scenario poses a significant risk known as the "51% Vulnerability"?

- a. When a majority of users hold more than 51% of the cryptocurrency tokens.
- b. When a single entity or a group controls more than 51% of the network's computing power.
- c. When more than 51% of the nodes in the network experience a temporary outage.
- d. When more than 51% of the transactions in a block are invalid due to cryptographic errors.

- ☐ a.
- ☒ b.
- ☐ c.
- ☐ d.

Yes, the answer is correct.

Score: 1

Accepted Answers:

b.

5)

1 point

Alice possesses 5 Bitcoins and initiates two separate transactions with the same Bitcoin. In which case does the double spending vulnerability occur?

- a. Alice pays for a coffee and a book with the same 5 Bitcoins.
- b. Alice accidentally sends 6 Bitcoins to a friend.
- c. Alice sends 2 Bitcoins to one friend and 3 Bitcoins to another.
- d. Alice checks her wallet balance but forgets to confirm the transaction.

- ☐ a.
- ☐ b.
- ☒ c.
- ☐ d.

No, the answer is incorrect.

Score: 0

Accepted Answers:

a.

6)

1 point

In a selfish mining attack, discovering more blocks by pool develops a longer lead on the public chain, and continues to keep these new blocks _____

- a. Private
- b. Public

- ☒ a.
- ☐ b.

Yes, the answer is correct.

Score: 1

Accepted Answers:

a.

7)

1 point

Which of the following scenarios is NOT a good use case for blockchain technology?

- a. A supply chain network where participants require real-time visibility into the movement and origin of goods.
- b. An online voting system aiming to enhance transparency, reduce fraud, and ensure the integrity of election results.
- c. A centralized banking system seeking to improve transaction speed and reduce costs.
- d. A healthcare system aiming to securely share patient records among different healthcare providers for better coordinated care.

- ☐ a.
- ☐ b.
- ☒ c.
- ☐ d.

Yes, the answer is correct.

Score: 1

Accepted Answers:

c.

8)

1 point

What is a major problem with Proof Of Work?

- a. It is difficult to implement
- b. It is unreliable
- c. Multiple miners have to be rewarded
- d. It is CPU-intensive and consumes enormous amount of power.

- ☐ a.
- ☐ b.
- ☐ c.
- ☒ d.

Yes, the answer is correct.

Score: 1

Accepted Answers:

d.

9)

1 point

In Practical Byzantine Fault Tolerance, ____.

- a. A master node selects the next node that adds the next block
- b. The node with most coins is chosen for adding the next block
- c. The nodes elect a leader and that leader adds the next block
- d. None of the above

- ☐ a.
- ☐ b.
- ☒ c.
- ☐ d.

Yes, the answer is correct.

Score: 1

Accepted Answers:

c.

10)

1 point

Alice places a bulk order for a cryptocurrency, and before it is processed, Bob, who is a miner, inserts his own buy order with a slightly higher price. In which case does the front-running attack occur?

- a. Alice's order is confirmed first due to network congestion.
- b. Bob's order is prioritized and confirmed ahead of Alice's order.
- c. Both Alice and Bob's orders are cancelled due to conflicting transactions.
- d. The network rejects both Alice and Bob's orders, causing delays in confirmation.

- ☐ a.
- ☒ b.
- ☐ c.
- ☐ d.

Yes, the answer is correct.

Score: 1

Accepted Answers:

b.

Week 12 : Assignment 12

The due date for submitting this assignment has passed.
Due on 2024-04-17, 23:59 IST.

Assignment submitted on 2024-04-17, 22:00 IST

1) 1 point

What of the following Indy transaction inserts a DID record in the Indy ledger

- a. INSERT
- b. INSERTDID
- c. NYM
- d. CREATE

- ☐ a.
- ☐ b.
- ☒ c.
- ☐ d.

Yes, the answer is correct.

Score: 1

Accepted Answers:

c.

2) 1 point

Ubin project is based on Blockchain and Distributed Ledger Technology (DLT) for clearing and settlement of payments and securities

- a. True
- b. False

- ☒ a.
- ☐ b.

Yes, the answer is correct.

Score: 1

Accepted Answers:

a.

3) 1 point

Does the information transferred to consumer: Consortium information such as catalog, pricing, etc.

- a. Not sensitive
- b. Sensitive

- ☐ a.
- ☒ b.

No, the answer is incorrect.

Score: 0

Accepted Answers:

a.

4) 1 point

How does an application program interact with the Fabric network?

- a. Application program runs chaincodes which commit data to the ledger.
- b. Application program connects to the Orderer(s) to interact with the Fabric network.
- c. Application program uses the Fabric SDK to connect to a Fabric Peer which in turn connects to the Fabric network.
- d. Application program directly connects to a particular Fabric Channel in the network.

- ☐ a.
- ☐ b.
- ☒ c.
- ☐ d.

Yes, the answer is correct.

Score: 1

Accepted Answers:

c.

5) 1 point

What is the correct order of phases in Project Ubin?

- i. Cross-border Payment versus Payment (PvP)
 - ii. Tokenized SGD
 - iii. Delivery versus Payment (DvP)
 - iv. Re-imagining RTGS
 - v. Enabling Broad Ecosystem Collaboration
- a. i, ii, iii, iv, v
 - b. ii, iv, iii, i, v
 - c. ii, iii, v, vi, i
 - d. i, iii, v, ii, iv

- ☐ a.
- ☐ b.
- ☒ c.
- ☐ d.

No, the answer is incorrect.

Score: 0

Accepted Answers:

b.

6) 1 point

In which of the attacks, end-user consumers can create multiple accounts/identities for accessing the consortium services?

- a. Byzantine faults
- b. Sybil attacks
- c. Impersonation attacks
- d. Sensitive information Leakage

- ☐ a.
- ☒ b.
- ☐ c.
- ☐ d.

Yes, the answer is correct.

Score: 1

Accepted Answers:

b.

7) 1 point

When does Algorand reach a tentative consensus?

- a. During strong synchrony only
- b. During weak synchrony under partial network connectivity only
- c. During both strong synchrony and weak synchrony
- d. During weak synchrony under full network connectivity only

- ☐ a.
- ☐ b.
- ☒ c.
- ☐ d.

Yes, the answer is correct.

Score: 1

Accepted Answers:

c.

8) 1 point

Quorum supports transactions with

- a. Only private state
- b. Only public state
- c. Both private and public state at the same time
- d. Either private or public state for a transaction

- ☐ a.
- ☐ b.
- ☒ c.
- ☐ d.

No, the answer is incorrect.

Score: 0

Accepted Answers:

d.

9) 1 point

Which of the following is true about the selection of the random committee in the Algorand network?

- a. There is a dedicated node which chooses the nodes to form the committee
- b. A distributed algorithm decides the list of nodes participating in the committee
- c. The nodes elect themselves as a committee member by winning a local computation
- d. A specific pool of node choose are given the responsibility of forming the committee

- ☐ a.
- ☒ b.
- ☐ c.
- ☐ d.

No, the answer is incorrect.

Score: 0

Accepted Answers:

c.

10) 1 point

What is the primary function of a channel in a Hyperledger Fabric network?

- a. To validate and order transactions on the blockchain
- b. To restrict access to specific participants in the network
- c. To store the complete history of all transactions
- d. To deploy and execute smart contracts

- ☐ a.
- ☒ b.
- ☐ c.
- ☐ d.

Yes, the answer is correct.

Score: 1

Accepted Answers:

b.