

# Data Analytics using Python

## Week 11 Question Bank Answer

### 1 Explain how to handle missing data in data set?

**Ans.1)** To handle missing data in a dataset, several strategies can be employed as outlined in the provided sources:

#### 1. Identification of Missing Values:

- Missing data can occur due to various reasons like oversight, lack of recording, or unavailability of information.
- Missing values are typically denoted in a matrix using a specific code.

#### 2. Treatment of Missing Data:

- Objects with all missing measurements or variables with only missing values are usually removed as they provide no information.
- For standardized data, mean values are calculated using available data only.
- When computing distances, precautions are taken to consider only available measurements for accurate calculations.

#### 3. Handling Missing Data in Distances:

- Distances between objects are computed by considering available measurements.
- Various methods can be used to address missing distances, such as removing objects, filling in average values, or replacing missing values with means to ensure complete distance calculations.

#### 4. Dealing with Dissimilarities:

- Dissimilarities are non-negative values that indicate how different two objects are.
- Dissimilarities can be computed in different ways, including using subjective ratings or objective measures like Pearson or Spearman correlation coefficients.

#### 5. Strategies for Clustering Analysis:

- Different types of variables like interval scale, binary, categorical, ordinal, and ratio-scaled variables require specific handling in cluster analysis.
- Dissimilarity computation methods vary based on the type of variables, ensuring accurate clustering results.

By following these steps, researchers can effectively manage missing data in a dataset, ensuring the integrity and accuracy of subsequent analyses like cluster analysis.

## 2 Differentiate between symmetric and asymmetric binary variable.

Ans.2)

| Criteria       | Symmetric Binary Variable                                                                | Asymmetric Binary Variable                                                                        |
|----------------|------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------|
| Definition     | Variables where the presence or absence of a characteristic is equally meaningful        | Variables where the presence and absence of a characteristic have different meanings              |
| Meaning        | Both states (presence and absence) are equally informative and interchangeable           | Presence and absence states convey different information and significance                         |
| Example        | Gender (Male/Female) where both categories hold equal importance and are interchangeable | Positive/Negative test results where the presence of a condition is distinct from its absence     |
| Interpretation | The two states are treated symmetrically in terms of their impact and interpretation     | The two states have asymmetric implications, with one state being more significant than the other |
| Application    | Commonly used in scenarios where both states are equally relevant and interchangeable    | Utilized when the presence or absence of a characteristic carries different implications          |

This table summarizes the key differences between symmetric and asymmetric binary variables, highlighting their distinct characteristics and applications.

### 3 What do you mean by categorical variable ? how to find dissimilarity between categorical variables?

**Ans.3)** Categorical variables are a type of variable that can take on more than two states or categories. Unlike binary variables which have only two possible states, categorical variables can have multiple distinct states or categories.

Some key points about categorical variables:

- A categorical variable is a generalization of a binary variable, where the variable can take on more than two states.
- The states of a categorical variable can be denoted by letters, symbols, or a set of integers, but these integers do not represent any specific ordering.
- To compute the dissimilarity between two objects described by categorical variables, the following approach can be used:

1. Let the number of states (categories) of the categorical variable be  $M$ .

2. The dissimilarity between two objects  $i$  and  $j$  can be computed based on the ratio of mismatches:

$$d(i, j) = (p - m) / p$$

Where:

- $m$  is the number of matches (i.e., the number of variables for which  $i$  and  $j$  are in the same state)
- $p$  is the total number of variables

3. Weights can be assigned to increase the effect of  $m$  or to assign greater weight to the matches in variables having a larger number of states.

For example, if we have a categorical variable "test-1" with 4 possible states, and we want to find the dissimilarity between two objects 2 and 1, where object 2 is in state 3 and object 1 is in state 1, the dissimilarity would be calculated as:

$$d(2,1) = (4 - 0) / 4 = 1$$

This shows that the dissimilarity between the two objects is 1, since they are in different states for the single categorical variable.

#### 4 What do you mean by ordinal variable? how to find dissimilarity between ordinal variable?

**Ans.4)** Ordinal variables are a type of categorical variable where the categories have a meaningful order or ranking, but the differences between the categories are not necessarily equal.

Some key points about ordinal variables:

- Ordinal variables have a defined sequence or ranking of the categories, such as "low", "medium", "high".
- The categories can be mapped to numerical ranks (e.g. 1, 2, 3), but these numbers only represent the order, not a quantitative difference.
- Examples of ordinal variables include survey responses on a Likert scale, academic letter grades, and professional ranks like "assistant", "associate", "full" professor.

To compute the dissimilarity between objects described by ordinal variables:

1. For each ordinal variable  $f$ , replace the original values  $x_{if}$  with their corresponding ranks  $r_{if}$ , where  $r_{if} \in \{1, 2, \dots, M_f\}$  and  $M_f$  is the number of ordered states of variable  $f$ .
2. Optionally, standardize the ranks to the range 1 using the formula:  
$$z_{if} = (r_{if} - 1) / (M_f - 1)$$

This normalizes the ranks to a common scale across variables with different numbers of states.
3. Calculate the dissimilarity between objects  $i$  and  $j$  for variable  $f$  using a distance metric like Euclidean distance:  
$$d_{ij}(f) = |z_{if} - z_{jf}|$$
4. The overall dissimilarity between objects  $i$  and  $j$  is then computed as:  
$$d(i, j) = \sqrt{\sum d_{ij}(f)^2 / p}$$

Where  $p$  is the total number of variables.

This approach treats the ordinal variables as interval-scaled after converting to ranks, allowing the use of standard distance metrics to quantify the dissimilarity between objects. The standardization step ensures each ordinal variable contributes equally to the overall dissimilarity.

## 5 What is ratio-scaled variable?

**Ans.5)** A ratio-scaled variable is a type of variable that provides a positive measurement on a nonlinear scale, typically following a specific mathematical formula. These variables are characterized by having a true zero point, meaning that a value of zero indicates the absence of the quantity being measured.

Key points about ratio-scaled variables include:

- They allow for ratios to be formed, making multiplication and division meaningful.
- Common examples of ratio-scaled variables include measurements like weight, height, time, and temperature on the Kelvin scale.
- Ratio-scaled variables often follow a formula like  $xif=A \times Bt$  if  $xif=A \times Bt$ , where  $AA$  and  $BB$  are positive constants, and  $tt$  represents time or another variable.

When computing the dissimilarity between objects described by ratio-scaled variables, there are several methods that can be employed:

1. **Treat as Interval-Scaled Variables:** While not ideal due to potential scale distortion, ratio-scaled variables can be treated similarly to interval-scaled variables.
2. **Apply Logarithmic Transformation:** Transforming ratio-scaled variables using logarithmic functions can help normalize the data for dissimilarity calculations.
3. **Treat as Continuous Ordinal Data:** Assign ranks to the values of ratio-scaled variables and treat these ranks as interval-valued for dissimilarity computations.

By understanding the nature of ratio-scaled variables and applying appropriate transformations, researchers can effectively compute dissimilarities between objects described by these types of variables in cluster analysis and other statistical analyses.

**6 Explain three methods to handle ratio-scaled variables for computing dissimilarity between objects.**

**Ans.6)** There are three main methods to handle ratio-scaled variables when computing the dissimilarity between objects:

**1. Treat Ratio-Scaled Variables as Interval-Scaled:**

- This approach involves treating the ratio-scaled variables like interval-scaled variables when computing dissimilarities.
- However, this is generally not a good choice, as it is likely to distort the scale of the ratio-scaled variables.

**2. Apply Logarithmic Transformation:**

- For a ratio-scaled variable  $f$  with value  $x_{if}$  for object  $i$ , a logarithmic transformation can be applied using the formula:  
 $y_{if} = \log(x_{if})$
- The transformed  $y_{if}$  values can then be treated as interval-scaled for the purpose of dissimilarity computation.
- This logarithmic transformation helps to normalize the ratio-scaled data and make it more suitable for distance-based calculations.

**3. Treat as Continuous Ordinal Data:**

- The ratio-scaled values  $x_{if}$  can be treated as continuous ordinal data, where their ranks are used as interval-valued for dissimilarity computation.
- This approach involves replacing the original ratio-scaled values with their corresponding ranks, which are then standardized to the range 1 before calculating the dissimilarities.

The latter two methods, logarithmic transformation and treating as continuous ordinal data, are generally considered more effective approaches for handling ratio-scaled variables in dissimilarity computations. The choice between these two methods may depend on the specific characteristics of the ratio-scaled variables and the requirements of the application.

## 7 Give the classification of clustering methods

**Ans.7)** The classification of clustering methods can be summarized as follows:

# Clustering Methods

## 1. Partitioning Methods

### 1.1.K-Means

A centroid-based technique that partitions a set of objects into k clusters, aiming to maximize intra-cluster similarity and minimize inter-cluster similarity.

### 1.2.K-Medoids

Similar to K-Means but uses medoids (actual data points) as cluster centers instead of centroids.

## 2. Hierarchical Methods

### 2.1.Aggglomerative

Also known as bottom-up clustering, starts with each object in its own cluster and merges clusters iteratively based on similarity.

### 2.2.Divisive

Top-down clustering that begins with all objects in one cluster and splits clusters based on dissimilarity.

The key points are:

- Partitioning methods organize the objects into k partitions (clusters), where k is a fixed parameter.
- Hierarchical methods create a hierarchical decomposition of the data objects, forming a tree-like structure.
- Hierarchical methods can be further classified into:
  - Agglomerative (bottom-up): Starts with each object in its own cluster and successively merges clusters.
  - Divisive (top-down): Starts with all objects in one cluster and successively splits clusters.

The choice of clustering algorithm depends on the type of data and the specific purpose of the analysis. It is often recommended to try multiple algorithms on the same data, as cluster analysis is primarily used as a descriptive or exploratory tool.

## 8 Explain K-means clustering algorithm.

### Ans.8) K-Means Clustering Algorithm

The K-Means clustering algorithm is a popular method used for partitioning a set of data objects into k clusters based on their features.

Explanation of the K-Means clustering algorithm:

#### 1. Initialization:

- The algorithm starts by randomly selecting k objects from the dataset as the initial cluster centers.
- These initial objects represent the mean value of the objects in each cluster.

#### 2. Assignment:

- Each remaining object is then assigned to the cluster to which it is most similar, based on the distance between the object and the cluster mean.
- The similarity is typically measured using a distance metric like Euclidean distance.

#### 3. Update Cluster Means:

- After assigning all objects to clusters, the algorithm calculates the new mean for each cluster.
- The mean value is recalculated as the average of the objects in the cluster.

#### 4. Iteration:

- Steps 2 and 3 are repeated iteratively until there is no change in the assignment of objects to clusters.
- The algorithm converges when the cluster assignments stabilize.

#### 5. Objective Function:

- The K-Means algorithm aims to minimize the sum of squared errors within each cluster.
- The objective function tries to make the resulting k clusters as compact and separate as possible.

#### 6. Final Result:

- Once the algorithm converges, the final result is a set of k clusters, where each object is assigned to the cluster with the closest mean.

#### 7. Example:

- For instance, in a dataset with two variables, the algorithm iteratively assigns objects to clusters based on their proximity to the cluster centers, updating the means until convergence is achieved.

By following these steps, the K-Means clustering algorithm effectively partitions the data into k clusters, optimizing the intra-cluster similarity and minimizing the inter-cluster similarity based on the mean values of the objects in each cluster.



9 Differentiate between partitioning and hierarchical clustering methods.

Ans.9) Difference Between Partitioning and Hierarchical Clustering Methods

| Criteria             | Partitioning Clustering Method                                                             | Hierarchical Clustering Method                                                                      |
|----------------------|--------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------|
| Definition           | Divides data into k partitions (clusters) where k is predefined.                           | Creates a tree-like structure of clusters, forming a hierarchy of nested clusters.                  |
| Flexibility          | Less flexible as the number of clusters (k) needs to be specified beforehand.              | More flexible as it does not require the number of clusters to be predefined.                       |
| Cluster Formation    | Forms non-overlapping clusters where each object belongs to only one cluster.              | Forms a hierarchy of clusters where objects can belong to multiple levels of clusters.              |
| Algorithm Complexity | Generally computationally less complex compared to hierarchical methods.                   | Can be computationally more complex, especially in agglomerative hierarchical clustering.           |
| Interpretability     | Easier to interpret as the final clusters are distinct and well-defined.                   | Hierarchical structure provides insights into relationships at different levels of granularity.     |
| Scalability          | Can be more scalable for large datasets due to the fixed number of clusters.               | May face scalability challenges with very large datasets due to the hierarchical structure.         |
| Cluster Similarity   | Focuses on optimizing similarity within clusters and dissimilarity between clusters.       | Considers similarity at different levels of the hierarchy, capturing nested relationships.          |
| Use Cases            | Commonly used in scenarios where the number of clusters is known or needs to be specified. | Suitable for exploring relationships at various levels of granularity without predefining clusters. |

By understanding the differences between partitioning and hierarchical clustering methods, researchers can choose the most appropriate approach based on the nature of the data, the desired level of granularity, and the specific objectives of the analysis.

## 10 Compare agglomerative and divisive hierarchical clustering methods.

| Criteria      | Agglomerative Hierarchical Clustering                                                                                                                           | Divisive Hierarchical Clustering                                                                                                                                                    |
|---------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Approach      | Bottom-up strategy that starts with each object in its own cluster and successively merges the closest clusters until all objects are in one cluster.           | Top-down strategy that starts with all objects in one cluster and recursively splits clusters until each object is in its own cluster.                                              |
| Process       | Begins with n clusters (where n is the number of objects) and iteratively merges the two closest clusters, reducing the number of clusters by one in each step. | Begins with one cluster containing all objects and iteratively splits the cluster with the highest dissimilarity until each object is in its own cluster.                           |
| Advantages    | <ul style="list-style-type: none"><li>- Computationally less complex</li><li>- Can handle non-convex and irregularly shaped clusters</li></ul>                  | <ul style="list-style-type: none"><li>- Can potentially correct mistakes made in earlier splitting decisions</li><li>- More flexible in handling different cluster shapes</li></ul> |
| Disadvantages | Once a merge decision is made, it cannot be undone, leading to potential errors in the final clustering.                                                        | <ul style="list-style-type: none"><li>- Computationally more complex, especially for large datasets, as it requires evaluating all possible splits at each step.</li></ul>          |
| Suitability   | Suitable when the number of clusters is not known in advance and the focus is on exploring the hierarchical structure of the data.                              | Suitable when the number of clusters is not known in advance and the focus is on identifying the optimal number of clusters through a top-down approach.                            |

The choice between the agglomerative and divisive hierarchical clustering methods depends on the specific characteristics of the data and the goals of the clustering analysis. Agglomerative methods are generally more efficient and easier to implement, while divisive methods offer more flexibility in handling complex cluster shapes but are computationally more demanding.

## 11 Give the measures for distance between clusters.

**Ans.11)** The measures for distance between clusters in hierarchical clustering methods are typically calculated using various metrics to determine the similarity or dissimilarity between clusters.

Some common measures for distance between clusters include:

### 1. **Single Linkage (Nearest Neighbor):**

- Measures the distance between the closest points of two clusters.
- The distance between two clusters is defined as the minimum distance between any two points in the clusters.

### 2. **Complete Linkage (Farthest Neighbor):**

- Measures the distance between the farthest points of two clusters.
- The distance between two clusters is defined as the maximum distance between any two points in the clusters.

### 3. **Average Linkage:**

- Measures the average distance between all pairs of points in two clusters.
- The distance between two clusters is defined as the average distance between all pairs of points in the clusters.

### 4. **Centroid Linkage:**

- Measures the distance between the centroids of two clusters.
- The distance between two clusters is defined as the distance between the centroids of the clusters.

### 5. **Ward's Method:**

- Minimizes the increase in variance when merging two clusters.
- The distance between two clusters is defined by the increase in the total within-cluster variance when the clusters are merged.

These distance measures play a crucial role in hierarchical clustering algorithms by determining how clusters are merged or split based on their similarity or dissimilarity. The choice of distance measure can significantly impact the clustering results and the structure of the dendrogram formed during hierarchical clustering.

## 12 What is dendrogram?

- Ans.12)** A dendrogram is a tree-like diagram that illustrates the arrangement of the clusters in hierarchical clustering. It displays the relationships between the clusters and objects in a dataset based on their similarity or dissimilarity. In a dendrogram:
- Objects are represented by leaves at the bottom of the tree.
  - Clusters are formed by joining objects or smaller clusters at different levels of the tree.
  - The height of the vertical lines in the dendrogram represents the dissimilarity between clusters or objects: the longer the line, the more dissimilar the clusters are.

Dendrograms are commonly used in hierarchical clustering to visualize the clustering process and help identify the optimal number of clusters based on the structure of the tree. They provide a clear and intuitive representation of the hierarchical relationships between objects and clusters in the dataset.

**OR**

A dendrogram is a tree-like diagram that illustrates the arrangement of the clusters in hierarchical clustering. It provides a visual representation of the relationships and similarities between the objects or clusters in a dataset.

Here are the key details about dendrograms:

### 1. Visualization of Hierarchical Structure:

- The dendrogram displays the hierarchical structure of the clusters, showing how objects are grouped together at different levels of similarity.
- The objects are represented by the leaves (bottom) of the tree, while the internal nodes represent the clusters formed at different stages of the hierarchical clustering process.

### 2. Cluster Merging Process:

- The dendrogram depicts the sequence of merging or splitting of clusters as the hierarchical clustering algorithm progresses.
- The vertical height of the lines in the dendrogram represents the dissimilarity or distance between the merged clusters.
- The longer the vertical line, the greater the dissimilarity between the joined clusters.

### 3. Determining Optimal Number of Clusters:

- By examining the structure of the dendrogram, researchers can identify the appropriate number of clusters to extract from the data.
- This is typically done by looking for "natural" gaps or large increases in the vertical height of the dendrogram, which indicate the optimal number of clusters.

### 4. Interpretation and Analysis:

- Dendrograms provide an intuitive way to visualize the hierarchical relationships between objects and clusters.
- They allow researchers to explore the structure of the data, identify outliers, and understand the similarities and dissimilarities between the objects.
- The dendrogram can be used to guide the selection of the final clustering solution based on the research objectives and the characteristics of the data.

In summary, the dendrogram is a crucial tool in hierarchical clustering, as it enables the visualization and interpretation of the clustering process, facilitating the identification of the optimal number of clusters and the understanding of the underlying data structure.

### 13 Differentiate between k-means and hierarchical clustering methods.

Ans.13)

| Criteria                 | K-Means Clustering                                                                   | Hierarchical Clustering                                                                                      |
|--------------------------|--------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------|
| Approach                 | Partitioning method that divides the data into a pre-specified number of k clusters. | Hierarchical method that creates a tree-like structure of nested clusters.                                   |
| Number of Clusters       | Requires the number of clusters (k) to be specified in advance.                      | Does not require the number of clusters to be specified in advance.                                          |
| Cluster Formation        | Forms non-overlapping clusters where each object belongs to only one cluster.        | Forms a hierarchy of overlapping clusters where objects can belong to multiple levels of the hierarchy.      |
| Flexibility              | Less flexible as the number of clusters needs to be predetermined.                   | More flexible as it does not require the number of clusters to be specified.                                 |
| Computational Complexity | Generally less computationally complex compared to hierarchical methods.             | Can be more computationally complex, especially for agglomerative hierarchical clustering.                   |
| Interpretability         | Easier to interpret the final, distinct clusters.                                    | Provides more insights into the hierarchical relationships between clusters.                                 |
| Sensitivity to Outliers  | More sensitive to outliers that can significantly impact the cluster centers.        | Less sensitive to outliers as they are typically assigned to their own clusters.                             |
| Suitability              | Suitable when the number of clusters is known or needs to be specified.              | Suitable for exploring the hierarchical structure of the data without pre-specifying the number of clusters. |

The choice between k-means and hierarchical clustering methods depends on the specific characteristics of the data, the research objectives, and the desired level of interpretability and flexibility in the clustering analysis.

## 14 What are the difficulties with hierarchical clustering?

**Ans.14)** Some of the key difficulties with hierarchical clustering methods are:

### 1. Irreversibility of Decisions:

- Hierarchical clustering methods, both agglomerative and divisive, are rigid in the sense that once a merge or split decision is made, it cannot be undone.
- This can lead to errors in the final clustering if an earlier decision turns out to be suboptimal.

### 2. Sensitivity to Outliers:

- Hierarchical clustering methods can be sensitive to outliers in the data, as they can significantly impact the similarity/dissimilarity calculations and the resulting cluster structure.

### 3. Computational Complexity:

- Especially for agglomerative hierarchical clustering, the computational complexity can be high, as it requires evaluating the distances between all pairs of clusters at each step.
- This can make hierarchical clustering methods less scalable for very large datasets.

### 4. Interpretation of Cluster Hierarchy:

- The hierarchical structure of clusters produced by these methods can be complex and challenging to interpret, especially when dealing with a large number of objects.
- Determining the appropriate number of clusters to extract from the dendrogram can also be subjective.

### 5. Handling Missing Data:

- Hierarchical clustering methods may face difficulties in handling datasets with missing values, as the distance/dissimilarity calculations need to be adjusted to account for the missing information.

### 6. Suitability for Specific Data Types:

- Certain hierarchical clustering methods may be more suitable for specific data types (e.g., interval-scaled, binary, categorical) and may require additional preprocessing or transformations to handle mixed-type variables.

These limitations of hierarchical clustering methods should be considered when choosing the appropriate clustering approach for a given problem and dataset.

## 15 What are the limitations of hierarchical clustering?

**Ans.15)** The limitations of hierarchical clustering methods include:

### 1. Irreversibility of Decisions:

- Once a merge or split decision is made in hierarchical clustering, it cannot be undone, potentially leading to suboptimal clustering results.

### 2. Sensitivity to Outliers:

- Hierarchical clustering methods can be sensitive to outliers, which can significantly impact the clustering structure and the formation of clusters.

### 3. Computational Complexity:

- Agglomerative hierarchical clustering, in particular, can be computationally complex, especially when evaluating distances between all pairs of clusters at each step.

### 4. Interpretation Challenges:

- The hierarchical structure produced by these methods can be complex and challenging to interpret, especially with a large number of objects or clusters.

### 5. Handling Missing Data:

- Hierarchical clustering methods may face difficulties in handling datasets with missing values, requiring adjustments in distance calculations to account for missing information.

### 6. Subjectivity in Determining Cluster Numbers:

- Determining the optimal number of clusters from a dendrogram can be subjective, as there is no definitive method to identify the ideal number of clusters.

### 7. Scalability Issues:

- Hierarchical clustering methods may face scalability challenges with very large datasets due to the hierarchical structure and the computational complexity involved.

Understanding these limitations is crucial when choosing hierarchical clustering methods and interpreting the results effectively in various data analysis scenarios.

## 16 What is decision tree?

**Ans.16)** A decision tree is a popular supervised machine learning algorithm used for both classification and regression tasks. It is a tree-like structure where each internal node represents a feature or attribute, each branch represents a decision rule, and each leaf node represents the outcome or prediction.

Key characteristics of decision trees include:

- **Splitting:** The process of dividing the data based on the values of features to create homogeneous subsets.
- **Nodes:** Internal nodes represent features, branches represent decisions, and leaf nodes represent outcomes.
- **Decision Rules:** Rules are learned from the data to make predictions or classifications.
- **Predictions:** Decision trees can be used for both categorical (classification) and continuous (regression) outcomes.
- **Interpretability:** Decision trees are easy to interpret and visualize, making them popular for understanding the decision-making process.

In summary, decision trees are versatile and intuitive models that use a tree-like structure to make decisions based on the features of the data, making them valuable tools in machine learning for both prediction and classification tasks.



**17 What are various measures or linkage methods to calculate the distance between two clusters.**

**Ans.17)** There are several measures or linkage methods that can be used to calculate the distance between two clusters in hierarchical clustering:

**1. Single Linkage (Nearest Neighbor):**

- The distance between two clusters is defined as the minimum distance between any two points in the clusters.
- It uses the distance between the closest pair of objects, one from each cluster.

**2. Complete Linkage (Farthest Neighbor):**

- The distance between two clusters is defined as the maximum distance between any two points in the clusters.
- It uses the distance between the most distant pair of objects, one from each cluster.

**3. Average Linkage:**

- The distance between two clusters is defined as the average distance between all pairs of objects, one from each cluster.
- It calculates the mean distance between all pairs of objects in the two clusters.

**4. Centroid Linkage:**

- The distance between two clusters is defined as the distance between the centroids (mean vectors) of the two clusters.
- It uses the Euclidean distance between the cluster centroids.

**5. Ward's Method:**

- The distance between two clusters is defined as the increase in the total within-cluster variance when the two clusters are merged.
- It aims to minimize the sum of squared differences within all clusters.

These linkage methods provide different ways to calculate the distance or dissimilarity between clusters, leading to different clustering structures and results. The choice of linkage method depends on the characteristics of the data and the specific goals of the clustering analysis.