

Alpha1 Sequencer — Unified Recording Workflow (Linear & Loop)

Prerequisites

- MIDI controller connected to MIDI IN (TRS)
- External sound module connected to MIDI OUT (TRS → DIN via adapter)
- Device is a sequencer only (no internal sound engine)
- Incoming MIDI is passed through in real time

Common Preparation (Both Modes)

1. Power on device
2. Select Project number
3. (Optional) Clean Project
4. Set BPM (Stop mode only)
5. Select Track (Track N = MIDI Channel N)
6. Choose `seq:` mode (Linear or Loop)

Linear Recording Workflow

Characteristics

- Destructive recording
- One pass replaces previous content of current track
- Used for structured, timeline-based recording

Steps

1. Ensure `seq:` = Linear
2. Select desired Track
3. Press REC
4. Count-in: 4 beats (LED + piezo)
5. Recording starts (REC LED lights up)
6. Play MIDI performance
7. Press STOP to finish
8. Press PLAY to audition
9. Repeat for other tracks
10. Save Project

■■ Recording over an existing track permanently erases its content.

Loop Recording Workflow

Characteristics

- Non-destructive overdub by default
- Continuous looping
- Live track switching supported

Steps

1. Set `seq:` = Loop
2. Set Loop Length
3. Select Track
4. Press REC
5. Count-in: 4 beats
6. Recording starts, loop runs continuously
7. Overdub MIDI events
8. Switch tracks during recording:
 - FF → Track +1
 - REW → Track -1
9. Press REC during recording → clears current track
10. Press STOP when finished
11. Save Project

■■ Avoid long notes near loop wrap to prevent hanging notes.

Use FF + REW for MIDI Panic (All Notes Off).

Restrictions During Recording

- Menu access blocked

- Save / Load / Clean blocked
- Loop length blocked
- seq: mode blocked

Metronome & Indicators

- LED Metronome: Play & Rec
- Piezo Metronome: Rec only
- First beat accented by piezo
- Count-in only in Rec mode

Notes

- Maximum 16 tracks (16 MIDI channels)
- Projects stored in flash (persistent)
- Designed for real-time performance recording