



**TRIBHUVAN UNIVERSITY
INSTITUTE OF ENGINEERING
PULCHOWK CAMPUS**

Assignment 3

By:

Sinjal Dahal (081/BEL/080)

**DEPARTMENT OF COMPUTER AND ELECTRONICS ENGINEERING
LALITPUR, NEPAL**

1. Write the following records into file grocery.txt:

```
records = [  
{'name':"rice","price":120,"category":"grocery"},  
{'name':"sugar","price":220,"category":"grocery"},  
{'name':"wheat","price":320,"category":"grocery"},  
{'name':"rcereal","price":420,"category":"grocery"},  
]
```

with headings: ID NAME PRICE CATEGORY

again, read the written records from same file and display the contents as above record.

Grocery Write Code:

```
records = [  
    {'name':"rice","price":120,"category":"grocery"},  
    {'name':"sugar","price":220,"category":"grocery"},  
    {'name':"wheat","price":320,"category":"grocery"},  
    {'name':"rcereal","price":420,"category":"grocery"},  
]
```

with open("grocery.txt", "w") as f:

```
    f.write("ID\t\tNAME\t\tPrice\t\tCategory\n")
```

```
    for i in range(len(records)):
```

```
        data = records[i]
```

```
f.write(f"{i+1}\t\t{data['name']}\t\t{data['price']}\t\t{data['category']}\n")
```

Grocery Read Code:

```
f = open("grocery.txt", "r")
```

```
print("\nGROCERY RECORDS:\n")
```

```
line = ""
```

```
while True:
```

```
    char = f.read(1)
```

```
    if not char:
```

```
        if line != "":
```

```
            print(line)
```

```
            break
```

```
    if char == "\n":
```

```
        print(line)
```

```
        line = ""
```

```
    else:
```

```
        line += char
```

```
f.close()
```

Output In Text File:

GROCERY RECORDS:

ID	NAME	Price	Category
1	rice	120	grocery
2	sugar	220	grocery
3	wheat	320	grocery
4	rcereal	420	grocery

Output In Terminal:

GROCERY RECORDS:

ID	NAME	Price	Category
1	rice	120	grocery
2	sugar	220	grocery
3	wheat	320	grocery
4	rcereal	420	grocery

2. Write a python code to explain the concept of seek() method in file handling.

The seek(offset) method moves the file pointer to a specific position (number of bytes from the start of the file). It's mainly used in reading or writing at a specific position in the file.

Code:

```
with open("sample.txt", "w") as f:  
    f.write("Hello, My name is Sinjal Dahal.\nWe are becoming  
lazy.")
```

```
with open("sample.txt", "r") as f:  
    print("Reading full file:")  
    print(f.read())  
  
    # Move file pointer to the beginning  
    f.seek(0)  
    print("\nAfter seek(0):")  
    print(f.read(5)) # Read first 5 characters  
  
    # Move pointer to position 18  
    f.seek(18)  
    print("\nAfter seek(18):")  
    print(f.read(6))
```

Output:

```
Reading full file:  
Hello, My name is Sinjal Dahal.  
We are becoming lazy.
```

```
After seek(0):  
Hello
```

```
After seek(18):  
Sinjal
```

[LINK](#)